

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

Characteristics of Concrete by Using Various Types of Steel Fibres

Subha Kesavulu. A¹, Mallikarjuna.M²

P.G. Student, Department of Civil Engineering, SVR College of Engineering, Nandyal, Karnool,
Andhra Pradesh, India¹

Assistant Professor, Department of Civil Engineering, SVR College of Engineering, Nandyal, Karnool,
Andhra Pradesh, India²

ABSTRACT: Different forms of metallic fibers can be used to enhance concrete. Steel fibers are usually categorised depending on their manufacturing technique. The addition of steel fibers to concrete necessitate an alteration to the combination layout to catch up on the loss of workability due to the greater paste required for coating the surface of the delivered metal fibers. While many technical and low cost blessings are benefited from the usage of SFRC, drawbacks also can be discovered. They are however no longer possibly to motive essential issues. It was thought that metallic fibers will have terrible implications in concrete exercise (i.e. Transporting, surfacing, finishing etc), however experience has proven that the affect of metal fibers on these realistic factors is negligible. This research is based on investigating the effect of various forms of metallic fibers on electricity parameters and durability of concrete for M-forty grade using fibers like immediately fiber, crimped fiber and hooked fiber. This take a look at is to have a look at the compressive power, Split tensile strength, flexural electricity, and sturdiness of metal fiber reinforced concrete (SFRC) containing fibers of zero%, 1%, 2% and 3%, four%, 5% by using extent of cement.

KEYWORDS: Steel fibers, M-40 grade, compressive strength, Split tensile strength, flexural strength, Durability.

I. INTRODUCTION

Presently a day's human prerequisite is considerably higher than shield, with the progression of human social orders, structure must be more bound in space occupation, extensive and more grounded than some time recently. Present day structures are created with lovely appearance as well as for long life and strength. Propel innovation in structural building and in engineering encourages planners and specialists to show up and quality. Aside from nature's effect like in type of head honchos, surge and seismic tremor; structures additionally withstand in environmental condition like storm, moistness and vast variety in temperature as indicated by atmosphere. In the present work we likewise explored different avenues regarding steel filaments and different fixings (Steel fiber). Test with various fixation and diverse size of fiber, were arranged and tried for the compressive quality against traditional cement.

Information from the performed explore were recorded and compressive quality related examination have been finished. Our fundamental question of the work is to enhance the Fiber fortified cement (FRC) is Portland bond concrete strengthened with pretty much haphazardly appropriated filaments. In FRC, a huge number of little strands are scattered and appropriated haphazardly in the solid amid blending, and in this manner enhance solid properties every which way. FRC is concrete based composite material that has been created lately. It has been effectively utilized as a part of development with its magnificent flexural-elasticity, protection from spitting, affect protection and phenomenal porousness and ice protection. It is a compelling approach to build durability, stun protection and protection from plastic shrinkage breaking of the mortar. Fiber is a little bit of strengthening material having certain attributes properties. They can be round, triangular or level in cross-area. The fire is regularly depicted by a helpful parameter

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

called viewpoint proportion. The viewpoint proportion of the fiber is the proportion of its length to its distance across. The standard purpose behind consolidating strands into a concrete lattice is to build the sturdiness and elasticity and enhance the breaking misshapening attributes of the resultant composite. For FRC to be a reasonable development material, it must have the capacity to contend financially with existing strengthening framework. FRC composite properties, for example, break protection, support and increment in strength are reliant on the mec

II.RELATED WORK

Steel fiber strengthened cement is a composite material having filaments as the extra fixings, scattered consistently at irregular in little rates, i.e. in the vicinity of 0.3% and 2.5% by volume in plain cement SFRC items are produced by adding steel filaments to the elements of cement in the blender and by exchanging the green cement into molds. The item is then compacted and cured by the customary strategies. Isolation or balling is one of the issues experienced amid blending and compacting SFRC. This ought to be maintained a strategic distance from for uniform appropriation of strands. The vitality required for blending, passing on, putting and completing of SFRC is marginally higher. Utilization of container blender and fiber gadget to aid better blending and to lessen the arrangement of fiber balls is fundamental. Extra fines and restricting most extreme size of totals to 20mm sometimes, bond substance of 350 kg to 550 kg for every cubic meter are typically required.

Steel filaments are added to cement to enhance the auxiliary properties, especially tractable and flexural quality. The degree of change in the mechanical properties accomplished with SFRC over those of plain cement relies upon a few elements, for example, shape, measure, volume, rate and appropriation of filaments. Plain, straight and round strands were found to grow exceptionally powerless bond and thus low flexural quality. For a given state of strands, flexural quality of SFRC was found to increment with viewpoint (proportion of length to equal width).

Despite the fact that higher proportions of strands gave expanded flexural quality, workability of green SFRC was observed to be antagonistically influenced with expanding viewpoint proportions. Thus perspective proportion is for the most part restricted to an ideal incentive to accomplish great workability and quality. Dark proposed that perspective proportion of under 60 are best from the purpose of taking care of and blending of strands, however a viewpoint proportion of around 100 is alluring from quality perspective. Schwarz however recommended angle proportion in the vicinity of 50 and 70 is more practicable incentive for prepared blend concrete. In a large portion of the field applications experimented with to date, the span of the filaments shifts between 0.25 mm and 1.00mm in breadth and from 12mm to 60mm long, and the fiber content went from 0.3 to 2.5 percent by volume. Higher challenges of fiber up to 10% have likewise been tested. Expansion of steel filaments up to 5% by volume expanded the flexural quality to around 2.5 times that of plain concrete.

As clarified above, blending steel filaments extensively enhances the auxiliary properties of cement, especially malleable and flexural quality. Malleability and post splitting quality, protection from weakness, spalling and wear and tear of SFRC are higher than on account of regular fortified cement. SFRC is in this manner observed to be a flexible material for the make of wide assortments of precast items, for example, sewer vent covers, chunk components for connect decks, roadways, runways, and burrow linings, machine establishment pieces, entryway and window outlines, heaps, coal stockpiling dugouts, grain stockpiling canisters, stair cases and break waters. Innovation for this produce of SFRC light, medium and substantial obligation sewer vents covers has been created in India by Structural Engineering Research Center, Chennai. Field explores different avenues regarding two percent of fiber content showed that SFRC runway chunks could be around one a large portion of the thickness of plain solid sections for a similar wheel stack scope.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

III. MATERIALS AND METHODS

Plain concrete has a low elasticity, restricted pliability and little protection from splitting. Inward small scale breaks are naturally present in the solid and its poor rigidity is because of the proliferation of such miniaturized scale splits, in the end prompting fragile crack of the solid. It has been perceived that the expansion of little, firmly divided and consistently scattered strands to the solid would go about as break arrester and would generously enhance its Compressive and flexural quality properties. This kind of cement is known as fiber strengthened cement. The pleated level steel strand were utilized as a part of this examination. The sizes (Length/perspective proportion) of the steel strands are of 30mm/60.

Many years of the experience had prompted the generation of the five most productive steel fiber sorts. The proficiency of the at present created fiber depends on the two its adequacy in solid framework and the effortlessness of its generation, which thusly affects its cost. These five most prevalent sorts of steel fiber.

A measurable examination of the arrangement created on the planet shows that 67.1% of fiber comprises of the snared sort. The other most mainstream strands are: straight fiber (9.1%), mechanically distorted fiber (9.1%), pleated fiber (7.9%), and other fiber of various endings (6.6%). The effectiveness of scattered support relies upon various elements. Notwithstanding, the most critical of them is the angle proportion of the filaments, which impacts the workability and separating of strands in new solid blend. In light of workability, the solid blend viewpoint proportion of steel fiber ought not be higher than 150. A measurable examination of the viewpoint proportion of delivered steel filaments.

The viewpoint proportion of filaments accessible on the world market ranges from 20.4 to 152, which is shown in Figure 2. So as to portray the recurrence of a particular fiber viewpoint proportion, Figure 2 displays a casing demonstrating a separation between the lower and upper quartile which is extremely limited and envelops the perspective proportion from 45 to 63.5. At the end of the day, fiber of the angle proportion from 45 to 63.5 constitutes half of the number of inhabitants in assorted types offered by makers of steel fiber utilized for altering concrete.

BENEFITS OF USING STEEL FIBERS IN CONCRETE

The use of steel fiber in concrete can improve its many properties. The benefits of using steel fibres in concrete are as follows:

- ✚ Steel Fibers are typically distributed for the duration of a given pass phase whereas reinforcing bars or wires are located only in which required
- ✚ Steel fibers are exceedingly quick and carefully spaced in comparison with non-stop reinforcing bars of wires.
- ✚ It is usually now not feasible to acquire the identical location of reinforcement to place of concrete using steel fibers in comparison to using a network of reinforcing bars of wires
- ✚ Steel Fibers are usually delivered to concrete in low quantity dosages (regularly less than 1%), and were shown to be effective in decreasing plastic shrinkage cracking.
- ✚ Steel Fibers normally do not drastically regulate free shrinkage of concrete, however at high sufficient dosages they can boom the resistance to cracking and reduce crack width (Shah, Weiss, and Yang 1998).

Steel Fibers in Concrete can improve:

- ✚ Crack, Impact and Fatigue Resistance
- ✚ Shrinkage Reduction
- ✚ Toughness- by preventing/delaying crack propagation from micro cracks to macro-cracks.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017



Regularly the filaments are included at the bunch plant, soon after every solid total are being blended. A few people would demand to have the fiber included at the jobsite, yet then the QA/QC ought to have more control on how much fiber is included. The steel fiber maker can give direction on the best way to blend and the sum expected to acquired wanted outcomes. Know that in the event that you add to much fiber, it may appear at the surface when completing the solid so be mindful about the sums being blended.

The first severe civil engineering buildings with the software of SFRC were carried out inside the Nineteen Sixties. Nevertheless, the advantages of the material had been not absolutely liked till a decade later. Since that time, SFRC has determined severa packages on a wider scale. Moreover, the application of SFRC is continually increasing. Firstly, SFRC was used to build runways of airports. In the USA, 28 runways built of SFRC modified by 0.Three-2.0% of metallic fiber of different sorts have been completed between 1972 and 1980 (Lankard During those 14 years of commentary of the construction initiatives, handiest scarce cracks and neighborhood damage had been observed. In the USA, fiber bolstered concrete is used to repair surfaces of motorways and airports in addition to to build dams and canals (Lankard 1975). Recently it has been Shotcrete with the addition of metallic fiber that's gaining an increasing number of reputation among constructors. Unstable slopes, landslides, and road embankments were secured with Shotcrete put on a formerly stretched metallic mesh. Steel fiber bolstered Shotcrete (SFRS), the mesh, whose attachment and laying are time-ingesting, may be abandoned. With conventional spraying of Shotcrete onto mesh, it frequently happens that Shotcrete is stopped via the mesh and spraying shadows appear. Apart from that, the mesh can vibrate as spraying reasons grains of sand hit it. This in flip, hinders an awesome bond among the mesh and Shotcrete. With the software of SFRS the lack of cloth all through the laying segment is reduced by means of half of in comparison with Shotcrete without fibers The utility of SFRS allows one to avoid those technological troubles and moreover creates a opportunity of creating thinner sprayed layers, which concurrently are extra proof against cracks

IV. OBJECTIVE OF STUDY

Today it is steel fiber which is for the most part used to fortify cement and defeat the issue of weakness. This paper portrays the most fascinating utilizations of steel fiber fortified cements (SFRC) everywhere throughout the world. Right off the bat, the creator exhibits the development of steel filaments and SFRC. Also, the paper covers the contemporary significance of SFRC in structural building.

Steel fiber solid ground surface can give better protection than limit breaks in solidified cement, and additionally most extreme protection from withstand overwhelming burdens, either unique or static. In the event that you choose to utilize steel fiber solid ground surface, you can choose to utilize a 'joint-less floor'. Joint-less floors will be floors that have insignificant joints, giving spaces without joints as vast as 40 or 50 meter traverse wide. Steel fiber dose will change extraordinarily upon the venture planned utilize, and the sorts of work being supplanted. Regular measurements are in the range between 20-30kg/m³ to 40-50kg/m³ for joint-less floors. Trowelling solid will install steel filaments into the solid surface creating a superior complete item. Steel strands will improve to split protection of the solid, and they can likewise be utilized to supplant or supplement auxiliary support.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

V. EXPERIMENTAL INVESTIGATIONS

The details of number of blocks to be tested while the experimentation process is given in the below table

Sl.No	% Replacement of Steel fibre	Compressive strength of concrete					Split tensile strength of concrete			Flexural strength of concrete			Durability of concrete
		7days	14days	28days	56days	90days	28days	56days	90days	28days	56days	90days	
1	0.00%	3	3	3	3	3	3	3	3	3	3	3	3
2	1.00%	3	3	3	3	3	3	3	3	3	3	3	3
3	2.00%	3	3	3	3	3	3	3	3	3	3	3	3
4	3.00%	3	3	3	3	3	3	3	3	3	3	3	3
5	4.00%	3	3	3	3	3	3	3	3	3	3	3	3
6	5.00%	3	3	3	3	3	3	3	3	3	3	3	3
Total		90 cubes					60 cylinders			60 prisms			18 cubes

In each batch 3 cubes, 3 cylinders and 3 prisms were casted. Totally 108 cubes, 60 cylinders and 60 prisms were casted during entire experimentation.

Shape and Dimensions of Blocks:

Type of test	Shape of block	Length(m)	Breadth(m)	Height(m)	Diameter(m)	Volume of block (m ³)
Compressive strength	Cube	0.15	0.15	0.15	--	0.00375
Split tensile strength	Cylinder	--	--	0.30	0.15	0.00530
Flexural strength	Square prism	0.1	0.1	0.7	--	0.00700

VI. MATERIALS

The material used for this experimental work are cement, sand, water, steel fibres, and super plasticizer.

Cement: Ordinary Portland cement of 53 grade was used in this experimentation conforming to I.S. – 12269-1987. ordinary Portland Cement (OPC) is a champion among the most acclaimed constructing materials used the entire path over the globe. There is a spellbinding story behind the naming of this for the most part used solid thing. The name 'Portland' was given by the British bond creator, Joseph Aspdin in 1824, as a result of its strong comparability to

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

Portland Stone, a kind of white diminish limestone found in the isle of Portland, Dorset in England. Joseph Aspdin is in like manner credited to have ensured the vital bona fide fake solid, which he named as the Portland bond. Key Features: While the focal blend constituents of ordinary Portland Cement (OPC) are Calcium, Silica, Alumina and Iron, bond creators constantly research and attempt endeavors to additionally fortify and enhance the quality and different highlights of this specific kind of concrete. At UTRA TECJH Cement, the 53 Grade OPC Cement which gives much higher concrete quality to coordinate the rising requests of higher quality building material in the urban world.

53 Grade OPC Cement: Ideal for the following applications

- ✚ High-rise buildings
- ✚ All types of R.C.C. works
- ✚ Industrial works
- ✚ Pre-stressed concrete work like bridges, silos, etc.
- ✚ Pre-cast elements such as Railway sleepers and concrete pole.

PARAMETERS OF CEMENT

Parameter		ULTRA TECH Cement 53 Grade	IS:12269
Sp. Surface (m ² /kg.)		340 ± 10	225 m ² /kg. minimum
Setting Time (in minutes)	Initial	100 ± 5	30 minutes minimum
	Final	150 ± 5	600 minutes maximum
Expansion	Le-Chatelier Expansion (in mm)	1.5 mm max.	10 mm maximum
	Autoclave Expansion (in %)	0.17%	0.8% maximum
Compressive Strength (MPa)	3 Days	40 ± 2	27 MPa minimum
	7 Days	50 ± 2	37 MPa minimum
	28 Days	61 ± 2	53 MPa minimum

Concerning different assessments of bond, the 53 Grade OPC Cement gives dependably higher quality stood out from others. As indicated by the Bureau of Indian Standards (BIS), the audit number of a solid highlights the base compressive quality that the bond is depended upon to finish inside 28 days. For 53 Grade OPC Cement, the base compressive quality achieved by the bond toward the complete of the 28th day shouldn't be under 53Mpa or 530 kg/sqcm.

FINE AGGREGATES :Locally open sand zone II with specific gravity 2.65, water absorption 2% and fineness modulus 2.92, changing in accordance with I.S. – 383-1970. It is the aggregate the lion's share of which passes 4.75

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

mm IS sifter and contains simply such an extraordinary measure of coarser as is permitted by detail. As showed by source fine aggregate may be depicted as:

Ordinary Sand– it is the aggregate coming to fruition in light of the normal disintegration of shake and which has been put away by streams or frosty associations

According to gauge the fine aggregate may be portrayed as coarse sand, medium sand and fine sand. IS subtle elements gather the fine aggregate into four sorts according to its assessing as fine aggregate of exploring Zone-1 to auditing Zone-4. The four auditing zones end up being powerfully better from assessing Zone-1 to evaluating Zone-4. 90% to 100% of the fine aggregate passes 4.75 mm IS strainer and 0 to 15% passes 150 micron IS sifter depending on its assessing zone. Sand is an ordinarily happening granular material made out of finely isolated shake and mineral particles. It is portrayed by gauge, being superior to shake and coarser than buildup. Sand can in like manner imply a textural class of soil or soil sort; i.e. an earth containing more than 85% sand-sized particles by mass.

The association of sand changes, dependent upon the area shake sources and conditions, yet the most broadly perceived constituent of sand in inland terrain settings and non-tropical waterfront settings is silica (silicon dioxide, or SiO_2), usually as quartz. The second most fundamental sort of sand is calcium carbonate, for example aragonite, which has generally been made, over the past half billion years, by various sorts of life, like coral and shellfish.

Fine aggregate are in a general sense sands won from the land or the marine condition. Fine sums generally involve typical sand or squashed stone with most particles experiencing a 9.5mm sifter. In like manner with coarse aggregates these can be from Primary, Secondary or Recycled sources.

Those particles passing the 9.5 mm (3/8 in.) sifter, inside and out passing the 4.75 mm (No. 4) sifter, and pervasively hung on the 75 μm (No. 200) sifter are called fine aggregate.



The above figure shows the test sieves of both fine and coarse aggregate. the materials which are pass through the sieves.

COARSE AGGREGATE: Squashed shake stones of 10 mm measure having specific gravity of 2.70, fineness modulus of 2.73, conforming to IS 383-1970 Aggregates are idle granular materials, for instance, sand, shake or pounded stone that are a last outcome in their own right. They are moreover the unrefined materials that are a fundamental settling in concrete. For a nice strong mix, aggregates ought to be spotless, hard, strong particles free of expended chemicals or coatings of soil and other fine materials that could cause the rot of concrete.

It is the aggregate an expansive bit of which is hung on 4.75 mm IS strainer and contains just so remarkably better material as is permitted by specific. According to source, coarse aggregate may be depicted as:

Uncrushed Gravel or Stone– it comes to fruition in light of trademark disintegrating of shake

Beat Gravel or Stone– it comes to fruition in view of crushing of shake or hard stone.

To some degree Crushed Gravel or Stone– it is a consequence of the blending of the more than two aggregate.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

As demonstrated by measure coarse aggregate is delineated as assessed aggregate of its apparent size i.e. 40 mm, 20 mm, 16 mm and 12.5 mm et cetera for example an evaluated aggregate of apparent size 20 mm suggests an aggregate an extensive part of which passes 20 mm IS strainer. A coarse aggregate which has the sizes of particles fundamentally having a place with a singular sifter gauge is known as single size aggregate. For example 20 mm single size aggregate mean an aggregate most of which passes 20 mm IS strainer and its genuine piece is hung on 10 mm IS sifter.

It is the aggregate made out of both fine aggregate and coarse aggregate. As showed by measure All-altogether is depicted as in without any reservations sums of its apparent size, i.e. 40mm, 20mm et cetera. For example, all altogether of apparent size of 20mm means an aggregate a huge part of which experiences 20 mm IS strainer and contains fine sums also.

WATER: By and large consumable water should be utilized. This is to ensure that the water is shoddy loosened from such pollutions as suspended solids, natural depend and broke down salts, which may furthermore antagonistically influence the homes of the solid, particularly the setting, solidifying, vitality, solidness, pit expense, and numerous others.

VII.CONCLUSIONS

1. The material properties of the cement, fine aggregates and coarse aggregates are within the acceptable limits as per IS code recommendations so we will use the materials for research.
2. Slump cone value for the steel fiber concrete increases with increasing in the percentage of steel fiber so the concrete was not workable by increasing in the percentage.
3. Compaction factor value of steel fiber reinforced concrete decreases with increase in the percentage of steel fibers and the maximum values of compaction factor was observed at 2% of steel fibers.
4. The compressive strength of concrete is maximum at 0% of steel fibers and is the optimum value for 7days curing, 28days curing, 56days curing, 90days curing.
5. Split tensile strength for the cylindrical specimens is maximum at 0% of steel fibers for 28days curing, 56days curing, 90days curing.
6. The flexural strength of copper slag concrete is also maximum at 2% of steel fibers for 28days curing, 56days curing, 90days curing.
7. The percentage loss of weight and percentage loss of compressive strength due to acid attack is increases with increase in the percentage of steel fibers.
8. The percentage loss of weight and percentage loss of compressive strength due to alkalinity attack is increases with increase in the percentage of steel fibers.
9. The percentage loss of compressive strength due to sulphate attack is decreases with increase in the percentage of steel fibers.

So the replacement of 3 % of steel fibers is generally useful for better strength values in M30 grade of concrete.

REFERENCES

1. A.M. Shende¹, A.M. Pande², M. Gulfam Pathan³ et and all., On the review of "A Review Study on Fiber Reinforced Concrete" published in year 2012 in IJRET journal.
2. Amit rana on the review of "Some Studies on Steel Fiber Reinforced Concrete" in paper published in IJETAI journal in the year 2013.
3. Mr. Nikhil A. Gadge¹, Prof. S. S. Vidhale² et and all.,(2013) "experimental study on mechanical and durability properties of high strength concrete incorporating ggbs and steel fibers" on the paper published in the year 2013. In IJMCCE journal.
4. Boer, S. and Groeneweg, T. and Leegwater, G., and Pieterse, I. 2004. Low-cost Housing in Kenia. Delft University of Technology.
5. Odelberg, G. 1985. "Producing and Promoting of Swedish Steel Fibers to the Market". Steel Fiber Concrete US-Sweden Joint Seminar, Stockholm 3-5June, 1985. Jamrozy, Z. 1983.
6. Mechanika KompozytówBetonopodobnych. Zakład Narodowy Imieni Ossolińskich, Wydawnictwo Polskiej Akademii Nauk. Jamrozy, Z. 1985.
7. Drutobeton. Wydawnictwo Politechniki Krakowskiej. Kraków. Jamrozy, Z. 2002. "Betony ze Zbrojeniem Rozproszonym". XVII Ogólnopolska Konferencja Warsztat Pracy Projektanta Konstrukcji. Ustron.
8. Johnston, C. D. 2001. Fibre Reinforced Cements and Concretes. Gordon and Breach Science Publishers. Katzer, J. 2003. "Włókna Stalowe Stosowane do Modyfikacji Betonu". Polski Cement. (3/2003).



ISSN(Online): 2319-8753
ISSN (Print): 2347-6710

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 6, Issue 12, December 2017

9. Kayvani, A. and Saeki, N. and Shimura, K. 1995. "Applying Waste Shavings in Concrete". Proceedings of the Eleventh International Conference on Solid Waste Technology and Management. Philadelphia, PA, USA.
10. Lankard, D.R. 1975. Fiber Concrete Applications. Rilem Symposium. The Construction Press, LTD.
11. Lankard, D. R. 1985. "Preparation, Properties and Applications of Cement-based Composites Containing 5 to 20 Percent Steel Fiber". Steel Fiber Concrete USSweden Joint Seminar. Stockholm