

Feasibility Study of Levitation Force at Structural Joints to Improve Energy Dissipation

Pratiksha S. Narwate¹, Sayali R. Londhe², Shashank V. Kadu³

U.G. Scholars, Department of Civil Engineering, Pimpri - Chinchwad College of Engineering, Nigdi, Pune, India

ABSTRACT: Earthquake vibrations can be controlled by using various types of energy dissipating devices such as Dampers, Bracings, Base isolation etc. Dampers are the energy dissipating devices used in the structure, so as to control vibrations in structure resulting into reduction of the violent earthquake motions transmission into the structure. A magnetic levitation type seismic isolation device composed of permanent magnets can theoretically remove horizontal vibration completely. Bracings are provided so that no twisting is induced in the building owing to unsymmetrical stiffness in plan of the structure. At preliminary stage, the bracing system analysis using competent software to have the idea about the behaviour of structure over seismic forces under earthquake condition. Various important parameters are to be considered while having the analysis of the structure with provision of bracings. The same analysis is to be done using hybrid dampers along with levitation force.

Various energy dissipating devices are used to reduce the effect of earthquake on structure but it can only reduce effect up to some extent. This facilitates the need for implementation of additional techniques for a better behaviour and stiffness of the structure. This paper enlightens the technique to reduce the effect of earthquake using various energy dissipating devices along with repulsive force by using a pair of magnet to levitate the structural joints such as column-beam and study the improvement in performance of structure.

KEYWORDS: Column and beam joints, Seismic Isolation, Vibration Control, Magnetic Levitation.

I. INTRODUCTION

A disruptive disturbance that causes shaking of the surface of the earth due to underground movement along a fault plane or from volcanic activity is called earthquake. The nature of forces induced is reckless, and lasts only for a short duration of time. Yet, bewildered are the humans with its uncertainty in terms of its time of occurrence, and its nature. However, with the advances made in various areas of sciences through the centuries, some degree of predictability in terms of probabilistic measures has been achieved. Further, with these advances, forecasting the occurrence and intensity of earthquake for a particular region, say, has become reasonably adequate, however, this solves only one part of the problem to protect a structure - to know what's coming! The second part is the seismic design of structures - to withstand what's coming at it! Over the last century, this part of the problem has taken various forms, and improvements both in its design philosophy and methods have continuously been researched, proposed and implemented. Various types of bracing and dampers are used to reduce the effect of earthquake on structure but it can only reduce effect up to some extent. This facilitates the need for implementation of additional techniques for a better joint isolation. We are attempting to reduce the effect of earthquake using repulsive force by using a pair of permanent magnet to levitate the joint and study the improvement in stiffness of structure under extreme earthquake conditions.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

II. RELATED WORK

We have developed a model and its description is as follows. A structural infinite model of levited structure.

Description of model:

1. Multi-storeyed rigid jointed frame (zone 5)
2. Layout - No. of bays in X-direction -4@4m each
No. of bays in Y-direction -3@3m each
- 3.No. of storey -4
4. Ground storey height-4m
- 5.Floor to Floor height-3m
- 6.Imposed load-3 KN/M²
- 7.Material use-Fe250

The soil below the foundation is assumed to be hard strata with damping.

Table No1: Details of Model

Dimensions	ISMB125(Beam ,Column)	ISLC100(Bracing)
Depth	125mm	100mm
Top flange width	75mm	50mm
Top flange thickness	7.6mm	6.4mm
Thickness of web	4.4mm	4mm
Bottom flange width	75mm	50mm
Bottom flange thickness	7.6mm	6.4mm

Table No 2: Case wise Model descriptions




Figure 1 Conventional steel building without bracing




Figure 2 Conventional steel building with V-bracing




Figure 3 Conventional steel building with X-bracing

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

From the consideration of behavioral analysis of multistory steel building, three conditions were considered. In this consideration Case I refer (Figure 1) an attempt is made to design a simulating model for Conventional steel building without bracing is considered and results were obtained under standard condition and these results were further compared with Case II refer (Figure 2) in which Conventional steel building with V-bracing arrangement and Case III refer (Figure 3) in which Conventional steel building with X-bracing were analyzed for comparing and establishing the relation on the effect of the bracing on conventional steel building.

III. ANALYSIS OF MODELS

This paper enlightens the comparative behavioural analyse of the Conventional Unbraced Steel building with X-braced and V- Braced steel building with same geometry and nature condition. The models were analysed for parameters like Base shear, Storey shear, Story Displacement, Storey Drift, and Joint Displacements by applying seismic coefficient method as per IS: 1893: 2002 Part I. By various arrangement of bracing in conventional G+3 steel structure.

Governing equations:

- Seismic base shear calculation (v_b)
IS:1893:2002 (part 1) cl. 7.5.3, page no. 24

$$V_b = Ah * W \text{-----(i)}$$

- Lateral Force Calculation (Q_i)
IS:1893:2002, cl. 7.7.1, page no. 24

$$Q_i = V_b \times \frac{w_i h_i^2}{\sum w_i h_i^2} \text{-----(ii)}$$

Table No 3: Lateral Load Distribution

Storey	Height(h _i)	Weight(w _i)	w _i *h _i *h _i	Q _i in kN	V _i in kN
4	13	154.96	26188.24	19.27882	19.28
3	10	159.724	15972.40	11.75829	31.04
2	7	159.724	7826.48	5.76156	36.80
1	4	159.724	2555.58	1.88133	38.68
		Σw _i *h _i *h _i	52542.70		

IV. RESULTS AND DISCUSSIONS

Based on feasibility study for the various forces, moments, reactions which are more predominant, the design of structural joint i.e., steel column and steel beam joints especially.

In this study, G+3 multi-storey steel building consisting of every component parts made up of rolled steel sections and plates are considered for slab, assumed and assembled using appropriate welding and bolting techniques. For the seismic analysis, building is assumed as a SMRF(Special Moment Resisting Frame) lying in zone V with 5 % damping. The building is analysed for conventional without bracing and the results for storey displacement, storey drift, joint displacement, joint drift and the reactions were obtained. The special arrangement of bracings were analysed in the study, like 'X' type bracing and 'V' type bracing to identify suitability of bracing system which helps to reduce or improve the energy dissipation. Finally both these special arrangement of bracing system were now compare with conventional arrangement of SMRF steel building to highlight the behaviour of each building in feasibility study point of view and to obtained more predominant forces to be considered in design of levitated energy dissipating device .





Based on the above study following results were obtained which are explained here:


International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

<div style="text-align: center;">Max Storey Displacement</div>  <p style="text-align: center;">(a)</p>	<div style="text-align: center;">Joint Displacement</div>  <p style="text-align: center;">(b)</p>		
<p>Maximum storey displacement in X-direction and in Y-direction in mm (for V-bracing ,X-bracing and without bracing respectively.)</p>		<p>Joint displacement in X-direction and in Y-direction in mm (for V-bracing ,X-bracing and without bracing respectively.)</p>	
<div style="text-align: center;">Joint Drift</div>  <p style="text-align: center;">(c)</p>	<div style="text-align: center;">Storey Drift</div>  <p style="text-align: center;">(d)</p>		
<p>Joint drift in X-direction and in Y-direction in mm (for V-bracing ,X-bracing and without bracing respectively.)</p>		<p>Storey drift in X-direction and in Y-direction in mm (for V-bracing ,X-bracing and without bracing respectively.)</p>	



V. CONCLUSIONS

Based on feasibility study carried out, on the behaviour of G+3 multistorey unbraced and braced building models, following conclusions were derived:

- Inertial force is more predominant in Y direction for maximum storey displacement.
- The behaviour of joint displacements are irrespective of the line of action of earthquake force.
- The storey drift of structure is the function of inertie force and the intensity of earthquake force.
- The storey displacement, joint displacement and storey drift are the important parameters to be considered in design of magnetic hybrid damper.

REFERANCES

- [1] Yash A. Mulik, Rajnish R. Bariya, Aishwarya S. Ingle, Kamlesh S. Zinjurke, "An Investigation Study of Effective Use of Magnetic Levitation to Control Horizontal Vibrations for Seismic Isolation of the Structures" International Journal of Engineering Research, Volume No.5, Issue Special 1 pp : 18-20,8 & 9 Jan 2016.
- [2] N. Peter, "Tuned-Mass Systems for the Seismic Retrofit of Buildings", Seventh International Congress on Advances in Civil Engineering: 2000.
- [3] C. C. Lin et al., "Seismic response reduction of irregular buildings using passive tuned mass dampers", Engineering Structures, Vol.22, 1999, pp. 513–524.
- [4] S Chakraborty and B. K. Roy, "Reliability based optimum design of Tuned Mass Damper in seismic vibration control of structures with bounded uncertain parameters", Probabilistic Engineering Mechanics, Vol. 26, 2011, pp. 215–221.
- [5] Vajreshwari Umachagi1, Katta Venkataramana2, G. R. Reddy3, Rajeev Verma4, "Applications of Dampers For Vibration Control of Structures: An Overview",IJRET: International Journal of Research in Engineering and Technology, pp.06-11.
- [6] M. Tsuda, T. Kojima, T. Yagai, and T. Hamajima, "Vibration characteristics in magnetic levitation type seismic isolation device composed of multiple HTS bulks and permanent magnets, IEEE Trans. Appl. Supercond" vol. 17, 2007.
- [7] Beaty, B. "Maglev Magnetic Levitation Suspension Device". [online] <http://amasci.com/maglev/magschem.html> [October 2005].
- [8] M. Tsuda, T. Kawasaki, T. Yagai, and T. Hamajima, Member, IEEE "Dependence of Horizontal Vibration Characteristics on Load Weight Distribution in Magnetic Levitation Type Seismic Isolation Device" IEEE TRANSACTIONS ON APPLIED XI. SUPERCONDUCTIVITY, VOL. 18, NO. 2, JUNE 2008.
- [9] B V Jayawant "Electromagnetic suspension and levitation" Rep. Prog. Phys., Vol. 44, 1981. Printed in Great Britain.
- [10] Beaty, B. "Maglev Magnetic Levitation Suspension Device". [online] <http://amasci.com/maglev/magschem.html> [October 2005]
- [11] M. Tsuda, T. Kawasaki, T. Yagai, and T. Hamajima, Member, IEEE "Dependence of Horizontal Vibration Characteristics on Load Weight Distribution in Magnetic Levitation Type Seismic Isolation Device" IEEE TRANSACTIONS ON APPLIED XI. SUPERCONDUCTIVITY, VOL. 18, NO. 2, JUNE 2008.
- [12] Md. Emdadul Hoque and Takeshi Mizuno "Magnetic levitation technique for active vibration control" Magnetic Bearings, Theory and Applications www.intechopen.com