

Performance Comparison of MIMO Techniques: Opportunities and Challenges

Neha Chaudhary

Department of Electronics, Guru Nanak Dev University, Amritsar, Punjab, India

ABSTRACT: Multi-user Multiple-Input Multiple-Output (MIMO) deals with big benefits above conventional point-to-point MIMO: mainly it works using cheap single-antenna terminals, where scattering atmosphere is not mandatory, and resource distribution is easy because every single active terminal operates all of the time-frequency bins. In this paper we studied various types of error detection techniques using ZF, MMSE, and SIC etc.

I. INTRODUCTION

Multiple-Input Multiple-Output (Mimo) technology has been broadly studied throughout the last two eras and applied to several wireless standards meanwhile it can considerably increase the capacity and reliability of wireless systems. Initially work focus on the problem of point-to-point MIMO links where 2 devices communicate with multiple antennas but now focus has shifted in current years to extra practical multi-user systems, in which typically a base station (BS) with numerous antennas at the same time serves a set of single-antenna users as well as the multiplexing gain is usually shared among all users. In this technique, expensive equipment is only needed on the BS finish of the link, and the user terminals can be comparatively cheap single-antenna strategies. MIMO in structures brings improvements on four faces [4]:

- improved data rate, because if worked on more antennas, the more self-governing data streams can be directed out and the more terminals can be assisted simultaneously;
- improved reliability, because with more antennas, more distinct tracks that the radio signal can broadcast over;
- enhanced energy proficiency, because the base station can emphasis its emitted energy into the spatial instructions where it identifies that the terminals are positioned; and
- Reduced interference as the base station can intentionally escape transmitting into directions where spreading interference would be damaging.




Figure: Illustration of Massive MIMO systems

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

Linear signal sensors with low complication, such as the MF,ZF, and MMSE detectors, are real-world candidates for massive MIMO systems [6]. They can asymptotically attain capacity as the total of antennas at the BS is big enough compared to the number of users as well as the channel vectors from diverse users are independent. The results of massive MIMO systems established on several linear receivers have been calculated from several perspectives. A performance evaluation among the MMSE and the MF receivers in genuine system settings is delivered in [15]. It displays that the MMSE receiver can attain the equal performance as the MF receiver by fewer antennas, particularly when around exists inter-cell interference. 2 types of MMSE receivers are measured: the optimal MMSE receiver delightful different transmit power levels from dissimilar users into account plus a suboptimal MMSE receiver assuming equivalent transmits power. In [17], the precise data rate, symbol-error rate, and outage performance of the ZF receivers are derived. Also centralized MIMO systems, the entirety rate of the ZF receivers in distributed MIMO systems is also studied and lower and upper bounds on the sum rate are derived.

Basic Precoding: To spread extreme spectral efficiency, the ZF precoder needs less computation than the MF precoder, an unexpected result based on the detail that fewer users are helped for the ZF precoder at top spectral efficiency. Note that the user collection problem may convert more complex as the number of users raises [8].

Multi-Cell Precoding: Linear precoders can similarly be used in multi-cell massive MIMO systems, wherever cooperating BSs are considered to jointly serve users in different cells [7]. Dependent on the overhead of the info exchange among the BSs, there are 3 scenarios: single-cell processing, coordinated beam forming, and network MIMO multi-cell processing. Single-cell processing is founded on the hypothesis that BSs first have channel information for users in their specific cells and no information near users in other cells. Corresponding beam forming abuses channel information from a BS to users of all cells. The system MIMO multi-cell processing idea is based on full cooperation between BSs, where not only channel information then also data is globally shared.

1. Various Techniques

MMSE based: numerous detection schemes for manifold antenna systems making use of the lattice-reduction algorithm are projected. They displayed that the straightforward way to achieve MMSE exposure after lattice-reduction does not yield satisfying outcomes [14]. In its place, they planned a new method, wherever LR is applied to a prolonged system model. In combining with successive interference cancellation, this policy nearly leads to maximum-likelihood performance. Additionally, we examined the impact of a sorted QR decomposition on the LLL algorithm plus demonstrated that SQRD can intensely decrease the computational energy. Thus, we reached at a near-optimum detector with very low difficulty [17].

Minimum Mean Square Error (MMSE) equalizer for 2x2 MIMO channel

In the first time slot, the received signal on the first receive antenna is,

$$y_1 = h_{1,1}x_1 + h_{1,2}x_2 + n_1 = [h_{1,1} \ h_{1,2}] \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + n_1$$

The received signal on the second receive antenna is,

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

$y_2 = h_{2,1}x_1 + h_{2,2}x_2 + n_2 = [h_{2,1} \ h_{2,2}] \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + n_2$. where y_1, y_2 ...are the received symbol on the first and second antenna respectively,

$h_{1,1}$ is the channel from 1st transmit antenna to 1st receive antenna,

$h_{1,2}$ is the channel from 2nd transmit antenna to 1st receive antenna,

$h_{2,1}$ is the channel from 3rd transmit antenna to 2nd receive antenna,

$h_{2,2}$ is the channel from 2nd transmit antenna to 2nd receive antenna,

x_1, x_2 are the transmitted symbols and

n_1, n_2 is the noise on 1st, 2nd receive antennas.

ZF based : receivers usually need higher BS total power consumption than the MMSE based receivers to uphold the similar SINR at the receiver. The power consumption of the indication processing segment is also an vital factor to be measured in determining the complete BS total power consumption. In certain cases, the power consumption of the signal processing element may surpass the transmission power savings gained from receive diversity gains (multiple receive antennas) and receiver IC systems. It might also contribute to the rise in the BS total power consumption more meaningfully than the additional transmission power wanted to maintain the receiver SINR in the presence of inter-cell interference. In over-all, the MMSE-SIC receiver is the well-organized, if the lowest BS total power consumption [11]. Equivalently,

$$y = Hx + n$$

To solve for x , The **Zero Forcing (ZF) linear detector** for meeting this constraint $WH=1$. Is given by,

$$W = (H^H H)^{-1} H^H$$

Using the **Zero Forcing (ZF)** equalization, the receiver can obtain an estimate of the two transmitted symbols x_1, x_2 , i.e.

$$\begin{bmatrix} \hat{x}_1 \\ \hat{x}_2 \end{bmatrix} = (H^H H)^{-1} H^H \begin{bmatrix} y_1 \\ y_2 \end{bmatrix}$$

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

SIC based: This method is of low computational complexity but can achieve a moderate performance. The performance more deteriorates if the per layer encoders are traded by just one encoder for all layers. Here, the intrusion withdrawal does not profit from the decoding advance of the previously perceived layers. All this persuades the strategy of a more flexible, upgraded detector. A capable approach to this problem looks to be an iterative receiver structure. The ideal detector within this iterative building is an a posteriori probability (APP) detector causing inappropriately a great computational complexity. A suboptimal, less complex method is the request of an adaptive linear filter as detector. Such a method has been proposed in [2] for multiuser detection, in [3] for occurrence selective channels and in [4] for threaded. In this article the addition to generalized MIMO systems is examined [18].

In classical **Successive Interference Cancellation**, the receiver arbitrarily takes one of the estimated symbols, and subtracts its effect from the received symbol y_1 , and y_2 . However, we can have more intelligence in choosing whether we should subtract the effect of x_1 first or x_2 first. To make that decision, let us find out the transmit symbol (after multiplication with the channel) which came at higher power at the receiver. The received power at the both the antennas corresponding to the transmitted symbol x_1 is,

$$P_{x_1} = |h_{1,1}|^2 + |h_{2,1}|^2.$$

The received power at the both the antennas corresponding to the transmitted symbol x_2 is,

$$P_{x_2} = |h_{1,2}|^2 + |h_{2,2}|^2.$$

If $P_{x_1} > P_{x_2}$ then the receiver decides to remove the effect of x_1 from the received vector y_1 , and y_2 and then re-estimate x_2 .

Expressing in matrix notation,

$$r = h x_2 + n$$

II. CHALLENGES AND ISSUES FACED IN MAKING MIMO

1) *Propagation Models:* Most current work on massive MIMO is founded on the evidence that as the number of antennas raises, the individual user networks are still spatially uncorrelated and their channel vectors asymptotically develop pairwise orthogonal under favorable propagation conditions. Moreover, very vastly correlated frequency vectors cannot be purified orthogonal by increasing the number of antennas [16]. This advises that user scheduling would be a critical component of huge MIMO systems and is considerable more important than in regular MIMO implementation wherever more complicated signal dispensation can be used to separate spatially linked users.

2) *Modulation:* To build a BS with a large number of antennas, low-cost power-efficient RF amplifiers are required; single-carrier transmission is capable to attain near-optimal sum-rate performance at low-transmit-power-to-receiver-noise-power ratios, deprived of requiring equalization at the receiver and multi-user resource sharing. Whether this is likely for more general and difficult scenarios needs further investigation.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

3) *Hardware Impairments*: Only imperfect work has been done on the effect of hardware impairments on massive MIMO systems. Hardware impairments can lead to channel estimate error and a capacity ceiling even though a high array increase can still be realized with an increase in the number of antennas at the BS. The user side damage is simpler compared to the BS side. Fortunately, the pilot contamination subject in the non-ideal case is really easier to mitigate associated to the ideal case

III. LITERATURE SURVEY

Hoydis, Jakob et al. [2]: They differentiate massive MIMO from “classical” MIMO as a specific operating condition of cellular networks wherever multiuser interference, channel estimation errors, and noise have a small impact associated to pilot contamination. Massive MIMO delivers another to cell-size shrinking, the outdated way of increasing the network capacity. System model explanations for channel estimation, pilot contamination, and channel path loss and antenna connection for each link. **Jungnickel et al. [4]**: They analyze recent attainments in the transition from theoretical to practical ideas and note future research guidelines. They displayed in measurements with macro-plus-small cell scenarios that spectral efficiency can be better by flexible clustering plus efficient user collection, and that adaptive response compression is useful to decrease the above significantly. Moreover, we display in sizes that fast feedback reporting mutual with advanced channel prediction are able to mitigate the impairment effects of JT CoMP. **Lu, Lu, et al. [15]**: In this weekly, they presented an inclusive overview of state-of-the-art research on the topic, which has newly attracted considerable attention. We initiate with an information hypothetical analysis to illustrate the conjectured rewards of massive MIMO, and then we address enactment issues related to channel estimation, finding and precoding schemes.

IV. CONCLUSION

In this article, we have widely described massive MIMO systems from several different outlooks. By providing a BS with a big number of antennas, spectral also energy efficiency can be intensely improved. Conversely, to get the profits of massive MIMO a reality, significant additional research is desired on a number of problems, comprising channel correlation, hardware applications and impairments, interference organization, and modulation.

REFERENCES

- [1] Larsson, Erik G., et al. "Massive MIMO for next generation wireless systems." *IEEE communications magazine* 52.2 (2014): 186-195.
- [2] Hoydis, Jakob, Stephan Ten Brink, and Mérouane Debbah. "Massive MIMO in the UL/DL of cellular networks: How many antennas do we need?." *IEEE Journal on selected Areas in Communications* 31.2 (2013): 160-171.
- [3] Lu, Lu, et al. "An overview of massive MIMO: Benefits and challenges." *IEEE journal of selected topics in signal processing* 8.5 (2014): 742-758.
- [4] Jungnickel, Volker, et al. "The role of small cells, coordinated multipoint, and massive MIMO in 5G." *IEEE Communications Magazine* 52.5 (2014): 44-51.
- [5] Swindlehurst, A. Lee, et al. "Millimeter-wave massive MIMO: The next wireless revolution?." *IEEE Communications Magazine* 52.9 (2014): 56-62.
- [6] Huh, Hoon, et al. "Achieving" massive MIMO" spectral efficiency with a not-so-large number of antennas." *IEEE Transactions on Wireless Communications* 11.9 (2012): 3226-3239.
- [7] Björnson, Emil, et al. "Massive MIMO systems with non-ideal hardware: Energy efficiency, estimation, and capacity limits." *IEEE Transactions on Information Theory* 60.11 (2014): 7112-7139.
- [8] Hoydis, Jakob, Stephan Ten Brink, and Mérouane Debbah. "Massive MIMO: How many antennas do we need?." *Communication, Control, and Computing (Allerton)*, 2011 49th Annual Allerton Conference on. IEEE, 2011.
- [9] Choi, Junil, David J. Love, and Patrick Bidigare. "Downlink training techniques for FDD massive MIMO systems: Open-loop and closed-loop training with memory." *IEEE Journal of Selected Topics in Signal Processing* 8.5 (2014): 802-814.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

- [10] Björnson, Emil, et al. "Massive MIMO systems with non-ideal hardware: Energy efficiency, estimation, and capacity limits." *IEEE Transactions on Information Theory* 60.11 (2014): 7112-7139.
- [11] Ngo, HienQuoc, Erik G. Larsson, and Thomas L. Marzetta. "Energy and spectral efficiency of very large multiuser MIMO systems." *IEEE Transactions on Communications* 61.4 (2013): 1436-1449.
- [12] Björnson, Emil, MariosKountouris, and MérouaneDebbah. "Massive MIMO and small cells: Improving energy efficiency by optimal soft-cell coordination." *Telecommunications (ICT), 2013 20th International Conference on.IEEE*, 2013.
- [13] Cui, Shuguang, Andrea J. Goldsmith, and Ahmad Bahai. "Energy-efficiency of MIMO and cooperative MIMO techniques in sensor networks." *IEEE Journal on selected areas in communications* 22.6 (2004): 1089-1098.
- [14] Björnson, Emil, Luca Sanguinetti, and MariosKountouris. "Deploying dense networks for maximal energy efficiency: Small cells meet massive MIMO." *IEEE Journal on Selected Areas in Communications* 34.4 (2016): 832-847.
- [15] Lu, Lu, et al. "An overview of massive MIMO: Benefits and challenges." *IEEE journal of selected topics in signal processing* 8.5 (2014): 742-758.
- [16] Yang, Nan, et al. "Safeguarding 5G wireless communication networks using physical layer security." *IEEE Communications Magazine* 53.4 (2015): 20-27.
- [17] Wubben, Dirk, et al. "Near-maximum-likelihood detection of MIMO systems using MMSE-based lattice-reduction." *Communications, 2004 IEEE International Conference on.Vol. 2.IEEE*, 2004.
- [18] Zimmermann, Ernesto, Wolfgang Rave, and Gerhard Fettweis. "On the complexity of sphere decoding." *Proc. International Symp.on Wireless Pers. Multimedia Commun., AbanoTerme, Italy. 2004.*