

Parameter Estimation of GFDM

M.Kaviya¹, Dr.S.Sumathi²

P.G. Student, Communication Systems, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India¹

Head of the Department, Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India²

ABSTRACT: Right now, explore parameter estimation for Generalised Frequency Division Multiplexing (GFDM) flags over recurrence specific blurring channels. In light of the attributes of the second request cyclostationary measurements of GFDM signals we create calculations to indiscriminately evaluate unadulterated square length, by and large square term, image span and number of subcarriers. The proposed algorithms are robust to timing, phase and carrier frequency uncertainties and don't require any a priori knowledge of the received signal. Simulation results verify the feasibility of the proposed algorithms.

KEYWORDS: Generalized Frequency Division Multiplexing, parameter estimation, signal analysis, digital modulation.

I. INTRODUCTION

In some particular areas of communications, like passive spectrum monitoring and spectrum sensing, the receiver features a little or no a priori knowledge of the received signals, such as symbol rate. However, most post-processing are supported the a priori knowledge of those parameters. For example, modulation identification, including feature-based (FB) algorithms and likelihood function-based (LB) algorithms, needs to sample the input signal at symbol rate. Accordingly, these technical parameters must be accurately estimated before conducting the remaining post-processing if they are unknown.

Over the past couple of decades, symbol rate estimation for signal carrier (SC) signals has been well addressed. Among all proposed algorithms, the most popular one is the cyclostationary-based methods due to their simplicity, availability, and robustness. The only drawback is that for signals with small excess bandwidth (low roll-off factor), estimation performance rapidly degrades as the search of the regenerated spectrum line may be plagued with spurious peaks. To address this issue, a maximum-likelihood (ML) function based algorithm has been developed. An effective algorithm has been also proposed modulation types with offset between in-phase and quadrature components, such as OQPSK signals. In general, symbol rate estimation for SC signals has already been well addressed.

Due to the various applications of orthogonal frequency division multiplexing (OFDM), its parameter estimation has been also intensively studied in the past decade. The second-order cyclostationarity is capable of regenerating spectrum lines associated with the desired parameters, including symbol duration and cyclic prefix duration of OFDM signals.

Due to their low computational complexity and robustness to channel distortion, the cyclostationary-based algorithms have become most popular. In particular, the algorithm in exhibits outstanding performance under severe time-dispersive channels and low signal-to-noise ratio (SNR) environment. In general, parameter estimation for OFDM signals has already met the requirement of practical necessity. Recently, generalized frequency division multiplexing (GFDM) has become the most promising modulation scheme for the air interface of 5G networks and is also with potential applications in other wireless networks. OFDM and SC signals can be regarded as special cases of GFDM signals. Although there has been investigation on cyclostationary-based detection for standard GFDM signals through simulation under ideal channel environments to the best of our knowledge, no literature has addressed blind parameter estimation for GFDM signals, especially under the practical scenarios with frequency-selective fading channels, carrier frequency,

phase and timing offsets. As the structure of GFDM signals is more sophisticated than the existing signals, more parameters need to be estimated under the aforementioned severe conditions. Accordingly right now, will examine daze parameter estimation for GFDM signals. The second-request cyclostationarity under recurrence specific channels with parameter unsure ties is first examined. At that point the comparing calculations for dazzle estimation of unadulterated square span, in general square term, image length, and number of subcarriers are created.

II. RELATED WORK

A flexible multicarrier regulation plan, named Generalized Frequency Division Multiplexing (GFDM) has additionally been proposed for the air interface of 5G systems. The flexibility of GFDM permits it to cover CP-OFDM and single-bearer recurrence area adjustment (SC-FDE) as extraordinary cases. GFDM is predicated on the balance of free squares, where each square contains assortment of subcarriers and subsymbols. The subcarriers are filtered with a model filter that is circularly moved in time and recurrence area. This procedure diminishes the OOB discharges, making divided range and dynamic range allotment plausible without extreme obstruction in occupant administrations or different clients. The subcarrier filtering can result in non symmetrical subcarriers and both between image obstruction (ISI) and between transporter impedance (ICI) may emerge. By and by, efficient getting methods can wipe out this obstruction, for example a coordinated filter beneficiary with iterative impedance wiping out can do a comparable image mistake rate (SER) execution as OFDM over various channel models.

GFDM might be a promising answer for the 5G PHY layer since its flexibility can address the different necessities. For ongoing applications, the sign length must be decreased to fulfill certain idleness prerequisites. Since GFDM is confined during a square structure of MK tests, where K subcarriers convey M subsymbols every, it's conceivable to style the time-recurrence structure to coordinate the time limitations of low inactivity applications.

Distinctive filter drive reactions are frequently wont to filter the subcarriers and this decision influences the OOB emanations and in this manner the SER execution. As will be appeared, GFDM permits building signals in their recurrence and time qualities. In this manner, the plan holds all primary benefits of OFDM at the estimation of some extra execution multifaceted nature. In a GFDM hinder, the overhead is kept little by including one CP for an entire square that contains various subsymbols. This benefit are frequently wont to improve the unearthly efficiency of the framework or it are regularly exchanged for a further cyclic suffix (CS), which permits to loosen up the synchronization necessities of different clients in a MTC situation. Moreover, all significant synchronization calculations created for OFDM are regularly adjusted for GFDM.

Obviously, numerous information different yield (MIMO) will be a key component in 5G systems. Right now show that space-time coding (STC) are regularly viably joined with GFDM for accomplishing transmit and get assorted variety. In spite of the fact that the expanded unpredictability of GFDM will most likely be reasonable with the advancement of gadgets, our proposed conspire are frequently actualized with the present innovation as of now. A flexible, adjustable Field Programmable Gate Array (FPGA) stage has been wont to build up a GFDM evidence of-idea and testbed for exploratory research. An efficient beneficiary structure is utilized to actualize the coordinated filter or zero-constraining collectors bolstered any model filter.

This work contributes with the resulting new angles: We present an inside and out portrayal and numerical assessment of two methods that improve the phantom properties of GFDM, specifically embeddings protect images and squeezing the square limits. SER execution is explored with new scientific articulations for the AWGN, recurrence specific and time-variation channel.

A method for applying space time coding to GFDM is proposed, which takes into account full decent variety gain in spite of the very reality that the waveform is non-symmetrical. Systems to synchronize the beneficiary which are known from OFDM are adjusted to GFDM. In any case, during this case, furthermore the imperative of protecting the incredible otherworldly properties of the waveform is tended to. The bit blunder rate execution of straight and iterative GFDM collectors is assessed together with mistake control coding.

A few arrangements of GFDM parameters are introduced, which work a recommendation the best approach to configure the transmitter and beneficiary such it can address the four 5G application situations. Furthermore, ultimately, an efficient collector engineering is displayed that grants to execute get filters with discretionary data transmission.

III. SYSTEM MODEL

A. GFDM TRANSEIVER

By and large, the framework model can be found in the square graph of the framework is shown in Figure 1. GFDM is a multicarrier transmission plot based squares where each square contains information images complex KM that is disseminated to constantly M and recurrence space K . Each subcarrier in GFDM divided at $1/TS$ and each square has a term of MTS GFDM where TS is the image span.

The testing recurrence is set to N/TS coming about N tests per image and MN tests per square. GFDM utilizing beat molding channel is roundabout with a periodicity n/NM (n Nod M N) so as to accomplish the tail-gnawing, for example roundabout convolution, at the transmitter. The transmitted sign will be given Saleh Model before being passed to the receiving wire as appeared in Figure 1.

The output signal GFDM transmission operation before CP insertion can be expressed as

$$x[n] = \sum_{m=0}^{M-1} \sum_{k=0}^{K-1} d_{km} g_{km}[n] \quad n=0, \dots, MN-1$$

where

$$g_{km}[n] = g[(n - MN)_{|MN}] e^{-j2\pi kn/N}$$

is a shifted of the circular prototype filter $g[n]$, which is delayed by mN in time and k in frequency. $g_{km}[n]$ are weighted by the complex valued data symbols d_{km} , bounded by nature independent and identically distributed with variance and are taken from a standard X-QAM alphabet to get a complete transmission signal. The type of pulse shaping used in this study can be seen. M is the number of complex data symbols with $m=0,1,2, \dots, M-1$, K is the number of subcarriers with $k=0,1,2, \dots, K-1$ and N is the number of samples per symbol.

Equation can be rewritten as

$$X=Ad$$

X is the column vector that contains the samples of $x[n]$, A is a transmitter matrix $NM * KM$ the vector with the complex data symbols d and A contain the data symbols and therefore the shifted prototype filters within the following order:

$$A = (g_{0,0}, \dots, g_{K-1,0}, g_{0,1}, \dots, g_{K-1,M-1})$$

$$d = (d_{0,0}, \dots, d_{K-1,0}, d_{0,1}, \dots, d_{K-1,M-1})^T$$

with g_{km} is a column vector that contains a sample of $g_{km}[n]$. Before being transmitted through the remote channel at that point included cyclic prefix as NCP tests for defeating Inter Symbol Interference (ISI) among square GFDM. Since only one CP is required for all sub image the CP overhead of GFDM essentially diminished contrasted and OFDM.




Fig.1 Block diagram of the GFDM transceiver

On the receiver side synchronized time and frequency assuming perfect synchronization. Cyclic prefix also eliminated so that the channel matrix H can be replaced with a circular convolution matrix of size $N * N$. This allows for applications such as zero forcing channel equalization as applied to OFDM. Equations can be rewritten as follows transceiver

$$Y = HAd + w$$

The received signal after equalization channel into

$$\hat{z} = H^{-1}HA\hat{d} + H^{-1}\hat{w} = A\hat{d} + \hat{\tilde{w}}$$

Linear demodulation on the signal can be written $\hat{d} = Bz$. B is a matrix receiver $KM * KM$.

IV. EXPERIMENTAL RESULTS

In this section, we will evaluate the performance of the proposed algorithms for the three parameters of GFDM signals. The GFDM is with 64 subcarriers and 9 symbols within one block.

A. Overall Block Duration Estimation

The performance for both the coarse and fine search results are provided in Figure 2 and 3. Similar to the last subsection, as the performance relies on the estimate of the pure block duration, NCW has also major impact on the performance and signals with non-CISI-free filter also exhibit evidently worse performance than that with the CISI-free filters. Furthermore, as the magnitude of the CAF at the desired delay, $k = MPK$, and CF, $\alpha = 1$ PNA, may be different on the filter types, thus the corresponding performance is different. Nevertheless, as the CP only occupies a small proportion of the overall block duration, the impact of the filter types and the roll off factor is limited.

From the figure, the signal with the first order Xia filter exhibits slightly better performance than that with the RRC filter. The difference between the signals with the same filter but different roll-off factors is so minor and the performance can be regarded as the same.




Fig 2. Coarse search of block duration estimation




Fig 3. Fine search of block duration estimation

B. Symbol Duration Estimation

The performance for both the coarse and fine search results is demonstrated in Fig. 4 and 5. As indicated in Section IV.C, the symbol duration can be simply obtained and is mainly dominated by the estimate of the pure block duration for the RC filter. Thus from the figure, the performance for the two parameters are close to each other. For the RRC and the Xia filters, as WCAF is manipulated at $k=0$, thus the impact of filters and the roll-off factor is relatively more prominent. From the figure, the signal with the first-order Xia filter exhibits better performance than that with the RRC filters.




Fig 4. Coarse search of symbol duration estimation




Fig 5. Fine search of symbol duration estimation

For the same type of filters, the signal with a larger roll-off factors also exhibits evident better performance due to a larger magnitude of CAF at the desired delay and CF. Furthermore, for $NCW=0$, a series of spectrum lines will appear at integer times of the reciprocal of the overall symbol duration and thus result in relatively larger interference than the one with $NCW=0$. Therefore, a better performance both in coarse and fine search can be obtained for GFDM signals with $NCW=0$.

C. Number of Subcarriers Estimation

For GFDM signals with spectrum holes, we will estimate the bandwidth of each sub-GFDM signal and combine them together. The normalized bias and NMSE are illustrated in Figure 6 and 7. From the figure, the normalized bias is close to zero when SNR is above -4 dB. However, the NMSE still remains relatively large as a random error exists for almost all estimates. Furthermore, as the estimation of bandwidth is independent of parameter set, the difference in performance among signals with different parameters is consistent with that of the symbol duration estimation.




Fig 6. Normalised bias




Fig 7. NMSE

V. CONCLUSION

In this paper, the second-order statistics based algorithms have been proposed for the estimation of four parameters of GFDM signals, including the pure block duration, the overall block duration, the symbol duration and the number of subcarriers. The feasibility under a low SNR in frequency selective fading channels has been verified through simulation. Furthermore, the performance under different parameters has been also compared. The proposed algorithms require no a priori knowledge of the received signal and are computationally efficient. These advantages make it promising in some particular areas of communications, such as passive radio monitoring and spectrum sensing.

REFERENCES

- [1] Maximilian Matthe, Dan Zang and Gerhard Fettweis, "Low Complexity Iterative MMSE-PIC Detection for MIMO- GFDM ," IEEE Transaction on Communication, pp. 1-30, 2017.
- [2] Shravan Kumar Bandari, V. V. Mani and A. Drosopoulos, "Convolutional codes for MGFDM system ," IEEE Conference, pp 545-550, 2017.
- [3] Ahmad Nimr, Maximilian Matth e, Dan Zhang, and Gerhard Fettwei, "Optimal Radix-2 FFT Compatible Filters for GFDM ," IEEE Communication letters, vol. 21, no. 7, pp. 1497-1500, July 2017.
- [4] Seungyul Han, Youngchul Sung, and Yong H. Lee, "Filter Design for Generalized Frequency-Division Multiplexing, " IEEE Transactions on Signal Processing, vol. 65, no. 7, pp. 1644-1659, April 1, 2017.
- [5] Liang Chang, Geoffrey Ye Li, Jingchun Li, and Rong Li, "Blind Parameter Estimation of GFDM Signals Over Frequency-Selective Fading Channels," IEEE Transactions on Communication, vol. 64, no.3, pp. 1120-1131, March 2017
- [6] K. C. Bulusu, H. Shaiek, D. Roviras, and C. Laetitia, "PA Linearization of FBMC-OQAM Signals with Overlapped Recursive Error Correcting Predistortion," International Symposium on Wireless Communication Systems (ISWCS), pp. 533-537, 2016.
- [7] A. Ortega and L. Fabbri, "Performance evaluation of GFDM over nonlinear channel," ICTC 2016, pp. 12-17, 2016.
- [8] L. Sendrei and S. Marchevsk, "Nonlinear Noise Estimation and Compensation in GFDM Based Communication Systems for Cognitive Radio Networks", International Conference in Radioelektronika (RADIOELEKTRONIKA), pp. 313-316, 2015.
- [9] I. F. Akyildiz, S. Nie, S. C. Lin, and M. Chandrasekaran, "5G roadmap: 10 key enabling technologies," Comput. Networks, vol. 106, pp. 17-48, 2016.

International Journal of Innovative Research in Science, Engineering and Technology
An ISO 3297: 2007 Certified Organization *Volume 9, Special Issue 1, March 2020*
8th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '20)
18th-19th March 2020

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

- [10] D. Zhang, L. L. Mendes, M. Matthé, I. S. Gaspar, N. Michailow, and G. P Fettweis, "Expectation Propagation for Near-Optimum Detection of MIMO-GFDM Signals," *IEEE Trans. Wirel. Commun.*, vol. 15, no. 2, pp. 1045–1062, 2016.
- [11] M. Matthe, L. L. Mendes, N. Michailow, D. Zhang, and G. Fettweis, "Widely Linear Estimation for Space-Time-Coded GFDM in LowLatency Applications," *IEEE Trans. Commun.*, vol. 63, no. 11, pp. 4501–4509, 2015.
- [12] J. Datta, H. P. Lin, D. B. Lin, "A method to implement interference avoidance based MIMO-GFDM using spatial modulation", *IEEE International Conference on Advanced Technologies for Communications*, pp. 572-577, 2015.
- [13] G. Fettweis and S. Alamouti, "5G: Personal mobile Internet beyond what cellular did to telephony," *IEEE Commun. Mag.*, vol. 52, no. 2, pp. 140–145, Feb. 2014.
- [14] G. Wunder et al., "5GNOW: Non-orthogonal, asynchronous waveforms for future mobile applications," *IEEE Commun. Mag.*, vol. 52, no. 2, pp. 97–105, Feb. 2014.
- [15] N. Tadayon and S. Aissa, Modeling and Analysis of Cognitive Radio Based IEEE 802.22 wireless regional area networks, *IEEE Trans. on Wireless Commun.*, vol. 12, no. 9, pp. 4363-4375, Sep. 2013.