



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 11, November 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.569

 9940 572 462

 6381 907 438

 ijrset@gmail.com

 www.ijrset.com



Design and Implementation of IOT Based Saline Monitoring and Reporting System

Mrs.R. Anjanadevi¹, Jeevasuriyan S², Mandem Sudarshan Reddy³, Mathavatamilselvan M⁴,
Praveen H⁵

Professor, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering, Hosur,
Tamil Nadu, India ¹

U. G Scholars, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering, Hosur,
Tamil Nadu, India ²⁻⁵

ABSTRACT: As the world population is increasing, the requirement of health hindrance is additionally increasing day by day. Hence, it's obligatory for everybody during this world to require of their health properly. In these recent years, there's a speedy progress in treatment thanks to the technological advancement within the numerous fields of sensors, micro-controllers, and pc for reassuring quick recover of patients within the hospitals. the key and basic demand of the hospitalized patient is that each patient ought to be supplied with higher treatment and observation and will be equipped the proper quantity of important nutrition at the proper time. Among the assorted treatments, the saline medical aid is that the most vital that a lot of patients receive from the hospital. The bottle of saline is fed to the patients to treat dehydration and so improve their health. within the hospital, whenever a saline is fed to the patient, the patient must be incessantly administered by a nurse or a care taker. however sadly, they're some vital things, i.e. patient's blood re flexing into the saline tube system thanks to the negligence towards the saline completion and busy schedule of the accountable doctors, or the care takers, therefore a large variety of patients square measure dying or square measure being injured within the hospital. thence to forestall the patient from obtaining injured and to guard their lives throughout saline feeding hours, the saline level observance and automatic alert system has been developed. The projected system facilitates a classy methodology of dominant saline drop rate by observance the saline system remotely by victimisation IOT platform. The projected system consists of a sensing element used for observance the vital level of the saline liquid within the saline bottle and a mechanism which will stop the saline flow mechanically once the saline bottle is totally empty. This projected system will be utilised with efficiency in homes similarly as hospital.

KEYWORDS: saline monitor, IOT system, saline level detector.

I.INTRODUCTION

The Internet of Things (IoT) implies the employment of smartly connected devices and structures to utilize information collected by embedded sensors and actuators in machines and different physical things. this is often needed to unfold in real time completed the approaching years and this connection can discharge another estimation of organizations that improve the individual fulfilment of shoppers and gainfulness of endeavours. property engages web of Things by uniting normal things. convenience of those articles is essential in light-weight of the actual fact that basic protest level collaborations contribute towards mixture insight in IoT organize. The IoT can build the scope of administrations, every requiring shifting levels of information transfer capability, movableness and idleness. as an example, edges that are known with open eudaimonia or individual security can by and huge need low dormancy, but not high information transfer for capability in essence. On the opposite hand, edges that offer intelligence could likewise need high information transmission. In health centres, wherever patient's condition ought to be frequently discovered, it's unremarkably done by a doctor or different attendant. In developing countries like Asian nation thanks to famine of outlandish of doctors, it becomes strenuous once constant doctor must monitor several patients at the same time. therefore in such a condition, the doctor is also unaware of the condition of all the patients. within the case of AN emergency, even a bit delay in treatment could create a threat to patient's life. Our planned framework is useful in observant the sphere data and additionally dominant the sphere activities which supplies flexibility. dominant of each one in every of these tasks are going to be through remote detector systems related to web and can be addressed and performed by interfacing sensors. during this framework, we have a tendency to utilize totally different sensors for estimating conditions

3V3: - 3.3 V Power Pin.

GND: - Ground Pin.

RST: - Active Low Reset Pin.

EN: - Active High Enable Pin.

TX: - Serial Transmit Pin of UART.

RX: - Serial Receive Pin of UART.

GPIO0 & GPIO2: General Purpose I/O Pins. These pins decide what mode (boot or normal) the module starts up in. It additionally decides whether or not the TX/RX pins square measure used for Programming the module or for serial I/O purpose. To program the module victimisation UART, Connect GPIO0 to ground and GPIO2 to VCC or leave it open. To use UART for traditional Serial I/O leave each the pins open (neither VCC nor Ground) 12v Power provide is given to regulator for voltage regulation 12v to 5v then 5v provide is given to Wi-Fi device. VCC and GND pins square measure connected to regulator.

Relay to be activated the motor. It's connected to twelve provides then controlled by Wi-Fi device. HC-SR04 sensing element connected to Wi-Fi device. it's four pins. Positive and negative pins square measure connected to VCC and GND & another 2 pins square measure connected to Wi-Fi device. Buzzer indication used. It's connected to Wi-Fi device. It consists of 2 pins. IR sensing element are going to be connected to Wi-Fi device. it's 3 pins. VCC connected to positive and GND connected to negative. Output pin connected to Wi-Fi device.

V. FLOW CHART



Fig. 3 Flow Diagram of the saline monitor system

The flow chart outline which appeared in above fig. that speaks to a work process of saline monitoring system.

VI. WORKING

The saline observance system utilizes 12v power provide. the ability provide passes to Wi-Fi module ESP12E through transformer. 2 sensing elements named as IR and ULTRASONIC(HC-SR040) sensor connected to Wi-Fi module. unhearable sensing element detects the extent of saline, IR sensing element detects the reverse blood flow of the patient, whenever it detects the reverse blood, the BUZZER gets activated. A relay stops/runs motor through the directions given by Wi-Fi module. The nurse will analyze saline information through the applying program interface.

VII. EXPERIMENTAL SETUP

The circuit diagram consists the parts of core parts of ESP12e Wi-Fi device, 5v regulator, IR sensor, power supply, Relay, HC-SR04 sensing element, motor, buzzer. 12v Power provide is given to regulator for voltage regulation 12v to 5v then 5v provide is given to Wi-Fi device. VCC and GND pins are connected to regulator. Relay to be activated the motor. It's connected to twelve provides then controlled by Wi-Fi device. HC-SR04 sensing element connected to Wi-Fi device. it's four pins. Positive and negative pins are connected to VCC and GND & another 2 pins are connected to Wi-Fi device. Buzzer indication used. It's connected to Wi-Fi device. It consists of 2 pins. IR sensing element are

connected to Wi-Fi device. it's 3 pins. VCC connected to positive and GND connected to negative. Output pin connected to Wi-Fi device.

VIII. RESULT AND DISCUSSION



Fig. 2 Work done graph

X. LITERATURE SURVEY

1) Zeng, H., and Y. Zhao. "Design and implementation of liquid driblet primarily based motion sensing." Solid-State Sensors,

Normal saline is mostly referred as sterile answer of binary compound (NaCl) in water. The binary compound sterile answer is employed for nasal irritation, rinse contact lenses, blood vessel infusion and to scrub a replacement piercing. it's usually, to use traditional Saline in blood vessel drips (IVs), or the patients UN agency are unable to require fluids orally and are at risk of inflicting dehydration or blood disease. traditional saline contains nine grams of NaCl, and therefore the diffusion constant of NaCl is zero.93. the quantity of traditional Saline intake taken by patient is completely depends on state of patient however commonly it's between one.5 to three liters per day for associate degree adult. Generally, in hospitals saline level is monitored by nurses and patient's relatives.

2) Thongpance, Nuntachai, Yuttana Pititeeraphab, and Matida Ophasphanichayakul. "The style and construction of infusion pump calibrator."

There is invariably a necessity to see the saline level when bound time. the present system for saline level observance is incredibly time intense and inconvenient for nurses

3) Gavimath, Krishnamurthy Bhat, C. L. Chayalakshmi, R. S. Hooli, B. E. Ravishankera (2012) style and Development of Versatile Saline rate of flow mensuration System and GSM primarily based remote display because of increase within the population, there's a necessity for improvement in health care. as a result of the advancement in technology, the progress in medical field is fast. A reason behind this can be nothing however the mixture of medical and engineering disciplines. once the traditional Saline (NS) is to be placed intravenously then it's known as sterile

4) A. Phaniraj, Gayatri K, J. Thomas, and Dr S Prabhanja, Management of Saline and Electricity exploitation IOT, Journal of technology Engineering and software package Testing, 4(3), 2018

The device performance and accuracy were tested for the quantitative determination of saline levels. once lightweight is incident upon photodiode sensing element it sends a proof to Arduino and offers the output as values of red, blue, or inexperienced color through diode consistent with the alert message. The values of output voltages across photodiode against the saline level of the bottle within the sample were used for analysis. Out of those 3 levels every level incorporates a totally different analog input voltage across photodiode. as a result of this relationship, a standardisation curve was aforethought as shown in figure four and therefore the microcontroller is programmed consequently.



5) D. Ramya and Md.A. Hussain, a lightweight Weight Secured and economical Health observance System enforced Over IOT primarily based Networks, International Journal of Innovative Technology and Exploring Engineering (IJITEE), 8 (6), 2019

The utilization of an overseas patient observance system supported a LED-photodiode-based sensing element has enabled patient saline level observation at a stripped-down price. this technique is often used at the hours of darkness time conjointly once nurses may not be awake. The IoT-based system is efficient moreover it uses the minimum hardware attainable. the key difficulties visaged during this project were the clamping circuit mechanism of the saline tube and therefore the testing of various sensors.

XI. CONCLUSION

This project proposes the system which may mechanically monitor the saline rate by mistreatment ESP12E Wi-Fi device. It will wirelessly send data to nurse's or doctor's pc and show the ends up in the shape of saline bottle level and reverse flow of blood information may be updated in graph read. If any important condition means that send on-line notification to doctor/nurse with the assistance of IOT technology. The system is reliable, value effective and convenient for nurses. It may be reused for consecutive saline bottle. it's helpful for nurses similarly as doctors at rural hospitals. Nurses will simply monitor the saline level from distance. it's principally advantageous in the dark temporal order as there's no would like for nurses to travel to patient's bed to examine the amount of saline within the bottle.

REFERENCES

- [1] Mansi G. Chidgopkar, Aruna P. Phatale "AUTOMATIC AND cheap SALINE LEVEL observance SYSTEM mistreatment WIRELESS BLUETOOTH MODULE AND CC2500 TRANSRECEIVER " International Journal of analysis in Engineering and Technology; Volume:04 Issue: 09 |September-2018
- [2] C.C. Gavimath, Krishnamurthy Bhat, C.L. Chayalakshmi, R. S. Hooli and B.E. Ravishankera "DESIGN AND DEVELOPMENT OF VERSATILE SALINE rate measuring device AND GSM based mostly REMOTE display " International Journal of Pharmaceutical Applications Vol three, Issue 1, 2019.
- [3] Pattarakamon Rangsee, Paweena Suebsombut, Phakphoom Boonyanant "Low-Cost Saline driblet measuring System mistreatment for Common Patient space in Rural Public Hospital " The fourth Joint International Conference on data and Communication Technology, Electronic and engineering science (JICTEE) 978-1-4799-3855-1/14 2020
- [4] P. Kalaivani, T. Thamaraiselvi, P. Sindhuja and G. Vegha "Saline Level Observance System mistreatment Arduino UNO Processor " Asian Journal of engineering science and Technology (AJAST) Volume one, March 2018.
- [5] Priyadharshini.R, Mithuna.S, Vasanth Kumar.U, Kalpana Hindu deity. S, Dr. SuthanthiraVanitha.N. "Automatic blood vessel Fluid Level Indication System for Hospitals" International Journal for analysis in engineering science & Engineering Technology; Volume three Issue VIII, August 2020.

BIOGRAPHY



Mrs R. Anjana Devi.
Assistant professor,
Engineering Department,
Adhiyamaan college of Engineering,
Anna university.



Jeevasuriyan S,
Bachelor Of Engineering,
Adhiyamaan College of Engineering,
Anna University.



Mandem Sudarshan Reddy,
Bachelor Of Engineering,
Adhiyamaan College of Engineering,
Anna University.



Praveen H,
Bachelor Of Engineering,
Adhiyamaan College of Engineering,
Anna University.



Madhava tamilselvan,
Bachelor of Engineering,
Adhiyamaan college of Engineering,
Anna university.



**Impact Factor:
7.569**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details