



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 11, November 2021

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 7.569

9940 572 462

6381 907 438

[ijirset@gmail.com](mailto:ijirset@gmail.com)

[www.ijirset.com](http://www.ijirset.com)



# Energy Efficient Mobility Based Cluster Head Selection for Life Time Enhancement of Wireless Sensor Networks

Mr. Ashok kumar<sup>1</sup>, Baranidharan S<sup>2</sup>, Dhanraj M<sup>3</sup>, Bharathan S<sup>4</sup>, Mohan N<sup>5</sup>

Professor, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering, Hosur,  
Tamil Nadu, India <sup>1</sup>

U. G Scholars, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering, Hosur,  
Tamil Nadu, India<sup>2-5</sup>

**ABSTRACT:** Wireless sensing element networks (WSNs) contemplate a base station (BS) that communicates with unnumberable of wireless sensing element nodes by means that of a radio channel. information transmission and reception method square measure the main operations that consume power in WSN. Elimination of redundant information is vital issue in WSN, as a result of multiple nodes could sense constant overlapped space. This action can scale back the power consumption and use the information measure usage. because of the increasing WSN information packet congestion drawback within the cloud network, there's associate degree increasing risk for emergency information to not be processed on time or the chance of information obtaining lost within the cloud network. This project focuses on the hierarchical routing protocol that's supported cluster formula particularly low energy adaptative cluster hierarchy protocol (LEACH) that expands total network period, and it's the primary hierarchical energy custom-made protocol. Our planned protocol is termed Node Ranked-LEACH (NR-LEACH) that enhances the performance of the LEACH protocol. And additionally prioritizes emergency information packet routing supported the information symbol victimisation the Prioritizes WSN information Packet Routing.

**KEYWORDS:** Wireless sensing element network, cluster, LEACH, sensing element nodes, mobility, cluster head, routing, Homogeneous.

## I. INTRODUCTION

Wireless sensing element Networks (WSNs) will be outlined as a self-configured and infrastructure-less wireless networks to observe physical or environmental conditions, like temperature, sound, vibration, pressure, motion or pollutants and to hand and glove pass their information through the network to a main location or sink wherever the information will be determined and analysed. A sink or base station acts like associate degree interface between users and also the network. One will retrieve needed data from the network by injecting queries and gathering results from the sink. Typically, a wireless sensing element network contains many thousands of sensing element nodes. The sensing element nodes will communicate among themselves victimisation radio signals. A wireless sensing element node is supplied with sensing and computing devices, radio transceivers and power parts. The individual nodes in a very wireless sensing element network (WSN) square measure inherently resource constrained: they need restricted process speed, storage capability, and communication information measure. when the sensing element nodes square measure deployed, they're answerable for self-organizing associate degree applicable network infrastructure usually with multi-hop communication with them. Then the on-board sensors begin grouping data of interest. Wireless sensing element devices additionally answer queries sent from a "control site" to perform specific directions or give sensing samples. The operating mode of the sensing element nodes is also either continuous or event driven. world Positioning System (GPS) and native positioning algorithms will be accustomed acquire location and positioning data. Wireless sensing element devices will be equipped with actuators to "act" upon sure conditions. These networks square measure generally additional specifically referred as Wireless sensing element and mechanism Networks. Wireless sensing element networks (WSNs) change new applications and need non-conventional paradigms for protocol style because of many constraints. Thanks to the need for low device complexness alongside low energy consumption (i.e. long network lifetime), a correct balance between communication and signal/data process capabilities should be found.



**II. OBJECTIVE**

The objective of this project is to increase the lifetime of wireless sensor network under Cluster Head Selection and Prioritize Data Packets based on the application. To provide Fast Data Transmission and also to Reduce overhead by dynamic clustering.

**III. EXISTING METHOD**

Data transmission and reception method are the most important operations that consume power in WSN. Elimination of redundant information is vital issue in WSN, as a result of multiple nodes could sense an equivalent overlapped space. This action can scale back the general power consumption and use the information measure usage. Problems in range information routing in full IOT networks. Residual-Low Energy adjustive cluster Hierarchy (R-LEACH) Low Energy adjustive cluster Hierarchy-K suggests that protocol (LEACH-K) Weighted K-means based mostly LEACH-C (WLEACH-CK) Generic severity-based prioritized packet process Token-Oriented in-network Prioritization (TOP)

**IV. PROPOSED METHOD**

Enhanced protocol referred to as Node Ranked-LEACHA - clustering-based protocols adapt the employment of energy by giving a balance to all or any nodes to become a cluster head. Prioritizes WSN information Packet Routing - detector driven resolution to range WSN information routing in full IoT networks.

**V. METHODOLOGY**

1. WSN Simulator
2. CH Selection
3. CH Prioritization
4. Data Packet Prioritization
5. Data Routing and Transmission
6. Performance Evaluation

**VI. BLOCK DIAGRAM**




Fig. 1 Flow Diagram of the node generation



VII.RESULT AND DICUSSION

Sno	Monitor	Sensor	Energy	RSSI	Location	Delivered	Received	Delay
1	Environmental	Temperature	79	29	10.3433,78.9712	70	38	4
2	Environmental	Temperature	33	41	10.4533,78.3021	74	46	6
3	Environmental	Humidity	43	22	10.4533,78.3021	73	59	2
4	Environmental	Humidity	96	47	10.4533,78.3021	55	94	1
5	Environmental	Humidity	40	65	10.4533,78.3021	83	17	5
6	Health	Temperature	48	32	11.5433,79.1023	34	32	3
7	Health	Temperature	71	43	10.3433,78.9712	96	29	2
8	Health	Temperature	93	57	10.4533,78.3021	28	62	4
9	Health	Heart Beat	48	44	11.5433,79.1023	35	18	6
10	Health	Heart Beat	74	74	10.4533,78.3021	32	61	2

Fig. 2 Data sets




Fig. 3 Simulated output




Fig. 4 Model graph






Fig. 5 Graph for the simulated output

### VIII. LITERATURE SURVEY

1. HetEng: Associate in Nursing Improved Distributed Energy economical cluster theme for Heterogeneous IoT Networks

Author: Hamed Moasses; AbdulbaghiGhaderzadeh; KeyhanKhamforoosh Year: 2021

Overview

Network time period is usually a difficult issue in powered networks thanks to the issue of recharging or exchange nodes in some eventualities. cluster strategies ar a promising approach to tackle this challenge and prolong time period by with efficiency distributing tasks among nodes within the cluster. this study aimed to boost energy consumption in heterogeneous IoT devices victimisation Associate in Nursing energy-aware cluster methodology. during a heterogeneous IoT network, nodes (i.e., powered IoT devices) will have a range of energy profiles and communication capabilities. Most of the present cluster algorithms have neglected the heterogeneity of energy capability among nodes and assumed that they're of an equivalent energy. during this work, we tend to gift HetEng, a Cluster Head (CH) choice method that extended Associate in Nursing existing cluster algorithmic rule, named Smart-BEEM. to the current finish, we tend to projected a applied mathematics approach that distributes energy consumption among extremely energetic nodes within the topology by perpetually dynamical the CH role between the nodes supported their real energy levels (in joules). Experimental results showed that HetEng resulted during a vi.6% increase of alive nodes and three improvement in residual energy among the nodes incomparison with Smart-BEEM. Moreover, our method reduced the total number of iterations by 1 % on average.

2. clump Isolated Nodes to boost Network's Life Time of WSNs for IoT Applications.

Author: Vrince Vimal; KamredUdham Singh; Abhishek Kumar; Sachin Kumar Gupta; M. Rashid; R. K. Saket; SanjeevikumarPadman Year:2021

Overview

Because of the metaphysical shift within the technological era, the globe is witnessing machine to machine (M2M) communication. Sensors area unit ubiquitous, thanks to that wireless device networks (WSNs) area unit developing as a key sanctioning technology for the web of Things (IoT). M2M interaction poses a severe threat to the time period of the network. clump plays a necessary role in elevating the energy potency of the WSN. notably, uniform distribution of cluster heads (CHs) is crucial for achieving higher network time period and uninterrupted sensing from the world below observation. For this, we tend to propose AN economical two-fold clump algorithmic program, specifically second-fold clump (SFC). within the initial part, the choice of CH is formed supported zonal residual energy and zonal degree of property. within the second part, the leftover nodes called isolated nodes area unit clumped. CH is chosen supported the zonal degree of property to confirm that energy is disbursed (almost) uniformly by all the nodes. This uniformity makes it appropriate for integration with the IoT. to seek out out the effectuality of SFC, carried rigorous experimental study out wherever it's compared to 2 existing clump algorithms. The simulation results show that SFC outperforms its counterparts. The results showed that SFC improved network time period by some nine.6% and 10.2% compared to regional energy-aware clump theme and Residual-Low Energy adjustive clump Hierarchy (R-LEACH), severally.



### 3. A clump Routing algorithmic program for Extending the Lifecycle in WSN

Author: Hongbing Li; Xiaolong Liu; rule Luo; FTO Luo; Meng Huang; KunlinXie; Juan Chinese Year:2020

#### Overview

In order to increase the lifetime of wireless device networks and improve the soundness of wireless device networks, a cluster head election mechanism supported energy centre of gravity and regional segmentation is planned. The device network observation space was divided into finite sub regions, and also the common nodes of every sub region competed for cluster heads in their own regions, that created the distribution of cluster heads within the whole network additional uniform. every sub-region node is chosen for the cluster head supported 2 factors: energy centre and communication distance. The cluster head is chargeable for receiving the information perceived by standard nodes within the region, and also the received data is amalgamate and compressed and transmitted to the bottom station, so finding the issues of uneven cluster head distribution and unbalanced node energy loss within the clump algorithmic program. The simulation results show that compared with the normal LEACH clump algorithmic program and also the improved LEACH-M algorithmic program, the new algorithmic program are able to do the aim of leveling the energy loss of every node, effectively cut back the general energy loss of the device network, and so extend the network life cycle.

### 4. Energy economical clump Protocol supported Binary urochordate Swarm algorithmic program for Heterogeneous Wireless device Networks

Author: Qiang Tu; Loloishtong Liu; Yi Xie; Xingcheng Liu Year: 2020

#### Overview

Energy potency is one in all the key challenges in wireless device network (WSN) applications. Cluster-based routing may be a well-known topology management technique, that is taken into account as non-deterministic polynomial (NP)-hard. during this work, the issues of energy-efficient clump approach and routing improvement between cluster heads (CHs) and also the sink area unit studied. we tend to gift AN energy balanced clump protocol mistreatment binary urochordate swarm algorithmic program (ECBS) for heterogeneous WSNs. urochordate swarm algorithmic program (SSA) may be a novel meta-heuristic algorithmic program with sturdy international search capability. we tend to introduce key factors like CHs energy, cluster quality, and network coverage into the independent agency to seek out the best clump theme. so as to any effectively utilize energy and minimize energy expenditure, we tend to propose a technique referred to as the two-level gradient forwarding tree determined by a price operate. during this technique, the only hop and multi-hop transmission manners for the routing between CHs and also the sink area unit provided. Experimental results indicate that the planned routing effectively extends the soundness amount and life of the general network in comparison with different famous cluster-based routing protocols.

### 5. Prioritization of Mobile IoT knowledge Transmission supported knowledge Importance Extracted From Machine Learning Model

Author: Yuichi Inagaki; Ryoichi Shinkuma; Takehiro Sato; Eiji Oki Year: 2019

#### Overview

Predicting amount of your time abstraction knowledge from information collected by the mobile web of Things (IoT) devices is one resolution to the socialissues associated with road traffic. The mobile IoT devices for time period abstraction data prediction generate an especially high volume of information, creating it not possible to gather all of it through mobile networks. though some previous works have reduced the amount of transmitted knowledge, the prediction accuracy of time period abstraction data remains not ensured. Therefore, this paper proposes AN IoT device system that reduces the number of transmitted knowledge used as input for time period prediction whereas maintaining the prediction accuracy. the most contribution of this paper is that the planned system controls knowledge transmission from the mobile IoT devices supported the importance of information extracted from the machine learning model used for the prediction. Feature choice has been wide used for extracting the importance of information from the machine learning model. Feature choice strategies were conjointly accustomed scale back communication overhead in distributed learning. in contrast to the standard usage of feature choice strategies, the planned system uses them to manage the info transmission of the mobile IoT devices with priority. during this paper, the planned system is evaluated with a real-world vehicle quality dataset in 2 sensible eventualities victimisation the random forest model, that is AN extensively used machine learning model. The analysis results show that the planned system reduces the number of transmitted computer file for time period prediction whereas achieving a similar level of prediction accuracy as benchmark strategies.



## IX. CONCLUSION

In this paper, we've got given NR-LEACH, a brand new application-aware cluster routing protocol for WSNs aimed toward providing higher  $Q_i$ 's. it's supported the initial LEACH protocol, arguably the foremost well-known within the field. Since totally {different|completely different} WSNs have different functions and applications, we have a tendency to state the necessity for a theme that not solely is alert to these characteristics however conjointly exploits them to realize an improved QoS. Our protocol permits the user to classify the network's traffic into completely different priority levels in keeping with their importance for the appliance. Then, within the set-up part of LEACH, it assigns additional slots within the TDMA schedule to higher priority nodes. This way, the network provides additional resources, in terms of assigned time, to higher priority traffic. Also, this could be changed dynamically, for example aiming to changes within the network conditions. Our theme is integrated into the initial LEACH operation seamlessly, with AN nearly negligible overhead. during this paper, we have a tendency to gift a radical analysis of the impact of our planned contribution on 2 well-known QoS metrics: turnout and latency. we have a tendency to conjointly compare the performance of our protocol thereupon of the initial LEACH protocol. The simulations given show that our protocol will give a major improvement in turnout, reaching will increase of roughly 250% over original LEACH in bound cases. It conjointly decreases latency by nearly eightieth as compared to original LEACH for sure configurations of the simulated state of affairs. it's vital to notice that our protocol focuses on optimizing the QoS of elite traffic streams, not on fulfilling QoS constraints or providing point guarantees.

## REFERENCES

1. Cisco Visual Networking Index, Forecast and Trends, 2017-2022 study, 2019, April 2019, <https://www.cisco.com/c/en/us/solutions/collateral/service-provider/visual-networking-index-vni/white-paper-c11-741490.html>.
2. W. R. Heinzelman, A. Chandrakasan, and H. Balakrishnan, "Energy-efficient communication protocol for wireless microsensor networks," in Proceedings of the thirty third Annual Hawaii International Conference on System Sciences, pp. 10–19, Maui, HI, USA, seven Jan 2000. View at: Google Scholar
3. S. K. Singh, P. Kumar, and J. P. Singh, "A survey on successors of LEACH protocol," IEEE Access, vol. 5, pp. 4298–4328, 2017. View at: Publisher website | Google Scholar
4. A. Rozas, J. Blesa, E. Romero, and A. Araujo, "Controlling the degradation of wireless detector networks," in Proceedings of 2015 International Wireless Communications and Mobile Computing Conference (IWCMC), pp. 1217–1223, Dubrovnik, Croatia, 24-28 August 2015. read at: Google Scholar
5. V. Raghunathan, C. Schurgers, S. Park, and M. B. Srivastava, "Energy-aware wireless microsensor networks," IEEE Signal process Magazine, vol. 19, no. 2, pp. 40–50, 2002. read at: Publisher website | Google Scholar

## BIOGRAPHY



Mr. M. Ashokkumar,  
Assistant Professor,  
Engineering Department,  
Adhiyamaan College of Engineering,  
Anna University.



Baranidharan S,  
Student,  
Engineering Department,  
Adhiyamaan College of Engineering,  
Anna University.



Bharanthan S,  
Student,  
Engineering Department,  
Adhiyamaan College of Engineering,  
Anna University.



Dhanraj M,  
Student,  
Engineering Department,  
Adhiyamaan College of Engineering,  
Anna University



Mohan N,  
Student,  
Engineering Department,  
Adhiyamaan College of Engineering,  
Anna University.





Impact Factor:  
7.569



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details