



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

A futuristic digital interface with a glowing Earth globe in the center. The interface is overlaid on a background of a person's hands reaching out towards the globe. The interface includes various data visualizations such as bar charts, line graphs, and pie charts, along with text elements like 'BUSINESS', 'NETWORK SEARCH', 'LOADING 100%', and 'MEDIA'. The overall aesthetic is high-tech and data-driven.

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 11, November 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.569

 9940 572 462

 6381 907 438

 ijrset@gmail.com

 www.ijrset.com



Gesture Controlled Contactless Switch for Smart Home

Maharaja.M¹, Divya.N², Indraja.N³, Revathi.P⁴

Assistant Professor, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering,
Hosur, Tamil Nadu, India ¹

U.G. Students, Dept. of Electronics and Communications Engineering, Adhiyamaan College of Engineering, Hosur,
Tamil Nadu, India ^{2,3,4}

ABSTRACT: Home Automation is that the new trend in a very shopper market. There area unit several home automation systems with totally different options and facilities. All the house automation systems area unit accustomed management home appliances through a far off management. The device is a stationed unit or a wireless remote. The remote used for dominant appliances typically have keys or touch-based sensors. during this project, a home automation system is meant which may be controlled by gestures. The system designed during this project controls four appliances that area unit taken 15-watt bulbs for demonstration. The user will choose the appliance to be controlled through a show that shows the list of appliances in a very drag-able fashion. The user will swipe through the devices by moving a finger in left or right direction associated switch the appliance ON or OFF by moving a finger in an upward or downward direction.

KEYWORDS: COVID-19, Contactless, Gesture Sensor.

I. INTRODUCTION

A. Due to advancements in technology, there's associate degree improvement in living standards, by automating even easy tasks to advanced tasks. A predefined gesture is employed to show on/off the device. Gesture is outlined as a motion of limbs or the other part that ar created to emphasise speech. A waving hand suggests that au revoir, that is associate degree example of a dynamic gesture, and therefore the stop sign is associate degree example of a static gesture. it's necessary to clarify all the static and dynamic gestures over your time to grasp the message. Gesture recognition is that the interpretation of human motion by the computing machine. Hand gestures will be detected by the controller which will sense tilting and acceleration of movement. for various applications, completely different gesture recognition techniques ar used. this method can act as an overseas management for in operation all the buyer electronic devices gift in a very house, that is achieved through hand gestures rather than push buttons.

II. RELATED WORK


Bluetooth based mostly home automation system exploitation cell phones: In Bluetooth based home automation system the house appliances are connected to the Arduino BT board at input output ports exploitation relay. The program of Arduino BT board is predicated on high level interactive C language of microcontrollers; the affiliation is formed via Bluetooth. The secret protection is provided thus solely approved user is allowed to access the appliances. The Bluetooth affiliation is established between Arduino BT board and phone for wireless communication. during this system the python script is employed and it will install on any of the Symbian OS surroundings, it's transportable. One circuit is meant and enforced for receiving the feedback from the phone, that indicate the standing of the device. 2. Zigbee primarily based home automation system exploitation cell phones: to watch and management the house appliances the system is meant and enforced exploitation Zigbee. The device performance is record and store by network coordinators For this the Wi-Fi network is employed, that uses the four switch port customary wireless ADSL trendy router. The network SSID and security Wi-Fi parameter ar preconfigured. The message for security purpose initial method by the virtual home rule and once it's declared safe it's re-encrypted and forward to the important network device of the house. Over Zigbee network, Zigbee controller sent messages to the tip. the protection and security of all messages that ar received by the virtual home rule. to scale back the expense of the system and therefore the officiousness of various installation of the system Zigbee communication is useful. 3. GSM primarily based home automation system exploitation cell phones: owing to the mobile and GSM technology, the GSM primarily based home

automation is lure to analysis. The SMS primarily based home automation, GPRS based mostly } home automation and twin tone multi frequency (DTMF) based home automation, these choices we have a tendency to thought of primarily for communication in GSM. In figure shows the multidimensional language the work of A. Alheraish, it shows however the house sensors and devices move with the house network and communicates through GSM and SIM (subscriber identity module). The system use electrical device that convert machine perform into electrical signals which works into microcontroller. The sensors of system convert the physical qualities like sound, temperature and wetness into another amount like voltage. The microcontroller analysis all signal and convert them into command to grasp by GSM module. choose applicable communication technique among SMS, GPRS and DTFC supported the command that received GSM module.4. Wi-Fi based mostly } home automation system exploitation cell phones: Wi-Fi based home automation system primarily consist 3 modules, the server, the hardware interface module, and therefore the code package. The figure shows the system model layout. Wi-Fi technology is employed by server, and hardware Interface module to speak with one another. an equivalent technology uses to login to the server internet primarily based application. The server is connected to the web, thus remote users will access server internet primarily based application through the web exploitation compatible application. code of the newest home automation system is split to server application code, and Microcontroller (Arduino) code. The Arduino code, designed exploitation C language, exploitation IDE comes with the microcontroller itself. Arduino code is blameworthy for gathering events from connected sensors, then applies action to actuators and preprogrammed within the server. Another job is to report the and record the history within the server sound unit. The server application code package for the planned home automation system, could be a internet primarily based application designed exploitation asp.net. The server application code is accessed from internal network or from net if the server has real information science on {the net|the web|the net} exploitation any internet navigator supports asp.net technology. Server application code is blameworthy of, maintain the complete home automation system, setup, configuration. Server use info to stay log of home automation system elements, we elect to use XML files to avoid wasting system log.

III. METHODOLOGY

With increased technological advancements, switches require updating with current times. To avoid the risk of contracting [COVID-19](#), it has become important to not touch surfaces of buttons and keys that have been frequently used by other people. This calls for a need to innovate the switching technology for replacing a hand-operated switch, with an automatic contactless switch. So in this project, we will design a no-touch switch that works entirely on hand gestures. Our smart contactless switch includes a sensor that is capable of detecting hand movements and translates them into commands for controlling lights, fans and various home appliances. The system tracks the movement of hand from top to bottom, right to left, far and near or vice versa. Arduino UNO is connected with APDS9960 which catches the movements of the hands and switches on and off the appliances. The APDS-9960 is a five pin gesture sensors that has VIN, GND, SCL, SDA and INT. The SCL pin is for clock time and SDA is for data input. The INT pin is used to create interrupt between every gesture. The APDS-9960 requires 5V DC supply. In case of an invalid gesture the, “gesture unavailable” message appears. In this system right to left movement of hand switches on the fan and left to right switches off. The Movement top to bottom switches on the LED and bottom to top switches off the LED.

IV. EXPERIMENTAL RESULTS





V. CONCLUSION

The methodologies higher than are compared on the idea of price, Hardware potency, and period of time application. scrutiny Bluetooth, Wi-Fi and Voice Recognition, Bluetooth is price economical and simple to implement however hardware potency is low because the vary of Bluetooth is 10-100 meters. Wi-Fi is expensive compared to alternative methodologies as net affiliation and high-end devices are needed. it's simple to implement however needs constant attention. Voice-based is expensive, Hardware potency is low and period of time application is tough. Gesture-based is simple to implement needs less price and Hardware potency is high. To concede, Hand Gesture-based Home Automation is one amongst the foremost effective solutions for home automation systems and conjointly opens the gates for automation in several fields

REFERENCES

- [1] Yadnya Adhiya, Shriya Ghuge, H.D Gadade "A survey on home automation system practice IOT" IJRITCC Volume_5_IssuesMarch_17_Volume_5_Issue_3.
- [2] Kim Imamu Amiri LeRoi Jones, John Barleycorn Ghobril, Sami Malek, RouwaidaKanj, AymanKayssi "Low worth Arduino/Android-based Energy-Efficient Home Automation System with wise Task Scheduling", 2013 Fifth International Conference on procedure Intelligence, Communication Systems and Networks.
- [3] HayetLamine and HafedhAbid," remote of a domestic instrumentation from Associate in Nursing robot application supported Raspberry pi card", IEEE dealing fifteenth international conference on Sciences and Techniques of Automatic management & laptop computer engineering - STA'2014, Hammamet, Tunisia, Dec 21-23, 2014.
- [4] YunCui, MyoungjinKim, YiGu, Jong-jinJung, and HankuLee, "Home Appliance Management System for observation Digitized Devices practice Cloud Computing Technology in gift device Network Environment", Hindawi business Corporation International Journal of Distributed device Networks Volume 2014, Article ID 174097.
- [5] Shih-Pang Tseng, Bo-Rong Li, Jun-Long Pan, and ChiaJuLin,"An Application of web of Things with Motion Sensing on wise House", 978-1-4799-6284-6/14 c ©2014 IEEE.
- [6] Kim Imamu Amiri LeRoi Jones, John Barleycorn Ghobril, Sami Malek, RouwaidaKanj, AymanKayssi," SmartPower Management System For Home Appliances And successfulness supported Wireless Sensors Network And Mobile Technology", 2015 XVIII AISEM Annual Conference, 978-1-4799-8591-3/15©2015 IEEE
- [7] Shiu Kumar," gift wise HOME SYSTEM practice robot APPLICATION ", International Journal of laptop computer Networks & Communications (IJCNC) Vol.6, No.1, Jan 2014.
- [8] January Gebhardt, archangel Massoth, Stefan Weber and TorstenWiens, "Ubiquitous wise Home dominant Raspberry Embedded System", UBICOMM: The Eighth International Conference on Mobile gift Computing, Systems, Services and Technologies, 2014.
- [9] BakiKoyuncu, "PC remote of Appliances by practice phonephone Lines", 1995, IEEE Transactions on shopper physics, Vol. 41(1), pp. 201-209.
- [10] Greichen, J.J., "Value primarily based home automation or today's market," IEEE Transactions on shopper physics, vol. 38, no. 3, pp.34- 38, Aug. 1992
- [11] Alheraish, "Design and Implementation of Home Automation System," IEEE Transactions on shopper physics, vol. 50, no. 4, pp.1087-1092, Nov. 2004.



**Impact Factor:
7.569**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details