



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 1, January 2022

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.569

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com



Depression Level Analysis through Real Time Image

Miss. Jagtap Sayali Navanath¹, Miss. Jare Mayuri Mahadev², Miss. Tamboli Saniya Raju³,
Prof.V.S.Nalawade⁴

B.E Student, Department of Computer Engineering, S.B.Patil college of Engineering Indapur, Pune, India^{1,2,3}

Department of Computer Engineering, S.B.Patil college of Engineering Indapur, Pune, India⁴

ABSTRACT: Clinical depression is a type of soft biometric trait that can be used to characterize a person. Because of its importance in a variety of legal situations, this mood illness can be included in forensic psychological evaluations. In recent years, research into the automatic detection of depression based on real image has yielded a variety of algorithmic approaches and auditory indicators. Machine learning algorithms have recently been used successfully in a variety of image-based applications. Automatic depression recognition - the recognition of facial expressions linked with sad behavior is one of the most important applications. Modern algorithms for detecting depression usually look at both geographical and temporal data separately. This method restricts the capacity to capture a wide range of face expressions as well as the use of different facial parts. This research introduces a novel machine learning strategy for accurately representing face information associated to depressive behaviors from real-world images. Our suggested architecture outperforms state- of-the-art algorithms in automatic depression recognition, according to results from two benchmark datasets.

KEYWORDS: Depression recognition, face recognition, convolutional neural network.

I. INTRODUCTION

Early recognition and accurate diagnosis of depression Studies focusing on individual-level neuro imaging data analyses are necessary if this approach is to be clinically useful [6] but the inherent complexity of the data and its analyses continues to be an obstacle [1]. Depression, it is a general psychiatric disorder with a life time prevalence of ~ 20 % in the general population, is associated with high rates of disability, impaired psychosocial functioning and decreased life satisfaction are important criteria for optimizing treatment selection and improving outcomes, thus reducing the economic and psychosocial burdens resulting from hospitalization, lost work productivity and suicide [2–4]. Guided by established classification criteria (DSM-5) [5], the diagnosis of psychiatric disorders including depression relies solely on inferences based on self-reported information and observed general behavior. Identifying people with established depression does not usually present as a clinical challenge with standard clinical instruments but the potential for ambiguity, bias and low reliability of a are essential criteria for optimizing treatment selection and improving outcomes, thus reducing the economic and psychosocial burdens resulting from hospitalization, lost work productivity and suicide [2–4]. Guided by established classification criteria (DSM-5) [5], the diagnosis of psychiatric disorders including depression relies solely on inferences based on self-reported information and observed behavior.

Identifying people with established depression does not usually present as a clinical challenge with standard clinical instruments but the potential for ambiguity, bias and low reliability of a are essential criteria for optimizing treatment selection and improving outcomes, thus reducing the economic and psychosocial burdens resulting from hospitalization, lost work productivity and suicide [2–4]. Guided by established classification criteria (DSM-5) [5], the diagnosis of psychiatric disorders including depression relies solely on inferences based on self-reported information and observed behavior.

II.RELATED WORK

Sr. No.	Paper title	Author Name	Year of Publication	Problem solved in this paper : Existing Problem Statement	Technique used to solve problem : Existing Problem Solution	What will be future work : Future Scope
1	Machine Learning based Depression Analysis and Suicidal Ideation Detection System using Questionnaires and twitter	Swati Jain, Suraj Prakash Narayan, Rupesh Kumar Dewang, Utkarsh Bhartiya, Nalini Meena and Varun Kumar	2019	Authors have proposed a depression analysis and suicidal ideation detection system, for predicting the suicidal acts based on the level of depression.	XGBoost, Logistic Regression classifier	Among future directions, we hope to understand how social media behavior analysis can help in leading to development of methods for analyzing depression at scale.
2	Reliable crowdsourcing and deep locality preserving learning for expression recognition in the wild	S. Li, W. Deng and J. Du	2018	we propose a new DLP-CNN (Deep Locality-Preserving CNN) method, which aims to enhance the discriminative power of deep features by preserving the locality closeness while maximizing the inter-class scatters.	DLP-CNN (Deep Locality-Preserving CNN) method	DCNN can learn more discriminative feature for expression recognition task.
3	Automated depression diagnosis based on deep network to encode facial appearance and dynamics	Y. Zhu, Y. Shang, Z. Shao, and G. Guo	2018	The proposed framework is designed in a two stream manner, aiming at capturing both the facial appearance and dynamics.	deep convolutional neural networks	This paper will work on accuracy improvement.
4	Disentangled representation learning gan for pose-invariant face recognition	L. Tran, X. Yin, and X. Liu	2018	this paper proposes Disentangled Representation learning Generative Adversarial Network (DR-GAN) with three distinct novelties.	Disentangled Representation learning-Generative Adversarial Network (DR-GAN)	Authors will extend GAN with a few distinct novelties, including the encoder-decoder structured generator, pose code, pose classification in the discriminator, and an integrated multi-image fusion scheme..
5	Artificial intelligent system for automatic depression level analysis through visual and vocal expressions	A.Jan, H. Meng, Y. F. A. Gaus, and F. Zhang	2017	In this paper, an artificial intelligent system is proposed to monitor depression.	Spectral Low-level Descriptors (LLDs) and Mel-frequency cepstral coefficients (MFCCs), Feature Dynamic History Histogram (FDHH)	Further ideas can be investigated to improve the system performance. The performance may improve if additional facial expression images are added into the training process of the VGG-Face deep network.
6	Deep residual learning for image	K. He, X. Zhang, S. Ren, and J.	2017	Authors present a residual learning	Deep Residual Learning	Further ideas can be investigated to



	recognition	Sun		framework to ease the training of networks that are substantially deeper than those used previously.		improve the system performance.
7	Learning deep features for discriminative localization	B. Zhou, A. Khosla, A. Lapedriza, A. Oliva, and A. Torralba	2017	In this work, we revisit the global average pooling layer and shed light on how it explicitly enables the convolutional neural network (CNN) to have remarkable localization ability despite being trained on image level labels.	convolutional neural network (CNN)	Furthermore we demonstrate that the Class Activation Mapping localization technique generalizes to other visual recognition tasks i.e., our technique produces generic localizable deep features that can aid other researchers in understanding the basis of discrimination used by CNNs for their tasks.
8	Depaudionet: An efficient deep model for audio based depression classification	X. Ma, H. Yang, Q. Chen, D. Huang, and Y. Wang	2017	This paper presents a novel and effective audio based method on depression classification	CNN(Convolution neural network),LSTM(Long Short-Term Memory)	Furthermore, they work on image.
9	Multimodal depression detection:fusion analysis of paralinguistic, head pose and eye gaze behaviors	S. Alghowinem, R. Goecke, M. Wagner, J. Epps, M. Hyett, G. Parker, and M. Breakspear	2017	This paper steps towards developing a classification system-oriented approach, where feature selection, classification and fusion-based experiments are conducted to infer which types of behaviour (verbal and nonverbal) and behaviour combinations can best discriminate between depression and non-depression.	Support Vector Machine	Future automated depression monitoring studies could consider this promising analysis.
10	Learning compact binary face descriptor for face recognition.	J. Lu, V. E. Liong , X. Zhou, and J. Zhou	2016	In this paper, author propose a compact binary face descriptor (CBFD) feature learning method for face representation and recognition	Pixel difference vector (PDV), compact binary face descriptor (CBFD)	This framework to further improve the recognition performance.

III.COMPRATION

Most of previous work on automatic depression assessment focuses on extracting discriminant features from facial region captured in image frames to access the intensity of depression. State-of-the-art machine learning models exploit spatial and temporal information separately, using an image processing for feature extraction, and some scheme for map the variation of the features, or for averaging the level of depression in each face frame. These approaches



represent facial region in image based on spatial features, which limit their ability in encoding rich dynamic information required for depression level estimation. However, these methods exploit temporal information from image, and the facial expression variations occur in wide range. Moreover, this approach employs structures with fixed receptive field which may impair the exploitation of different facial areas.

IV. ACKNOLEGMENT

We express our sincerely thanks and convey our heartfelt gratitude to the Computer Engineering Department Of Shahajirao Patil Vikas Pratishthan's S.B.Patil College Of Engineering, Head of Department Prof.Shirkande.S.T Project., Co-Coordinator Prof.Gavali.A.B.For providing their constant support, help, motivation and encouragement from beginning to till end to develop this project idea a grand success. And also thanks to everyone who directly or indirectly helped us in completing work successfully.

V. CONCLUSION

From the consideration of all the above points we conclude that face image may be a useful tool in discriminating between depressed and healthy individuals. Given the questionable reliability of diagnoses based on clinical symptoms, this quantitative methodology may be a useful adjunctive clinical decision support for identifying depression and it supports independent studies confirming the potential clinical utility of computer-aided diagnosis of depression using face image

REFERENCES

- [1] X. Ma, H. Yang, Q. Chen, D. Huang, and Y. Wang, "Depaudionet: An efficient deep model for audio based depression classification," in Proceedings of the 6th International Workshop on Audio/Visual Emotion Challenge, ser. AVEC '16. ACM, 2016, pp. 35–42.
- [2] S. Alghowinem, R. Goecke, M. Wagner, J. Epps, M. Hyatt, G. Parker, and M. Breakspear, "Multimodal depression detection: fusion analysis of paralinguistic, head pose and eye gaze behaviors," IEEE Transactions on Affective Computing, vol. PP, no. 99, pp. 1–1, 2016.
- [3] Y. Zhu, Y. Shang, Z. Shao, and G. Guo, "Automated depression diagnosis based on deep networks to encode facial appearance and dynamics," IEEE Transactions on Affective Computing, vol. PP, no. 99, pp. 1–1, 2017.
- [4] J. Lu, V. E. Liong, X. Zhou, and J. Zhou, "Learning compact binary face descriptor for face recognition," IEEE transactions on pattern analysis and machine intelligence, vol. 37, no. 10, pp. 2041–2056, 2015.
- [5] A. Jan, H. Meng, Y. F. A. Gaus, and F. Zhang, "Artificial intelligent system for automatic depression level analysis through visual and vocal expressions," IEEE Transactions on Cognitive and Developmental Systems, vol. PP, no. 99, pp. 1–1, 2017.
- [6] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2016, pp. 770–778.
- [7] B. Zhou, A. Khosla, A. Lapedriza, A. Oliva, and A. Torralba, "Learning deep features for discriminative localization," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 2016, pp. 2921–2929.
- [8] L. Tran, X. Yin, and X. Liu, "Disentangled representation learning gan for pose-invariant face recognition," in In Proceeding of IEEE Computer Vision and Pattern Recognition, Honolulu, HI, July 2017.
- [9] S. Li, W. Deng, and J. Du, "Reliable crowdsourcing and deep locality preserving learning for expression recognition in the wild," in The IEEE Conference on Computer Vision and Pattern Recognition (CVPR), Jul 2017.
- [10] M. Abadi, P. Barham, J. Chen, Z. Chen, A. Davis, J. Dean, M. Devin, S. Ghemawat, G. Irving, M. Isard et al., "Tensorflow: A system for largescale machine learning," in Proceedings of the 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI). Savannah, Georgia, USA, 2016.
- [11] J. Deng, W. Dong, R. Socher, L. J. Li, K. Li, and L. Fei-Fei, "Imagenet: A large-scale hierarchical image database," in 2009 IEEE Conference on Computer Vision and Pattern Recognition, 2009, pp. 248–255.
- [12] D. Yi, Z. Lei, S. Liao, and S. Z. Li, "Learning face representation from scratch," CoRR, vol. abs/1411.7923, 2014. [Online]. Available: <http://arxiv.org/abs/1411.7923>
- [13] D. H. Hubel and T. N. Wiesel, "Receptive fields, binocular interaction and functional architecture in the cat's visual cortex," The Journal of Physiology, vol. 160, no. 1, pp. 106–154, 1962.
- [14] D. E. King, "Dlib-ml: A machine learning toolkit," Journal of Machine Learning Research, vol. 10, no. Jul, pp. 1755–1758, 2009.



- [15] M. Abadi, P. Barham, J. Chen, Z. Chen, A. Davis, J. Dean, M. Devin, S. Ghemawat, G. Irving, M. Isard et al., “Tensorflow: A system for largescale machine learning,” in Proceedings of the 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI). Savannah, Georgia, USA, 2016.
- [16] M. Sidorov and W. Minker, “Emotion recognition and depression diagnosis by acoustic and visual features: A multimodal approach,” in Proceedings of the 4th International Workshop on Audio/Visual Emotion Challenge, ser. AVEC '14, 2014, pp. 81–86.



**Impact Factor:
7.569**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details