

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

EDIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Special Issue 1, April 2022

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.118

9940 572 462

6381 907 438

 \bigcirc





International Journal of Innovative Research in Science, Engineering and Technology
An ISO 3297: 2007 Certified OrganizationVolume 11, Special Issue 1, April 20229th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22)28 th -29 th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

Removable Mass Memory Unit in Docking Station

Dr T. Menakadevi¹, Manjunath V², Arun D³, Chethan Babu B⁴, Mathivanan C⁵

Professor, Department of Electronics and Communication Engineering, Adhiyamaan College of Engineering,

Hosur, Krishnagiri, Tamilnadu, India¹

Executive Officer, Axis Cades Aerospace & Technology, Bangalore, India²

U.G. Student, Department of Electronics and Communication Engineering, Adhiyamaan College of

Engineering, Hosur, Krishnagiri, Tamilnadu, India^{3,4,5}

ABSTRACT: Removable mass memory unit (RMMU) is a docking station which converts SATA 3.0 to USB 3.0 and vice versa. Docking Station is used by the pilot during the flight and all data of flight is stored in the docking station. The storage device is connected and data also recovered. The docking station also store machine planning operations. The storage device has one USB connector and SATA connector and one power connector. This storage device is fabricated on PCB with microcontroller and voltage conversion circuit. The memory unit is qualified to store all action of flight.

I. INTRODUCTION

A flight recorder is an electronic recording device placed specifically in fighter aircraft for storing the data. These generally fall into two categories, removable and internal and have been manufactured to withstand harsher environmental condition than would be encountered for consumer grade electronics. Removable memory devices are typically used in quick access recorders and multi role recorders which allow personal to remove the storage device for data download at an analysis station and insert a new one. Data stored on recorder with internal storage can be accessed using standard communication interfaces. Encryption of data is typically in sensitive operation where there is a security risk of data is intercepted. In docking station there are multiple storage device in that we take single memory storage unit for our project.

II. LITERATURE SURVEY

[1] Hotswappable Multi-Cartridge Docking Module, Steven L. Kaczeus, Sr., San Jose; Thomas McKnight; Roy J. Edwards, Nov 1993. [2] Enhanced three factor security protocol, T. Jenitha, S. Amutha, I. Shri Ram, Feb 2019.[3] A Novel NAND Flash Memory Architecture for Maximally Exploiting Plane-Level Parallelism, Myeongjin kim, Wontaeck jung, Hyuk-jun lee, Eul-young chung, Aug 2019.[4] Wireless Flight Data Recorder (FDR) for airplanes, Ankan-Ashish, S-Chougule, jan 2012.[5] JET AIRCRAFT DATA ACQUISITION SYSTEMS, Adam Rojewski, Jarosław Bartoszewicz, 2018.

III.OBJECTIVE

The main objective is to fabricate a memory docking station in printed circuit board (PCB). The microcontroller is programed to work as the interface between personal computer and storage device. The stored data in the storage device get analysed by loading the drive in memory docking station. The design also includes external appearance.



International Journal of Innovative Research in Science, Engineering and TechnologyAn ISO 3297: 2007 Certified OrganizationVolume 11, Special Issue 1, April 20229th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22)

28 th -29 th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

IV.WORKING PRINCIPLES

- This memory docking station will be only used by the piolet of fighter jet. The piolet carry the storage device and insert in a docking station.
- The memory storage device is connected SATA 3.0 which will collect all type of data like airbase communication altitude, speed, GPS, radar, etc. (ref.no.[8], [9])
- The solid state drive (SSD) is a storage device and it is connected manually in the docking station via SATA.
- After the SSD connected recording indication is shown in LED.Yellow LED (LD2) will glow during data transfer (Bus activity) activity on memory unit.
- > The fighter jet make scouting, fighting over warzone and all data of the jet records and stored in SSD.
- > The piolet get the docking station to the airbase for data analysing procedure.
- The data is analysed in personal computer by connecting USB 3.0.



V.BLOCK DIAGRAM

Figure 1: Block Diagram of Removable mass memory unit docking station



International Journal of Innovative Research in Science, Engineering and Technology *An ISO 3297: 2007 Certified Organization* 9th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22) 28th -29th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

VI. CIRCUIT SCHEMATICS



Figure 2: Circuit Schematics of Removable mass memory unit docking station

VII.ASM 1053-6G BRIDGE CONTROLLER

- > It is a bridge controller provides a turnkey way to integrate a USB interface design and operate in 5V.
- > This controller is used to work as an interface between storage device and personal computer.
- > Using the USB pin it has high speed and full speed operation like read and transferring the data.
- ▶ It transfer bulk of data simultaneously and supports 20/25/30 MHZ external crystal mode.
- ► ASM1053-6G chip from ASMedia requires 3.3V and 1.2V supply voltages for its operation.
- VBUS is extended to the chip as a signal which helps the docking station to be detected by windows OS with or without storage device.



International Journal of Innovative Research in Science, Engineering and TechnologyAn ISO 3297: 2007 Certified OrganizationVolume 11, Special Issue 1, April 20229th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22)

28 th -29 th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India



Figure 3: Architecture of ASM 1053-6G

VIII. PCB DESIGN & ELECTRIC DESIGN

The multilayer printed circuit board used to fabricate the memory docking station. It has more circuit route for mapping in PCB. PCB consists of bridge controller ASM1053 6G (SATA to USB) voltage regulator, voltage selection MUX, flash, USB 3.0 type B connector, 3.5mm power connector and other associated electronics. Using OrCAD software we design a circuit schematics diagram with standardized symbol used for docking station circuit. With the help of circuit schematics we assign footprints to the components. Once the PCB design completed next step is to fabricate the PCB. The fabricated circuit board is assembled with electronic components as per schematic diagram and tested for working process. External power supply is given to the docking station the power selection MUX is switch that distributed the power to microcontroller and control circuit. Following the power selection MUX voltage regulator distribute the voltage over microcontroller and other electronics blocks. The bridge controller programmed to collect the data from the jet via SATA 3.0 connector (ref.no. [7]). For indication of loading the storage device in docking station the LED is connected. Clock circuit maintain the signal in constant frequency. The USB 3.0 B type connector used to read the data from storage device which is connected in SATA by personal computer.



International Journal of Innovative Research in Science, Engineering and Technology *An ISO 3297: 2007 Certified Organization* 9th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22) 28th -29th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India



Figure 4: Main PCB Component placement (Top Side)



Figure 5: Bottom side of the main PCB

IX. MECHANICAL DESIGN

This developed memory unit docking station is fixed within a metal shell made of aluminium alloy HE20. It is heat resistive and all external parts painted with black polyure than to avoid corrosion of metal. All the plates have electromagnetic indication (EMI) gaskets, when all the plates are assembled together these gaskets will get compressed and provide the proper continuity between the plates to provide the protection from EMI/EMC. When memory unit is inserted, spring loaded guide will be with tension and provides the required amount of pressure to eject when memory unit is unlocked. The opening (window in the front plate) will have a transparent polycarbonate transparent sheet placed to view the inserted storage device.



International Journal of Innovative Research in Science, Engineering and Technology
An ISO 3297: 2007 Certified OrganizationVolume 11, Special Issue 1, April 20229th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22)
28 th -29 th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India



Figure 6: Mechanical appearance of removable mass memory unit docking station

X. RESULT

Removable mass memory unit docking station is tested by transferring data from storage device and vice versa. The data from the jet like radar, altitude, speed, GPS, airbase communication and other action of the aircraft. The removable storage device stores all data via SATA. The device is connected through USB and the data is transferred and get analysed by the PC.

REFERENCES

- [1] Ayeni BK, Yisah SO, 2016 "Cloud based architecture solution for aircraft flight data recorder", Current Journal of Applied Science and Technology, Volume 13.
- [2] Li CY, Ye GR, Yang QF, 2014, "Design of flight data signal generator system", In Applied Mechanics and Materials, Volume 556, Trans Tech Publ. p. 5143–5147.
- [3] Y. Hu, H. Jiang, D. Feng, L. Tian, H. Luo and C. Ren, "Exploring and exploiting the multilevel parallelism inside SSDs for improved performance and endurance", *IEEE Trans. Comput.*, vol. 62, no. 6, pp. 1141-1155, Jun. 2013.
- [4] J.-U. Kang, J.-S. Kim, C. Park, H. Park and J. Lee, "A multi-channel architecture for high-performance NAND flash-based storage system", *J. Syst. Archit.*, vol. 53, no. 9, pp. 644-658, Sep. 2007.
- [5] D. Landsman and D. Walker, AHCI and NVMe as Interfaces for SATA Express–Devices, 2013, [online] Available: https://sata-io.org/.
- [6] Ranjani MB, Poovendran R (2016) Image duplication copy move forgery detection using discrete cosine transforms method. Int J Appl Eng Res 11(4):2671–2674.
- [7] T Prasannavenkatesan, T Menakadevi Songklanakarin, "Resource-based routing protocol for mobile adhoc network", Journal of Science and Technology, 2020, Volume 42, Issue 4.
- [8] Menakadevi Thangavelu, Prasannavenkatesan Theerthagiri, "Mobility speed prediction using ARIMA and RNN for random walk mobility model in mobile ad hoc networks", Concurrency and Computation: Practice and Experience, 2021, Volume 34, Issue 4.
- [9] R. Raghu and T. Menakadevi, "A Survey on Anonymous Secure On Demand Routing Protocols in MANETs", Middle-East Journal of Scientific Research, 2016, Volume 24, Issue 12.



International Journal of Innovative Research in Science, Engineering and Technology
An ISO 3297: 2007 Certified Organization9th National Conference on Frontiers in Communication and Signal Processing Systems (NCFCSPS '22)
28 th -29 th April 2022

Organized by

Department of ECE, Adhiyamaan College of Engineering, Hosur, Tamilnadu, India

BIOGRAPHY



Dr T. Menakadevi, Professor, Electronics And Communicat Engineering Department, Adhiyamaan College of Engineering, Anna University



Arun. D, AC18UEC004, Electronics And Communicat Engineering Department, Adhiyamaan College of Engineering, Anna University



Chethan Babu. B, AC18UEC008 Electronics And Communicat Engineering Department, Adhiyamaan College of Engineering, Anna University



Mathivanan. C, AC18UEC041 Electronics And Communicat Engineering Department, Adhiyamaan College of Engineering, Anna University





Impact Factor: 8.118





INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com