



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 4, April 2023

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com



Exploring the Underlying Constraints to the Use of Geosynthetic Material for Civil Engineering in Road Construction

Prof. Natish Sayyed¹, Prof. Ritesh Raut², Hrishkesh Sawarkar³, Abhishek Mohate⁴, Ashutosh Jha⁵, Ashutosh Jha⁶, Md Nadeem Alam⁷, Nikhil Kumar Singh⁸, Pratima Binzade⁹

¹Head of Department, Department of Civil Engineering, NIT Polytechnic College, Nagpur, India

²Guide, Department of Civil Engineering, NIT Polytechnic College, Nagpur, India

^{3,4,5,6,7,8,9} Diploma Student, Department of Civil Engineering, NIT Polytechnic College, Nagpur, India

ABSTRACT: Geosynthetic materials are becoming increasingly popular in civil engineering because of their ability to improve road performance and durability. However, the use of geosynthetic materials in road construction is often limited by several factors such as: B. Cost, technical limitations, lack of knowledge and experience, environmental concerns, availability and access to materials and regulatory restrictions. This paper examines the limitations underlying the use of geosynthetic material for civil engineering in road construction and focuses on how these limitations can be overcome through careful evaluation, education and training, research and development of new materials and technologies. Geosynthetics are synthetic materials specifically designed for use in civil engineering, including road construction. They are designed to provide a variety of benefits including increased strength and durability, improved drainage and filtration, and reduced environmental impact. Despite these advantages, the use of geosynthetics in road construction is often limited by several factors that can make it difficult to integrate into a project.

KEYWORDS: Geotextile, distress of pavement, filtration, separations and reinforcement geosynthetics, pavement, subgrades, pavement, separation, embedment soil.

I.INTRODUCTION

India is a huge country with very diverse climate and terrain conditions. The resulting different subsoil conditions create a number of problems for civil engineers. Over the past two decades, the demand for the construction of civil engineering structures in a variety of topographical conditions has increased. To improve poor subsoil conditions in unfavourable locations, civil engineers traditionally rely on conventional raw materials such as brick, cement, steel, etc. However, situations arise where there is uneven quality and/or unavailability of the desired soil in and around the construction site, leading to high material transport costs. These and other technical limitations associated with building traditional structures on weak soils are driving civil engineers to seek alternative solutions. One such alternative that has become a popular material/technique in recent years is geotextiles and related products, now commonly referred to as geosynthetics. In most cases, plastics are made from chemical fibres; however, they can also consist of natural fibres. In fact, geosynthetics are synthesized for use in civil engineering projects to facilitate construction, ensure better performance of structures, and reduce long-term maintenance. They are widely used in almost all geotechnical and hydraulic engineering projects.

Generally, such projects include airport and highway surfacing, railways, canals, coastal erosion works, dams, embankments, retaining walls, etc. in the last decade. The use of geotextiles has experienced phenomenal growth worldwide. However, the Indian engineering community is still learning about this family of new materials through field and laboratory research, field trials, conferences and workshops. Actual use has been very limited compared to perceived need and potential. Recent trends in the use of geotextiles in the Indian context have been summarized. With the confidence gained from the limited Indian experience. The 1995 version of the Road and Bridge Works Specification submitted by the Department of Surface Transport (Road Wing) included geosynthetics for use in underground drainage. Road reinforcements, slope stabilization work and reinforced soil structures.

Historically, great advances in building technology have only come about because of simultaneous advances in building material technology. Big, great buildings started to appear as we moved from using wood to stone to



reinforced concrete floors and more recently reinforced concrete. Metal construction enabled the construction of bridges and buildings larger than would have been possible with braided steel or other traditional materials. Since the geotechnical materials are earth and rock, it is hard to imagine that the same advances in geotechnical construction and ceramics could be made in our field. The integration of other soil improvement strategies is largely due to the development of construction equipment by manufacturers and contractors. Geosynthetics have been used extensively in geotechnical and environmental engineering for four decades. Over the years, these products have helped designers and contractors solve a variety of engineering problems where the use of traditional building materials is limited or expensive. There are a variety of geosynthetic types and geosynthetic applications in geotechnical and environmental engineering. Due to space limitations, this document reviews progress in the use of these materials for consolidation and environmental protection. Polymeric reinforcement materials are the underlying basis for the greatest advances in engineered materials geosynthetics.

Geosynthetics are a planetary product of polymeric (synthetic) materials used with earth, rock, or other geotechnical (geo)materials as part of a public engineering project or program. There are some developments that have grown so quickly and consistently. Before the term geosynthetics was coined, all related products were grouped under one keyword, geotextiles. Giroud outlined the advances in this field with his global theme "From Geotextiles to Geosynthetics: A Revolution in Geotechnical Engineering" at the 3rd International Geotextile Conference in Vienna. In a statement, he noted that "without geotextiles, geotechnical engineering is no longer possible". This statement will be even more effective in 2016 with new and innovative products. Some examples of this use of prefabricated geosynthetic vertical drains (PVD) to reinforce soil acceleration instead of sand channels, reinforced soil walls instead of reinforced concrete walls, reinforced soil embankments instead of unreinforced flat embankments, geosynthetically compacted combined rock drainage substitutes, etc.

II. CONSTRAINTS TO THE USE OF GEOSYNTHETICS IN ROAD CONSTRUCTION

1. Cost:

One of the main constraints to the use of geosynthetics in road construction is cost. Geosynthetics accoutrements can be more precious than traditional accoutrements used in road construction, similar as concrete or asphalt. This can make it delicate for some systems to justify the use of geosynthetics.

2. Lack of Knowledge and Experience

Numerous masterminds and contractors may not be familiar with the use of geosynthetics in road construction, which can make it delicate to incorporate them into a design. This can affect in a lack of understanding of the benefits and limitations of geosynthetics, and a lack of knowledge of how to duly design and install them.

3. Specialized Limitations

Geosynthetics accoutrements have certain specialized limitations, similar as their strength and continuity. In some cases, traditional accoutrements may be more suited to the specific conditions of a design. For illustration, some geosynthetics may not be suitable to repel heavy business or extreme rainfall conditions.

4. Regulatory Constraints

Some nonsupervisory agencies may not allow the use of certain types of geosynthetics accoutrements, or may bear fresh testing and instrument before they can be used in construction systems. This can add to the cost and complexity of incorporating geosynthetics into a design.

5. Vacuity and Access to Accoutrements

Depending on the position and vacuity of geosynthetics accoutrements, it may be delicate or precious to gain them for use in road construction systems. This can be a particular concern in remote or underdeveloped areas, where transportation and logistics may be more gruelling.

6. Environmental enterprises

Some geosynthetics accoutrements may have negative environmental impacts, similar as releasing dangerous chemicals into the soil or water. This can be a concern for nonsupervisory agencies and design stakeholders, and can make it delicate to gain blessing for the use of geosynthetics.

III. OVERCOMING CONSTRAINTS TO THE USE OF GEOSYNTHETICS IN ROAD CONSTRUCTION

Despite these limitations, there are ways to overcome the barriers to the use of geosynthetics in road construction. One way is to carefully assess the specific needs and requirements of each project and consider the benefits and limitations of using geosynthetics. This can help determine if the use of geosynthetics is cost effective and appropriate for a particular project. Education and training can also help increase awareness and knowledge of geosynthetics among industry professionals. This can include training in the design, installation and maintenance of geosynthetics, as well as training on the benefits and limitations of geosynthetics in road construction.



IV. A BRIEF HISTORY OF GEOSYNTHETIC WORKS IN INDIA

An excellent summary of the development and application of geosynthetic technology in India can be found in Rao and Saxena, Rao and Rao. The first geotextile workshop was held in New Delhi in 1985. Rao tells the story of the development of geosynthetics in India. Work related to geosynthetics in India dates back to the mid-1980s when a road was built over a railway bridge in Ludhiana in 1985 using polymeric reinforcement cords and lakes as recycled materials. The height of building was about 8 m. This wall has reported a 15% cost saving plus savings during construction due to the nature of the approach. For more details on the various geosynthetic structures, see. India's particular contribution to geosynthetics lies in the natural materials of coir and jute. These products are used in many geosynthetic systems such as soil erosion, water and leachate control, low volume road construction, accelerated reinforcement, paving fabric to control exposed cracks inflexible roads, etc. Among the various functions that can be achieved by geosynthetics are fragmentation, Water, filtration, liquid barrier, erosion control.



V. FUNCTIONS OF GEOSYNTHETICS

1. Drainage

Geosynthetics can allow water to pass through their plane. Advanced geosynthetics with high aircraft penetration perform drainage functions where they are placed in the ground to prevent water overflow and transport them quickly toward the aircraft without fine particle migration.

2. Screen

When a flowing liquid (water, air) stalls particles, the geosynthetic stops the fine particles and allows the liquid to pass. Although the collected particles increase the pressure of the liquid, the strainer can withstand the pressure.

3. Barrier/Containment/Impregnation

Some geosynthetics can be used as an unstoppable barrier against liquids or gases. It can also be used as a soundproofing. Inaccessible on runways and aircraft, geosynthetics act as hydraulic barriers when placed under the weight of soil by preventing water erosion through large amounts of soil. Water rise from ditches can be controlled by placing a liner on the bottom and sides of the ditch.

4. Protection

Geosynthetics can protect against injury and death. For example, the geotextile can act as a flood on the geomembrane, preventing or reducing any kind of damage to the geomembrane layer during construction. Geosynthetics are used to protect the underlying layer from potential damage from the presence of angular objects such as beads and stones on the fence.

5. Separation

Geosynthetic can separate the two layers of soil, preventing them from mixing. Gravity geosynthetics, when created between two types of soil with vastly different particle sizes, perform the task of keeping them apart and preventing particles from mixing. For example, when building sidewalks, a basic-size unit is often placed directly on the ground floor. If this road is soft clay, the gravel tends to dig into the ground under the road load, resulting in a mixed soil. Basecoat performance will degrade over time with mixing. This can be avoided by laying geosynthetics in line of sight between the subsoil and the base course. It prevents mixing and leads to better method performance.

6. Filtration

Geosynthetics can allow water to pass through a plane while blocking or retaining soil particles. Filtration Strong geosynthetics where they are found between two layers of soil, one pure refined and the other rocky, through which water flows, creating the function of flexible filtration. They allow the passage of water without the passage of a fine particle of earth and water. Geosynthetics can be used in place of soil conversion filters when suitable soil is not available near the site.

7. Reinforcement

Geosynthetics can increase soil size and improve structural stability in terms of strength and deformation compared to unstable soils. Highly elastic reinforcing geosynthetics perform the task of stabilizing the soil where they are applied in



one or more layers to improve earthworks performance. The soil itself performs well under pressure but is not in good condition and soil performance is enhanced by the ability to handle the force of geosynthetics. This improves soft soil loosening, improves stability on steep slopes and reduces ground pressure behind end structures.

8. Erosion Control

Geosynthetics can be used to prevent or reduce soil erosion due to precipitation and surface water currents. Geosynthetics can be used for temporary or permanent erosion control along embankments. Temporary geosynthetics for erosion control contain decaying natural fibers such as jute. Distributed on a slope in the form of trellises or mats, they prevent soil erosion until plant growth sets in and then subsides. Permanent Erosion Control Geosynthetics are products made from the-layer cellular structure that provide erosion control, support plant growth and trap greenery to strengthen the root system.

VI. CONCLUSION

Geosynthetics are increasingly used in civil engineering for road construction due to their excellent mechanical properties, durability and economy. However, there are still some limitations that limit its widespread use in certain applications. One of the main limitations is the lack of standardized testing methods for geosynthetics, which makes it difficult to compare products from different manufacturers. This can create inconsistencies in product performance and make it difficult to select the most appropriate product for a particular application. Another limitation is the lack of knowledge and awareness among engineers and contractors about the proper design, installation and maintenance of geosynthetics.

This can lead to improper installation, which can affect product performance and ultimately lead to failure. In addition, there are also environmental concerns associated with the use of geosynthetics, particularly with regard to their disposal at the end of their useful life. While some products are recyclable, others may need to be sent to landfill, which can have a negative impact on the environment. In general, although geosynthetics have many advantages for road construction, it is important to consider these limitations when selecting and designing with these materials. Addressing these limitations through standardization, education, and environmentally sound disposal can help further encourage the use of geosynthetics in construction.

REFERENCES

1. N.S. Correia, J. G. Zornberg, Mechanical response of flexible pavements enhanced with geogrid-reinforced asphalt overlays, *Geosynthetics International*. 2015 Dec 9;23(3):183-193.
2. Rajagopal, K., & Chandramouli, S. (2014). Studies on geosynthetic-reinforced road pavement structures. *International Journal of Geotechnical Engineering*, 1938-6362.
3. Zornberg, J.G. & Gupta, R. (2010), Geosynthetics in pavements: North American contributions. *International Conference on Geosynthetics*, 1(1), 379-400.
4. Laurinavičius, A., & Oginskas, R. (2006). Research and evaluation of Lithuanian asphalt concrete road pavements reinforced by geosynthetics. *The baltic journal of road and bridge engineering*. 1(1),21-28.
5. S.W. Perkins, B.R. Christopher, N. Thom, G. Montestruque, L. Korkiala-Tanttu, A. Want, Geosynthetics in pavement reinforcement applications, *Proceedings of 9th International Conference on Geosynthetics*, Vol. 1, Guarujá, Brazil, 2010, pp. 165-192.
6. J.P. Giroud, J. Han, Design method for geogrid-reinforced unpaved roads, I. Development of design method & II. Calibration and applications. *Journal of Geotechnical and Geoenvironmental Engineering*. 2004 Aug;130(8):775-797.
7. J. G. Zornberg, R. Gupta, Geosynthetics in Pavements: North American Contributions, Theme Speaker Lecture, 9th International Conference on Geosynthetics, Guarujá, Brazil, May, Vol. 1, pp. 379-400.
8. J.W. Button, R.L. Lytton, Guidelines for Using Geosynthetics with HMA Overlays to Reduce Reflective Cracking, Report 1777-P2, Project Number 0-1777, Texas Department of Transportation, Austin, TX, 2003.
9. G. Montestruque, Contribution to the development of a design method to retrofit pavements using geosynthetics in anti-reflexion cracks, 2002. Ph. D. Dissertation, Aeronautic Institute, Brazil.



INNO SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.423



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

9940 572 462 6381 907 438 ijirset@gmail.com



www.ijirset.com

Scan to save the contact details