



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 5, May 2023

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

 9940 572 462

 6381 907 438

 ijrset@gmail.com

 www.ijrset.com

Garbage Classification Using Deep Learning And Image Recognition Technology

Mr. Shafeeq K I¹, Mrs. Neethu Prabhakaran²

P.G. Student, Department of Computer Science & Engineering, IES Engineering College, Thrissur, Kerala, India¹

Assistant Professor, Department of Computer Science & Engineering, IES Engineering College, Thrissur, Kerala, India²

ABSTRACT: Garbage control is a serious and unsolved difficulty across many countries. Many countries have particular garbage control regulations. There is no mounted approach to manage the garbage appropriately. Right waste recycling can give suitable income to the government. That's why we propose an automation technique to hit upon and categorize waste well. Garbage type is an essential level in permitting cost-powerful recycling the various duties required for recycling.

Nowadays, with the rapid development of industry, human beings each day existence is turning into increasingly wealthy and numerous. But, whilst enjoying the pride introduced by way of cloth life, a huge wide variety of garbage are produced. They are diverse, and people lack the information related to garbage type, which results in the problem of guide or robotic class. This paper studies a garbage class algorithm model primarily based on deep gaining knowledge of convolutional neural community green internet to help pick out garbage type. A critical trouble inside the recycling enterprise is the segregation of waste before recycling or every other waste remedy tactic. In India, at present state of affairs waste is not segregated when accumulated from families. So a lot of team of workers and effort are needed to separate this waste. In addition to this humans working on this industry are prone to numerous infections triggered because of poisonous materials present in the waste. So the concept is to lower the human intervention and make this waste segregation method more effective. The proposed project is aimed to build an image classifier that identifies the Garbage and detects the sort of waste material by the use of Convolutional Neural community. The principle goal of this paper is to categorise the images of the waste materials using CNN. Right here I have trained dataset using MobileNetV2 model through using switch studying method of CNN for category.

KEYWORDS: Garbage Classification, Deep Learning, Image Recognition, Convolutional Neural Networks.

I. INTRODUCTION

Garbage control inside the gift time is known to all of us but unfortunately, it's miles unnoticed via numerous people which are utilized to portray sports for waste segregation to take care of problems added about by means of incorrect garbage disposal. Illegal dumping has been a steady difficulty in numerous city communities on the planet. The smells and pollution delivered about by way of abandoned household matters and unloaded trash, and construction leftovers spoil the city in addition to threatens the wellness of the residents. To diminish unlawful dumping, a couple of city areas have planned community-based voluntary reporting frameworks and remark digicam-based monitoring frameworks. However, those methodologies require manual gazing and popularity, which are inclined and luxurious towards false alarms. Garbage is a worldwide difficulty that influences all of us and each unmarried living being. In our, normal lives we may additionally neglect to separate appropriately the garbage of our houses, and industrially the groups in price of this part want to spend numerous cash on exertions and paintings. The technique in which the garbage is segregated is splitting of garbage into divergent components. that is often achieved with the aid of hand picking bodily which a few the time reasons hazardous and dreadful to human fitness if not accurately completed. To solve this problem, garbage classification, and identity is familiar which allows all people especially the government authorities and officials to efficaciously segregate wastes in particular the recyclable ones. To automatize the manner of recycling, it's miles critical to recommend clever frameworks which could see waste classification successfully.

Since the introduction of deep learning, Image classification has come to be extra green and accurate than ever. It has boosted the development of computer vision and helped humans in numerous fields. In this work, we look at modern deep learning or image classification techniques to categorise garages.

Deep learning has gain traction in recent years, and its rapid development has greatly aided human convenience. Computer vision technology had a significant impact on public life and has already established itself as an essential component of human life. Many researchers are currently undertaking experiments the use of these improvements to use to garbage category duties.

II. RELATED WORK

Throughout the previous years, various works have been executed with the point of limiting the effect of the incorrect disposal of waste. Many neural network and support vector machine based image classification projects are being done previously.

In the experiment [2] they showed that the SVM (Support Vector Machine) [1] performed better than the CNN. SVM [1] achieved a test accuracy of 63% using a 70/30 training/testing data split. In that experiment [2] the test accuracy that they achieved was only 22%. Which was way below acceptance level. They claim that the CNN's inability to learn is caused by poor hyper parameters organizations. As stated in this research paper [2], If the time frame had been longer, they could have collected much more data to improve their CNN results. In their experiment.

In other experiment [3], they tried to identify a single garbage object in an image and place it in one of the recycling classes using Support Vector Machines (SVM) [1] with HOG features, simple Convolutional Neural Network (CNN), and CNN with residual blocks. In their experiment [4] they calculate the effectiveness of Simple CNN, and their test accuracy was 90%. In their research they stated that that very deep convolutional neural networks are difficult to train [4]. In their experiment [3] , after implementing ResNet they get 91.40% test accuracy.

The researchers of this paper [4] discovered, a multi-layer deep neural network can produce unexpected results. In this case, the training accuracy dropped as the layers increased, technically known as vanishing gradients. Therefore, the residual network was proposed to diminish this problem. A residual network, or ResNet [5] for short, is an artificial neural network that helps to build deeper neural network by utilizing skip connections or shortcuts to jump over some layers. There are two main types of blocks used in ResNet [3], depending mainly on whether the input and output dimensions are the same or different.

- Identity Block: When the input and output activation dimensions are the same.
- Convolution Block: When the input and output activation dimensions are different from each other

DenseNet [4] (Dense Convolutional Network) is an architecture that focuses on making the deep learning networks go even deeper, but at the same time making them more efficient to train, by using shorter connections between the layers. DenseNet [4] is quite similar to ResNet [3] with some fundamental differences. ResNet [3] uses an additive method (+) that merges the previous layer (identity) with the future layer, whereas DenseNet [4] concatenates (.) the output of the previous layer with the future layer. The DenseNet has different versions, like DenseNet-121, DenseNet-160, DenseNet201, etc.

Next generation of mobile vision applications is MobileNetV2 [1]. MobileNetV2 [1] is a substantial step forward from MobileNetV1 [2] and advances the state of the art in mobile visual identification, classifying object, object detection and semantic segmentation. MobileNetV2 [1] improves on the fundamentals principals of MobileNetV1 [2]. It used depth wise separable convolution as efficient building blocks. However, MobileNetV2 [1] was introduced two new features to the architecture. First one is linear bottlenecks between the layers, and second one is shortcut connections between the bottlenecks.

KellowPardini, Joel J.P.C. Rodrigues, [7] proposes that global industry is going through necessary changes with the entirely different world of perspective known as the Internet of Things (IoT). The author proposes the necessary equipment's and program and interchanges that intends in upgrading squander the board and remember for the interaction. The structure come after an IoTfound technique in which the disposal of waste is persistently perceive by radar that reveal the stuffing stage of each recess in a contagious manner. This information is put across and handled in an IoT framework with enhanced courses and producing relevant scalable information for checking the waste segregation precisely as far as asset and the executives in the local area.

Nandini S, Nanditha K, Meghashree C, Dr.Manjula G [8] says that the framework is created to beat the difficulties, boundaries and to give an open door to upgrades in squander the board and isolation framework. The Automatic waste the executives and isolation framework utilize the idea of Internet of Things framework, in which the framework is put around urban areas, using this implanted framework for isolating and screening the heights of the canister. This situation with canisters is shipped off to specialists to empty the receptacles and also the areas of containers are followed through web where the framework lessens human intercession, collaboration and furthermore diminishes the utilization of time and cost.

SonaliPreetha [9] The author puts forth an "Automatic Waste Segregator (AWS)" which can be utilized by associations taking care of enormous number of individuals and subsequently managing a great deal of everyday garbage. The garbage classifier is constructed utilizing an algorithm, prepared and trained on trash image dataset. The result is then conveyed to a Raspberry Pi board. The junk would be tossed to the respective bins which is classified into number of receptacles based on the requirement. Each of the three canisters are filled by plate like structure which acts as base associated with it will recognize the kind of trash also the comparing plate opens and the waste falls into the correct container. The AWS is associated with an organization subsequently security is of most extreme significance.

Md. Wahidur Rahman, [10] proposes that the paper mirrors an able design of the waste administration framework in light of profound learning, the model delivers a keen method for arranging absorbable and inedible waste utilizing a Convolutional Neural Network (CNN) algorithm, a well-known profound knowledge gaining worldview. The plan too presents a structural plan of a shrewd garbage can that uses a microcontroller with various sensors. This strategy utilizes IoT network and Bluetooth network in information checking. IoT empowers power of continuous information within anyplace, simultaneously Bluetooth helps small area information checking via an android app. To inspect the adequacy of the created model, the precision of waste name classification, sensors information assessment, and framework ease of use scale (SUS) are listed and deciphered.

Saputraa and Kusriani [11] The said method to classify waste is involving profound learning calculation for object location utilizing YOLOv4- minuscule with darknet. The images comprise of 3860 trash pictures isolated to four sub-classes such as paper, glass, plastic and metal. During analyzing step, every model takes three unique sources of info like pictures, recordings, what's more is webcams. In the YOLOv4 model, tests hyperparameter was likewise done in the development esteems and information expansion. The outcome demonstrates that YOLOv4 have preferred execution over YOLOv4-little for object location, albeit as far as implementation speed of YOLOv4 results are good. The excellent outcomes from the YOLOv4 arrive at mAP of 87.5%, accuracy 0.76, review 0.80, F1-score 0. And average IoU 64.02%, the good YOLOv4- minuscule outcome is mAP 82.84%, accuracy 0.56, review 0.84, F1-score 0.68 and average IoU 46.36%.

AndhyPancaSaputra, Kusriani [12] Said that the industry, urban and worldwide populace steps are expanded, it did the contamination and natural debasement in view of the waste. The normal issue connected with squander is the waste arranging that is still inappropriately taken care of the family step to the last removal site. The arrangement presented in this exploration is involving profound studying calculation for object location utilizing YOLOv4 with darknet. In the testing level, every model uses three unique sources of info like pictures, recordings and webcams. In the YOLOv4-little model, tests hyperparameter was additionally done on development values and mosaic information expansion. The outcome demonstrates that the YOLOv4 has preferable execution over YOLOv4-minuscule for object identification and albeit as far as implementation speed of the YOLOv4-small's scores are better. The exploration additionally demonstrates that the model with more modest development values and it uses a mosaic have an ideal presentation.

III. METHODOLOGY

In this project, I am implementing MobileNetV2 model for the purpose of Garbage Classification Using Deep Learning and Image Recognition Technology and comparing the same with the different types of model like Simple CNN, DenseNet121 and ResNet50 for the garbage classification scenario.

The MobileNetV2 structure is based totally on an inverted residual shape wherein the input and output of the residual block are skinny bottleneck layers opposite to standard residual fashions which use expanded representations inside the input an MobileNetV2 uses light-weight depth wise convolutions to clear out capabilities inside the intermediate

expansion layer. additionally, we find that it's miles important to remove non-linearities in the slim layers with a purpose to hold representational strength.

The Figure 1. below shows the architecture and the number of layers of a pre-trained MobileNetV2 model:




Figure 1 MobileNetV2 Architecture

For my work, I have used a popular garbage classification dataset from Kaggle. It has total 2532 files. There are 2527 images in this dataset. These images are 384*512 pixels in size and fall into one of six recycling categories: cardboard, glass, metal, paper, plastic, and trash. There were around 2527 pictures with 403 images of cardboard, 501 images of glass, 410 images of metal, 594 images of paper, 482 images of plastics, and 137 images of trash . These divisions were made depending on the pictures contained in the separate respective folder.

To improve the model's accuracy, image scraping is done to increase the dataset set, and some of the most misclassified images are removed. Image scraping is nothing but collecting images from the web and preparing a dataset from those images.

IV. EXPERIMENTAL RESULTS

Figures shows the results of the Garbage classification and the comparison with the different CNN models. To improve the model's accuracy, image scraping is done to increase the dataset set, and some of the most misclassified images are removed. Image scraping is nothing but collecting images from the web and preparing a dataset from those images




Figure.2 Input Data Samples



```

Anaconda Prompt (Anaconda) x + -
(base) E:\Projects\Trash_classifier-main\Trash_classifier>python predict.py
2023-04-19 15:42:32.387891: I tensorflow/core/platform/cpu_feature_guard.cc:193] This TensorFlow binary is optimized with
h oneAPI Deep Neural Network Library (oneDNN) to use the following CPU instructions in performance-critical operations:
AVX AVX2
To enable them in other operations, rebuild TensorFlow with the appropriate compiler flags.
1/1 [=====] - 0s 392ms/step:
cardboard
1/1 [=====] - 0s 31ms/step :
cardboard
1/1 [=====] - 0s 31ms/step :
cardboard
1/1 [=====] - 0s 32ms/step
metal
1/1 [=====] - 0s 31ms/step
metal
1/1 [=====] - 0s 32ms/step
metal
1/1 [=====] - 0s 31ms/step
paper
1/1 [=====] - 0s 31ms/step
paper
1/1 [=====] - 0s 32ms/step
plastic
1/1 [=====] - 0s 32ms/step
plastic
1/1 [=====] - 0s 32ms/step
plastic
(base) E:\Projects\Trash_classifier-main\Trash_classifier>
    
```

Figure. 3(a) Output Data Samples Through Command Console




Figure. 3 (b) Output Data Samples Through Web Console

In this project we are comparing the training loss of different models on the same input dataset. Also seeing the change in validation accuracy per epoch. To compare the evaluation matrices here also using the confusion matrices. The projects output show that the MobileNetV2 achieved the best performance among all the models used in all other experiments while accomplishing 98% accuracy.




Figure. 3 (b) DenseNet121 Loss and Accuracy plot




Figure. 3 (c) MobileNetV2 Loss and Accuracy plot




Figure. 3 (d) ResNet50 Loss and Accuracy plot




Figure. 3 (e) Simple CNN Loss and Accuracy plot

SL No	Model Name	Accuracy
1	Simple CNN	0.73
2	ResNet50	0.92
3	DenseNet121	0.91
4	MobileNetV2	0.98

Figure. 3 (f) MobileNet V2 Comparison With Other Models

V. CONCLUSION

Garbage classification is an important step in the waste management process. Our research shows that a variety of deep learning approaches may be utilized to categorize waste with great accuracy. We use a garbage image dataset available on Kaggle to train various CNN-based models in this work. Even though these models performed well, it is not certain that they will perform well in real-life circumstances because most of the photographs in the dataset had clean backgrounds. In future, we plan to train these models with a larger dataset. With additional categories. We also wish to incorporate realtime garbage detection to make the garbage collection process more efficient.

The main issue of this project was the dataset which includes images that are slightly different from local waste materials. This is the reason for which the model predicted wrongly on a few local waste images. The future work that should be taken for consideration is a similar method however an improvement in the datasets by including pictures of locally taken waste materials. There is a need of attaching images of the waste materials in the training dataset which are not clean and looks dirty. This will help the model predicting actual local waste materials which include mostly dirty household items. This can assist in getting some improved classification with a higher accuracy rate. The dataset should also include many images that contain pictures of multiple waste materials so that the framework can easily be trained to predict multiple objects in a single image without giving any error in the detection process. Further research of this project should also consider including different types of other bulky waste categories in the dataset. By intensifying the list of categories this framework will get more developed and would surely help in the improvement of the proper waste management process.

REFERENCES

- [1] Noble, William S, "What is a support vector machine?".journal - Nature biotechnology,publisher - Nature Publishing Group noble2006support
- [2] Yang, Mindy and Thung, Gary "Classification of trash for recyclability status". CS229 Project Report noble2006support
- [3] S. Meng and W. -T. Chu, "A Study of Garbage Classification with Convolutional Neural Networks," 2020 Indo – Taiwan 2nd International Conference on Computing, Analytics and Networks (Indo-Taiwan ICAN), 2020, pp. 152-157, 10.1109/Indo-TaiwanICAN48429.2020.9181321
- [4] Gao Huang, Zhuang Liu, Laurens van der Maaten and Kilian Q. Weinberger. Densely Connected Convolutional Networks, 2016; arXiv:1608.06993
- [5] Andrew G. Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto and Hartwig Adam. MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications, 2017; arXiv:1704.04861.
- [6] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov and Liang-Chieh Chen. MobileNetV2: Inverted Residuals and Linear Bottlenecks, 2018, The IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 2018, pp. 4510-4520; arXiv:1801.04381.
- [7] KellowPardini, Joel J.P.C. Rodrigues, Ousmane Diallo, Ashok Kumar Das, Victor Hugo C. de Albuquerque, Sergei A. Kozlov, "A Smart Waste Management Solution Geared towards Citizens", 22 April 2020.
- [8] Namratha A M, Nandini S, Nanditha K, Meghashree C, Dr. Manjula G, "Automatic Waste Management and Segregation System using IoT", International Journal of Engineering Research & Technology (IJERT), Volume 9, Issue 12.
- [9] SonaliPreethaNandagopalan, Silpa S, Prakriti Sharma K P, "Automatic Waste Segregator Using Image Classification", International Journal of Scientific Research in Computer Science, Engineering and Information Technology, Volume 4, Issue 11, 30 September 2020.
- [10] Md. Wahidur Rahman, Rahabul Islam, Arafat Hasan, Nasima Islam Bithi, Md. Mahmudul Hasan, Mohammad Motiur Rahman, "Intelligent waste management system using deep learning with IoT".
- [11] AndhyPancaSaputraa and Kusri B, "Waste Object Detection and Classification using Deep Learning Algorithm: YOLOv4 and YOLOv4-tiny", Turkish Journal of Computer and Mathematics Education, Vol.12 No.6, 5 April 2021.
- [12] Md. Mainul Ahsan, EmdadulHaque, Rezwan Ahmed"Garbage Classification Using Deep Learning Techniques" Project Report.



Impact Factor: 8.423



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details