



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 4, April 2024

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

Corrosion Detection Using Machine Learning

Dr.U. Kumaran, R.G. Uma Dharshini, M. Santhiya Devi

Associate Professor, Dept. of CSE, Kamaraj College of Engineering and Technology, VirudhuNagar, Tamilnadu, India

UG Student, Dept. of CSE, Kamaraj College of Engineering and Technology, VirudhuNagar, Tamilnadu, India

UG Student, Dept. of CSE, Kamaraj College of Engineering and Technology, VirudhuNagar, Tamilnadu, India

ABSTRACT: Corrosion, sometimes referred to as rust, can result in significant structural damage, decreased productivity, and higher maintenance expenses. Early rust detection is essential to averting these problems and guaranteeing the longevity of assets. Machine learning, a branch of artificial intelligence, can analyse and interpret massive volumes of data, it can spot trends and anomalies, which makes it a possible solution for rust detection. It does, however, require an awareness of the essential elements and procedures involved in applying machine learning approaches to the detection of corrosion or rust on a variety of surfaces. Our suggestion is to use rust detecting software to identify and forecast the metal's lifespan

KEYWORDS: Corrosion Detection, Detection Application, Machine Learning, metal lifespan.

I.INTRODUCTION

The Corrosion comes in various forms. Firstly, uniform corrosion This kind of corrosion causes a metal's surface to corrode uniformly, gradually reducing the thickness of the substance. Usually, it occurs when metal is exposed to corrosive substances or environments, such moisture. Even while uniform corrosion might not look as bad as other kinds, overtime it cannonetheless erode the metal's structural integrity. Regional Corrosion: Pitting The creation of tiny crater sorpition the metal surface is a hall mark of pitting corrosion. It happens when a tiny hole in the metal's protective layer allows for localized corrosion to happen. Pitting corrosion can be very sneaky since it can cause the metal to penetrate quickly and deeply. Crevice Corrosion: This type of corrosion can build up in small areas or crevices where stagnant electrolytes can remain stationary. It frequently affects locations where two surfaces converge or where metal parts are fastened together, like overlapping plates or bolted joints. Crack corrosion is difficult to identify and treat, and it can cause serious localized damage.

A subset of artificial intelligence (AI) called machine learning (ML) focuses on creating computer systems that can learn from data. Over time, software applications can perform better because to the wide range of techniques that machine learning (ML) incorporates. Algorithms used in machine learning are trained to identify patterns and relationships in data. They reduce dimensionality, classify information, cluster data points, make predictions, and even assist in the creation of new content by using past data as input. Machine learning has broad applications in numerous industries. As an illustration, ML Even while machine learning is an effective tool for problem-solving, enhancing company operations, and automating chores, it is a difficult technology that calls for substantial resources and in-depth knowledge. Selecting the appropriate algorithm for a task requires a solid understanding of statistics and mathematics. Large volumes of high-quality data are frequently needed for machine learning algorithm training in-order to get correct results. The results themselves can be hard to interpret, especially when they come from complicated algorithms like deep learning neural networks that are designed to resemble the human brain. Additionally, machine learning handles manual activities that are too complex for humans to handle on a large scale, such processing the massive amounts of data produced by digital gadgets now a days. A common way to classify classical machine learning is by the process of an algorithm learning to improve its prediction accuracy. Supervised learning, unsupervised learning, semi-supervised learning, and reinforcement learning are the four fundamental categories of machine learning. The kind of algorithm that data scientists select is determined on the type of data. Many of the methods and algorithms are not exclusive to any one of the main machine learning categories mentioned above. Depending on the data collection and the problem to be solved, they are frequently modified to fit several categories. In supervised learning, variables to be analysed for correlations are defined by data scientists and supplied to algorithms as labelled training data. In supervised learning, the algorithm's input and output are both stated. Although supervised learning was first used by the- majority of machine learning algorithms, unsupervised methods are starting to gain traction. The process of

identifying and locating rust or corrosion on the surfaces of metal structures, equipment, or other objects is called rust detection. Rust, also known as corrosion, is a naturally occurring process that occurs when metal surfaces react with

oxygen and moisture, leading to the formation of iron oxide, which weakens and damages the metal. The identification of rust is an essential part of maintenance, safety, and asset preservation in a variety of industries. The methods used to carry out rust detection include visual inspection, sensor-based measurements, and the application of technology, such as computer vision and machine learning models, which can be trained to identify rust patterns in images or sensor data. These models can automate the detection process and provide real-time feedback. The machine learning algorithms such as Random Forest is flexible, robust, and performs well on a wide range of datasets, it is frequently employed in many different disciplines. It is especially well-liked for assignments where the main goal is prediction accuracy rather than interpretability. Classification and regression problems in industries including banking, healthcare, marketing, and ecology are some examples of its uses.

II. RELATED WORK

Detection of corrosion on steel structures using an artificial neural network

Mojtaba Khayatazad et al. introduced a novel approach for corrosion detection in steel structures using artificial neural networks (ANNs). Unlike convolutional neural networks (CNNs) that require extensive training datasets and time-consuming parameter fine-tuning, the proposed ANN model achieves high performance with a training dataset size less than 0.1% of typical CNNs. The ANN outperforms existing image processing algorithms in terms of both speed and accuracy, making it suitable for practical applications after a quick and straightforward training process.

Furthermore, the authors present Rust SEG, a new deep learning method for accurately segmenting images to detect corrosion automatically. Rust SEG leverages deep learning techniques to classify images for the presence of corrosion, followed by an analysis of pixel contributions to this classification decision. Subsequently, the method refines its predictions to generate a pixel-level segmentation mask without requiring per-pixel labelled datasets for training.

A Comparison of Deep Learning Techniques for Corrosion Detection

In their study, Tom Bolton et al. and colleagues aimed to identify the most precise deep learning model suitable for corrosion detection. To achieve this, they conducted an experimental comparison assessing the performance of five machine learning algorithms when applied to corrosion detection from image data.

The deep learning methods commonly employed to address object recognition tasks typically demand substantial volumes of training data. Acquiring this data involves manual labeling by domain experts in corrosion, which is a challenging and costly process. The time and expenses involved escalate notably, particularly with the adoption of more intricate pixel-level annotations.

Image-Based Surface Defect Detection Using Deep Learning

In their study, Prahar M Bhatt and colleagues underscored the vital role of automatically identifying surface defects in images, particularly within manufacturing applications. While traditional image processing methods have been effective for specific tasks, they often struggle with challenges such as noise, varying lighting conditions, and complex background textures. Consequently, there is a growing interest in leveraging deep learning approaches to automate defect detection.

Their survey paper introduces a comprehensive framework that categorizes various research endeavours into three distinct classifications: based on the context of defect detection, learning techniques employed, and methods for defect localization and classification. By employing this approach, the existing body of literature is systematically organized. Furthermore, the paper highlights potential future research avenues by analysing emerging trends within the field of deep learning. Defect detection using deep learning offers adaptability by allowing customization of the network to identify specific defects based on the dataset. Additionally, parameters learned from one network can be applied to similar networks, resulting in high success rates for surface defect detection. Moreover, there is no

requirement for custom coding for training various types of defects. Utilizing labelled data for different defects with the corresponding network enables a highly flexible defect detection mechanism, as demonstrated in multiple studies discussed within this article.

Surface Rust Detection Using Ultrasonic Waves in a Cylindrical Geometry by Finite Element Simulation

In their study, Qixiang Tang and colleagues introduced a technique for early-stage corrosion detection in slender steel members, vital for averting buckling failures in steel structures. They devised an active photo acoustic fibre optic sensor (FOS) system capable of identifying early-stage corrosion on steel plates and rebars using surface ultrasonic waves. Their aim was to explore a potential method for identifying surface corrosion/rust on steel rods through numerically simulated surface ultrasonic waves. They utilized the finite element method (FEM) to simulate the propagation of ultrasonic waves on steel rod models, employing the pitch-catch mode of damage detection with one source (transmitter) and one sensor (receiver).

Their investigation centred on analysing radial displacements at the receiver is simulated and scrutinized using short-time Fourier transform (STFT), to identify, pinpoint, and assess surface rust between the transmitter and receiver. Their analyses in both the time and frequency domains unveiled that ultrasonic wave propagation could estimate the presence, location, and dimensions (length, width, and depth) of surface rust. The paper outlines their finite element analysis of ultrasonic waves on both intact and corroded steel rod models, presenting a methodical approach to detecting, locating, and quantifying surface rust. Despite yielding several empirical equations, the authors believe their proposed damage detection algorithm can be tailored to address other corrosion detection challenges utilizing distributed photoacoustic fibre optic sensors on steel rods or rebars.

III. PROPOSED WORK




Fig 1: Proposed work

Collection of corrosion dataset

Corrosion image dataset is implemented as input dataset which is taken from dataset repository. The input dataset is in of the format (.png, .jpg), and classified into two types corrosion and no corrosion.

Pre processing images

To recognize the images as the input image we have to Pre-process the image by following certain procedures, The collected input images are subjected to pre- processing. In the first Pre-processing step, Data must be converted to train the model and it can be implemented by Resizing the images & Gray Scale Conversion. We are extracting the feature from the pre-processed image using, Mean Standard Variance:

$$\sigma = \sqrt{\frac{1}{n} \sum_{i=1}^n (x_i - \mu)^2} \quad (1)$$

$$\sigma^2 = \frac{1}{n} \sum_{i=1}^n (x_i - \mu)^2 \quad (2)$$

where, σ is the standard deviation, μ is the mean, x_i are the individual data points and n is the total number of data points in the dataset.

and Local Binary Pattern. Pre processing is a crucial part of the machine learning pipeline, as the quality of the data and how it is prepared can significantly impact the performance of the model. The main goals of pre processing are to clean, transform, and prepare the data so that it can be effectively used for training and evaluation.

Prepare Training And Test Image Sets

Data splitting in machine learning is the process of dividing our dataset into multiple subsets for different purposes. The most common splits are typically into two sets: The training set, and the test set. The training set is the largest portion of your dataset, and it used to train our machine learning model. The model learns from the patterns in the data to make predictions or classifications.

The test set is a separate portion of the data that our model has never seen before. It is used to evaluate the model's performance and assess how well it generalizes to new, unseen data. The test set provides an unbiased estimate of how our model is likely to perform in the real world. There as on for splitting the data into these two sets is to avoid over fitting, a common problem in machine learning where a model performs exceptionally well on the training data but poorly on new, unseen data. By using a test set, you can assess the model's performance on data it has not been trained on, providing a more accurate measure of its effectiveness.

The specific size of each set (e.g., the ratio of training data to test data) can vary depending on the dataset size, but common splits are something like 80% for training, and 20% for testing. The key is to strike a balance between having enough data to train your model effectively, and evaluate its performance accurately, we have followed the similar split-up.

Training the model with classification algorithms

Random Forest is a powerful ensemble learning algorithm used in machine learning for both classification and regression tasks. It is based on the idea of creating multiple decision trees and combining their predictions to achieve better overall accuracy and reduce overfitting. And that is why we have used random forest as one of the classification algorithms, whereas XG Boost is better equipped to capture complex relationships between features and the target variable. It uses gradient boosting, which builds decision trees sequentially, with each tree focusing on correcting the errors of the previous ones. And hence to make the model predict the corrosion with higher accuracy we have used XGBoost. Both the algorithms build decision trees to train the dataset and finds the region of corrosion in the metal.

Performance Estimation

After training the model, we apply it to test input images. Subsequently, we detect the regions affected by corrosion and predict the remaining lifespan using a classification algorithm. During this stage, we evaluate the model's performance using various metrics including precision, recall, F1-score, accuracy, and macro and weighted averages. Additionally, we present the comparison graph to illustrate the model's performance compared to other methods or variations.

$$\text{Macro average} = \frac{1}{N} \sum_{i=1}^N M_i \quad (3)$$

$$\text{Weighted average} = \sum_{i=1}^N \frac{M_i \times \text{support}_i}{\text{support}_i} \quad (4)$$




IV. RESULTS AND DISCUSSION

Target	Precision	Recall	F1-score	Support
0	1.00	0.99	1.00	186
1	0.97	1.00	0.99	36
accuracy			1.00	222
Macro average	0.99	1.00	0.99	222
Weighted average	1.00	1.00	1.00	222

Fig 2: performance metrics for random forest

Target	Precision	Recall	F1-score	Support
0	1.00	0.99	1.00	186
1	0.97	1.00	0.99	36
accuracy			1.00	222
Macro average	0.99	1.00	0.99	222
Weighted average	1.00	1.00	1.00	222

Fig 3: performance metrics for XGBoost

**Fig 4: Final comparison graph**

Adopting machine learning (ML) for weed identification and control in agriculture marks a significant step forward in achieving efficient, sustainable, and environmentally friendly farming practices. By using advanced ML algorithms, agricultural systems can now distinguish between crops and weeds with high accuracy, enabling precise targeting and treatment of weeds. This precision not only leads to a substantial reduction in herbicide usage, helping both the environment and reducing farming costs but also contributes to improved crop yields by minimizing competition for resources. Furthermore, the adaptability and scalability of ML models ensure that this technology can be integrated across various farming scales and machinery, making it a versatile tool for modern agriculture. Despite facing challenges such as data diversity and the cost of technology adoption, the future of ML in agriculture looks promising, with potential for further advancements and broader implementation. Machine learning in weed management exemplifies the transformative impact of technology on agriculture, driving the industry towards more sustainable and productive practices.

V. CONCLUSION

Thus, our proposed system uses the implementation of Corrosion detection in metal surfaces by using machine learning techniques. The System for the effective prediction of Corrosion detection in the metals is found in the corrosion for the purpose of contributing the development of advanced materials, coatings, and methods for corrosion prevention and control, benefiting a wide range of industries. Our project helps identifying and assess the extent of corrosion, allowing for appropriate actions to be taken to mitigate its effects and ensure the continued functionality and safety of assets and structures. Corrosion in oil and gas pipelines and storage tanks can result in leaks, spills, and environmental contamination. It can also lead to the release off lammable or toxic substances, creating safety hazards. Therefore, developing an accurate model is much needed.

REFERENCES

- [1] Detection of corrosion on steel structures using an artificial neural network by Mojtaba Khayat azad issue,02 May 2022.
- [2] RustSEG -- Automated segmentation of corrosion using deep learning issue, 11 May 2022 B. Burton, W.T. Nash, N. Birbilis.
- [3] A Comparison of Deep Learning Techniques for Corrosion Detection issue, November 2022 DOI:10.1007/978-3-031-20601-6_18
In book: Proceedings of the 8th International Conference on Intelligent Systems and Informatics 2022 (pp.189-198)
- [4] Image-Based Surface Defect Detection Using Deep Learning by Prahar M Bhatt.
- [5] Deep learning corrosion detection with confidence by Will Nash issue, 31st march 2022.



- [6] Corrosion Detection Method of Transmission Line Components in Mining Area Based on Multiscale Enhanced Fusion by Jun Wu Issue 24, June.
- [7] Surface Rust Detection Using Ultrasonic Waves in a Cylindrical Geometry by Finite Element Simulation by Qixiang Tang, Issue 15, Oct.
- [8] RPN-FCN based Rust detection on power equipment by Jiangru Yuan, Issue 31, Jan.
- [9] Non-destructive Testing for Corrosion Evaluation of Metal under Coating by Ruikun Wu and Ruizhen Yang, Issue 30 Jun 2021.
- [10] Sensors in advancing the capabilities of corrosion detection: A review by M. Sai Bhargava Reddy, Omar Shehata, Issue Volume 332, Part 1, 1 December 2021, 113086.



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details