

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

DIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 4, April 2024

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.423

9940 572 462

S 6381 907 438

🖂 ijirset@gmail.com

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

|| Volume 13, Issue 4, April 2024 ||

| DOI:10.15680/IJIRSET.2024.1304415 |

BLDC Motor Speed Control with RPM Count

Swaraj Kadam, Sumit Patil, Shruti Gour

TCOER Student, Department of Electrical Engineering, TCOER Engineering College, Pune, India

Associate Professor, Department of Electrical Engineering, TCOER Engineering College, Pune, India

ABSTRACT: This project focuses on developing a speed control system for a Brushless DC (BLDC) motor while simultaneously monitoring its RPM. The system utilizes a microcontroller, such as Arduino or Raspberry Pi, along with a sensor to measure the motor's RPM. By adjusting the pulse width modulation (PWM) signal sent to the motor, the speed can be controlled. The RPM count is obtained through feedback from an optical encoder or Hall effect sensor. The combination of speed control and RPM count provides precise control over the motor's performance. This project offers an exciting opportunity to explore the intricacies of BLDC motor control and enhance our understanding of its applications

KEYWORDS: BLDC motor speed control, RPM count

I. INTRODUCTION

The purpose of this project is to develop a system that can control the speed of a Brushless DC (BLDC) motor while simultaneously monitoring its RPM (rotations per minute). BLDC motors are widely used in various applications, such as robotics, electric vehicles, and industrial automation, due to their efficiency and reliability. In this project, we will be utilizing a microcontroller, such as Arduino or Raspberry Pi, to control the speed of the BLDC motor. The control will be achieved by adjusting the pulse width modulation (PWM) signal sent to the motor. By varying the duty cycle of the PWM signal, we can regulate the average voltage and current supplied to the motor, thus controlling its speed. To accurately measure the RPM of the motor, we will incorporate a sensor, such as an optical encoder or a Hall effect sensor. These sensors provide feedback on the rotational position of the motor's rotor, allowing us to calculate the RPM.

II. METHODOLOGY

Components Required:

The main components used are Arduino Uno ATMEGA32P Microcontroller, Transformer, Bridge Rectifier, Voltage Regulator, 16*2 LCD Display, IR Sensor, BLDC Motor, Keypad Matrix

Working Principle

In this project the 230V AC supply is given to transformer, The stepdown transformer 230V to AC 12V The transformer gives output of 12V And 0v, The 12v And 0v output voltage is fed to Bridge Rectifier circuit convert AC into DC using diode Arranged in bridge circuit the output wave generated is of same polarity irrespective of same input. To control the speed of a BLDC motor, we use a technique called pulse width modulation (PWM). This involves adjusting the width of the electrical pulses sent to the motor. By changing the duty cycle of the PWM signal, we can control the average voltage and current supplied to the motor, thus controlling its speed.

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



|| Volume 13, Issue 4, April 2024 ||

| DOI:10.15680/IJIRSET.2024.1304415 |

III. MODELING AND ANALYSIS




Figure1: Block Diagram of Model

IV. RESULT AND DISCUSSION

Specifications of Model

Microcontroller -

ATmega38p 8 bit AVR family microcontroller Operating voltage - 5v Recommended input voltage - 7-12V Input voltage limit - 6-20V

step down transformer*

Input vontage - 230v AC Output voltage - 12V -0V Output current - 1A

Voltage Regulator

IC 7805 voltage regulator with 5v output voltage Minimum and maximum input voltage - 7and 25 V Operating current -5mA Highest junction temperature is 125°c

BLDC motor

Type - C8025M125 DC Voltage -12V Current - 0.22A

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)

| e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

|| Volume 13, Issue 4, April 2024 ||

| DOI:10.15680/IJIRSET.2024.1304415 |




FIGURE 2: HARDWARE OF MODEL

V. CONCLUSION

In conclusion, this project has successfully demonstrated the ability to control the speed of a Brushless DC (BLDC) motor while monitoring its RPM. By utilizing a microcontroller and adjusting the pulse width modulation (PWM) signal, we were able to regulate the motor's speed with precision. The incorporation of a sensor, such as an optical encoder or Hall effect sensor, provided accurate feedback on the motor's rotational position, allowing us to calculate the RPM. This RPM monitoring ensures that the motor operates at the desired speed for specific applications, enhancing its efficiency and performance. By undertaking this project, we have gained valuable insights into the complexities of BLDC motor control and the importance of RPM monitoring. This knowledge can be applied to various fields, including robotics, electric vehicles, and industrial automation, where precise speed control is crucial.

ACKNOWLEDGEMENTS

The It is our privilege to express our sincerest regards to our project guide, **Prof. Shruti Gaur** for his valuable inputs, able guidance, encouragement, whole hearted cooperation and constructive criticism throughout the duration of our project. We deeply express our sincere thanks to our head of department **Dr Prof. J.V.Satre Mam HOD of Electrical Department** for encouraging and allowing us to present the project at our department premises for partial fulfillment of requirement leading to the award of B.E degree. The completion of project would not been possible without their help and insights

REFERENCES

1. Mack, James E.; Shoemaker, Thomas (2006). "Chapter 15 – Distribution Transformers" (PDF). The Lineman's and Cableman's Handbook (11th ed.). New York: McGraw-Hill. pp. 15-1 to 15-22. ISBN 0-07-146789-0. Archived from the original (PDF) on 2013-02-10. Retrieved 2013-01-12.

2. Yazdani, Amirnaser; Iravani, Reza. Voltage-Sourced Converters in Power Systems Modeling, Control, and Applications. Willey. ISBN 9780470521564.

3. ^ Horowitz, Paul; Hill, Winfield (1989). The Art of Electronics (Second ed.). Cambridge University Press. pp. 44–47. ISBN 0-521-37095-7.

4. Texas Instruments LM2825 Integrated Power Supply 1 A DC-DC Converter, retrieved 2010-09-19

5. ^ Linear Technology µModule Regulators, retrieved 2011-03-08

INTERNATIONAL Standard Serial Number India







INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com