



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 4, April 2024

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

ijrset@gmail.com

www.ijrset.com

Design and Development of Bionic Arm using 3D Printer

Shrikant Bawane, Sanket Verulkar, Harshal Patil

U.G. Student, Department of Mechanical Engineering, PRMIT&R, Badnera, Amravati, Maharashtra, India

U.G. Student, Department of Mechanical Engineering, PRMIT&R, Badnera, Amravati, Maharashtra, India

Assistant Professor, Department of Mechanical Engineering, PRMIT&R, Badnera, Amravati, Maharashtra, India

ABSTRACT: A 3D printable plan and its examination for a myoelectric prosthetic arm was investigated in this paper. The arm is electronically incited and constrained by a client flexing and loosening up his/her biceps muscles. The bionic arm introduced has the extent of being utilized by an individual without any appendages or not having it from beneath the elbow. The primary goal of this work was to make a savvy prosthetic which was likewise complex enough Regularly such gadgets are mechanically impelled and subsequently not however recognizably muddled as myoelectric gadgets seem to be. The innovation of 3D Printing is something that caused another time of expectation for genuinely tested 3D printing has its impediments however development and advancement in the field will just prompt enhancements over the long haul. Minimal expense moderate strength materials for the body what's more, parts accessible wherever was utilized for its development body to make it as reasonable as could really be expected. The gadgets utilized were less, consequently not so convoluted to investigate. The created plan showed guarantee as it could do numerous essential things having 9 DOFs.

This concentrate on theme covers an expansive scope of designing disciplines. The base of the framework is an imaginative mechanical plan for a 3D printed prosthetic arm. Cutting edge electronic actuators, that is servo engines and hardware utilizing sensors vitalize the gadget and take into consideration complex control plans. It is trusted that this work will be of worth to the future prosthetic assembling designers of this subcontinent. The primary target of the examination was satisfied however because of the issues and weaknesses of accessibility and backing local area for the advancements utilized, seen in generally immature nations a few highlights of the arm were not accomplished true to form be that as it may, the venture is regardless encouraging.

KEYWORDS: Bionic Arm, Prosthetic Arm, EMG Module Bionic Arm, Biomechatronic, Myoelectric,

I. INTRODUCTION

It very well may be contended that the most important belonging to any individual is their body. Supplanting a missing human appendage, particularly a hand, is a difficult undertaking which makes one really value the intricacy of the human body. Until current times the plan of prosthetic appendages has advanced moderately gradually. After some time, materials improved, and plans began integrating pivots and pulley frameworks. This prompted basic mechanical body-controlled gadgets such as metal snares which can open and close as a client twists their elbow for instance. Late times anyway have given way to huge progressions in prosthetic gadgets. Zero in isn't just on the actual parts of a gadget yet in addition to the control and biofeedback frameworks. Gradually we are moving toward a high level trans-human reconciliation among machine and body. Maybe soon prosthetic gadgets will be quicker, more grounded and perhaps better than our natural Appendages.

All through this study we will investigate myoelectric prosthetic arm. It is planned to plan a gadget which mirrors the capability of the human arm as best as could really be expected and can be controlled somewhat by solid contractions. The name was fixed with an understanding to construct a savvy yet serious areas of strength for decently, stylish and generally significant of every one of the different developments prepared prosthetics utilizing 3D printing innovation and minimal expense Myo ware sensors.

The human finger altogether has 4 levels of opportunity [1]. Three of these are the revolutions of each joint, Distal Interphalangeal Joint, Proximal Interphalangeal Joint, Metacarpophalangeal Joint (DIP, PIP, MCP) which consolidate to control flexion and augmentation of the finger. The knuckle (MCP joint) likewise considers

snatching/adduction (squirring the finger from side to side). The complicated movements of this mind-blowing piece of natural, bio machine which can't be recreated in man-made fingers are exact and consummate and their broad clarification are past the extent of this section. But for an overall origination a figure is given beneath for portrayal and understanding.[2]




Figure 1: Degree of Freedom of Human Hand

In the thumb the lower CMC joint additionally considers snatching/adduction which gives 5 DOFs in the thumb [3]. Fingers, and all joints in the human body are impelled (moved) by means of withdrawal of muscles and ligaments. skill emerges from the various levels of opportunity of the human hand. The fine engine controls an individual has over their singular finger joints considers a huge range of many-sided undertakings to be accomplished. Conversely, business prostheses are restricted to basic undertakings somewhat due to the absence of fine control in the fingers.

Several arms such as the Bebionic 3 [4] and I Limb [5] are myoelectric controlled robotic arms commercially available to the public. Numerous more prosthetic arms exist in research labs around the world which are typically evolved as models to test progressed plans and ideas. Research prosthetics are by and large more mind boggling concerning mechanical plan, control and observing frameworks yet are second rate compared to business gadgets concerning common sense, cost and strength [6]. Other such arms considered were Vanderbilt Hand [7], Intrinsic Hand [8], Shadow Hand [9]. The contribution from our project was to showcase a prosthetic hand made with technologies available locally and with ease and even at low cost if compared to industrial alternatives.

II. BIONIC ARM

2.1 Methodology

The bionic arm executed and tried was tweaked for a particular client to fit with his removal conditions. It was made to give the client the capacity to perform fundamental getting a handle on activities and permit the client to take part in his everyday exercises really. The client was brought into the world with a little part of his right arm, as displayed in Figure 1. The client is a 24-year-old male with no other critical medical problems. He utilized various past prosthetic arms, whose parts and make are not point by point. He observed that these arms are not adequately useful or weighty or are awkward or costly. The client gave his educated assent for consideration before he partook in the review. The review was led as per the Announcement of Helsinki, and the convention was endorsed by the Morals Council with reference (SP190402-01).




Figure 2: Amputation case with user wearing Myo Arm Band

The client's input was thought about while dealing with the plan of a minimal expense tweaked bionic arm. The client was vigorously engaged with the mechanical plan period of the bionic arm. The prosthetic arm introduced in this work is constrained by a multi-channel sEMG sensor that is utilized to gain the muscles' exercises. The muscles' exercises address various signals, which are utilized to play out the necessary activity by the hand appended to the arm. The hand has 9 levels of opportunity (DOF), which empower it to perform different exact activities according to the client's interest. The schematic graph delineating the means expected to control the bionic arm is displayed in Figure 2. A data set of sEMG motions is made with each of the units related with signal handling, highlight acknowledgment, and AI to list the signs that are expected for developments of the finger actuators in the bionic hand to perform explicit hand stances.




Figure 2: Schematic chart to control bionic arm

2.2 Working

When the user thinks about moving their arm or hand, the sensors in the bionic arm detect these electrical signals. The microprocessors interpret these signals and send commands to the motors, instructing them to move the arm or hand accordingly. The result is a natural and intuitive control mechanism that allows users to perform a wide range of tasks with their bionic arm.

2.3. Bionic Arm Design

Handicapped people with appendage removal might be disheartened with specific parts of accessible appendages in the market because of their restrictions. A redid plan for the client through a singular plan process has been embraced here, which can focus on a plan that satisfies the need of a singular tragically handicapped person case, especially regarding its minimal expense and light weight. The ongoing gadgets accessible in the market range from 4000 up to 20,000 USD [10]. A nitty gritty market examination of the expense related with prosthetic appendages was ordered by the creators in [11]. A basic corrective arm and hand might cost somewhere in the range of 3000 and 5000 USD. The expense of a useful prosthetic arm, then again, may cost between 20,000 to 30,000 USD [11]. The fundamental objective is to make a modest and reasonable bionic arm for handicapped people costing around 295 USD. These days, the progression of and simple admittance to 3D-printing innovation have decreased the expense of assembling bionic arms and give more straightforward answers for the plan of prosthetic arms modified for clients [12]. The client's left arm aspects were estimated to manufacture the right arm with similar aspects for a symmetric look. A reflected calculation was expected utilizing a PC supported plan (computer aided design) programming. The elements of the impacted arm were thought about and implanted in the plan to foster a wearable arm with sufficient space for the Myo armband to fit and be disguised from view.

The 3D model plan for the bionic arm is displayed in Figure 4. The plan depends on various models, as recorded and depicted beneath:



Figure 4 : Bionic arm 3D model.

III. RESULTS

The study on the design and development of bionic arms demonstrates significant progress. Through advancements in materials and designs, including myoelectric and externally powered systems, greater control and functionality have been achieved. Integration of sensory feedback mechanisms enhances user perception, while neural interfaces enable direct brain-arm communication. Machine learning algorithms contribute to adaptive control, further improving user-device interaction. Additionally, 3D printing allows for personalized prosthetics tailored to individual needs. These advancements pave the way for enhanced functionality, comfort, and societal acceptance of bionic arms in the future.

IV. REAL-TIME IMPLEMENTATION

Different testing conventions were proposed to the client for testing the arm plan and the EMG signal control with the ideal classifier empowered. The client rehearsed for multi week on the most proficient method to perform various motions and have the option to control his muscles. After the preparation stage, the client wore the Myo armband in his lower arm and afterward played out the prepared signals (clench hand (shut), spread fingers (open), wave-in, wave-out) involving his muscles for 20 continuous times. In this way, the client was approached to perform two unique signals sequentially for multiple times to test the day-to-day exercises that can be performed by the bionic arm. The signals were planned with four different hand stances, as displayed in Table 5.

Gesture	Hand Action
Close	Closed hand and fingers
Open	Open hand and fingers
Wave-in	Closing one finger
Wave-out	Closing two fingers

Table 5: Mapping between trained gestures and hand actions

The testing situations showed the capacity of the client to control the bionic hand precisely after the preparation stage. The bionic hand developments were enhanced to permit the client to perform various exercises (holding objects, getting a handle on, drinking, and composing). In single-activity testing, the client was approached to perform each activity in turn. The single activities incorporate making a clench hand, spreading the fingers, shutting one finger, and shutting two fingers, as displayed in Figure 9.




Figure 9: (a) writing with pen (two finger close action)
(b) holding of notebook (one finger close action)
(c) Using PC mouse (one finger close action)
(d) holding a ball (fist action)




Figure 10: (a) Holding a ball (Front view)
(b) Passing egg (Holding with two fingers)
(c) Holding a ball (Side view)

The client played out each activity dully for 20 sequential times. The consequences of testing each single activity show a base discovery pace of 85%. In the blend of two activities, the client performed opening and shutting with a triumph pace of 95%, opening and shutting of one finger with 90%, and opening and shutting of two fingers with 85%, as displayed in Figure 11.




Figure 11: Success rate of hand actions

V. CONCLUSION

A redid 3D-printed bionic arm was planned, created, and tried for a right arm handicapped person. The 3D-printed bionic arm was intended to have a minimal expense, solace, light weight, strength, and appearance. To work with a nonexclusive control of the bionic arm, EMG information were gathered for a bunch of four motions (clench hand, spread fingers, wave-in, wave-out) from a great many members. The gathered information was handled and include extraction was performed to prepare a classifier. The help vector machine classifier was found to out-play out the brain organization and choice tree classifiers, arriving at a typical exactness of 89.93%. Continuous testing of the bionic arm with the related classifier programming empowered the client to play out his everyday exercises.

Extra highlights are expected to additionally work on the bionic arm; for instance, a multi-level of-opportunity wrist joint connector. This can be accomplished by utilizing two servo engines with sections or by using a round controller. Besides, air-ducted movable attachments can permit the client to mount and descent the bionic arm effortlessly.

REFERENCES

1. George Elkoura, Karan Singh. Handrix: Animating the Human Hand. Department of Computer Science, University of Toronto, Toronto, Canada Side Effects Software, Inc., Toronto, Canada. Eurographics/SIGGRAPH Symposium on Computer Animation (2003). [[Google Scholar](#)]
2. Mahdi Elsayed Hossain, 3D Printed Myoelectric Prosthetic Arm (Thesis), 2014. [[Google Scholar](#)]
3. Hands Facts and Tivia. The electronic textbook of <http://www.eatonhand.com/hw/facts.htm> [[Google Scholar](#)]
4. Myoelectric Bionic 3 bionic hand. CNET, November 2012. [[↗](#)]
5. Touch Bionics. i-limb Digits Clinician User Manual. 2014. [[↗](#)]
6. Claudio Melchiorri, Gianluca Palli, Giovanni Berselli, and Gabriele Vassura. Development of the UB hand IV. Bologna University, Overview of Design Solutions and Enabling Technologies, September 2013. [[Google Scholar](#)]
7. Frank Rothling, Robert Haschke, Jochen J. Steil, and Helge Ritter Neuroinformatics Group, Faculty of Technology, Bielefeld University. Platform Portable Anthropomorphic Grasping with the Bielefeld 20-DOF Shadow and 9-DOF TUM Hand. Proceedings of the 2007 IEEE/RSJ International Conference on Intelligent Robots and Systems San Diego, CA, USA, Oct 29 - Nov 2, 2007. [[↗](#)]
8. Weir, R., Mitchell, M., Clark, S., Puchhammer, G., Haslinger, M., Grausenburger, R., Kumar, N. [[Google Scholar](#)]
9. Christian Pylatiuk, Stefan Schulz and Leonhard Döderlein. Results of an Internet survey of myoelectric prosthetic hand users. Prosthetics and Orthotics International, Sage Publications Dec1, 2007. [[Google Scholar](#)]
10. Said, S.; Sheikh, M.; Al-Rashidi, F.; Lakys, Y.; Beyrouthy, T.; Naitali, A. A Customizable Wearable Robust 3D Printed Bionic Arm: Muscle Controlled. In Proceedings of the 3rd International Conference on Bio-Engineering for Smart Technologies (BioSMART), Paris, France, 24–26 April 2019; pp. 1–6. [[Google Scholar](#)]



11. Zuniga, J.; Katsavelis, D.; Peck, J.; Stollberg, J.; Petrykowski, M.; Carson, A.; Fernandez, C. Cyborg beast: A low-cost 3d-printed prosthetic hand for children with upper-limb differences. *BMC Res. Notes* **2015**, *8*, 1–8. [[Google Scholar](#)] [[CrossRef](#)] [[Green Version](#)]
12. McGimpsey, G.; Bradford, T. C. *Limb Prosthetics Services and Devices Critical Unmet Need: Market Analysis*; Bioengineering Institute Center for Neuroprosthetics, Worcester Polytechnic Institution: Worcester, MA, USA, 2010. [[Google Scholar](#)] Available online: <https://openbionicslabs.com/shop/chestnut-board> (accessed on 15 April 2019).



INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details