

Fatigue Life Estimation of Blade of Engine – A Review

A. Pateriya¹, S.S.Narkhede²Associate Professor, Department of Mechanical Engineering, Pdm. Dr.V.B.K.College of Engineering,
Maharastra, India¹P.G. Student, Department of Mechanical Engineering, Pdm. Dr.V.B.K.College of Engineering,
Maharastra, India²

ABSTRACT: This paper involves various failure mechanisms and the general practices followed by a blade designer for deciding a blade configuration were also described. Although some significant advances have been made during past some decades in the design technology of the blade. First the designing of the blade geometry completed with CAD software and analysis with the analysis software. Blade failures still continue to take place, and hence efforts are still on to understand in totality the blade dynamics which has caused in large number of technical papers. Some of important are presented here. In this review stress is placed on paper dealing with general structural analysis of blade by analytical modeling, blade excitation and fatigue life estimation of blade.

KEYWORDS: Review, Design, blade, Failures.

I. INTRODUCTION

The propulsion system for an aircraft is the engine which is designed to accelerate a stream of gas that is used to produce the reactive thrust necessary to propel the aircraft. A typical engine consists of different modules like compressor, combustor, turbine, exhaust system etc.[1]. The frontal part of the engine, the compressor consisting of a number of stages of alternate rotating and stationary aerofoil, draws air in, compresses and delivers it into the combustion chamber. Both rotor and stator blades of compressor experience severe aerodynamic, mechanical and thermal loads in service. Despite best efforts, failures are encountered during testing due to various reasons, namely design, manufacturing, material selection, assembly etc. The common modes of failure in compressor blades is fatigue failure as a result of improper assembly, fretting, mechanical abnormalities induced during manufacturing or by foreign and internal object damage during engine run [2-4]. Systematic investigation helps in identifying the root cause of the failure and helps in preventing recurrence of the incident both during design & development as well as operational phases. The blade is a part of rotary mechanical device that extracts energy from a fluid flow and converts into useful work and purpose of blade technology are to extract the maximum quantity of energy from the working fluid to convert it into useful work with maximum reliability, minimum cost, minimum supervision and minimum starting time.

CFX-Blade Gen is an advanced, interactive blade design tool for turbo machinery modeling developed by AEA Technology Engineering Software Inc. Blade Gen incorporates years of soft turbo-machinery design and analysis expertise into an easy to use graphical environment utilizing terminology familiar to engineers involved in the design of rotating machinery. With Blade Gen, the user can redesign existing blades to achieve new design objectives or create completely new blade designs from scratch. Blade Gen represents a pivot all in between blade design, advanced fluid analysis and manufacturing. Used in combination with the CFX-Blade Gen plus Analysis Module, users can rapidly evaluate the performance of a component. Alternately, the geometry can be exported through CFX-Turbo Grid to CFX-TASC flow to provide a more rigorous analysis.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 11, November 2016

It also produces blade geometry files that can be exported to CAD design in package such as CATIA and AutoCAD. This enables the user to efficiently transition from preliminary blade design, to full3D viscous flow analysis, and finally to a CAD environment.

II. FAILURES

Losses on the Blade consist of the mechanical loss; tip clearance loss, secondary flow loss and blade profile loss etc. More than 60% of total losses on the Blade is generated by the two latter loss mechanisms. These losses are directly related with the reduction of Blade efficiency. In order to provide a new design methodology for reducing losses and increasing Blade efficiency, a three-dimensional axial-type blade shape will be designed by using CAD software like ProE or CATIA and optimization of design will be performed by analyzing different parameters using ANSYS workbench software.

Blade efficiency is the most important factor on the performance of heavy duty gas turbines for power plants, air turbines, or turbo expanders etc. This efficiency is related very closely with losses in the passage. Losses on the Blade consist of mechanical losses due to the friction of rotating parts or bearings, tip clearance losses due to the flow leakage through tip gap, secondary flow losses due to curved passages, and profile losses due to the blade shape. So, it needs to develop a new design technology for providing an optimum blade profile with either same or different material.

The break down and failures of turbo machineries have been influencing such as consequential damages and most importantly the cost to repairs. To avoid these, it is obvious that the blading of turbo machinery must be made structurally stronger, that means not in dimensions and/or use of materials of construction, but keeping the operating stresses well within the limits.

Blades function as airfoils by developing a gas dynamic lift from the pressure difference, which the airfoil causes, between the blades upper and lower surfaces. High-pressure stages are generally impulse stages and low-pressure stages are reaction stages. Thus, a single free standing blade can be considered as pre-twisted continuous beam with an asymmetric airfoil cross-section mounted at a stagger angle on a rotating disc. Reasons for failure of bladed disc are Excessive stresses, Resonance due to vibration, operating environmental effects. High cycle fatigue plays a significant role in many blade failures. During operation, periodic fluctuations in the steam force occur at frequencies, corresponding to the operating speed and harmonics and cause the bladed disk to vibrate. The amplitude of these vibrations depends in part of the natural frequencies of the bladed disk to the forcing frequency. Large amplitude vibration can occur when the forcing frequency approaches or becomes resonant with the natural frequency of the blades. Steam Blade manufacturers typically design and manufacture blades with adequate margins between the forcing frequencies and the fundamental natural frequencies to avoid resonance.

FAILURES IN BLADE

In the following paragraphs various failure modes of the blade are discussed along with different kinds of stresses in the blade and the nature of aerodynamic excitation. A brief discussion of each of the above failure mechanisms follows in order to understand their significance.

Excessive Stress

The total stress at any location of the blade is sum of the centrifugal tension, centrifugal bending, steady steam bending and the alternating bending. The amplitude of alternating bending depends on the dynamic bending force, damping factor and the resonant frequency. Each of these is briefly discussed below to highlight their importance.

Centrifugal Stress

In turbo engine, centrifugal stress is never the main cause of a blade failure, except in the rare cases of Blade run-away or due to low cycle fatigue caused by frequent start ups/shutdowns. However, centrifugal stress is an important contributing factor with fatigue failure, corrosion fatigue failure and stress corrosion failures. The level of centrifugal stress is kept at such a level so

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 11, November 2016

as to have enough margins for alternating stress. The blade configuration is designed so as to keep the center of gravity of shroud, airfoil and root attachments, on common radial axis. This prevents centrifugal induced torsion stresses.

III.MODELING

There has been a continuing improvement in the analytical modeling for the determination of natural frequencies of the system comprising of a set of blades mounted on the bladed disk. The early attempts to model the blade as a beam element have gradually led to a more detailed finite element representation. This finite element representation of real blade profile becomes necessary especially when plate or shell type of vibratory modes is induced.

Le-Chung Shaiu and Teng-Yuan Wa (1997), studied the free vibration behavior of buckled composite plates by using finite element method. Unlike beams or columns, plates can carry a much-increased load after buckling without failure. Here triangular plate element is taken for finite element analysis. This element is developed based on a simplified high order plate theory and large deformation assumptions. The nonlinear governing equations of motion for plates is linearized into two sets of equations by assuming small amplitude vibration of the laminates about its buckled static equilibrium profile. In the post buckling region, the buckled plate may shift from one buckling mode to another. Due to this buckle pattern change, plate is also suddenly changed which in turn makes the natural frequencies of the plate to have sudden jump. The buckling mode of plates shifted from first to second. Then the stiffness of the plate is increased which makes a sudden increase in natural frequencies.

Hu X X and Tsuigi T (1999), had done free vibration analysis on curved and twisted cylindrical thin panels. Blades are part of turbomachinery rotating at high speed, so it is important to ensure safety while rotating. A turbomachinery blade is treated as a cylindrical thin panel twist, chordwise and spanwise curvatures along lengthwise direction. The non-linear strain-displacement relations of the model are derived based on the general thin shell theory and a numerical method for analyzing the free vibrations of curved and twisted cylindrical thin panels is presented by means of the principle of virtual work for the free vibration using Raleigh-Ritz method. It is shown that the method is effective for analyzing the free vibrations of the turbomachinery blades, and can provide accurate results when the proper number of integrating points and terms of displacement functions are adopted. The effects of curvature and twist on the vibrations are studied. This method is adequate for evaluating the vibration characteristics even if the models have large curvatures and large twists.

Rao J S (1974), made a two-dimensional analysis of free vibrations in the tangential direction. The first step is to develop the potential and kinetic energies for the tangential motion of the blades and shrouds. Second, Hamilton's principle is applied to derive the differential equation of motion and the boundary conditions.

Tsuji and Sueoka (1990), deal with the free vibration of cylindrical panels by using Raleigh-Ritz method. Blades of turbo machinery are twisted in axial direction and cambered in the chord wise direction. The blade has been idealized to a twisted cantilevered cylindrical panel and numerical methods have investigated its vibratory characteristics. The convergence of frequency parameters is studied with the increase of number of strip and of terms in assumed solution functions. To demonstrate the usefulness of the method, the frequency parameters obtained. The frequency parameters and the modes of vibration are analyzed for typical twisted cylindrical panels and the effect of pre twist on them is investigated.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 11, November 2016

Leissa, MacBain and Kielb (1984), made a comprehensive study of the numerous previous investigations on the free vibration of twisted cantilever plates of rectangular platform which are results of a joint industry, government and university effort. Theoretical results received from different FEM programs utilizing shell theory and beam theory were compared with two independent sets of data obtained from experiments. Reasonable agreement among the theoretical results was found but it was recommended that further improvement in analysis method is necessary for increased dependability.

Sagar P Kauthalkar and Devendra S Shikarwar, had investigated the deformations and stresses induced in blade geometry they have found out the maximum elongations and temperatures are observed at the blade tip section and minimum elongation and temperature variations at the root of the blade. Temperature distribution is almost uniform at the maximum curvature region along blade profile. Temperature is linearly decreasing from the tip of the blade to the root of the blade section. Maximum stress induced is within safe limit.

Avinash V Sarlashkar, Girish A Modgil, Mark L Redding summarizes the architecture and capabilities of Blade Pro, an ANSYS based Bladeblade analysis system with extensive automation for solid model and F.E. model generation, boundary condition application, file handling and job submission tasks for a variety of complex analyses.

IV. CONCLUSION

In this paper, analyzed previous generals and designs of the blade to do further optimization, Finite element results for free standing blades give a complete image of structural characteristics, which can utilized for the improvement in the design and the operating conditions. From the review it can be noted that there are various factors like blade angle, blade geometry, number of perforated holes and the material of the blade can affect structural as well as thermal stresses.

REFERENCES

1. A H Shah, G S Ramsekhar and Y M Desai (2002), "Natural Vibration of Laminated Composites Beams by Using Fixed Finite Element Modeling", Journal of the sound and vibration, Vol. 257, pp. 635-651.
2. Avinash V Sarlashkar (2001), "Blade ProTM: An ANSYS-Based BladeBlade Analysis System", Impact Technologies, LLC, Rochester, NY 14623, U.S.A Yoo H H, J Y Kwak and J Chung, Vibrational analysis of rotating pre twisted blades with a concentrated mass, Journal of sound and vibration, Vol 240, No. 5.
3. Hu, XX and T Tsuji (1999), Free Vibrational Analysis of Curved and Twisted Cylindrical thin Panels", Journal of Sound and Vibration, Vol. 219, No. 1, pp. 63-68.
4. J S Rao, R Bahree and A M Sharan (1989), "The Design of Rotor Blades Taking into Account the Combined Effects of Vibratory and Thermal Loads", Transactions of ASME, Journal of Engineering gas turbines and Power, Vol.111, pp. 610-618.
5. Le-chungshiau and Teng-yuanWu (1997), "Free Vibration of Buckled Laminated Plates by Finite Element Method", Transactions of the ASME, Journal of Vibrations and Acoustics, Vol. 111, pp.635-644.
6. Leissa A W, Macbin J C and Keilb R E(1984), Vibration of Twisted Cantilever Plates Summary of Provisions; Current Studies", Journal of sound and vibration, Vol. 96, Vol. 20, pp. 159-167.
7. Michel Arnal (2007), "Fluid Structure Interaction Makesfor Cool Gas BladeBlades", ANSYS Advantage, Vol. 1, No.1.
8. Rao J S (1974), "Application of Variational Principle to Shrouded BladeB2lades", Proceedings of 19th cong. ISTAM, pp. 93-97.
9. Sagar P Kauthalkar (2008), "Analysis of Thermal Stresses Distribution Pattern on Gas Turbine", International Journal of Engineering, Education and Technology (ARDIJEET) ISSN 2320-8.
10. Tsuneo Tsuji and Teisukesueoka (1990), "Vibrational Analysis of Twisted thin Cylindrical Panels by Using Raleigh-Ritz method", JSME International Journal, Series iii, Volume 33, pp. 501-505.
11. Swati Biswas, MD Ganeshachar, Jivan Kumar and VN Satish Kumar" Failure Analysis of a Compressor Blade of Gas Turbine Engine" ICONS-2014.