

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

Environmental Impact on Cement Production

Ravi Kant¹

Department of Civil Engineering, Vivekananda Global University, Jaipur, India¹

ravikant_pareek@vgu.ac.in¹

ABSTRACT:Controlling contamination is an obligatory legitimate and social necessity appropriate to any industry. As cement industry is one of the greatest CO₂emitters, it is appropriate to talk about different available resources of CO₂capture, which will be done straightaway. At long last, we give a record of production of Nano cement and favorable circumstances related with Nano cement. Nanofillers, for example, nanotitania, nanosilica, and nanoalumina can be produced in huge mechanical scale by means of top-down methodology of diminishing size of normally accessible mass crude materials to those in thenanorange of 1 nm–100 nm. We notice the planning of nanotitaniaand nanosilica from Sri Lankan mineral sands and quartz deposits, separately, for the utilization as added substances in cement items to improve execution and decrease the sum and cost of cement creation and resulting ecological effects. As of now, mineral sands and different fortunes of minerals are exported without much worth expansion. Straightforward substance modifications or actual medicines would increase the value of these natural materials. Sri Lanka is skilled with exceptionally unadulterated quartz and graphite from which silica and graphite nanoparticles, individually, can be arranged by straightforward size decrease measures. These can be utilized as added substances in cements. Detachment of constituents of mineral sands is as of now a continuous cycle.

KEYWORDS:Cement Production, Mineral, Nano Cement, Silica, Guidelines.

I. INTRODUCTION

This paper is an all-encompassing form of the Conference Paper published in the Proceedings of the 28th International Symposium on Transport Phenomena, Peradeniya, Sri Lanka. As portrayed in it, cement is a fine substance made [1]with calcined lime and mud as major fixings. Dirt utilized gives silica, alumina, and iron oxide, while calcined lime fundamentally gives calcium oxide. In cement assembling, crude materials of cement are acquired by impacting rock quarries by exhausting the stone and setting off explosives. These divided rocks are then transported to the plant and put away independently in storehouses. They are then conveyed, independently, through chutes to crushes where they are then squashed or beat to lumps of ~1/2inch–sized particles. Contingent upon the kind of cement being created, required extents of the squashed clay, lime stones, and some other required materials are then mixed by a cycle known as prehomogenization and processed in a vertical steel factory by crushing the material with the pressure exerted through three clone like rollers that turn over a turningmilling table[2].

Moreover, even factories inside which the material is pummeled by methods for steel balls are likewise utilized. It is at that point homogenized again and calcined, at 1400°C, in rotary kilns for the crude material to be changed to a clinker, which is a little, dull dark knob 3-4 cm in width. The clinker is released from the lower end of the furnace while it is red-hot, cooled by different advances, ground and blended with small measures of gypsum and limestone, and very finely ground to deliver cement. In the calcination cycle, in the oven, at high temperatures, the above oxides respond framing more complex compounds[3]. For example, response somewhere in the range of CaCO₃, Al₃(SiO₃)₂, and Fe₂O₃ would give a perplexing combination of alite, (CaO)₃SiO₂; belite, (CaO)₂SiO₂; tricalcium aluminate, Ca₃(Al₂O₃); and ferrite stage tetra calciumaluminoferrite, Ca₄Al₂O₃Fe₂O₃ with the advancement of CO₂ gas in the Portland cement clinker. Be that as it may,

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

there can be many other minor parts additionally since common dirt likewise contains Na, K, etc. In the synthetic examination of cement, its elemental structure is investigated (e.g., Ca, Si, Al, Mg, Fe, Na, K, and S). Then, the arrangement is determined in wording of their oxides and is by and large communicated as wt. % of oxides.

Cement production causes natural effects at all phases of the cycle[4]. These remember discharges of airborne contamination for the type of residue and gases; commotion and vibration while working apparatus and during impacting in quarries; and limestone quarries are noticeable from significant distances and may for all time deform the neighborhood climate. Hardware to lessen dust discharges during quarrying and production of cement is utilized by a few cement delivering organizations. Hardware to trap and separate fumes gases are additionally progressively utilized[5].

Atmosphere: Cement assembling contributes ozone harming substances straightforwardly through the creation of carbon dioxide when calcium carbonate is warmed (delivering lime and carbon dioxide) and by implication using energy, especially if the energy is sourced from petroleum derivatives[6]. The cement business produces about 5% of worldwide man-made CO₂ discharges, of which half is from the compound cycle, and 40% from copying fuel. The measure of CO₂ discharged by the cement business is almost 900kg of CO₂ for each 1000kg of cement delivered. It is fascinating to take note of that the recently evolved cement sorts from Novacem and Eco-cement can assimilate carbon dioxide from encompassing air during solidifying[7].

Energizes and crude materials: A cement plant devours 3–6GJ of fuel per ton of clinker created, contingent upon the crude materials and the cycle utilized. Most cement furnaces today use coal and petrol coke as essential energizes and, less significantly, flammable gas and fuel oil[8]. Chosen squander and results with recoverable calorific worth can be utilized as fills in a cement furnace, supplanting a bit of regular non-renewable energy sources, similar to coal, in the event that they meet severe determinations. Chosen squander and results containing helpful minerals, for example, calcium, silica, alumina and iron can be utilized as crude materials in the furnace, supplanting crude materials, for example, mud, shale and limestone. Since certain materials have both helpful mineral substance and recoverable calorific worth, the differentiation between elective fills and crude materials isn't in every case clear. For instance, sewage muck has a low yet critical calorific worth and consumes to give debris containing minerals valuable in the clinker lattice[7].

Creating cement has huge positive and negative effects at a neighborhood level. On the positive side, the cement business may make work and business openings for nearby individuals, especially in distant areas in non-industrial nations where there are not many different chances for monetary turn of events. Negative effects incorporate unsettling influence to the scene, residue and clamor and interruption to nearby biodiversity from quarrying limestone (the crude material for cement). In Sri Lanka, cement industry was introduced four decades ago by the state and managed by the state until very recently. Sri Lanka is perhaps the only country in this region, which uses 100% dry process for manufacturing cement. Puttalam Cement Company Ltd is the only factory that involves cement production from raw material excavation to cement packing[9].

The use of cement has long been the basis for development of society and for the welfare of the people for generations. Cement, which is made from cement, has been the ultimate material for construction. Cement manufacturing process is technology intensive. Raw material extraction causes serious environmental problems by damaging the landscape and most of these raw materials become scarce[10]. The cement industry recognizes its responsibility to manage the environmental impact, associated with the manufacturing of its product. Mainly, there are two types of cement production process; such as wet process and dry process. The preparation of cement includes mining, crushing, and grinding of raw materials, calcining the materials in rotary kiln, cooling, resultant clinker, mixing the clinker with gypsum and milling and bagging the finished cement. The cement production technologies in use cause extensive power consumption, gas emissions, noise pollution

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

environmental heating and emissions of fuel (CO_2 , NO_x , SO_2 and CO) from the kiln and precalciner. These are the major sources of environmental pollution in the cement industry to the best possible extent[11].

A cement creation plant comprises of the accompanying three cycles: Raw material cycle, clinker consuming cycle and get done with granulating measure. The crude material cycle and the clinker consuming cycle are each characterized into the wet cycle and the dry cycle. The major measures associated with creation are removal of limestone smashing of limestone, arrangement of other crude materials, pounding of crude materials in the crude plant, stockpiling of crude dinner in a crude plant storehouse, mixing of limestone powder to control CaCO_3 rate, consuming of crude supper to structure clinker, pounding the clinker with gypsum in cement plant and capacity of cement in storehouse pressing and dispersion of cement.

The determinations of crude materials utilized for cement creations are limestone 2470 (ton/day), laterite 130 (ton/day), crude feast (ground crude materials) of around 2600 ton/day that are gone through the oven towards the terminating end where warmth is applied with hefty heater oil. Temperature produced from consuming oil is brought up in the crude supper up to around 1450°C to structure the clinker at the pace of 1500 ton/day. The oven feed is set up by proportioning, pounding and mixing the crude material into a reliable and homogeneous synthesis so that, after mellow warming CO_2 and water could be removed. The crude materials are handled at very high temperature so they can respond by strong responses to frame clinker. These last items decide the cement attributes, for example, solidifying time, the early strength and the last strength. The biggest volume of crude material required is CaCO_3 or similar materials for example, shellfish shells (in areas where proper). The CaCO_3 is frequently mined in lumps up to a distance across of 750mm. These should be squashed to about 10mm, and afterward blended in with sand, shale, and different elements for additional crushing. Crushing and responses of crude materials, for example, limestone (97%-96%) and laterite (3%-4%) happens under controlled conditions to produce clinker. In the wake of crushing, contingent on the specific cycle, water might be added. The blend is then taken to some high – temperature preparing unit, known as turning furnace for change to solidify clinker. The clinker should be cooled before additional preparing. At that point it is ground in the plant with gypsum and other potential added substances to a fine powder of wrapped up cement.

Minerals of common inception just as modern items can be utilized for the creation of cement. Beginning materials for this intention are mineral mixes, containing the primary parts of cement, lime, silica, alumina, and iron oxide. The two primary segments are for the most part limestone and earth. In cement crude materials. The lime segment is for the most part spoken to by a measure of 76-80%. Limestone is of a transcendently fine-grained glasslike structure which impacts its tone. The principle segment of dirt is framed by hydrous aluminum silicates. Dirts are partitioned into the accompanying mineral gatherings; Kaolin gathering and Montmorillonite gathering. Chalk is sedimentary stone, which is shaped during the cretaceous period in topographical time. Impacting isn't needed for quarrying chalk and the smashing cycle can likewise be discarded. This sort of crude material extensively brings down the cement creation costs. Calcium carbonate (CaCO_3) which is wide spread in nature of all topographical developments fits the bill for the creation of cement. The most widely recognized types of Calcium carbonate is very much like marble, limestone and chalk.

II. CONCLUSION

Essentially, different sorts of cements and their chemical composition and applications in the current designing and chemical world have been talked about in detail. Different types of upgrading materials and fillers created utilizing Nano-innovation for the beneficial and effective cement manufacturing have been referenced with the chemical background. The mechanical imperfections when cement is concerned and potential arrangements that can be given through chemistry and nanotechnology have been thought in detail. Likewise, CO_2 -entangling substance compounds such as zeolites and metal natural structure and their contribution in making sturdiness of the cement manufacturing have been shown with their science. Climate effect of cement assembling and how to control the contamination of the climate when assembling

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Website: www.ijirset.com

Vol. 6, Issue 1, January 2017

measures that are being executed have been talked about utilizing a few standard processes, including the Calera cycle, oxy-burning cycle, and monoethanolamide (MEA) measure. As of now, the applications of nanoscience and nanotechnology have been acquiring popularity in different fields of science and innovation. The potential of nanotechnology to advance the presentation of cement and to prompt the improvement of novel, sustainable, advanced cement based composites, and shrewd materials with extraordinary mechanical, warm, and electrical properties is promising, and numerous novel chances are required to arise what's to come. So finally, the most up to date pattern of making Nano-cement and its improvement towards current creating and updating world is portrayed ahead of time.

REFERENCES

- [1] S. P. Dunuweera and R. M. G. Rajapakse, "Cement Types, Composition, Uses and Advantages of Nanocement, Environmental Impact on Cement Production, and Possible Solutions," *Advances in Materials Science and Engineering*. 2018, doi: 10.1155/2018/4158682.
- [2] G. Habert, "Environmental impact of Portland cement production," in *Eco-Efficient Concrete*, 2013.
- [3] E. Hallström, A. Carlsson-Kanyama, and P. Börjesson, "Environmental impact of dietary change: A systematic review," *Journal of Cleaner Production*. 2015, doi: 10.1016/j.jclepro.2014.12.008.
- [4] D. Babor, D. Plian, and L. Judele, "Environmental Impact of Concrete," *Bul. Institutului Politeh. din Iasi. Sect. Constr. Arhit.*, 2009.
- [5] R. Bajpai, K. Choudhary, A. Srivastava, K. S. Sangwan, and M. Singh, "Environmental impact assessment of fly ash and silica fume based geopolymer concrete," *J. Clean. Prod.*, 2020, doi: 10.1016/j.jclepro.2020.120147.
- [6] G. Sandin and G. M. Peters, "Environmental impact of textile reuse and recycling – A review," *Journal of Cleaner Production*. 2018, doi: 10.1016/j.jclepro.2018.02.266.
- [7] J. S. Damtoft, J. Lukasik, D. Herfort, D. Sorrentino, and E. M. Gartner, "Sustainable development and climate change initiatives," *Cem. Concr. Res.*, 2008, doi: 10.1016/j.cemconres.2007.09.008.
- [8] A. A. Olajire, "The brewing industry and environmental challenges," *J. Clean. Prod.*, 2020, doi: 10.1016/j.jclepro.2012.03.003.
- [9] M. Uwasu, K. Hara, and H. Yabar, "World cement production and environmental implications," *Environ. Dev.*, 2014, doi: 10.1016/j.envdev.2014.02.005.
- [10] Q. A. Nguyen and L. Hens, "Environmental performance of the cement industry in Vietnam: the influence of ISO 14001 certification," *J. Clean. Prod.*, 2015, doi: 10.1016/j.jclepro.2013.09.032.
- [11] T. R. Naik, "Sustainability of Concrete Construction," *Pract. Period. Struct. Des. Constr.*, 2008, doi: 10.1061/(asce)1084-0680(2008)13:2(98).
- [12] Basant Ali Sayed Alia, Abeer Badr El Din Ahmedb, Alaa El Din Muhammad, El Ghazalic and Vishal Jain, "Incremental Learning Approach for Enhancing the Performance of Multi-Layer Perceptron for Determining the Stock Trend", *International Journal of Sciences: Basic and Applied Research (IJSBAR)*, Jordan, page no. 15 to 23, having ISSN 2307-4531.
- [13] Nisha Pandey, B. S. Chowdhary, Bhagwan Das, D. M. Akbar Husain, Vishal Jain, Tanesh Kumar, "Design of Data Processing Device on Low Power SPARTAN6 FPGA", *International Journal of Control and Automation (IJCA)*.
- [14] Sujeet Pandey, Puneet Tomar, Lubna Luxmi Dhirani, D. M. Akbar Hussain, Vishal Jain, Nisha Pandey, "Design of Energy Efficient Sinusoidal PWM Waveform Generator on FPGA", *International Journal of Signal Processing, Image Processing and Pattern Recognition (IJSIP)*, Vol. 10 No. 10, October, 2017, page no. 49-58 having ISSN No. 2005-4254.