

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

Diagnosing Stress in Terms of Natural Etiquettes

Dr. Shubhangi D.C¹, Madeeha Fatima²

Professor Chairman, Department of Studies in Computer Science and engineering, Visvesvaraya Technological
University Center for PG Studies, Kalaburagi, Karnataka, India¹

PG student, Department of Studies in Computer Science and engineering, Visvesvaraya Technological University
Center for PG Studies, Kalaburagi, Karnataka, India²

ABSTRACT: Psychological stress is intimidating public's health. It is non- inconsequential to identify stress timely for pre-emptive care. Popularity of societal media, persons are used to distribution their everyday accomplishments and cooperating with groups on public media stands, making it achievable to influence online societal network into for stress recognition. In this paper, we find that clients push is barely related to that of his/her systems without attempting to shroud media, and we business a basic dataset from utilitarian social stages to adequately take in the relationship of user's weight and social correspondences. We initially describe a usual of stress-related written, graphic, and social elements from numerous aspects, and then recommend a hybrid model - a factor graph model (FGM) joined with Convolutional Neural Network (CNN) to influence tweet data and social communication info (social interaction data) for stress recognition.

KEYWORDS: Convolution Neural Network(CNN), Hybrid Model, Stress recognition, Social communication.

I. INTRODUCTION

A regularly expanding number of youngsters today are over-trouble with juvenile stress from different points of view: academic future, self-understanding, amongst individual, and affection. Enduring pressure may prompt uneasiness, withdrawal, animosity, or poor adapting abilities, for example, medication and liquor utilize, debilitating young people's wellbeing and improvement. Henceforth, it is critical for the two young people and their watchmen/instructors to know about the worry ahead of time, and deal with the worry before it ends up extreme and begins causing medical issues.

The present web-based social networking littler scale blog offers an open channel for us to helpful and unpretentiously sense immature's weight in light of his/her tweeting substance and practices. This investigation depicts a structure to additionally foresee young person's future youthful feeling of anxiety from smaller scale blog, and talks about how we address the difficulties (information deficiency and multifaceted forecast) utilizing machine learning and multi-variation time arrangement expectation strategies. Approaching occasions that may perhaps impact adolescent's feelings of anxiety are additionally fused into our expectation strategy. Our test comes about exhibit the viability of considering associated highlights and occasion impact in forecast. To the best of our insight, this is the main work on foreseeing young person's future feeling of anxiety by means of smaller scale blog.

Disregarding the way that not all weight is negative, a particular level of weight can be valuable to help improve execution. Nonetheless, contemplates uncover that an overabundance of stress can inimically impact prosperity of a man ; the amount of understudies uncovered inclination overwhelmed and centered has extended steadily in the latest decade. The greater part of students bear colossal levels of stress in the midst of a common school semester.

As demonstrated by a general review uncovered by Newbusiness over bit of the masses have experienced an undeniable rising in stress throughout the latest two years. As indicated by existing examination works, long haul pressure has been observed to be identified with numerous illnesses, e.g., clinical discouragements, a sleeping disorder

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

and so forth. All these uncover that the quick increment of stress has turned into an extraordinary test to human wellbeing and life quality. Accordingly, there is noteworthy significance to identify worry before it transforms into serious issues.

Imprisonments Exist in Tweeting Content Based Stress Detection. To begin with, tweets are restricted to a greatest of 140 characters on social stages like Twitter and Sina Weibo, and clients don't generally express their upsetting states straightforwardly in tweets. Second, clients with high mental pressure may show low liveliness on informal organizations, as announced by an ongoing report in Pew Research Center.³ These marvels cause the innate information sparsity and equivocalness issue, which may hurt the execution of tweeting content based pressure discovery execution.

Clients' Social Interactions on Social Networks Contain Useful hint for Stress Detection. Social mental examinations have mentioned two fascinating objective facts. The first is temperament virus: a terrible state of mind can be exchanged starting with one individual then onto the next amid social collaboration. The second is etymological echoes: individuals are known to emulate the style and influence of someone else. These perceptions spur us to extend the extent of tweet-wise examination by fusing follow-up social associations like remarks and retweeting exercises in client's pressure recognition. This may really alleviate the single client's information sparsity issue.

II. RELATED WORK

Bogomolov et al. [1] proposed an elective approach giving confirmation that day by day stress can be dependably perceived in view of social measurements, got from the client's cell phone movement and from extra markers, for example, the climate conditions and the identity characteristics. Hong L. and so forth [2] proposed StressSense to inconspicuously perceive worry from human voice utilizing cell phones. Paredes, P. etc. [3] investigated the initial lab evidence of the use of a computer mouse in the detection of stress.

Fan et al. [4] contemplated the feeling proliferation issue in interpersonal organizations, and found that outrage has a more grounded relationship among unexpected clients in comparison to euphoria, showing that contrary feelings could spread all the more rapidly and comprehensively in the system. As stress is generally considered as a negative inclination, this conclusion has helped the authors to find stress and was accomplished by merging the social influence of customers for push area.

Glen Coppersmith et al. [5] proposed a novel technique to identify stress particularly post traumatic stress among the military veterans by using proposed classifier internet based life utilizing straightforward ventures of accessible Twitter data .

Human feeling is one critical fundamental power influencing and influenced by the progression of interpersonal organizations. A fascinating inquiry is "how might we foresee a man's inclination in view of his memorable feeling log and his informal organization?". Y. Zhang et al. [6] proposed a MoodCast strategy in view of a dynamic persistent factor diagram demonstrate for displaying and anticipating clients' feelings in an informal community.

C.Tan,L et al. [7] showed that information about social associations can be used to improve customer level supposition examination. The fundamental inspiration driving this approach is that clients that are by one means or another "associated" might probably hold comparable sentiments.

Paredes, P., Sun, D., and Canny, J.[8], With the fast spread of informal organizations, explores on utilizing web based life information for physical and mental human services are likewise progressively developing. Sadilek et al. [9] utilize Tweeter postings to see the spread of flu signs. Paul M.J. et cetera [10] apply the Ailment Topic Aspect Model to in excess of 1.5 million thriving related tweets and discover connection between's lead threat factors and ailments, the maker utilize social signs showed from Twitter postings to foresee discouragement before it is addressed.

III.METHODOLOGY

Numerous examinations via web-based networking media based feeling investigation are at tweet level, utilizing content based phonetic highlights and great grouping approaches. A framework titled Mood Lens to achieve feeling investigation on Chinese small scale blog stage Weibo, characterizing feeling classifications into four kinds, i.e., furious, disturbing, upbeat, and dismal. A current framework contemplated the feeling proliferation issue in

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

informal communities, and found that outrage has a more grounded connection among unexpected users in comparison to euphoria, showing that bad feelings could extent all the more rapidly and extensively in network. As stress is for the most part measured as a bad feeling, this deduction can relief us in joining the social impact of users for stress location.

Traditional mental stress location is essentially in view of face to face interviews, self-documents polls or wearable sensors. Customary techniques are really responsive, which are typically work expending, time-costing and hysteretic. These works basically use the literary substance in informal communities. In all actuality, data in informal organizations is normally made out of consecutive and between associated things from differing sources and modalities, influencing it to be really cross-media data. Though some user level feeling recognition thinks about must be done, the part that community connections plays in one's mental stress states, and in what way we can consolidate such data into stress identification haven't been inspected yet

Inspired by mental assumptions, we originally describe an arrangement of properties for stress recognition from tweet level and user level perspectives separately: 1) tweet level qualities from material of user's single tweet, and 2) user level appearances from user's weekly tweets.

The tweet level appearances are for most portions made through out of semantic, visual and social deliberation (i.e., being liked, retweeted, or commented) traits disconnected from a self-contained tweet's content, picture, and deliberation list. The user level characteristics anyway are through out of: (a) posting behavior qualities as condensed from user's weekly tweet postings; and (b) social collaboration traits removed from user's social networks with buddies.

Experimental comes about establish that by abusing users' community connection traits, the planned model can develop the recognition execution (F1 score) by 6-9% terminated that of the situation of workman ship techniques. This proves the proposed qualities can fill in as excessive signals in control the info sparsity and vagueness concern. In accumulation, the planned model can similarly expertly join tweet affluence and social cooperation to enhance stress recognition implementation.

We assemble a few stressed twitter posting records by various ground reality naming techniques from a few prominent social broadcasting stages and altogether calculate our planned strategy on various perspectives. We carry out studies on a certifiable vast scale records and choice up bits of information on networks between social communications and stress, and additionally social arrangements of stressed users.

3.1 System Architecture:

Figure 1 gives details of the system architecture. For recognizing stress levels or percentage among people here textual data is been considered, were different users logs in to their respective social media account, in our case- twitter and make a tweet. This data is collected and could be observed by the users followers/followee and they can do any action like being retweeted, liked or comment. By using neural networks and the classifier and cross auto encoder stressful words will be extracted from the tweets of the users and interactions among its friends. Thus, analyzing the data we plot a factor graph for the percentage of stressed and non-stressed tweets for a particular user and also overall stress level of all the users.




Figure 1: System Architecture

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

3.2 Attributes classification

We initially characterize two arrangements of credits to gauge the distinctions of the pushed and non-focused on clients via web-based networking media stages: 1) tweet-level characteristics from a client's single tweet; 2) client level traits abridged from a client's week by week tweets.

3.2.1 Tweet-level Attributes

Tweet-level properties portray the phonetic and visual substance, and in addition social consideration factors (being preferred, remarked, and retweeted) of a solitary tweet. We can group words into various classes, e.g. positive/negative feeling words, degree intensifiers. Furthermore, we extricate semantic traits of emojis, so we can outline watchword in square sections to discover the emojis. Twitter embraces Unicode as the portrayal for all emoticons, which can be separated specifically. For phonetic characteristics we utilize LTP(Language Technology Platform) which is a planned getting ready stage which joins a suite of predominant normal vernacular taking care of (regular dialect handling NLP) modules and pertinent corpora. Especially for the syntactic and semantic parsing modules, it achieved remarkable results in some essential appraisals. In light of XML interior information portrayal, clients can undoubtedly utilize it and corpora by conjuring DLL (Dynamic Link Library) or Web benefit APIs (Application Program Interface), and view the handling comes about straightforwardly by the representation device. Expecting that we need to get the grammatical feature labels of a record, we can actualize it with Python programming dialect effortlessly as appeared,

```
from ltp_interface import *
CreateDOMFromTxt("test.txt") # Load a text
POSTag() # Invoke POS tagger
for i in range( CountSentenceInDocument() ): # Handle each sentence in a document
word_list = GetWordsFromSentence(i) # Get words
pos_list=GetPOSsFromSentence(i)#GetPOS
```

3.2.2 User-Level Attributes

Contrasted with tweet-level traits extricated from a solitary tweet, client level characteristics are separated from a rundown of client's tweets in a particular testing period. We utilize multi week as the testing time frame in this paper. On one hand, mental pressure regularly comes about because of aggregate occasions or mental states. Then again, clients may express their perpetual worry in a progression of tweets as opposed to one. We have to incorporate more integral data around tweets, e.g., clients' social collaborations with companions.

3.3 Model Learning and cumulative attributes:

We characterize low-level substance properties from each single tweet in tweet-scope, and measurable characteristics from amassed tweets in client scope. In tweet-scope, we worry about the low-level substance properties of a solitary tweet, while in client scope, we worry about one's states reflected by a few tweets in a period. These two arrangements of characteristics can't be joined specifically since their numerical portrayals are not in a similar area. So we have to create inactive client scope content traits from low-level substance characteristics at first.

Cross auto encoders : As opposed to outlining the client's state alone, we additionally join the detail qualities with numerous modalities of each tweet by using an as of late proposed cross-media show, specifically the Cross Autoencoders (CAE) [11].

An auto encoder is an essential unit in profound neural systems for taking in unmistakable qualities from information [12-14]. It is a shallow system containing one shrouded layer and matched info/yield layers. The framework is set up to replicate input outline from activation of the covered layer, which is extremely engaged by the data itself. The recreation can be planned by

$$\begin{aligned}y &= d^1 w^1 x + b^1 \\x &= d^2 w^2 y + b^2\end{aligned}\quad (1)$$

where x is the input pattern and y is the activation of hidden units, x denotes the reconstruction result from the hidden units. w^1 and w^2 are the connection weights while b^1 and b^2 are bias to the postsynaptic units. d^1 and d^2 are activation functions of the units, where sigmoid functions are rational choice in many scenario.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

Preparing a CAE is very unique in relation to standard auto-encoders. There isn't unequivocal target for standard auto-encoders to learn include crosswise over modalities of each single tweet and they have a tendency to learn highlight inside each single methodology with few relationship association between various modalities . we prepare the CAE with an edited arrangement of information that contribution from maybe a couple modalities of each tweet.

$$\begin{aligned} r &= f(w_t q_t + w_i q_i + w_s q_s + b) \\ (q_t^-, q_i^-, q_s^-) &= f(w^- a + b^-) \end{aligned} \tag{2}$$

where where r is the joint representataion of methodology . w_t, w_i, w_s, w^- , are the association weights of encoders and decoders for various modalities f(.)is the initiation work ,we utilize a sigmoid enactment capacity and q_t^-, q_i^-, q_s^- are the reconstruction results.

The possibility of CAE is to compel the model to develop missing modalities in the preparation organize and to take in cross modalities relationship from information. We physically incapacitate the visual modalities or potentially social connection methodology of the preparation information and expect it to build every one of the three modalities. We set up the CAE with modified strategy of information q_t^-, q_i^-, q_s^- that duties from one modalities are missing, while meanwhile requiring to replicate all the three.

stochastic slope drop is utilized to prepare CAE,we assess the vitality work as takes after: $K(q_t^-, q_i^-, q_s^-; \theta) = \frac{1}{2} (\sum_{p \in t, i, s} \|q_p^- - q_p\|^2) + \frac{\lambda}{2} (\sum_{p \in t, i, s} \|w_m\|^2 + \|w_m^-\|^2)$ (3)

In the first place term measures exactness reproduction ,the second is the regularization to avoid show over fitting which is known as weight rot. λ is regularization weight.

The traits of tweets from a client's week by week tweet postings in course of events frame a period arrangement. To likewise exhibit a client as a subject obviously of activity of tweets, we apply Convolutional Neural Networks (CNN) [15]. CNNs have extensive learning limit while having many less associations and parameters to get the hang of contrasting with comparative size standard system layer. They center around learning stationary neighborhood characteristics for arrangement like pictures (pixel arrangement), talks and other time-arrangement.

3.5 Adapting incompletely named factor graph(PFG)

We utilized PFG to learn and distinguish pressure state utilizing social associations and tweet's substance .We define a target work by amplifying the restrictive likelihood of clients' pressure states S given a progression of property increased systems

$$K = \{K^t = \{(V^t, E^t, X^t, S^t)\}, t \in \{1, \dots, T\},$$

And $V = V^1 = \dots = V^T, |V| = N$ i.e., $P_\theta(S | G)$. The factor diagram [16] gives an approach to factorize the "worldwide" likelihood as a result of "nearby" factor capacities, which makes the amplification straightforward, i.e.,

$$\begin{aligned} P(S | G) &= \frac{P(X, G | S) P(S)}{P(X, G)} \propto P(S | G) P(X | S) \propto P(S | G) \prod_{v_i \in V} P(x_i | s_i) P(S | G) \\ &= \prod_{t=1}^T \prod_{i=1}^N f(x_i^t, s_i^t) h(s_i^t, s_i^{t+1}) \prod_{e \in E^t} g(s_e), \end{aligned} \tag{4}$$

The joint likelihood has three sorts of factor capacities, comparing to the instincts we have talked about.

Characteristic Factor. We utilize this factor $f(x_i^t, s_i^t)$ to speak to the connection between's client v_i 's pressure state at time t and her/his properties x_i^t . All the more specifically, we instantiate the factor by an exponential-direct capacity:

$$f(x_i^t, s_i^t) = \frac{1}{Z_\alpha} \exp \{\alpha^t x_i^t\} \tag{5}$$

where α is a parameter of the proposed model, and Z_α is a standardization term.

Dynamic Factor. We utilize this factor $f(s_i^t, s_i^{t+1})$ to represent the time connection between user v_i 's pressure state at time t and t+1. All the more specifically, we instantiate the factor by an exponential-direct capacity:

$$h(s_i^t, s_i^{t+1}) = \frac{1}{Z_\gamma} \exp \{\gamma^t h'(s_i^t, s_i^{t+1})\}, \tag{6}$$

where γ is the model parameters for this sort of factor, $h^t(\cdot)$ is defined as a vector of pointer capacities, and Z_γ is the standardization term.

Social Factor. We utilize social factor $g(s_e)$ to represent the connection between user v_i and v_j 's stress states according to c at time $g(s_e) = \frac{1}{Z_{\beta_c}} \exp \{\beta_c^T g'(s_i^t, s_i^t)\}$ (7)

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

where β_c is the model parameters for this kind of factor, $g^i(\cdot)$ is defined as a vector of pointer capacities, and Z_{β_c} is the standardization term. At long last, by joining Eq. (4), (5), and (6) into Eq. (3), the target work as the log-likelihood of the proposed show is,

$$Q = \sum_{t=1}^T \sum_{i=1}^N \alpha^t x_i^t + \sum_{t=1}^T \sum_{i=1}^N \gamma^t h'(s_i^t, s_i^{t+1}) + \sum_{t=1}^T \sum_{e \in E^t} \beta_c^T g'(s_i^t, s_j^t) - \log Z, \quad (8)$$

Where $Z = Z_\alpha \prod_{c \in C} Z_{\beta_c} Z_\gamma$ is the global standardization term.

Algorithm . Learning and Inference by Factor Graph

Input: a series of time-varying attribute augmented network G with stress states on some of the user nodes, learning rate η ;

Output: parameter value $\theta = \{\alpha, \{\beta_c\}, \gamma\}$ and full stress state vector S ;

Randomly initialize S ;

Initialize model parameters θ ;

repeat

 Compute gradient $\nabla \alpha, \nabla \beta_c, \nabla \gamma$;

 Update $\alpha \leftarrow \alpha + \eta \times \nabla \alpha$;

 Update $\beta_c \leftarrow \beta_c + \eta \times \nabla \beta_c$;

 Update $\gamma \leftarrow \gamma + \eta \times \nabla \gamma$;

until convergence

Learning the predictive model is to estimate configuration parameter θ and to maximize the function.

IV. RESULTS AND DISCUSSION

4.1 Accumulation of dataset

Dataset DB1: We first slither 350 million tweets information by means of Sina Weibo's gushing APIs from 2009.10 to 2012.10. At that point we gather tweets containing sentence designs like "I feel focused on this week" and "I feel focused on so much this week" as the week by week focused on state mark, and tweets containing "I feel loose" and "I feel non-worried" as the non-focused on state name. The "I feel" design has been ended up being compelling as ground truth information marks in feeling investigation in [17]. In this way, we collect over 19000 weeks of users' tweets that are labeled as stressed, and over 17000 weeks of non-stressed users' tweets. There are 492,676 tweets from 23304 users in total. We take this dataset for observation and experiments, which is represented by DB1. The points of interest of the dataset are appeared in Table 1.

Table 1. Details of dataset DB1 collection

Tweets label	Number of users	Number of tweets	Number of weeks	Number of tweets/week	Number of interacting users/weeks
Stressed	11,074	239,038	19,136	12.5	6.99
Non-stressed	12,230	253,638	17,861	14.2	5.79
Sum	23,304	492,676	36,997	13.3	6.35

We perform our experiments on four datasets DB1-DB4 collected from three different micro-blog platforms: Sina Weibo, Tencent Weibo1, and Twitter. The details of the other 3 datasets are shown in Table 2. The Tencent Weibo (DB3) and Twitter (DB4) are labeled using the sentence pattern method. Particularly, to maintain a strategic distance from the commotion in information ground truth, we build up a little scale dataset DB2 from Sina Weibo. DB2 is gathered from the clients that have shared the score of a mental pressure scale2 with 50 things by means of Sina Weibo.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

Table 2
Details of collected tweet datasets DB2-DB4 from different blog platform

Platform	Stress label	Number of tweets	Number of users	Number of weeks	Tweets/week
DB2:Sina Weibo (2010.2-2011.9)	Stressed	1,459	98	98	14.9
	Non-stressed	1,845	112	112	16.5
	Sum	3,304	210	210	15.7
DB3:Tencent Weibo (2011.11-2013.3)	Stressed	138,570	7,845	8,974	15.4
	Non-stressed	172,585	8,239	9,976	17.3
	Sum	311,155	16,084	18,950	16.4
DB4:Twitter (2009.6-2009.12)	Stressed	54,748	4,905	6,081	9.0
	Non-stressed	75,357	4,018	6,545	11.5
	Sum	130,105	8,923	12,626	10.3

Comparison Methods. We look at the running with social occasion frameworks for mental weight affirmation:

- Naive Bayes (NB) is a fundamental probabilistic classifier in setting of Bayes' theory that finds the back probability by figuring prior probability of qualities. The classifier names test with the best found back [18].
- Support Vector Machine (SVM) is a standard and joined classifier that is ended up being conceivable on a gigantic demand of get-together issues. It endeavors to find a hyperplane that assignments overseeing tests into their classes with most finished the best edge [19]. In our weight, we use SVM with RBF part which can manage most nonlinear kept portrayals better.
- Random Forest (RF) is a get-together learning technique for decision trees by building a strategy of decision trees with offbeat subsets of qualities and stowing them for delineation occurs as planned [20].
- Deep Neural Network (DNN). The proposed display show up with the convolutional neural network(CNN) with cross autoencoders.
-

Comparison of performance effecting different classifiers

To assess the viability of the proposed show, we initially play out a completely test against substantial scale DB1 from Sina Weibo. To assess the model productivity, we think about the CPU time of each preparation demonstrate. For the order models previously mentioned, we likewise think about their effectiveness execution. Despite the way that the arrangement of model ought to be conceivable detached, profitability is so far a great factor for evaluating a count. For DNN display, we aggregate up both pre-preparing stage and fine tuning stage. Table 3 records the CPU time of each model to prepare with every single marked datum.

Table 3
Comparison of results using different classifiers

Model	SVM	RF	NB	DNN
CPU time(s)	3.46×10^4	4.49×10^3	3.11	189×10^4

Effect of various modalities in content properties: Tweets content accompany numerous modalities. Since content is the essential piece of a tweet, we test utilizing exclusively message characteristics, utilizing blend of content and visual qualities, utilizing mix of content and social traits, and also utilizing all properties.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

Table 4
Comparison of result using different attributes(modalities)

Feature	Text	Text+visual	Text+Social	All
Accuracy	0.8613	0.8745	0.8621	0.9145
F1-score	0.8695	0.8865	0.8712	0.9320

As shown in Table 4, we report predict performance of using text(content) attributes (composed with only the named attributes in Table 5) alone as well as combining with statistical attributes. Using just text attribute gains rather high performance. Simply combining visual or social attributes even reduces the result, especially the social attributes. This trend is even more obvious when both types of attributes (content and statistical) are used. Nevertheless, using all attributes together outperforms using only text attributes.

For the pooling strategy, we likewise test the each of the three strategies: max pooling, mean-over-instance (MOI) pooling and mean-after some time (Saying) pooling. For far reaching examinations, we test SVM, RF, NB and in addition the proposed DNN as classifiers in this analysis. For this analysis, a 4-layer DNN is utilized. Table 5 demonstrates the results of expansive preliminaries. As to classifiers, SVM gets a precision of 75.3% and performance F1-score 0.8314 using the two properties together and max pooling. RF gets practically identical results where the precision is 75.15% and F1-score is 0.826. NB does not work splendidly with quantifiable characteristics. It gets its best result working with content based property alone using MOI pooling. The proposed DNN classifier accomplishes the general best execution with a precision of 78.57% and F1-score of 0.8443.

Table 5
Comparison of performance effecting different classifiers

Pooling strategies	Classifier	Support vector machine			Random forest			Naive Bayes classifier			Deep neural networks		
		Demography	Content	Both	Demography	Content	Both	Demography	Content	Both	Demography	Content	Both
MAX	Accuracy Performance	-	Used	75.3% 83.14%	-	Used	75.15% 82.6%	-	Less used	Less than 60%	-	Used	76.9% 84.9%
MOI	Accuracy performance	Used	Used	74.3% 82.1%	Used	Used	71.4% 82.2%	Used	Used	68.1% 75.6%	Used	Used	76.6% 83.4%
MOT	Accuracy Performance	-	Used	74.5% 82.6%	-	-	75.4% 82.5%	-	Used	64.8% 73.4%	-	Used	78.57% 84.43%

Analysis of stressed and un-stressed users from different platforms. Figure 2 below depicts analysis of stressed and unstressed users ,Analyzing stressed and un-stressed users of various social networks with relative distribution of number of users tweets and plotting the data on a pie chart depicts the impact of different users stressed or un-stressed in their respective fields based on the contents of social interactions like tweets’ comments ,retweets and likes. For example, among the users which are considered, relative distribution of stress is higher for businessmen.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018




Figure 2. Result analysis of various users being stressed or un-stressed

We further evaluate our model on other datasets DB2-DB4 to show that our model is a universal model. For this part of experiments, we use statistical attributes together with content attributes using MOT pooling, and with 4-layer DNN model. DB2 from Sina Weibo with PSTR name. We utilize a developed model prepared with extensive scale Sina Weibo dataset, and after that test it against another arrangement of subject freely examined from Sina Weibo.

DB3 from Tencent Weibo. We test on data collected from another major Chinese Micro-blog platform. For this test, we use the attribute extractor trained with large scale Sina Weibo dataset and only finetune the network with Twitter dataset in 5-fold. The accuracy is 76.78% and performance is 0.7915 which demonstrate the potential of the proposed model.

DB4 from Twitter. We also test against the twitter dataset. We still use the attribute extractor trained with large scale Sina Weibo dataset and only finetune the network with Twitter dataset in 5-fold. The accuracy is 67.43% and f1-score is 0.7224.

V. CONCLUSION

We demonstrated a scheme for identifying user's mental stress states from user's weekly social media data, utilizing tweet's material and furthermore users' social relations. Utilizing genuine societal media info as the premise, we considered connection amongst user's mental stress states and social collaboration practices. To completely use together substance and social collaboration data of user's tweets, we planned a cross breed display which joins FGM with a CNN.

In this effort, we additionally found a few fascinating wonders of stress. We originate that quantity of societal structures of meager association of stressed users is around 14% greater than that of non stressed users, demonstrating that social arrangement of stressed users' companions have a tendency to be fewer associated and fewer convoluted than that of non stressed users. These marvels might be helpful orientations for upcoming correlated investigations.

We can make use of image for their finding of stress as it is posted by a user. Using these images we have to compute the user's Stress level.

REFERENCES

- [1]. Andrey Bogomolov, Bruno Lepri, Michela Ferron, Fabio Pianesi, and Alex Pentland. Daily stress recognition from mobile phone data, weather conditions and individual traits. In *ACM International Conference on Multimedia*
- [2]. Lu, H., Frauendorfer, D., Rabbi, M., Mast, M. S., Chittaranjan, G. T., Campbell, A. T., ... & Choudhury, T. (2012, September). StressSense: Detecting stress in unconstrained acoustic environments using smartphones. In *Proceedings of the 2012 ACM Conference on Ubiquitous Computing* (pp. 351-360). ACM.
- [3]. Paredes, P., Sun, D., & Canny, J. (2013, May). Sensor-less sensing for affective computing and stress management technology. In *Pervasive Computing Technologies for Healthcare (PervasiveHealth)*, 2013 7th International Conference on (pp. 459- 463). IEEE
- [4]. R. Fan, J. Zhao, Y. Chen, and K. Xu, "Anger is more influential than joy: Sentiment correlation in weibo," *PLoS One*, vol. 9, 2014, Art. no. e110184.
- [5]. Glen Coppersmith, Craig Harman, and Mark Dredze. Measuring post traumatic stress disorder in twitter. In *Proceedings of the International Conference on Weblogs and Social Media*.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 7, Issue 6, June 2018

- [6]. Y. Zhang, J. Tang, J. Sun, Y. Chen, and J. Rao, "Moodcast: Emotion prediction via dynamic continuous factor graph model," Proc. IEEE 13th Int. Conf. Data Mining, 2010, pp. 1193–1198.
- [7]. C.Tan,L. Lee, J.Tang,L.Jiang,M.Zhou,andP.Li,"User-levelsentiment analysis incorporating social networks," in Proc. SIGKDD Int.Conf.Knowl.DiscoveryDataMining,2011,pp.1397–1405.
- [8]. Paredes, P., Sun, D., & Canny, J. (2013, May). Sensor-less sensing for affective computing and stress management technology. In Pervasive Computing Technologies for Healthcare (PervasiveHealth), 2013 7th International Conference on (pp. 459- 463). IEEE.
- [9]. Sadilek, A., Kautz, H. A., & Silenzio, V. (2012, June). Modeling Spread of Disease from Social Interactions. In ICWSM.
- [10]. Paul, M. J., & Dredze, M. (2011, July). You are what you Tweet: Analyzing Twitter for public health. In ICWSM.
- [11]. H. Lin, J. Jia, Q. Guo, Y. Xue, J. Huang, L. Cai, L. Feng. Psychological Stress Detection from Cross-media Microblog Data Using Deep Sparse Neural Network. In proceedings of IEEE International Conference on Multimedia & Expo, 2014.
- [12]. Hinton, G. E., & Salakhutdinov, R. R. (2006). Reducing the dimensionality of data with neural networks. Science, 313(5786), 504-507..
- [13]. Hinton, G. E. (2007). Learning multiple layers of representation. Trends in cognitive sciences, 11(10), 428-434.
- [14]. Bengio, Y. (2009). Learning deep architectures for AI. Foundations and trends® in Machine Learning, 2(1), 1-127.
- [15]. Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet Classification with Deep Convolutional Neural Networks. In NIPS (Vol. 1, No. 2, p. 4).
- [16]. F. R. Kschischang, B. J. Frey, and H.-A. Loeliger, "Factor graphs and the sum-product algorithm," IEEE Trans. Inform. Theory, vol. 47, no. 2, pp. 498–519, Feb. 2001.
- [17]. Kamvar, S. D., & Harris, J. (2011, February). We feel fine and searching the emotional web. In Proceedings of the fourth ACM international conference on Web search and data mining (pp. 117- 126). ACM
- [18]. Ng, A. Y., & Jordan, M. I. (2002). On discriminative vs. generative classifiers: A comparison of logistic regression and naive bayes. Advances in neural information processing systems, 2, 841-848.
- [19]. Chang, C. C., & Lin, C. J. (2011). LIBSVM: a library for support vector machines. ACM Transactions on Intelligent Systems and Technology (TIST), 2(3), 27.
- [20]. Svetnik, V., Liaw, A., Tong, C., Culberson, J. C., Sheridan, R. P., & Feuston, B. P. (2003). Random forest: a classification and regression tool for compound classification and QSAR modeling. Journal of chemical information and computer sciences, 43(6), 1947-1958