

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

IoT Based Intelligent Medication System for Monitoring the Physical Health

Priyanka J. Solanke¹, Scientist. K. Lakshman²

P.G. Student, National Institute of Electronics & Information Technology (NIELIT), Aurangabad. Maharashtra, India¹

Scientist 'C', National Institute of Electronics & Information Technology (NIELIT), Aurangabad. Maharashtra, India²

ABSTRACT: The Internet of Things (IoT) provides an efficient and new life to the healthcare field. It also has a rapid development of many fields. But the more important are real in the field of Medical. One of the better ways the doctors are capable to certainly and quickly right to use the relevant patient information's and including the patient medical history. Through the Internet of Things, tremendously improves the quality of information and the patient care in the Medical field.. Ontology aids computers in additionally understanding the symptoms and medical resources. So, Ontology helps to create a rehabilitation strategy and reconfigure medical resources according to patient's specific requirements rapidly and repeatedly. Internet of things serves as a catalyst for the healthcare and plays prominent role in wide range of healthcare applications Technology plays the major role in healthcare not only for sensory devices but also in communication, recording and display device. It is very important to monitor various medical parameters and post operational days. Hence the latest trend in Healthcare communication method using IOT is adapted.

KEYWORDS: Internet of Things, PIC microcontroller, ESP8266 Wi-Fi module, Smart medicine box, old age patients, permanent diseases, setting up time table, notification, sensing capability.

I. INTRODUCTION

Currently, worldwide aging and regularity of persistent diseases are flattering a broad concern. Numerous countries are undergoing hospital restructuring by reducing number of hospital beds and escalating home healthcare, which is envisioned to perk up health care quality, has fascinated wide-ranging attention. In order to track the physical status of the elderly and, in the meanwhile, to keep them healthy, the proposed idea will be helpful. IoT expands the Internet into our everyday lives by wirelessly connecting various smart objects, and will bring significant hangs in the way we live and interact with smart devices. The new wave in the era of computing will be outside the sphere of the conventional desktop. Internet of Things (IoT) is a network where many of the objects that surround us will be networked in one form or another. By using this technology the heartbeat sensors of the patient is collected through the heartbeat sensors and is fed to the computer server for processing and encryption [5]. Thus this platform can continuously monitor the patient providing proper alarms and trigger a message when there is any abnormal variation in the pulse rate. The status of the patient is generated every day and is stored in the server in the encrypted format. The encryption algorithm used here is the arithmetic part of elliptical curve cryptography without generating a curve. This platform flawlessly fuses IoT devices with in-home healthcare services for improved user experience and service efficiency. The swift paced life has always taken a levy on the people [8]. The satire is that new medicines are found for the never ending chain of diseases and often require timely medication with course therapy for curing. The existing techniques in market for the reminder include a pill box with a normal alarm. But this does not help in checking, overdose and wrong dosage among the patients. This proposed idea is a valuable solution to the medical noncompliance problem. Dropping patients non-compliance, guarantees better health, longer life expectancy, and better quality of life. The invention uses a dispensing scheme to help patients keep trail of their medicine consumption through a series of LED alarm indicator signals and audio alarm indicator signals [6]. Internet of Things is the primary technology for interconnecting all the medical resources of the rehabilitation systems. Also to combine the Networking technologies that enables a wide range of applications, devices or things to interact and communicate among themselves. The human services errands are

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

accordingly moved from traditional clinical environment to pervasive easy to use environment [11]. Likewise, the scope of observing subjects could be fundamentally extended, shifting from the patients at critical care, e.g., in an emergency vehicle, to those with incessant maladies. Specifically, the body sensors conveyed in, close to the human body, too as the setting mindful sensors like the ones inserted in cell phones, can be utilized to gauge the basic wellbeing parameters or key signs, for example, pulse, temperature, circulatory strain. In day-to-day life most of the people need to take medicines which was not there in past couple of years and the reason behind this is diseases are increasing in large amount. So sooner or later many people come in contact with these diseases. Some diseases are temporary diseases while many are permanent life threatening diseases. Life threatening diseases gets mixes with the human body in such a way that they can't leave the body ever and they increases in rapid time. Life span of humans became less because of such diseases and to overcome or to live a better life we need to take medicines regularly and also in large amount. We need to be in advice of Doctor who tells us to take desired pills in desired way so that patients face problems like forgetting pills to take at right time and also when Doctor changes the prescription of medicine patients have to remember the new schedule of medicine [10]. This problem of forgetting to take pills at right time, taking wrong medicines and accidentally taking of expired medicine causes health issues of patient and this leads to suffer from unhealthy life. Our project is to make PIC Microcontroller based Smart medicine box which uses Real time clock. The new awaited feature in our project is our system is sensible that patient has taken medicine or not and thus the patient can't postpone the time on which he needs to take pills. It is compulsory for the patient to take pills from the box at the right time otherwise our systems continues to make large sound until the medicine is taken out from the box. This notification feature adds life years to the patient and thus this thing is not available in any device which is the necessity for present days. Besides, other IoT sensors conveyed in warm homes or at healing facility rooms may give extra profitable data about nature where the observed patient found. For example, the temperature, the level of moistness, the lighting and additionally some patients sweat which can be measured by cutting edge shrewd beds and so forth, permitting the medical stuff to accomplish more precise analysis and hence convey more effective treatment [3].

II. LITERATURE SURVEY

A combination between electronic and mechanical pill boxes or dispensers is presented. It's been included certain traditional pills organizers, which represents a first step in these developments and allowed us to obtain ideas about design useful patterns in development of this solution. In is presented a pill dispenser which has different prescribed administration schedules. It includes a plurality of pill storage compartments, each of them capable of holding more than one pill [10]. This device has a pill detector and generates a signal to alert patients to take the prescribed medicine. There are twelve storage compartments, arranged in a ring about a vertically rotating wheel. However, this solution has a limitation Due to this pill dispenser can only hold doses for 24-hours. A current design presented in Cheyenne, shows a device that allows the storing and dispensing of pills and various supplements. In this section, a combination between electronic and mechanical pill boxes or dispensers is presented [9]. It's been included certain traditional pills organizers, which represents a first step in these developments and allowed us to obtain ideas about design useful patterns in development of this solution. In is presented a pill dispenser which has different prescribed administration schedules. It includes a plurality of pill storage compartments, each of them capable of holding more than one pill. This device has a pill detector and generates a signal to alert patients to take the prescribed medicine [12]. There are twelve storage compartments, arranged in a ring about a vertically rotating wheel. However, this solution has a limitation due to this pill dispenser can only hold doses for 24- hours. A current design presented in Cheyenne shows a device that allows the storing and dispensing of pills and various supplements (i.e., food, drug, supplements, liquids, powders or pills).This device works such as an alarm clock and may work with blister packed pills or alternatively uses an encapsulated compartment to hold and dispense loose pills. Also, it can be connected by wireless to external environments (cellphones, computers) [1]. However, this device does not allow the management of several dosages and different Kind of pills. Another solution is the e-pill. It has in its stock various alternatives to organize and dispense pills, can be mentioned especially two i) A device dedicated to dispense pills composed by 2 medication trays, and 3 day dosage discs. It has a circumference shape and it has turning compartments for each dosage time. The dosages are dispensed when an alarm is activated; this device does not and uses referential diseases, just uses dosages per days, and

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

is also not programmable for any schedule. ii) It is a reminder medication product focused on patients, caregivers or medical health professionals [7]. This device locks automatically and includes 2 keys. For patients trying to get medications before it is time there is tamper resistant. This device considers supply pills in one week, four times per day. Also it has alarm and text message reminders disadvantages perceived are to close device by interaction of keeper and is not Independent. As far as we know, more than it has been described before, there are many solutions which offers advantages as dispensing or alerting system however they do not provide an automatic reminder system, different alert forms or a study in IOT field, besides devices are economically difficult to access. In this work, it is proposed a solution that solves these problems [5].

III. DEVICE CONTRIBUTION

Improving lifestyle not only in elderly sick people also in general sick people is a main goal of this development; our device involves reliability and usability with a friendly technology. In the case of elderly people as in Marceline et al. It is well known with the years, the gradual degradation of faculties can affect the ability to cope with machine technology that is nowadays common in public spaces, like telephone cards and ticket machines (which requires physical and mental agility) or automatic tellers (where codes are needed to be memorized and alternatives must be selected rapidly)[3]. It is important to understand that these devices could become more an obstacle than an aid. This conclusion obtained through a study using two generations of men and women giving us a way to focus our priorities in development of a pillbox, considering parameters to interact correctly with elderly users mainly [5]. Achieving an appropriate reminder system combined with a new type of programming dosages inside a device may be a possible solution to currently. Interface that nowadays are everywhere to interact in a better way with a keeper or doctor who are tied most of the time to keep track from their patients, who can use easily technology interfaces. Give them partially release from that responsibility and focus only in load dosage in device [9]. While the interaction between patient and object. Won't be deep, is necessary to give a solution which doesn't complicate prospective interaction patient -pillbox, even though interact between them through technology is an important contribution which this work looks for. As Figure shows, a block diagram which summarizes the contribution of this paper. Here, it is an interaction between keeper and doctor (1) with the pillbox (4) through an interface (3) and a microcontroller. The device (4) sends notifications (5) to patient (6) and keeper (1). When a patient (6) takes the pill, there is an interaction between the pillbox (4) and a sensor (7). Finally, about that interactions are send.



Architecture of Health System

PIC 16F877A The PIC controller compared to other controllers is with low cost. The clock speed of the controllers is high with the rate of 20MHz. 8Kx14 words of FLASH program memory, 368X8 bytes of data memory (RAM), 256x8

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

bytes of EEPROM data memory and this is enough for the temperature control application. At the maximum clock rate, a PIC executes most of its instructions in 0.2 micro seconds or 5 instructions per microseconds. It has high speed in executing instruction. The efficiency and accuracy is very high. The instruction set consists of 35 instructions. For executing a program it requires only small steps. Power on reset and brown out protection ensure that the chip operates only when the supply voltage is within sections. A watch timer resets the PIC, if the chip malfunctions and deviates from its normal position. Any one of the core clock options can be supported including a low cost RC oscillator and a high accuracy crystal oscillator. These versatile timers can be characterized by inputs; control outputs and provide internal timing for program executions. The PIC microcontroller has a number of inbuilt modules such as analog to digital converter, universal asynchronous transmitter and receiver that increases versatility of microcontroller. The PIC IC (Integrated Chip) is having wide operating voltage range from 2.5 to 6V, using power saving devices with a less power loss. The PIC start plus development system includes PIC start plus development programmer and machine perception laboratory. The PIC start plus programmer gives the product developer the ability to program user software into any of the supported microcontrollers. The PIC start plus software running under MP LAB provides full interactive control over the programmer [6].

16×2 LCD is named so because; it has 16 Columns and 2 Rows. There are a lot of combinations available like, 8×1, 8×2, 10×2, 16×1, etc. but the most used one is the 16×2 LCD. So, it will have (16×2=32) 32 characters in total and each character will be made of 5×8 Pixel Dots. Operating Voltage is 4.7V to 5.3V Current consumption is 1mA without backlight Alphanumeric LCD display module, meaning can display alphabets and numbers Consists of two rows and each row can print 16 characters. Each character is built by a 5×8 pixel box Can work on both 8-bit and 4-bit mode It can also display any custom generated characters Available in Green and Blue Backlight [8].

ESP8266 offers a complete and self-contained Wi-Fi networking solution, allowing it to either host the application or to offload all Wi-Fi networking functions from another application processor. When ESP8266 hosts the application, and when it is the only application processor in the device, it is able to boot up directly from an external flash. It has integrated cache to improve the performance of the system in such applications, and to minimize the memory requirements. 802.11 b/g/n/d/e/i/k/r support; Wi-Fi Direct (P2P) support, P2P Discovery, P2P Group Owner mode, P2P Power Management. Infrastructure BSS Station mode / P2P mode / soft AP mode support, Hardware accelerators for CCMP (CBC-MAC, counter mode), TKIP (MIC, RC4), WAPI (SMS4), WEP (RC4), CRC; WPA/WPA2 PSK, and WPS driver; Additional 802.11i security features such as preauthentication, and TSN; Open Interface for various upper layer authentication schemes over EAP such as TLS, PEAP, LEAP, SIM, AKA, or customer specific; 802.11n support (2.4GHz / 5GHz); Supports MIMO 1 1 and 2 1, STBC, A-MPDU and A-MSDU aggregation and 0.4s guard interval; WMM power save U-APSD; multiple queue management to fully utilize traffic prioritization defined by 802.11e standard; UMA compliant and certified; 802.1h/RFC1042 frame encapsulation; Scattered DMA for optimal CPU off load on Zero Copy data transfer operations clock/power gating combined with 802.11-compliant power management dynamically adapted to current connection condition providing minimal power consumption; Adaptive rate fall back algorithm sets the optimum transmission rate and TX power based on actual SNR and packet loss information; Automatic retransmission and response on MAC to avoid packet discarding on slow host environment; Seamless roaming support; Configurable packet traffic arbitration (PTA) with dedicated slave processor based design provides flexible and exact timing Bluetooth co-existence support for a wide range of Bluetooth Chip vendors. Dual and single antenna Bluetooth co-existence support with optional simultaneous receive (Wi-Fi/Bluetooth) capability [12].

The DS1307 serial real-time clock (RTC) is a low-power, full binary-coded decimal (BCD) clock/calendar plus 56 bytes of NV SRAM. Address and data are transferred serially through an I2C, bidirectional bus. The clock/calendar provides seconds, minutes, hours, day, date, month, and year information. The end of the month date is automatically adjusted for months with fewer than 31 days, including corrections for leap year. The clock operates in either the 24-hour or 12-hour format with AM/PM indicator [2]. The DS1307 has a built-in power-sense circuit that detects power failures and automatically switches to the backup supply. Timekeeping operation continues while the part operates from the backup supply [9].

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

IV. TESTING METHODOLOGY

In order to verify the functionality of the device, a methodology developed for Paunovic, 2012 has been selected. It explained four phases for testing a device. Phases need to be executed sequentially, and then the transition to the next stage is only possible with positive report from previous stage. The advantage of this testing approach is providing a structured plan for finding and fixing errors and obtaining precise results. The first step of testing a device it is to examine the correctness of the device's hardware [4]. It means to verify the printed circuit board, links, components on the PCBs, etc. On this case most of the components are PCBs, so it is important to check the correct state of each one. In order to make that revision a Fluke multimeter has been used to measure the resistance of the lines and also to measure continuity of the layers. In this phase we test the correct function of the components. Here we assembly those ones that have sub systems for example the display and its shield or the DC motor and its driver. We prove each component in conjunction with its software. The third phase of the test aims to verify the stability of the system when the environmental and other conditions differ from nominal, defamed by device specification [3]. This phase involves testing beyond normal operation, often deliberate causing failure of the device, in the interest or consideration of the testing result. The final phase of device testing is to examine working in the conditions beyond nominal conditions, by improper use of the device, and the consequences of those situations. Robustness testing is defined as the degree to which a system or component can function properly in extreme conditions. These two phases has been skipped, because the main goal of this study it's to prove the final functionality of the device. The system is composed by different modules that are controlled by PIC Microcontrollers. There are different types of communication of each module. It could be one way or two ways. Therefore the PIC Microcontrollers send commands to the modules but also receive data from them [11].

V. CONCLUSION AND FUTURE WORK

Older people play an important role in the society. They are part of the priority group of healthcare. Therefore, creating new devices using the emerging technology in order to improve their lives quality is necessary. The creation of alternatives of medication devices looks promising and necessary due to that today only 1 of each 10 people in need have access to such system due to high costs and a lack of awareness, availability, personal trainee, policy and financing . The introduction of such devices in IOT could lead us to a future where important information of patients would be available anytime and anywhere, in order to make a correct treatment and to prevent calamities. 80 Based on open source solutions, a new alternative to remind medicine dosages was raised. Arduino Mega, as main controller works totally right and gives many other opportunities to develop. The objective of creating a device that allows the organization of several medication schedules, automatic opening system and an effective notification system was reached. As is mentioned in future works section, design and functionality will change not only with perceptions in developers of this prototype, is necessary to investigate a fellow implicated in this problem. IoT is an important aim pretended in this device, finding a way to keep pillbox connected to Internet and it will help surely to manage in better form the treatments in patients, mainly in elderly patients. With the wide use of internet this work is focused to implement the internet technology to establish a system which would communicate through internet for better health. Internet of things is expected to rule the world in various fields but more benefit would be in the field of healthcare. Hence present work is done to design an IOT based smart healthcare system using a PIC18F46K22 microcontroller Scientific validation method used is dedicated to validate electronic equipment and applications, for the future works this method will change and it let us evaluate response between elder patient and keepers with pillbox and this one with the biggest network is Internet. The data is also sent to the LCD for display so patient can know his health status. During extreme conditions to alert the doctor warning message is sent to the doctor's cell phone through GSM modem connected and at the same time the buzzer turns to alert the caretaker. The doctors can view the sent data by logging to the html webpage using unique IP and page refreshing option is given so continuously data reception achieved. Hence continuous patient monitoring system is designed.

The Future work of the project is very essential in order to make the design system more advanced. In the designed system the enhancement would be connecting more sensors to internet which measures various other health parameters

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 7, July 2019

and would be beneficial for patient monitoring i.e. connecting all the objects to internet for quick and easy access. Establishing a Wi-Fi mesh type network to increase in the communication range.

REFERENCES

- [1] Junaid Mohammed, AbhinavThakral, Adrian FilipOceanu, Colin Jones, Chung-Horng Lung, Andy Adler “Internet of Things: Remote Patient Monitoring Using Web Services and Cloud Computing” 2014 IEEE International Conference on Internet of Things (iThings 2014), Green Computing and Communications (GreenCom2014), and Cyber-Physical-Social Computing (CPSCom 2014),P.P 978-1-4799-5967-9/14.
- [2] BoyiXu, Li Da Xu, Senior Member, IEEE, HongmingCai, Cheng Xie, Jingyuan Hu, and Fenglin Bu “Ubiquitous Data Accessing Method in IoT-Based Information System for Emergency Medical Services” IEEE TRANSACTIONS ON INDUSTRIAL INFORMATICS, VOL. 10, NO. 2, MAY 2014, P.P1551-3203.
- [3] P. K. Sahoo, S. K. Mohapatra, and S. L. Wu. Analyzing healthcare big data with prediction for future health condition. IEEE Access, 4:9786–9799, 2016. ISSN 2169-3536.
- [4] S. Tyagi, A. Agarwal, and P. Maheshwari. A conceptual framework for iot-based healthcare system using cloud computing. In 2016 6th International Conference - Cloud System and Big Data Engineering (Confluence), pages 503–507, Jan 2016
- [5] B. G. Ahn, Y. H. Noh, and D. U. Jeong. Smart chair based on multi heart rate detection system. In 2015 IEEE SENSORS, pages 1–4, Nov 2015.
- [6] I. Chiuchisan, H. N. Costin, and O. Geman. Adopting the internet of things technologies in health care systems. In 2014 International Conference and Exposition on Electrical and Power Engineering (EPE), pages 532– 535, Oct 2014.
- [7] A. Dwivedi, R. K. Bali, M. A. Belsis, R. N. G. Naguib,P. Every, and N. S. Nassar. Towards a practical healthcare information security model for healthcare institutions. In 4th International IEEE EMBS Special Topic Conference on Information Technology Applications in Biomedicine, 2003., pages 114–117, April 2003.
- [8] S. C. Li, L. D. Xu, and X. H. Wang, “Compressed sensing signal and data acquisition in wireless sensor networks and Internet of Things,” IEEE Trans. Ind. Infomart. vol. 9, no. 4, pp. 2177–2186, 2013.
- [9] B. Nath, F. Reynolds, and R. Want, “RFID technology and applications,” Pervasive Computing. vol. 5, no. 1, pp. 22–24, Jan. /Mar. 2006.
- [10] P. Mohan, D. Marin, S. Sultan, and A. Deen, “Medinet: Personalizing the self-care process for patients with diabetes, and cardiovascular disease using mobile telephony, IEEE Engineering in Medicine” in Proc. 30th Ann. Int. Conf. Biology Society, 2008.
- [11] CharalamposDoukas, IliasMaglogiannis “Bringing IoT and Cloud Computing towards Pervasive Healthcare” 2012 Sixth International Conference on Innovative Mobile and Internet Services in Ubiquitous Computing, P.P 978-0-7695-4684-1/12
- [12] VandanaMilindRohokale, NeeliRashmi Prasad, Ramjee Prasad “A Cooperative Internet of Things (IoT) for RuralHealthcare Monitoring and Control” 2011 Center for TeleInFrastuktur, Aalborg University, Denmark, P.P 978-1-4577-0787-2/11