



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 5, May 2024

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

[ijirset@gmail.com](mailto:ijirset@gmail.com)

[www.ijirset.com](http://www.ijirset.com)

# IoT Based Industrial Workers Safety System

**Dr.P.Sellamuthu, M.E., Ph.D, M.Suresh**

Associate Professor, Department of Mechanical, Vinayaka Mission's Kirupananda Variyar Engineering College,  
Salem, Tamilnadu, India

ME, Industrial Safety and Engineering, Vinayaka Mission's Kirupananda Variyar Engineering College,  
Salem, Tamilnadu, India

**ABSTRACT:** Smart Monitoring system can effectively improve work safety in hazardous environments like construction sites and mining areas. Through real-time sensing and data collection, workers' health conditions and environmental risks can be monitored around the clock. This helps identify potential hazards early and take preventive measures. For workers, the wearable devices provide a layer of security and peace of mind. They no longer have to worry about falling from heights, inhaling toxic gases or suffering a medical emergency without anyone knowing. The system can automatically alert emergency contacts and dispatch help. The collected data can also be analyzed to identify high-risk activities or work conditions. Over time, insights from the data can help devise improved safety protocols and workplace modifications. Accidents can be reduced through proactive risk mitigation measures informed by data and experience. However, workers' privacy must be respected when implementing such monitoring systems. Data should only be collected for safety purposes, with full transparency. Workers' consent is essential. The system should aim to empower workers, not restrict them. With care and responsible use of technology, smart monitoring can truly enhance safety in hazardous occupations.

## I. INTRODUCTION

In the recent days, the invention towards a new occupational health and safety group in which work societies are directed towards active safety values. It's prognosticated that the safety analysis ways now in place are relatively delicate to address the implicit pitfalls which weaken the period. A new approach to assaying different pivotal criteria in colorful artificial sectors is explained precisely in this work. In this unique approach, accident reduction model fashion is applied to determine the separate weights of three main criteria and seventeen sub-criteria as a way of perfecting the decision-making process while in a problem. A check was initiated in different artificial sectors to gain dependable data for the exploration.

Underground digging exertion for mortal workers could be a veritably parlous circumstance where the troubles proliferation with the ascent in separation from the resistance. The more drawn out the mine, parcel honored is the peril. The security estimates prosecution is highly poor, especially inside the mine ventures. Coal is an important asset to every country since it has many applications. The preeminent vital businesses of coal is the development of nuclear energy, concrete, and creation and as a energy for different operations. The coal mineshafts have different dangerous prospects that embrace outrageous temperature and stickiness, release of harming feasts that form dangerous environmental rudiments for experts working there. a many staff starting their occupations in coal mineshafts or not in any way shape or form leaned to pick similar jobs as mining. This makes heaps of difficulties inside the vacuity of staff for the coal mining exchange. The security of workers working in mine venture is expanding step by step through advancements. The moderate of development that allows the mine perception procedures to turn into a ton of meliorated, nevertheless, blasts in underground mine actually do. The mishaps of catastrophes in coal mineshafts in generally as a result of the savage conditions and dangerous working circumstances. This makes the need of involving mine checking fabrics at a significant position for coal mineshafts.




FIGURE 1: REPRESENTATION OF BLOCK DIAGRAM

## II.LITERATUREREVIEW

[1].K.L.Nishitha1,R. Ravi Kumar2. HEALTH MONITORINGSYSTEM Intelligent health monitoring system of the long- span road stayed requires the comprehensive knowledge of instrumentation,logical and information processing technologies with the knowledge and gests in design, construction, operation and conservation of road outfit for long- term covering the performance throughout its lifecycle. It's necessary to perform detector- grounded structural monitoring for relating the conditions in order to assure the structural safety and to estimate thefunctional performance.The considerations for planting a proper monitoring system are applicable detector instrumentation, robust signal accession, dependable signal processing, and intelligent signal and information processing. Detector and tackle instrumentation, signal transmission, signal accession and analysis are schematically described substantially. Fire and gas detectors are used to cover entire train system. And for passenger safety, we're attaching a wireless RF system. With this advanced outfit, the exact dangerous spot is known with in lower time.[2].Premalatha1,R.P.Keerthana2,R.Abarna3 mortal HEALTH MONITORING SYSTEM. - Moving into a new period of healthcare, new tools and bias are developed to extend and ameliorate health services, similar as remote case monitoring and threat forestallment. In this conception, Internet ofeffects(IoT) and Cloud Computing present great advantages by furnishing remote and effective services. In India numerous cases are dying because of heart attacks and reason behind that they aren't getting timely and proper help. To give them timely and proper help first we want to nonstop monitoring of patient health. The fixed monitoring system can be used only when the case is on the bed and this system is only available in hospitals. The system is developed for home use by cases that aren't in critical condition but need to be constant or periodically covered by clinician or family. In any critical condition the SMS is shoot to doctor or any family member. In this paper, a prototype of a wireless health monitoring system able of transferring SMS related to the health status of the case is developed. [3].IC.Senthamilarasi, 2J.Jansi Rani, 3B.Vidhya, 4H.Aritha. A SMART Case HEALTH MONITORING SYSTEM USING IOT. The healthcare covering systems has surfaced as one of the most vital system and came technology acquainted from the oncedecade.Now,humans are facing a problem of unanticipated death due to colorful illness which is because of lack of medical care to the cases at right time. The primary thing was to develop a dependable case monitoring system using IoT so that the healthcare professionals can cover their cases, who are moreover rehabilitated or at home using an IoT grounded integrated healthcare system with the view of icing cases are watched for better. A mobile device grounded wireless healthcare monitoring system was developed which can give real time online information about physiological conditions of a case substantially consists of detectors, the data accession unit, microcontroller( i.e., Arduino), and programmed with a software( i.e., JAVA). The case's temperature, heart beat rate, EEG data are covered, displayed and stored by the system and transferred to the croaker's mobile containing the operation. 4)S.J. Jung andW.Y. Chung studied the Flexible and scalable case's health monitoring system in 6LoWPAN( 2007). The main advantage of this enabling factor is the combination of some technologies and dispatches result. The results of Internet of effects are synergetic conditioning gathered in colorful fields of knowledge like telecommunications, informatics and electronics.

## III.PROPOSEDSYSTEM

The ideal of the design is to design a smart health monitoring and safety system for workers grounded on internet of effects(IOT). A new approach to assaying different vital criteria in various artificial sectors is explained precisely in this work. In this unique approach, accident reduction model fashion is applied to determine the separate weights of

three main criteria and seventeensub- criteria as a way of perfecting the decision- making process while in a problem. A check was initiated in different artificial sectors to gain reliable data for the disquisition. The results show that the main criteria ‘mortal safety’ acquired a weight of72.5 while the separate weights of primary criteria machine security and work terrain safety fall to8.9 and18.4. The security estimates prosecution is highly poor, especially inside the mine ventures. Coal is an important asset to every country since it has many applications. The preeminent vital businesses of coal is the development of nuclear energy, concrete, and creation and as a energy for different operations. The coal mineshafts have different dangerous prospects that embrace outrageous temperature and stickiness, release of harming feasts that form dangerous environmental rudiments.The weight themain criteria, mortal safety indicates that thesub- criteria analogous as eye protection, manual lifting, materials are running practices, firefighting drills, training and safety officers are executed to a lower extent in ultimate of the surveyediligence.In this design we're covering main criteria, mortal safety indicates that thesub- criteria analogous as eye protection, manual lifting, material running practices, firefighting drills, training and safety officers are executed to a lower extent in ultimate of the surveyediligence.In this design we're covering a workers full time through IOT using different parameters of patient health position. For each parameter different detectors are used to cover health position and terrain in real time we're using IOT. Temperature is used to cover body temperature. Case heart detector used heartbeatposition monitoring, SPO2 detector used for oxygen position measuring, thermistors used for body temperature position monitoring. All these parameters are stored in Arduino microcontroller and also it'll be uploaded in IOT garçon. In case of abnormal status of patient exigency communication insinuated via IOT garçon or android app to the croakerand its cousins. All these parameters are stored in Arduino microcontroller andalsoit will be uploaded in IOT garçon in case of exigency IOT garçon covered by croakerhe'll help the treatment for the particular workers. In this way effective examiner workers real- time system act as brain. We use Wi- Fi module these indicate and sense whichtype of fault and also give the information.In this system, we've introduced an advanced way to descry faults. Arduino is working as the brain of our system. Relays are used for protection because relays insulate the cargo at the time of fault.




FIGURE 2:HEALTH HAZARDS FACED BY MINERS



FIGURE 3:IMPLEMENTATION IN REAL TIME

#### IV.MODULE DESCRIPTION

##### i)ARDUINO UNO:

Arduino is also referred as Genuino Uno is a microcontroller board grounded on the ATmega328P. It has 14 digital input/ output pins (of which 6 can be used as PWM outputs), 6 analog inputs, a 16 MHz quartz crystal, a USB connection, a power jack, an ICSP header and a reset button. It contains support the microcontroller; simply connect it to a computer with a USB string or power it with a AC- to- DC appendage or battery to get started. You can tinker with your UNO without fussing too important about doing commodity wrong, worst case script you can replace the chip for a many bones and start over again." Uno" means one in Italian and was chosen to mark the release of Arduino Software (IDE) 1.0. The Uno board and interpretation 1.0 of Arduino Software (IDE) were the reference performances of Arduino, now evolved to the newer releases. The Uno board is the first in a series of USB Arduino releases. The Uno board is the first in a series of USB Arduino boards, and the reference model for the Arduino platform; for an expansive list of current, Arduino indicator of boards.



FIGURE 4:ARDUINO UNO

##### ii)LCD DISPLAY:

Liquid Crystal Displays (LCDs) have applications which combine the parcels of both liquids and crystals. Rather than having a melting point, they've a temperature range within which the molecules are nearly as mobile as they would be in a liquid, but are grouped together in an ordered form analogous to a crystal. LCDs have displaced cathode ray tube (CRT) displays in most operations. They're generally more compact, featherlight, movable, less precious, more dependable, and easier on the eyes. They're available in a wider range of screen sizes than CRT and tube displays, and since they don't use phosphors, they cannot suffer image burn-in. LCDs are more energy effective and offer safer disposal than CRTs. An LCD consists of two glass panels, with the liquid crystal material sandwiched in between them. The inner face of the glass plates are carpeted with transparent electrodes which define the character, symbols or patterns to be displayed. Polymer layers are present.



FIGURE 5:LCD DISPLAY

##### iii)TEMPERATURE SENSOR:

A thermistor is a type of resistor whose resistance varies with temperature. The word is a carryall of thermal and resistor. Thermistors are extensively used as inrush current limiters, temperature detectors, temperature-resetting overcurrent detectors, and temperature-regulating heating elements. Thermistors differ from resistance temperature sensors (RTD) in that the material used in a thermistor is generally a ceramic or polymer, while RTDs use pure metal. The temperature response is also different; RTDs are useful over larger temperature ranges, while thermistors generally achieve a advanced perfection within a limited temperature range (generally -90 °C to 130 °C). Thermistors can be classified into


two types, depending on the sign of  $k$ . If  $k$  is positive, the resistance increases with increasing temperature, and the device is called a positive temperature coefficient (PTC) thermistor, or posistor. If  $k$  is negative, the resistance decreases with increasing temperature, and the device is called a negative temperature coefficient (NTC) thermistor. Assuming, as a first-order approximation, that the relationship between resistance and temperature is direct, also where,

$$\Delta R = k\Delta T$$

$\Delta R$  = change in resistance

$\Delta T$  = change in temperature

$k$  = first-order temperature coefficient of resistance



**FIGURE 6:TEMPERATURE SENSOR.**

**iv)HEARTBEAT SENSOR:**

A device for holding a twinkle detector in a fairly fixed relationship with respect to the end of a stoner's fingertip,holding the twinkle detector and three flexible bands that extend upward therefrom. The bands are acclimated to grip the stoner's fingertip. In one personification of the invention, the bands and base portion define aU-shaped channel of constantcross-sectional area. In this personification a holding structure for the twinkle detector is wedge-shaped, the wedge- shaped holding structure being acclimated to be held by the base portion so that thecross-sectional area defined by each band and the wedge- shaped holding structure decreases along the longitudinal length of the base portion. The heart beats up to 120 times per nanosecond in nonage. When resting, the adult mortal heart beats at about 70 bpm(males) and 75 bpm(ladies), but this rate varies among people.




**FIGURE 7:HEART BEAT SENSOR.**

Still, the reference range is typically between 60 bpm(if lower nominated bradycardia) and 100 bpm(if lesser, nominated tachycardia). Resting heart rates can be significantly lower in athletes. The child/ neonatal rate of twinkle is around 130- 150 bpm, the toddler about 100 – 130 bpm, the aged child's about 90 – 110 bpm, and the adolescent's about 80 – 100 bpm.The invention provides a device for holding a heartbeat sensor in a relatively fixed relationship with respect to a user's fingertip. The device includes a base portion for holding the heartbeat sensor, and a pressure producing means connected to the base portion for holding the user's fingertip.

**v)ALCOHOL SENSOR:**

Blood alcohol content(BAC), also called blood alcohol attention, blood ethanol attention, or blood alcohol position is most generally used as a metric of alcohol intoxication for legal or medical purposes. Blood alcohol content is generally expressed as a chance of alcohol(generally in the sense of ethanol) in the blood. For case, a BAC of 0.10 means that 0.10(one tenth of one percent) of a person's blood, by volume(generally, but in some countries by mass), is alcohol. This alcohol detector is suitable for detecting alcohol attention on your breath, just like your common breathalyzer. It has a high perceptivity and fast response time.



**FIGURE 8:ALCOHOL SENSOR**

**vi )ALARM:**

An alarm gives a acknowledgement in the form Of audible or visual warning about a issue. A buzzer or beeper is a signalling device, generally electronic applicants, which used in auto mobiles, house hold appliances similar as a microwave oven roaster, or game shows. It most generally consists of a number of switches or detectors connected to a control unit that determines if and which button was pushed or a preset time has lapsed, and generally illuminates a light on the applicable button or control panel, which was identical to an electric bell without the essence gong( which makes the ringing noise).



**FIGURE 9:ALARM**

**vi )LIMIT SWITCHES:**

The switch body contains electrical connections to amp orde-energize a circuit. The operating head incorporates a switch arm or plunger. This is also called an selector. The selector rotates when the target applies force. This movement changes the state of connections within the switch body. Several types of selectors are available. All switches use the following common delineations of contact type.

- Single Pole, Single Throw(SPST)
- Single Pole, Double Throw(SPDT)
- Double Pole, Single Throw(DPST)
- Double Pole, Double Throw(DPDT)

A switch that makes or breaks the connection of a single captain in a single branch circuit. This switch generally has two outstations.




FIGURE 10:LIMIT SWITCHES.

vii)GLOBAL POSITIONING SYSTEM:

GPS fitted buses ; ambulances, lines and police vehicles are common sights on the roads of developed countries. Known by numerous names similar as Automatic Vehicle Locating System( AVLS), Vehicle Tracking and Information System( VTIS), Mobile Asset Management System( MAMS), these systems offer an effective tool for perfecting the functional effectiveness and application of vehicles.




FIGURE 11:GPS

V. RESULT

7:53
36%

IoT Based Worker Safety

Longitude	78.04853
Latitude	11.577267
Heartbeat	0
Spo2	0
Temperature	32
Status	HELMET_NOT_FIX

VIEW LOCATION

FIGURE 12:OUTPUT(SNAPSHOTS)

## VI.CONCLUSION

Through this project, we simplified the factual problem of the detecting fault in underground area. We discover the position where the fault will be being and also find accurate distance of swell point. The line to line, single line, Line to base fault in underground cable is located to amend fault efficiently using simple generalities of ohms law. The result automatically shown in the phase, it gives the detail about distance, time of occurrence of fault with the help of PIC18F4550 and PSP8266 Wi-fi module in webpage.

## REFERENCES

- [1] E. A. Rogers and E. Junga, "Intelligent efficiency technology and market assessment," 2017.
- [2] M. R. Yuce, "Implementation of wireless body area networks for healthcare systems," *Sensors and Actuators A: Physical*, vol. 162, no. 1, pp. 116–129, 2010.
- [3] G. Aloï, G. Caliciuri, G. Fortino, R. Gravina, P. Pace, W. Russo, and C. Savaglio, "Enabling iot interoperability through opportunistic smartphone-based mobile gateways," *Journal of Network and Computer Applications*, vol. 81, pp. 74–84, 2017.
- [4] J. P. Dieffenderfer, E. Beppler, T. Novak, E. Whitmire, R. Jayakumar, C. Randall, W. Qu, R. Rajagopalan, and A. Bozkurt, "Solar Powered wrist worn acquisition system for continuous photoplethysmogram monitoring," in *Engineering in Medicine and Biology Society (EMBC), 2014 36th Annual International Conference of the IEEE*. IEEE, 2014, pp. 3142–3145.
- [5] E. Jovanov, A. Milenkovic, C. Otto, and P. C. De Groen, "A wireless body area network of intelligent motion sensors for computer assisted physical rehabilitation," *Journal of NeuroEngineering and Rehabilitation*, vol. 2, no. 1, p. 6, 2005.
- [6] P. Pace, G. Aloï, R. Gravina, G. Caliciuri, G. Fortino, and A. Liotta, "A nedge-based architecture to support efficient applications for healthcare industry 4.0," *IEEE Transactions on Industrial Informatics*, vol. 15, no. 1, pp. 481–489, 2019.
- [7] F. Wu, J. Redout, and M. R. Yuce, "We-safe: A self-powered wearable iot sensor network for safety applications based on lora," *IEEE Access*, vol. 6, pp. 40 846–40 853, 2018.



INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details