

A Review on Influence of Biofuel on I.C. Engine Emission

Hiren V. Mandalia

Department of Mechanical Engineering, Government Polytechnic, Jamnagar, India

ABSTRACT: Vehicles are the main sources for environmental pollution especially those associated with diesel engines. It causes a number of health diseases and harm to the ecosystem. It is very urgent to find alternative fuel for vehicles. Biofuel is an alternative for vehicles which have potential to reduce engine emissions and maintain the air quality better. In recent years, worldwide biofuel production and use raised drastically. Some developed countries have put their target and mandate to use biofuel. The aim of this review is to discuss the impact of biofuel on diesel engines emission. From this review it is found that biofuel significantly reduces engine emissions and it has potential to reduce more than 80% of GHG emission. Finally, biofuel can be a viable alternative to be used as a transportation fuel.

KEYWORDS: Biofuel development; emission reduction; ethanol; transportation sector

I. INTRODUCTION

Quick development of various car enterprises on the planet has brought about expansion of fumes emanations to nature. Vehicular outflows, for example, particulate matter, hydro carbon, carbon dioxides, carbon monoxides and nitrogen oxides are colossally in charge of the air quality crumbling [1]. Two primary interior burning motor sorts, for example, petrol motor and diesel motor add to corrupt the air quality in the urban environment. There are around 22% of worldwide GHG (nursery gas) outflows comes just from the transportation part due the expanding interest of vehicles. Figure 1 demonstrates the CO₂ discharge by transportation part [2]. The quick discharge development was driven by outflows from street transport area which expanded by 52% since 1990 and represented seventy five percent of transport emanation in 2011 [2]. The International Energy Agency (IEA) conjectures that the emanations of carbon dioxide (CO₂) from transport division will increment by 92% somewhere around 1990 and 2020 and it is assessed that 8.6 billion metric huge amounts of carbon dioxide will be discharged to the climate from 2020 to 2035 [3]. It has been likewise reported that, an expansion in normal worldwide temperature by 2o C will bring about death of a huge number of individuals [4]. It is exceptionally pressing to discover elective powers for transportation segment as this area is discharging higher GHG emanation and add to the fast development of worldwide oil request. As of late, consideration has been attracted to create cleaner elective powers from renewable sources to lessen the hurtful outflow to the air and to diminish the reliance on the petro-diesel fuel [5]. The most achievable option for vehicles being considered internationally are biofuel, for example, biodiesel and ethanol because of their renewable property and decrease of fossil CO₂ release which most likely adds to the worldwide atmosphere changes. Ethanol is created from various yields, for example, potatoes, sugarcane, grains, corn and sorghum and so on [6] while, biodiesel can be delivered from vegetable oils, reused waste oil and creature fats [7]. Subsequently this audit expects to examine the capability of decrease of fumes outflow utilizing biofuel as a part of IC motors either immaculate or mix structure alongside the key element of biofuel advancement and strategies set by legislature of various nations around the globe to utilize biofuel.




Figure 1: CO₂ emission by sectors [2]

II. ENVIRONMENTAL AND HEALTH HAZARDS OF FOSSIL FUEL EMISSION

Transportation division is one of the fundamental wellsprings of nursery gasses, for example, CO₂. This GHG outflow is in charge of overall environmental change. Overall immeasurable number of wellbeing issues and

respiratory illnesses are brought on via air contamination. Bothering of lungs and pneumonia, oedema and bronchitis are brought about by NO_x emanation. Additionally, NO_x emanation results in expanded affectability to tidy and dust in asthmatics. Tissue improvement of youthful youngsters and fetal development in pregnant ladies are brought on by CO emanation. HC discharge advances bleakness in individuals who have circulatory or respiratory issues. Laziness, eye bothering, sniffing and hacking and side effects similar to tipsiness are brought on by PAHs. Lung ailments are brought on by a few hydrocarbons which have close fondness for diesel particulates [1, 8]. Ozone contrarily influences wellbeing furthermore makes hurt biological communities. Fermentation is created by discharges of nitrogen oxides and sulfur emanations [13]. On the premise of harm of human body, fine particulate matter, lead and ozone are the most perilous components. Today, in creating nations, on the premise of presentation, poisonous quality, and surrounding fixations, fine particulate matter has turned into the toxin of most prominent concern.

III. POTENTIAL OF BIOFUEL AS A RENEWABLE ENERGY SOURCES

3.1 Biofuel development

The key elements for biofuel advancement are: (a) Renewable (b) Net Energy Output (c) GHG diminishment, (d) Job Creation, (e) Rural improvement, (f) Conversion innovation, (g) Food security (h) Biodiversity (i) Water Resource, (j) Nutrient and pesticides (k) Feedstock and soil, (l) Change in area use, (m) Contamination and air quality.

3.2 Biodiesel

Biodiesel is an ester based oxygenated powers comprising long chain unsaturated fats got from vegetable oils (both consumable and non-eatable) or creature fats and it is non unstable, biodegradable, non combustible, renewable, non - poisonous. It can be utilized as a part of diesel motor as option of diesel fuel without significant adjustment of the motor with same or better execution in contrast with conventional diesel fuel [9]. At present, the wellsprings of biodiesel incorporate soybean oil, sunflower oil, corn oil, utilized singed oil, olive oil, rapeseed oil, castor oil, lesquerella oil, milkweed (*Asclepias*) seed oil, *Jatropha curcas*, *Pongamia glabra* (karanja), *Madhuca indica* (Mahua) and *Salvadora oleoides* (Pilu), *Calophyllum inophyllum*, palm oil, linseed oil, green growth and so forth. Biodiesel can be created from vegetables oils in four diverse ways to be specific pyrolysis/splitting, weakening with hydrocarbons mixing, emulsification, and transesterification [10].

3.3 Ethanol

Ethanol is a minimal effort oxygenates which contains 34% higher oxygen content by weight [11]. Utilizing maturation process ethanol can be made organically from an assortment of biomass sources, for example, sugarcane, corn, sugar beet, molasses, cassava root, and so on [6]. Ethanol can be created from an assortment of feedstocks, for example, sugarcane, bagasse, miscanthus, sugar beet, sorghum, downpour, switch grass, scarcely, hemp, kenaf, potatoes, cassava, sunflower, natural product, molasses, corn, stover, grain, wheat, straw, cotton, different biomass, and also numerous sorts of cellulose waste and reaping, whichever has the best well-to-wheel appraisal. The essential strides for expansive scale generation of ethanol are: microbial (yeast) aging of sugars, refining, drying out and denaturing. Before maturation, a few yields require saccharification or hydrolysis of starches, for example, cellulose and starch into sugars. Saccharification of cellulose is called cellulolysis. Catalysts are utilized to change over starch into sugar. Figure 2 demonstrates the creation procedure of biofuel [12].




Figure 2: Production process of biofuel [12]

3.4 Biofuel Production and Use Target in Some Countries around the World

As of late, generation of biofuel around the globe raised radically. For instance, in 2010, expanding by 17% from 2009, overall biofuel generation achieved 105 billion liters (28 billion gallons US), and 2.7% of world's powers for street transport are to a great extent contributed from ethanol and biodiesel. This is driven basically by the administration's quest for vitality security, financial advancement (especially, change of exchange parities and extension of the farming segment), and neediness easing. Biofuel methodologies of the most Asian nations are engaged around the nation's fundamental agrarian item and new business open doors. Every one of these nations pay overwhelming endowments on petroleum transport fuel which are foreign made. Opposite, with a specific end goal to impact the commercialization of self-delivered biofuel, the nations need to pay more appropriations as cost of biofuels still somewhat higher [12]. Table 1 demonstrates biofuel focus of a few nations on the planet. Table 1: Biofuel focuses in a few nations around the globe [12]

Table 1: Biofuel targets in some countries around the world [12]

Countries	Years	Target	Feedstocks
U. S. A	2012	28 Billion ethanol	Corn, soybean oil, sorghum and
	2013	1 Billion liters of cellulosic ethanol	cellulosic sources in the future
	2020	25% Ethanol	
	2025	2% Biodiesel	
Brazil	2012	25% Ethanol and B2	Soybean, sugarcane, palm oil
	2013	B5 (2.4 billion biodiesel)	
	2020	B20	
EU	2005	2%	Rapeseed, sunflower, wheat sugar beet, barley
	2010	5.75%	
	2020	10%	
	2025	30%	
China	2010	1.5–2 Million biodiesel	Corn, cassava, sweet potato, rice, jatropha
	2020	10% Ethanol (=8.5 million tons) 10.6–12 million biodiesel	
Canada	2010	5% Ethanol	Corn, wheat
	2012	2% Biodiesel	
India	2012	5% Biofuel	Molasses, sugarcane in the future, jatropha
	2017	10% Biofuel	
Australia	2010	350 Million liters of biofuel	Wheat, sugarcane, molasses, palm oil, cotton
	2012	10% Ethanol and 10% biodiesel	oil
	2017	20% Ethanol and 20% biodiesel	
Japan	2010	360 Million liters biofuel	Imported ethanol, rice bran and
	2020	6 billion liters biofuel	
	2030	10% Biofuel	

IV. IMPACT OF BIOFUEL ON IC ENGINES EMISSION CHARACTERISTICS

The expanding industrialization and modernization of the world has to a stage up for the interest of petroleum determined fuel which is feasible to human wellbeing and in addition environment because of emanating green house gasses. Figure 3 [12, 13] demonstrate the diminishment of motor outflow utilizing biofuel. Ekrem [14] found that the utilization of biodiesel in diesel motors produces lower CO and smoke darkness and NO_x outflows contrasted with diesel fuel at full load condition. He proposed that lone low fixation mixes as far as execution effectiveness and naturally agreeable discharges could be perceived as the potential possibility to be ensured for full scale use in unmodified diesel motors. Saleh [15] found that Jojoba methyl ester (JME) increment 14% and 16% NO_x discharge at 1600 rpm and 1200 rpm separately contrasted with fossil diesel fuel. At lower motor pace JME produce higher HC and CO emanations however at higher motor velocity, there is no huge distinction amongst HC and diesel fuel while CO is lower than diesel. The outcomes additionally demonstrated that when the fumes gas distribution (EGR) rate is expanded, the NO_x outflows diminished. Be that as it may, CO and HC outflows expanded. They prescribed that the ideal EGR level is 5-15% for all motor speeds and stacks and that might be ideal in an exchange - off between HC, CO and NO_x discharges with little economy punishment. Study directed by Zhihao et al. [16] delineates that Pistacia Chinensis Bunge biodiesel mixed fuel radiates lower HC, CO and fumes smoke discharges. B10 and B20 diminishes NO_x discharge, be that as it may, B30 somewhat builds NO_x emanation due to having higher oxygen substance which results in higher barrel temperature. The discharge investigation by Selvam and Vadivel [17] demonstrates a radical decrease (34.7-63%) in carbon monoxide (CO), unburned hydrocarbon (UHC) and smoke thickness for all hamburger fat biodiesel mixed fuel. In any case, on account of oxides of nitrogen, there is a slight increment for all the mixed energizes and with flawless biodiesel (6.35%) contrasted with diesel fuel. Nurun Nabi et al. [18] reported that Pongamia biodiesel diminishes CO, smoke and motor commotion by half, 43% and 2.5dB individually however expanded NO_x outflow by 15% at high load conditions. The reason can be ascribed to the nearness of oxygen in

karanja biodiesel atomic structure. Raheman and Phadataré [19] discovered Karanja biodiesel mix (B20-B100) in a diesel motor decrease CO discharge (73-94%), smoke thickness (20-80%) and 26% in normal NO_x emanation than diesel fuel because of the complete burning of the biodiesel mix fuel. There was no critical variety in fumes temperatures.




Figure 3: GHG emission reduction of biofuel compared to fossil fuel [13]

Shi et al. [20] found that the utilization of biodiesel - diesel-ethanol mixes decreases particulate matter emanations by 30% and a general lessening in complete hydrocarbon yet marginally (5.6–11.4%) expansion the NO_x discharges in normal. If there should be an occurrence of unregulated outflow, for example, acetaldehyde and CH₃)₂CO expanded a bit when biodiesel-diesel-ethanol mixed fuel utilized. Banapurmath and Tewari [21] worked a diesel motor with 0%, 5%, 10%, 15% ethanol mixes and discovered decrease in HC and expansion in NO_x outflow with ethanol-biodiesel mixes contrasted with diesel and biodiesel fills. Zhu et al. [22] tried Euro V diesel fuel and ethanol-biodiesel mixes in a four-chamber direct infusion diesel motor. It was found that the expansion of 5% ethanol in biodiesel enhances motor execution marginally. It likewise could diminish NO_x, PM, CO and HC discharges contrasted with diesel fuel. In special case, higher centralization of ethanol in mix could build CO and HC emanations, while essentially diminishes NO_x and PM outflows. Yilmaz et al. [23] found at full load condition the mixed fuel expanded CO and HC emanations yet lessened NO outflows. They presumed that including ethanol in the mixes would be the ideal decision to lessen NO emanations for the focuses introduced in this study. Tooth et al. [24] reported that ethanol– diesel– biodiesel mixed fuel produce bring down NO_x discharges and higher HC and CO emanations because of higher inert warmth of vaporization which causes lower burning temperature. In the event of smoke discharge, mixed fuel (ethanol–diesel–biodiesel) brought it contrasted down with that of diesel and biodiesel–diesel fuel. The tops of smoke discharges were diminished in a vast degree with the expansion of rate of ethanol in mixed fills. At long last, they inferred that ethanol–diesel–biodiesel is reasonable contrasting option to decrease NO_x and smoke emanations in premixed lower temperature condition. Yilmaz et al. [24] researched the discharge of biodiesel - diesel-ethanol (BDE3, BDE5, BDE15 and BDE25) mixes in a diesel motor at various motor burden condition. Test results demonstrate that outflows are unequivocally relied on upon motor working conditions and biofuel fixation in the mix. Ethanol mixed energizes expanded CO outflows contrasted with that of diesel fuel for every single working condition however the mixed powers diminished NO emanations for all fixations. In general, lower rates of ethanol in the mix, diminished HC emanations and the other way around. Be that as it may, ethanol mixed fuel decreased HC emanations at more than half load conditions.

V. CONCLUSION

From this review it is found that vehicular emission is largely responsible for GHG emission and health hazards. This problem could be addressed by using biofuel in diesel engines in a blended form as biofuel have potential to reduce engine emission to the environment. This review indicates that biofuel have potential to reduce GHG emission more than 80%. Some developed countries have put their target and mandate to use biofuel. For example, the United States wants to use 25% ethanol within 2020, Brazil targets to implement B20 within 2020 and India targets to use B10 country wide within 2017. Some developing countries are exporting biofuel but not using as they are not conscious enough about the environment pollution. Government of those developing countries can take initiative to introduce biofuel as a fuel in their transportation sector to reduce global IC engine emissions.

REFERENCES

- Liaquat AM, Kalam MA, Masjuki HH, Jayed MH. Potential emissions reduction in road transport sector using biofuel in developing countries. Atmospheric Environment 2010; 44: 3869-77.
- (IEA) IEA. CO₂ EMISSIONS FROM FUEL COMBUSTION. <http://www.iea.org/publications/freepublications/publication/co2emissionsfromfuelcombustionhighlights2013pdf> 2013.
- Gorham R. An assessment of causes, strategies and tactics, and proposed actions for the international community. Division for Sustainable

- Development, Department of Economic and Social Affairs 2002; <http://www.un.org/esa/gite/csd/gorham.pdf>.
4. Mofijur M, Atabani AE, Masjuki HH et al. A study on the effects of promising edible and non-edible biodiesel feedstocks on engine performance and emissions production: A comparative evaluation. *Renewable and Sustainable Energy Reviews* 2013; **23**: 391-404.
 5. Rahman MM, Hassan MH, Kalam MA et al. Performance and emission analysis of *Jatropha curcas* and *Moringa oleifera* methyl ester fuel blends in a multi-cylinder diesel engine. *Journal of Cleaner Production* 2014; **65**: 304-10.
 6. Masum BM, Masjuki HH, Kalam MA et al. Effect of ethanol-gasoline blend on NO_x emission in SI engine. *Renewable and Sustainable Energy Reviews* 2013; **24**: 209-22.
 7. Arbab MI, Masjuki HH, Varman M et al. Fuel properties, engine performance and emission characteristic of common biodiesels as a renewable and sustainable source of fuel. *Renewable and Sustainable Energy Reviews* 2013; **22**: 133-47.
 8. Okona-Mensah KB, Battershill J, Boobis A, Fielder R. An approach to investigating the importance of high potency polycyclic aromatic hydrocarbons (PAHs) in the induction of lung cancer by air pollution. *Food and Chemical Toxicology* 2005; **43**: 1103-16.
 9. Atadashi IM, Aroua MK, Abdul Aziz AR, Sulaiman NMN. Production of biodiesel using high free fatty acid feedstocks. *Renewable and Sustainable Energy Reviews* 2012; **16**: 3275-85.
 10. Atabani AE, Mahlia TMI, Masjuki HH et al. A comparative evaluation of physical and chemical properties of biodiesel synthesized from edible and non-edible oils and study on the effect of biodiesel blending. *Energy* 2013; **58**: 296-304.
 11. Cardona CA, Sánchez ÓJ. Fuel ethanol production: Process design trends and integration opportunities. *Bioresource Technology* 2007; **98**: 2415-57.
 12. Masjuki HH, Kalam MA, Mofijur M, Shahabuddin M. Biofuel: Policy, Standardization and Recommendation for Sustainable Future Energy Supply. *Energy Procedia* 2013; **42**: 577-86.
 13. Jayed MH, Masjuki HH, Kalam MA et al. Prospects of dedicated biodiesel engine vehicles in Malaysia and Indonesia. *Renewable and Sustainable Energy Reviews* 2011; **15**: 220-35.
 14. Ekrem B. Effects of biodiesel on a DI diesel engine performance, emission and combustion characteristics. *Fuel* 2010; **89**: 3099-105.
 15. Saleh HH. Experimental study on diesel engine nitrogen oxide reduction running with jojoba methyl ester by exhaust gas recirculation. *Fuel* 2009; **88**: 1357-64.
 16. Zhihao M, Xiaoyu, Z., Junfa, D., Xin, W., Bin, X., Jian, W. Study on Emissions of a DI Diesel Engine Fuelled with *Pistacia Chinensis* Bunge Seed Biodiesel-Diesel Blends. *Procedia Environmental Sciences* 2011; **11**: 1078-83.
 17. Selvam DJP, Vadivel K. Performance and Emission Analysis of DI Diesel Engine Fuelled with Methyl Esters of Beef Tallow and Diesel Blends. *Procedia Engineering* 2012; **38**: 342-58.
 18. Nabi MN, Hoque SMN, Akhter MS. Karanja (*Pongamia Pinnata*) biodiesel production in Bangladesh, characterization of karanja biodiesel and its effect on diesel emissions. *Fuel Processing Technology* 2009; **90**: 1080-6.
 19. Raheman H, Phadatare AG. Diesel engine emissions and performance from blends of karanja methyl ester and diesel. *Biomass and Bioenergy* 2004; **27**: 393-7.
 20. Shi X, Pang X, Mu Y et al. Emission reduction potential of using ethanol-biodiesel-diesel fuel blend on a heavy-duty diesel engine. *Atmospheric Environment* 2006; **40**: 2567-74.
 21. Banapurmath NR, Tewari PG. Comparative performance studies of a 4-stroke CI engine operated on dual fuel mode with producer gas and Honge oil and its methyl ester (HOME) with and without carburetor. *Renewable Energy* 2009; **34**: 1009-15.
 22. Zhu L, Cheung CS, Zhang WG, Huang Z. Combustion, performance and emission characteristics of a DI diesel engine fueled with ethanol-biodiesel blends. *Fuel* 2011; **90**: 1743-50.
 23. Yilmaz N. Comparative analysis of biodiesel-ethanol-diesel and biodiesel-methanol-diesel blends in a diesel engine. *Energy* 2012; **40**: 210-3.
 24. Fang Q, Fang J, Zhuang J, Huang Z. Effects of ethanol-diesel-biodiesel blends on combustion and emissions in premixed low temperature combustion. *Applied Thermal Engineering* 2013; **54**: 541-8. Yilmaz N, Vigil FM, Burl Donaldson A, Darabseh T. Investigation of CI engine emissions in biodiesel-ethanol-diesel blends as a function of ethanol concentration. *Fuel* 2014; **115**: 790-3.