

An ISO 3297: 2007 Certified Organization

Volume 4, Special Issue 10, August 2015

3rd National Conference in Magna on Recent Trends in Mechanical Engineering 2015 [NCRTME 2015]

On 21st AUGUST, 2015

Organized by

Department of Mechanical Engineering, Magna College of Engineering, Chennai-600055, India.

Einstich Unsafe Pressure Alert System

M M Maheswar¹, K.R Ethirajulu², S.Naveen Sharen³, V.Arun⁴

UG Student, Department of Mechanical Engineering, JNN Institute of Engineering, Kannigaipair, Chennai, India^{1,2,3,4}

ABSTRACT:A EINSTICH UNSAFE PRESSURE ALERT SYSTEM (EUPAS) is an electronic system designed to monitor the air pressure inside the pneumatic tires on various types of vehicles. EUPAS report real-time tire-pressure information to the driver of the vehicle, via alarming the sound, or a simple low-pressure warning light. This alert system will gives the pre-sound to the driver before the pressure in the tires will get reduced.

TARGET

 \Box \Box Avoiding traffic accidents due to under-inflated tires by early recognition of the malfunction of tires

□ □ Reducing rolling resistance thus increasing overall fuel efficiency

REQUIREMENTS

A direct EUPAS consists of following requirements □ □ Tire;

 $\Box \Box \operatorname{Rim};$

 $\Box \Box$ Arc welding machine;

 \Box \Box Circular MS plate;

 \Box \Box Pressure limit valve cap;

 \square \square ON/OFF switch;

- \Box \Box radio frequency module; and
- $\Box \Box$ Alert speaker.

I. CONSTRUCTION

Initially the air pressure valve cap is split up and it is connected to the limit switch wire. Is designed to switch on the limit switch if the pressure inside the tube is reduced and it is connected to the transmitter which is attached inside the hub of the rim. The limit switch wire is connected with the transmitter and another limit is fitted nearby to the transmitter to stop the alarm. The receiver is connected with the burglar alarm. The receiver requires power source. The alarm will works at 220v. And also the transmitter contains a 12v battery in it. Then the receiver is connected with the burgler alarm to give the signal. The receiver also requires power source will get from the battery or from the power plug. They transmit through radio frequency which we saw before. We connect the pressure limit switch wire to the valve tube of the tire. We made some hole in the tube and attached another valve tube to release the air inside the tube to demonstrate. This is the total construction of EINSTICH UNSAFE PRESSURE ALERT SYSTEM



An ISO 3297: 2007 Certified Organization

Volume 4, Special Issue 10, August 2015

3rd National Conference in Magna on Recent Trends in Mechanical Engineering 2015 [NCRTME 2015] On 21st AUGUST, 2015

Organized by

Department of Mechanical Engineering, Magna College of Engineering, Chennai-600055, India.



This is pressure limit switch

II. WORKING

 \Box Initially the pressure limit switch wire is fitted with the valve tube. If the pressure is enough inside the switch will be off.

 \Box \Box If the pressure will reduce the switch will gets on the transmitter will switch on and it will transmits the signal to the receiver.

□ □ The receiver receives the signal and gives the alarm signal to the driver or particular person.

□ □ This alarm will alert the driver to make particular precausions to avoid in-flat tire problems and to avoid accidents.





An ISO 3297: 2007 Certified Organization 3rd National Conference in Magna on Recent Trends in Mechanical Engineering 2015 [NCRTME 2015] On 21st AUGUST, 2015

Organized by

Department of Mechanical Engineering, Magna College of Engineering, Chennai-600055, India. III. PROJECT PHOTOGRAPHY



IV. ADVANTAGES

 \Box \Box Here is actually only one real advantage to EUPAS hardware, but it's a big one – it can save your life and/or your tires.

□ □ EUPAS is designed to warn you by means of a dashboard light or by sending the alarm signal when any one of your tires has fallen below 25% of the carmaker's rated pressure.

 \Box \Box This will let you know you have a problem before the sidewalls of your tire begin to fold over and rub together, which is usually the first tactile warning of a problem.

 \Box \Box By this time your tires are already damaged beyond repair and unsafe. Running on them for much longer can cause the rest of the air in the tire to exit in a much more uncontrolled manner.

□ □ Nothing good ever comes of that. By warning you of a problem well before the liner of the tire is worn off, TPMS can not only save your life, it can save you a considerable amount of money.

V.CONCLUSION

This is the unsafe pressure alert system to indicate the low pressure inside the vehicle tire to avoid accidents and to avoid any damage of vehicle due to low pressure in the tire and also due to in-flat tires.



An ISO 3297: 2007 Certified Organization

Volume 4, Special Issue 10, August 2015

3rd National Conference in Magna on Recent Trends in Mechanical Engineering 2015 [NCRTME 2015]

On 21st AUGUST, 2015

Organized by

Department of Mechanical Engineering, Magna College of Engineering, Chennai-600055, India.

REFERENCES

- [1] **Systems-based approach to investigate unsafe pedestrian behaviour at level crossings** Accident Analysis & Prevention, Volume 81, August 2015, Pages 167-186 Teodora Stefanova, Jean-Marie Burkhardt
- [2] **Preceptorship:** Using an Ethical Lens to Reflect on the Unsafe Student Journal of Professional Nursing, Volume 28, Issue 1, January–February 2012, Pages 27-3 Vicki Earle-Foley, Florence Myrick, Florence Luhanga, Olive Yonge
- [3] Food Safety Assurance **Systems**: Investigation of Incidents in Industry Encyclopedia of Food Safety, Volume 4, 2014, Pages 301-308 P. McClure
- [4] Pressure, O2, and CO2, in aquatic Closed Ecological Systems Advances in Space Research, Volume 51, Issue 5, 1 March 2013, Pages 812-824 Frieda B. Taub, Anna K. McLaskey