

A Survey on an Intelligent Traffic Control System Using a Vehicular Ad Hoc Network

Sadaf Shaikh¹, Prof L.M.R.J.Lobo²M.E Student, Dept. of Computer Science and Engineering, Walchand Institute of Technology, Solapur, Maharashtra, India.¹Associate Professor, Dept. of Computer Science and Engineering, Walchand Institute of Technology, Solapur, Maharashtra, India.²

ABSTRACT: India is a highly populated country and is a fast growing economy. It is experiencing terrible road congestion problem in its cities. The growth of infrastructure is slow, as compared to the growth in number of vehicles. This is due to space and cost constraints. The traffic flow is non-lane based and unorganized. It requires traffic control solutions, which are different from those in urbanized countries. Intelligent management of traffic flows can shrink the negative impact of congestion. Vehicular Ad Hoc Network (VANETs) is a subclass of Mobile Ad Hoc Network. It provides wireless communication among vehicles and vehicles to road side equipment. This communication between vehicles is used for safety, ease and for entertainment purpose as well. The present paper proposes a methodology based on VANET and shift clustering algorithm to overcome these difficulties. It is predicted that using such environment would solve the problem of road traffic congestion to a great extent.

KEYWORDS: Ad hoc network, communication, Traffic Control, Vehicles, Vehicle Safety.

I. INTRODUCTION

Now days, the absolute volume of road traffic affects the safety and efficiency of traffic situations. Around million people are killed every year in road accidents. Road traffic safety has been a stimulating problem in traffic management. One probable way is to deliver the traffic information to the vehicles so that they can use them to analyse the traffic environment. It can be accomplished by exchanging the information of traffic situation among vehicles. All the vehicles are traveling into a versatile environment, hence a mobile network is needed which can be self-organized and proficient in operating without infrastructure support. With the evolvement of microelectronics, it becomes possible to add nodes and network devices into single units and wireless interconnection, i.e. an ad-hoc network. Additionally this network is evolved as mobile ad hoc network. Mobile Ad-hoc network is a wireless networks consisting of a collection of portable nodes with no static infrastructure, where some intermediate nodes should participate in forwarding data packets. MANET is composed of groups of self-organized wireless stations without a need to utilize any preinstalled infrastructure Vehicular ad-hoc networks (VANETs) are a sensational and growing field of study. There are many possibilities of using ad-hoc communication between vehicles for information distribution, safety, or even entertainment. These likelihoods, driven in the United States by the Department of Transportation, Intellidrive initiatives, have launched many different lines of research.

Due to the budget of vehicles and equipment, nearly all of this research has been done using simulation. However, the current collection of simulators widely available either wholly splits the vehicle and network stages of the simulation or overgeneralizes either the vehicle or networking simulation. The German Aerospace Centre (DLR) ongoing the development of the open source traffic simulation suite SUMO back in 2001. Since then SUMO has progressed into a full featured suite of traffic modeling utilities including a road network capable to read different source formats, demand generation and routing utilities from various input sources (origin destination matrices, traffic counts, etc.), a high performance simulation usable for single junctions as well as whole cities including a "remote control" interface (TraCI) to adapt the simulation online. SUMO is not only a traffic simulation, but rather a suite of

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 7, July 2016

applications which help to prepare and to perform the simulation of traffic. As the traffic simulation “sumo” needs the representation of road networks and traffic demand to simulate in an own format, both have to be imported or generated using different sources[10].

II. LITERATURE SURVEY

After the survey it was identified that traffic congestion is a main problem in cities of developing countries like India. Evolution in urban population and the middle class sector contribute ominously to the rising number of vehicles in the cities [1]. Congestion on roads eventually results in slow moving traffic, which escalate the time of travel, thus stands out as one of the key issues in metropolitan cities. In [3] an intelligent traffic control system to pass emergency vehicles smoothly is developed. Each individual vehicle is equipped with distinct radio frequency identification (RFID) tag (placed at a strategic location), which makes it difficult to remove or destroy. The use of RFID reader is predominant, NSK EDK-125-TTL, and PIC16F877A system on chip to read the RFID tags are attached to the vehicle. They use ZigBee modules on CC2500 and PIC16F-877A system on chip for wireless communications between the ambulance and traffic controller.

In [2] a vehicle driving system in a model analytical control structure that efficiently improves traffic flow is presented. The vehicle driving system regulates safe inter vehicle distance under the bounded driving turning condition by predicting the preceding traffic. It also focuses on improving the effect of braking on the vehicles that follow. Traffic is a perilous issue of transportation system in most of the cities of various countries. This is especially factual for countries like India and China, where the population is growing at higher rate. For example, Bangalore city, has observed an incredible growth in vehicle population in recent years. As a result, most of the roads and intersections are operating over the capacity (i.e., v/c is more than 1) and average journey speeds on some of the key roads in the central areas are lower than 10 Km/h at the peak hour [3]. In [4] the use of RFID traffic control to avoid problems that usually arise with standard traffic control systems is presented, specifically those related to image processing and beam interruption techniques are discussed. This RFID technique deals with multivehicle, multilane, multi road junction areas. It provides an efficient time management scheme, in which, a dynamic time schedule is worked out in real time for the passage of each traffic column. In [5] paper, we come across vehicle-to-vehicle (V2V) communication technology to implement computationally efficient decentralized algorithms for two-vehicle cooperative collision avoidance at intersections. Our algorithms employ a formal control theoretic method to guarantee a collision-free (safe) system, whereas overrides are only applied when necessary to prevent a crash. This work is to provide an experimental validation of our method on two instrumented vehicles engaged in an intersection collision avoidance scenario in a test track. Vehicular Ad hoc Networks (VANETs) are the promising approach to provide safety and other applications to the drivers as well as passengers. It becomes a key component of the intelligent transport system. A lot of works have been done towards it but security in VANET got less attention. In [6], we are introduced to VANET and its technical and security challenges. We also are introduced to some major attacks and solutions that can be implemented against these attacks. They have compared the solution using different parameters.

[7] Presents a predictive road traffic management system (PRTMS) based on the Vehicular Ad-hoc Network (VANET) architecture. The proposed PRTMS uses a novel communications scheme to estimate the future traffic intensities at different intersections based on a modified linear prediction algorithm. Based on the prediction, a central controller reduces the congestion level by rerouting the vehicles and adaptively changing the signaling cycles. An IEEE 802.11p based vehicle to infrastructure communications system is used to collect trip information and transmit control signals to enforce multi-junction traffic flow control. Simulations are conducted using an integrated OPNET model comprising of road infrastructure, vehicular mobility management and communications networking to jointly examine the performances of the proposed PRTMS and the VANET. In [8] they collect envisioned application from various sources and classify the unique network characteristics of vehicular networks. Based on this analysis they propose distinct communication patterns that form the basis of almost all VANET Applications. Communication patterns like Beaconing, Geobroadcast, Unicast Routing, Advanced Information Dissemination, and Information Aggregation out of these communication patterns using geobroadcasting and information aggregation are dealt with.

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 7, July 2016

In [9] , they developed a client to make SUMO and NS3 work parallel by TraCI (Traffic Control Interface) in NS3. It helps NS3 get SUMO's information and sends instructions to change the states of vehicles and traffic lights. They present a realistic road traffic model with kinds of vehicles and intelligent traffic lights. The model is built in SUMO (Simulation of Urban Mobility). We use Open Street Map to generate a realistic map near the bund in Shanghai. The traffic flow is built according to a survey which makes us get meaningful and reliable statistics. A mechanism of changing the traffic lights dynamically is introduced to minimize traffic jams and give high priority to emergency vehicle. In [11] we studied about SUMO simulator i.e how to install it, basic needs to run simulators, also studied about how to build network. After this we decided to use SUMO simulators as platform.

III. PROPOSED METHODOLOGY




Fig 1 : System Architecture of Proposed Concept

The block diagram of the proposed methodology to be used is explained in Fig1 above.

Vehicle Unit

Vehicle Unit is a device usually mounted in a vehicle used for exchanging information with Road side units and other Vehicle units. It Consist of RFID Tag, RFID Reader Media Server Media Client, Decision Unit, Vehicle Control Unit, Network Client. RFID Reader is used to read RFID signals these signals send to the decision unit to take the decision according to that Vehicle will perform the action. This information will be shared with Road side unit through Network client. It also includes Media Server and Media Client for entertainment purpose e.g to watch youtube videos, Google Map e.t.c. The main function of Vehicle Units is wireless radio access, ad-hoc and geographical routing, network congestion control, reliable message transfer, data security and IP mobility.

Road Side Unit

The RSU is a wave device usually fixed along the road or in dedicated locations Such as at junctions, at Traffic signal, or near parking spaces dedicated for short range communication based on IEEE 802.11p radio technology , and can also be equipped with Infrastructure Network. Main function of RSU is as under

- Extend the Communication Range.
- Providing Safety application such as accident warning.
- Provide internet connectivity to Vehicle Units.

Server Unit

Server contains database (memory database) and Server Module. It will store RFID Tags of Each vehicle. This also helps to track the stolen vehicle. Server module fulfills the request coming through Client Module from road side unit.

We proposed to develop the following intelligent vehicle safety applications

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 7, July 2016

1) V2V Communication

Provide Information about vehicle which is in communication range. Transmitted messages common to all vehicles include each vehicle GPS position, vehicle speed, path history, Acceleration and vehicle control information like brake status, steering, vehicle angle.

2) V2V Interoperability

When crash is predicted the vehicle will provide warning to driver. Driver remains in control all the time and vehicle will not automatically break or steer.

3) Emergency Speed Control

Automatic speed control when hard breaking vehicle detected.

4) Unsighted Spot Vehicle

When driver attempt to change lane with the vehicle which is still in his unsighted spot at that time the unsighted spot warning safety will lets the driver know that there is vehicle that may not be visible positioned. And make him aware about the presence of the vehicle

5) Lane Change Warning

When driver intends to change lanes into zone that will soon be occupied by a faster moving vehicle traveling in the same direction, using this v2v communication our vehicle will predict that and gives the warning message to driver i.e NOT Safe to change the Lane.

6) Forward Collision Warning

It will warn driver if he is approaching too quickly, and is in the potential rear end crash with stopped or slower moving vehicle ahead.

7) Do Not Overtake

You are moving behind slow speed vehicle and you want to overtake that vehicle, same time faster passing vehicle come in zone immediately warning message gives to driver i.e It is UNSAFE to pass.

8) Intersection Movement Assist

Warning is provided to driver if it is unsafe to enter into the intersection. Here Left Turn Assist Application also provided.

IV. CONCLUSION

This proposed methodology is aimed to acquire intelligent control over traffic and as vehicle having automotive control over it by emergency speed control, warn before lane change, forward collision warning etc. it will diminish the roadside accident; provide the clearance so that emergency vehicle can go smoothly. Emergency vehicles like ambulance, fire trucks, need to reach their destinations at the earliest. If they spend a lot of time in traffic jams, precious lives of many people may be in danger.

REFERENCES

- [1] M.Absar Alam and Fiasal Ahmed ; + "Urban Transport System and Congestion:Case Study Of Indian Cities",Transportation and communications bulletin for Asia and the Pacific.,No82,2013.
- [2] Md. Abdus Samad Kamal, Member, IEEE, Jun-ichi Imura, Member, IEEE, Tomohisa Hayakawa, Member, IEEE, Akira Ohata, and Kazuyuki Aihara. "Smart Driving of a Vehicle Using Model Predictive Control for Improving Traffic Flow",IEEE Transaction On Intelligent Transportation System, vol.15,No.2 April 2014.
- [3] Rajeshwari Sundar, Santhosh Hebbar, and Varaprasad Golla; IEEE, "Implementing Intelligent Traffic Control System for Congestion Control, Ambulance Clearance, and Stolen Vehicle Detection", IEEE Sensors Journal, Vol. 15, No. 2, February 2015.
- [4] S. Sharma, A. Pithora, G. Gupta, M. Goel, and M. Sinha,"Traffic light priority control for emergency vehicle using RFID", Int. J. Innov. Eng. Technol., vol. 2, no. 2, pp. 363–366, 2013.
- [5] Michael R. Hafner, Drew Cunningham, Lorenzo Caminiti, and Domitilla Del Vecchio, Member, IEEE"Cooperative Collision Avoidance at Intersection: Algorithms and Experiments", IEEE Transaction On Intelligent Transportation System, vol.14,No.3 September 2013.
- [6] Ram Shringar Raw, Manish Kumar, Nanhay Singh , "Security Challenges, Issues And Their Solutions For Vanet", International journal of network Security and its Applications Vol.5,No.5,September2013.
- [7] Nafi, N.S. ; RMIT Univ., Melbourne, QLD, Australia ; Khan, R.H. ; Khan,J.Y. ; Gregory, M.;IEEE "A Predictive Road Traffic Management System Based On Vehicular Ad-Hoc Network", IEEE November 2014.
- [9] Tick, J. ; Budapest Tech., Budapest ;. International Symposium on"Multi Server Architecture in Intelligent Traffic Control System", IEEE Logistics and Industrial Informatics, 2007.LINDI 2007



ISSN(Online) : 2319-8753
ISSN (Print) : 2347-6710

International Journal of Innovative Research in Science, Engineering and Technology

(An ISO 3297: 2007 Certified Organization)

Vol. 5, Issue 7, July 2016

- [10] Michael Behrisch, Laura Bieker, Jakob Erdmann, Daniel Krajzewicz, "Simulation of Urban Mobility" In Third International Conference on Advances in System Simulation, Institute of Transportation Systems German Aerospace Center Rutherfordstr. 2, 12489 Berlin, Germany
- [11] Institute of Transportation Systems [online] Available : " <http://www.dlr.de/ts/en/desktopdefault.aspx/tabid-1213/>"
- [12] SUMO Simulation of Urban Mobility [online] Available : " <http://www.sumo.dlr.de/daily/userdoc/Installing.html>.