

# Smart Response System for Wireless Load Control and Monitoring Using GSM

Mannur Vishwanath<sup>1</sup>, A. M. Gunasekhar<sup>2</sup>

M.Tech Student, Dept. of Electronics & Communication Engineering, Sree Rama Engineering College, Tirupati, India<sup>1</sup>

Assistant Professor & Head, Dept. of Electronics & Communication Engineering, Sree Rama Engineering College,  
Tirupati, India<sup>2</sup>

**ABSTRACT:**With the present headway in remote systems furthermore, different innovations actualized for mechanization, more imaginative and enhanced thoughts are created to manufacture mechanization frameworks encouraging remote controlling and observing of gadgets. In this paper, a GSM based remote home robotization framework is proposed and conveyed which executes its capacity of controlling also, observing machines remotely. It is consistent, costeffective, low power utilization; very productive GSM (Global System for Mobile Communication) based remote home framework. This System (IVRS) is extemporized to adorn the framework's security and simplicity of operation. With the help of this framework the client can get to his home machines from anyplace and at whatever time according to the prerequisite supporting comfort. The framework allows the client direct gadgets through his versatile by sending voice charges utilizing IVRS framework. It likewise empowers the client to screen the status of burdens with SMS upgrade. A definite framework examination is completed and displayed in this paper.

## I. INTRODUCTION

Remote innovation has served in the field of mechanization since quite a while. With the coming of innovation and presentation of system empowered mechanization framework in each part, gadgets can be controlled and oversaw from remote area. This can be accomplished by actualizing systems with the backing of different remote advances, for example, ZigBee, Bluetooth, DTMF based portable and UWB and so on. There has been a quick extension and a potential increase of such computerized frameworks since it encourages the client to sort out the machines and gadgets according to his benefit.

Such robotized frameworks manages giving a system in a domain which joins PCs fringe gear, savvy chip bearing machines and sub-frameworks. With such conveyed framework, it guarantees controlling of power worked gadgets carefully continuously notwithstanding being physically away from the site. In any case, again these executions require either radio connection correspondence or wired correspondence to coordinate the gadgets to work in like manner. Be it wired or radio connection correspondence, each has its own impediments, for example, complex wire arrangement, systems of support, extent limitations, low information rate, high cost, programming courses of action and so forth.

The diverse frameworks have been proposed and actualized in territory of computerization. The DTMF tone produced computerization framework that proposes a strategy for controlling electronic frameworks remotely. An exertion has been made to handle issues identified with computerization framework in view of double tone multi-recurrence remote control technique for mechanical what's more, residential applications. The paper proposing another such framework is executed utilizing ZigBee remote individual zone network which encourages meddling of the individual framework establishment. Additionally home robotized frameworks in view of Bluetooth innovation empowering gadgets to be controlled utilizing Individual Area Network (PAN) is introduced. The system cases specified here will convey the data to remote clients through Internet. All these papers recommending frameworks have certain restrictions since the hubs sent can bring about system blockage, whole foundation must be set down from starting stage which is tedious also, is unpredictable in nature.

Consequently we have executed the GSM based IVRS joined framework which empowers client to control and screen the loads/machines remotely. The GSM based home computerization framework is created and executed which abuses the well created foundation of GSM cell framework. Also, the client don't require devoted handset as the GSM versatile can be utilized as telling gadget. Thus, no additional gadget must be acquired from the client side. The GSM system

that depends on radio wave correspondence passing on data in a constant procedure to control gadgets remotely is the most well-suited option among all the remote advancements. The IVRS framework empowers client to associate with framework which facilitates the control operation. Versatile correspondence system scope is greater than that of Local Area Network (LANs), hence client can take advantage of compact telephones to sort out the framework.

## II. EXISTING SYSTEM

In this framework we can control and monitor loads remotely by utilizing GSM, however here we can't get affirmation with respect to whether the specific burden has been controlled and observed. To beat this issue we have proposed a framework in which we can get affirmation with respect to the heaps.

### DISADVANTAGES

we cannot receive acknowledgement regarding the loads.

### PROPOSED SYSTEM

Here we executed IVRS framework to control and screen stacks remotely. we proposed this framework to defeat the issue which we confronted in the current framework. For that reason we utilized APR9600 module to get affirmation with respect to the loads.

## III. IMPLEMENTATION




Figure.1

Fig.1 shows the implementation of our proposed system. The main objective for implementing this system is to control and monitor the loads wirelessly. We will use GSM to control the loads, from GSM we will send commands to Micro Controller to switch ON or OFF the loads. The Micro controller will receive the commands and perform particular actions based upon the commands. We will receive information whether the loads have been switched or not in the form of Voice by using APR9600 modules.

The main modules used here are:

- 1) ARM7 micro controller
- 2) GSM
- 3) APR9600

### **ARM7 Micro Controller**

“ARM” is the abbreviation of “Advanced RISC Machines”. It is a widespread processor cores in the world. It is especially used in portable devices due to reasonable performance and low power consumption. ARM is a family of RISC architectures.

*LPC2148 Chip Features:*

- 16-bit/32-bit ARM7TDMI-S microcontroller in a tiny LQFP64 package.
- 8 Kb to 40 Kb of on-chip static RAM and 32 Kb to 512 Kb of on-chip flash memory.
- Single 10-bit DAC provides variable analog output (LPC2142/44/46/48 only).
- Two 32-bit timers/external event counters (with four capture and four compare channels each), PWM unit (six outputs) and watchdog.
- Multiple serial interfaces including two UARTs (16C550), two Fast I2C-bus (400 Kbit/s),

### **GSM**

GSM stands for Global System for Mobile Communication. In this project we are using SIM 900 GSM module in order to control the loads wirelessly.

### **APR9600**

APR9600 is an ease superior sound record/replay IC consolidating streak simple stockpiling method. Recorded sound is retained even after power supply is removed from the module. The replayed sound exhibits high quality with a low noise level. The APR9600 has a 28 pin DIP bundle. Supply voltage is between 4.5V to 6.5V. By this module we will get information regarding whether the load has been switched on or not in the form of voice.

### **ADVANTAGES**

- Low power consumption
- More reliable
- save energy.

## **IV. CONCLUSION**

The framework extravagantly portrayed in the above segments makes productive utilization of the most recent innovation to help clients keeping in mind the end goal to control the operation of the craved machine or load continuously from remote area. It can be mulled over as a unimaginable answer for the troubles confronted by the inhabitants of the house who are not physically exhibit at the area yet, can control the gadgets giving a constant robotization. The paper gives the outlining and usage of GSM based constant robotization framework. It likewise explains the Interactive Voice Response System (IVRS) outlining coordinated with Voice IC hardware which is the remarkable component of the actualized framework. Besides, the dormancy required in the execution of the operation is assessed and the point of interest investigation is illustrated. Subsequently an IVRS based framework encourages client to associate with the framework and it empowers the client to control the heaps remotely.

### **FUTURE SCOPE**

To this system we can add web server by which we can upload the data regarding the loads in the server. By this we can check the information of the loads by logging into the web server.

## **REFERENCES**

1. Ladwa, T.M.; Ladwa, S.M.; Kaarthik, R.S.; Dhara, A.R.; Dalei, N., “Control of remote domestic system using DTMF,” Instrumentation, Communications, Information Technology, and Biomedical Engineering (ICICI-BME), 2009 International Conference on , vol., no., pp.1,6, 23-25 Nov. 2009

**International Journal of Innovative Research in Science, Engineering and Technology**

*An ISO 3297: 2007 Certified Organization*

*Volume 6, Special Issue 2, February 2017*

**National Conference on Recent Advancements in Engineering & Technology and Management 2017 (NCRAETM 2K17)**

**18<sup>th</sup> February 2017**

**Organized by**

**Sree Rama Engineering College (SRET), Tirupati- 517 507, India**

2. Y. Tajika, T. Saito K. Termoto, N. Oosaka and M. Isshiki, "Networked home appliance system using Bluetooth technology integrating appliance control/monitoring with internet service, IEEE Trans. Consumer Electron., vol. 49, no. 4, pp. 1043-1048, Nov. 2003.
3. H. S. Kim, and C. G. Lee, "Wireless USB based home security system on the OSGi service platform, International conf. on Consumer Electron., pp. 1-2, Jan. 2007.
4. Mulla A., Baviskar J. and Baviskar A., "DTMF Based Automation System with Reduction of Noise using Goertzel DFT Estimation," Proceedings of The International Conference on Communication Systems and Network Technologies (CSNT), Bhopal , India, pp. 1124-1129, 7-9 April 2014.
5. Y. P. Tsou, J. W. Hsieh, C. T. Lin, and C. Y. Chen, "Building a remotesupervisory control network system for smart home applications, IEEEInternational Conf. on System, Man and Cybernetics, pp. 1826-1830, Oct.2006.
6. L. Ophir, "802.11 Over Coax A Hybrid Coax Wireless Home NetworkUsing 802.11 Technology, Consumer Communications and NetworkingConference, pp. 13-18, Jan. 2004.
7. Baviskar, J.J., Mulla, A.Y., Baviskar, A.J., Panchal, N.B. and Makwana, R.P., "Implementation of 802.15.4 for designing of home automation and power monitoring system," Electrical, Electronics and Computer Science (SCEECS), 2014 IEEE Students' Conference on, pp.1-5, 1-2 March 2014.
8. Karia D., Baviskar J., Makwana R., and Panchal N., "Performance Analysis of ZigBee based Load Control and Power Monitoring System, "International Conference on Advances in Computing, Communications and Informatics (ICACCI),Mysore, India, pp.1479-1484, August 2013.