

International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization

2nd National Conference on "RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

Ambient Intelligence used against the Mistreatment of Women

Indira Priyadharsini S¹, Harshitha M S², Chaithra P R³, Dr. K S Jagadeesh Gowda⁴

U.G Student, Department of Computer Science and Engineering, Sri Krishna Institute of Technology, Bengaluru,

Karnataka, India^{1,2,3}

Head of the Department, Department of Computer Science and Engineering, Sri Krishna Institute of Technology,

Bengaluru, Karnataka, India⁴

ABSTRACT- Thousands of people (mainly women) are daily mistreated, battered and abused by their ex-couples or their current couples. In this sense, electronic surveillance can be an efficient tool for helping to guarantee the safety of victims. The main objective of this paper is to present a promising approach to develop a useful wearable device in order to provide a communication protocol which is aimed at the protection of women under risk situations, including cases of misbehavior or physical assault using ambient intelligence(AmI). Ambient Intelligence, based on ubiquitous computing, represents a promising approach to make technology adapt to people in order to solve the challenge of developing strategies that allow the early detection and prevention of problems in safety environments and, more specifically, the protection of people under risk situations, including cases of mistreatment or loss. This paper produces an integral solution designed for improving the protection of mistreated and at-risk people by means of the integration of shock wave generator, alarm, wireless camera, Global System for Mobile communication (GSM), and Global Positioning Systems (GPS) technologies. A security alert message is sent to the police and the caretaker along with the victim's location, further assailant's image is also sent. On using voice commands, the alarm and the shock wave generator turns on. The hardware implementation has been done and tested.

KEYWORDS: Ambient intelligence, Mistreatment, Camera, GPS, GSM, Shock Wave generator.

I. INTRODUCTION

A woman is raped every 21 minutes in India and every 18 hrs in Delhi. It is shameful for the whole world. The primary reasons behind such shocking statistics is the society which is prejudiced against the girl child, lack of proper policing, ineffective laws etc. Even in this modern era women are feeling insecure to step out of their house because of increasing crimes in our country like harassment, abuse, violence etc., The corporate and IT sector are currently in boom. Many women are working in corporate even in night shifts. There is a feeling of insecurity among the working women. Many unfortunate incidents have been taking place in women's case. Problems may come many directions such as women walking on the road after the work, going to super market or many other reasons for which they go alone. People at home are not sure of their safe return.

Another factor is, women die without knowing the reason as they attend excursions and industrial trips conducted by the organizations. This happens due to attacks on women but not suicides. It is just the tip of the iceberg. Rape is a notoriously under-reported crime, thanks to its social stigma. While the long term solutions should aim to correct the above factors. Now there is a requirement of some change. Ambient intelligence refers to the electronic environments that continuously senses and responds to the presence and the desires of people using it. When they feel danger, this prototype directly gets connected to the satellite through Global Positioning Systems (GPS) when activated. The location is transferred through the Global System for Mobile communication (GSM) and this prototype is also provided



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization Volume 7, Special Issue 6, May 2018

2nd National Conference on **"RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY**

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

with a voice recognition system where the user can assert voice commands on danger and activate the shock wave generator system that produces 60 shockwaves in 1 second in emergency situations.

II. LITERATURE SURVEY

With reference to [1], battered intervention programs were opened for psycho-educational intervention of men that used the violence toward their partner or ex-partner. This was proposed in Spain, Costa Rica and Chile.

With reference to [2], a facial expression analyzing system was developed to report the threat based on facial expressions of danger. The camera captured images of the people and instantaneously the expressions of the people captured in those images were analyzed. On detection of the expressions which showed fear, a threat report was filed. With reference to [3], a self defense system was developed with GPRS (General Packet Radio Service) location tracking and Short Message Service (SMS) alerting through GSM networks. In this system the SMS contained information only about the victim location and the body posture of the victim. These messages will be sent to the predefined emergency numbers. In case if the caretaker wants to know the present location of the user, he/she can do so by sending a SMS to the SIM(Subscriber Identity Module) number of the lady which contains a secret password.

III. EXISTING SYSTEM

Various methods are existing for women security like pepper spray canisters, the Stun Rings, the Ultrasonic Dog Repellent, the Stun Gun, the Tear Gas Spray. There are also mobile phone based apps that can send an alert message using GSM networks and GPS locating tracking systems. There are various approaches towards wearable devices with only a SMS based alert and tracking of the victim using GSM and GPRS systems.

1. SMART SECURITY SOLUTION FOR WOMEN BASED ON INTERNET OF THINGS (IOT) PUBLISHED IN:

IEEE EXPLORER

This paper explains the application is programmed and loaded with all the required data which includes Human behavior and reactions to different situations like anger, fear and anxiety. This generates a signal which is transmitted to the smart phone.

2. ONE TOUCH ALARM SYSTEM FOR WOMEN'S SAFETY USING GSM PUBLISHED IN: IJECE

You sense danger, all you had to do, is hold on the button of the device. The device consists of a PIC microcontroller, GSM module, GPS modules. The system resembles a normal watch which when activated, tracks the place of the women using GPS Observation: Anytime (Global Positioning System) and sends emergency messages using GSM (Global System for Mobile communication), to stored contacts and the police control room.

3. PROTOTYPE OF AN INTELLIGENT SYSTEM BASED ON RFID AND GPS TECHNOLOGIES FOR WOMEN SAFETY PUBLISHED IN: IEEE XPLORER

In this paper, developed women safety system using Radio Frequency Identification (RFID) and Global positioning system (GPS). The main idea here is using a active RFID tag with passive RFID reader to scan the information and this information is transferred to the microcontroller.

In the above papers, use of smart phones lead to the following major problems: Battery low problem, signal problem and a economically unstable people cannot afford high-end smart phones.



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization

2nd National Conference on **"RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY**

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

IV. PROPOSED SYSTEM



The block diagram of the conceptual system is shown in above figure. The microcontroller acts as an embedded computing system and controls the activities of all the subsystems. It is interfaced with Emergency Switch, Wireless Camera, Voice recognition module, GPS Receiver, GSM Modulator demodulator (MODEM), High Voltage Shock Circuit and LCD display. The microcontroller periodically monitors the status of all the devices and also keeps on checking for any incoming SMS message from the parents or any caretakers. When there is no GSM network, on pressing the Emergency Switch, the processor activates the speech circuit to make loud shouting sound to catch the attention of the nearby people for help. It also prepares the High Voltage Electric Shock Circuit to be ready to give a non-lethal shock to the attacker. If the help is not available and if the system is not reset within the stipulated time, the system obtains location information from the GPS and prepares a text SMS containing the present location information and sends a SMS through the GSM modem to the police control room and a distress message to the pre-programmed mobile number along with the image of the assailant [3]. The design is implemented using an embedded microcontroller, in a modular form to be adaptable to different types of location tracking. Based on the total design of the system, the hardware and software of the system is designed to be near real-time monitoring of the women and immediate help. The lady can protect herself by the electric shock to the person harassing her. The software is developed in assembly language to demonstrate the system capability in providing real-time response. Using the location information supplied by this system, the location can be tracked and traced using GPS and Google Maps. Thus the lady will be safe and she feels protected. At the product level it can be as compact as a smart watch.

V. DESCRIPTION OF PROTOTYPE

ARM7-LPC2148 is the heart of this device. All the peripherals are interfaced into and programmed using this microcontroller. This processor is chosen because of its low power consumption and available two Universal Asynchronous Receiver/Transmitter (UART"s) which facilitates easy interfacing through multiplexing by maintaining the speed.

A GPS receiver system calculates the location of victim by precisely timing the signals sent by GPS satellites high above the Earth. Each satellite continuously transmits messages that include the time the message was transmitted and satellite position at the time of message transmission. The receiver uses the messages it receives to determine the transit time of each message and computes the distance to each satellite. This position is then displayed, perhaps with a moving map display or latitude and longitude.



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization Volume 7, Special Issue 6, May 2018

2nd National Conference on "RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

GSM modem is interfaced with ARM7 processor. This modem is used for audio calls, SMS and internet access through Attention commands (AT) commands.GSM accepts certain commands through serial interface and acknowledges these AT commands .The ten digit mobile number will be stored in the processor, the program instructs the MODEM to send text message using sequence of AT commands. For each command, processor sends acknowledgement message to the MODEM.



Fig (b): Working prototype

Voice recognition device supports maximum 80 voice commands, with each voice 1500ms (one or two words speaking). Maximum 7 voice commands are effective at same time. It recognizes the pre-recorded voice of the user and finds the keywords like "help", "save", "danger" etc and activates the system to generate help message and alarms the police station with the victim's location details and the image of the assailant[4]. All the status of the device along with the pre-loaded voice commands are displayed in 16x2 LCD. The wireless camera is interfaced to the ARM processor. The camera captures the live image of the assailant and the image is transmitted to the nearest police station. The alarm produces alarming sound based on reverse of the piezoelectric effect. These alarms can be used to alert a user of an event corresponding to a switching action, counter signal or sensor input. The alarm produces a same noisy sound irrespective of the voltage variation applied to it. Shock wave generators are used. The shock waves when generated can produce burns on the assailant.



Fig (c): Shockwave generator



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization

2nd National Conference on "RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

VI. WORKING PROCEDURE



Fig (d): The working flow diagram

The user on asserting any one of the pre-loaded voice commands can start operating the device. On acknowledgement of the voice command of the user and user's voice verification, the device turns on. On pressing a button, a message regarding the threat can be sent to the nearest police station and the family members whose contacts have been pre-loaded. The police station receives the message and user location tracking is been provided by GSM, GPS and GPRS modules. Along with the message, the user can also capture and send the image of the assailant to the police station with the help of miniature camera in the device. Additionally, to add more safety in cases where GSM network operators are not available, a built in shock generator produces shock waves which harms the attacker and the alarm which produces an alarming sound in the surrounding location. The user can also just press a button to send a message to the police station which will be unaware to the assailant.



Fig (e): The GPS location of the victim's latitude and longitude will be sent to the Police Station.



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization

2nd National Conference on "RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY (RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India



Fig (f): The voice recognition module asserts this message. The victim can speak out loud the key words like "help".



Fig (g): The messages received from the victim

VIII. TOOLS USED

Keil μ Vision: The prototype presented in this paper makes use of Keil μ Vision Software for coding purposes. We have written the C complier designed code for implementing our objectives. All the components like LCD display, GSM, GPS, Voice recognition module etc are all interfaced to ARM processor using Kiel μ Vision software and the prototype operates based on the codes being given to the processor.

IX. FUTURE SCOPE

The prototype proposed in the paper can be implemented into digital watch by reducing the size of the components. This device can be implemented for office security, colleges, and hospitals and also in parking system. By integrating a culturally-relevant educational curriculum (service) with a product (good) that is affordable and accessible, our innovation is helpful in saving women from harassment. In India lots of crime happens against women every day. "Smart Watch For Women" can readily solve this issue. We will install these watches at small scale and we will try for further progress in the same. Lastly fulfilling our main aim to spread this project in the whole world that is large scale production.

X. CONCLUSION

Women security can be increased by making use of this gadget. Inter-network between the women and the police station provides easy access to women to obtain safety with just a message .The image captured by the camera will serve as evidence and record for the police to trace the assailant. The prototype can be developed and made as digital watch.



International Journal of Innovative Research in Science, Engineering and Technology

An ISO 3297: 2007 Certified Organization

2nd National Conference on "RECENT TRENDS IN COMPUTER SCIENCE & INFORMATION TECHNOLOGY

(RTCSIT'18)"

13th-14th March 2018

Organized by

Departments of Computer Science & Information Science Engineering, Sri Krishna Institute of Technology, Bangalore, India

REFERENCES

[1] S. Ruiz, L. Negredo, A. Ruiz, C. García-Moreno, Ó. Herrero, M. Yela, et al., "Violencia de género", Programa de Intervención para Agresores, Ministry of Interior of Spain, May. 2010.

[2] E. Aarts and B. de Ruyter, "New research perspectives on Ambient Intelligence", Journal of Ambient Intelligence and Smart Environments, vol. 1, n. 1, pp. 5–14, Jan. 2009.

[3] J. Bajo, J. F. de Paz, Y. de Paz, and J. M. Corchado, "Integrating case- based planning and RPTW neural networks to construct an intelligent environment for health care", Expert Syst. Appl., vol. 36, n. 3, pp. 5844–5858, Apr. 2009.

[4] D. I. Tapia, A. Abraham, J. M. Corchado, and R. S. Alonso, "Agents and ambient intelligence: case studies", Journal of Ambient Intelligence and Humanized Computing, vol. 1, n. 2, pp. 85–93, Jun. 2010.

[5] BI Incorporated, "One-piece active GPS offender tracking: BI ExacuTrack® One".

[6] Vijayalashmi B, Renuka S, Chennur P, Patil S (2015) Self defense system for women safety with location tracking and SMS alerting through GSM network. International Journal of Research in Engineering and Technology (IJRET) 4: 57-60. [7]. Sriranjini R (2017) GPS and GSM based self defense system for women safety. Journal of Electrical and Electronic Systems, vol. 6, issue 2, ISSN: 2332-0796.

[8] Shashidhar, Shubham Sharma, Venugopal, Vinuth Raj(2017)Communication Protocol for the Guardian System aimed at the Protection of Mistreated Person. IJARIIE, vol. 2, n. 5, pp. 144-147.