

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

GSM Controlled Arduino Smart Home Security System

Deepak Kumar¹, Shruti Karkra², Manoj Pandey³

Student, Department of Electronics and Communication Engineering, Amity University Haryana, Haryana, India¹

Guide, Department of Electronics and Communication Engineering, Amity University Haryana, Haryana, India²

Guide, Department of Electronics and Communication Engineering, Amity University Haryana, Haryana, India³

ABSTRACT: This Paper is predicated on summary of a GSM based mostly device management, GAS discharge observation, & security system. This paper assesses the occasion of a moderate security framework. The low-control PIR, Accelerometer capitalizes on electrical phenomenon to detect someone's body that is in the range of device and MQ2 for detection of smoke and Gas leakage. Identification the nearness of any unapproved individual in a particular measure, it triggers alert and sets up a choice to a predefined assortment through a GSM electronic gear. This project may be additional extended to use in ménage and even in varied industries appliances wherever the whole monitor and management varied different parameters may conjointly performed at no price. This project offers users with monumental advantages of simplicity, being compatible to things wherever the presence close to the machine poses a good threat to safety, needing simply basic data of electronic messaging & what additional it's heaps of dependability.

KEYWORDS: PIR(Passive Infrared Sensor), MQ2(Smoke/Gas leak Sensor), Arduino Uno, ADXL335 (Accelerometer), GSM Modem.

I. INTRODUCTION

The new time of innovation has re-imagined conveyance. The overall population today approach cell phones thus the planet so has turned into an overall town. At some random minute, any unequivocal individual are frequently reached with the vagrant. Anyway the apparatus of nomad can't just be confined to causation SMS or starting discussions. New developments and thoughts are frequently created from it that may any upgrade its capacities. Advances like Infra-red, Bluetooth, etc that has made starting late goes to show the unquestionable reality that enhancements region unit in truth possible and thusly these updates have directed our life and the manner in which we will in general live. Remote organization of many home and workplace machines may be a subject of creating interest and starting late we've seen a couple of structures giving such controls.

Nowadays, except for supporting voice calls nomad are regularly acclimated send instant messages comparably as mixed media framework messages (that may contain film, illustrations, movements, and so forth). Causation translation messages are incredibly well-enjoyed among nomad clients. Moment electronic informing, since it is furthermore well-known, allows quick transmission of short messages that empower an individual to share ideas, suppositions and diverse applicable information. we've utilized the horribly thought to style a framework that demonstrations a stage to get messages that in truth region unit directions sent to oversee very surprising machines and gadgets associated with the stage. We have planned framework that is predicated on the GSM innovation that viably allows control from a far off space to the required area. The machine of our brief framework is tremendous inside the ever unique mechanical world. It allows a bigger level of opportunity to an individual whether it's predominant the unit machines or work environment supplies. The need to be physically blessing to oversee apparatuses of a precise area is wiped out with the use of our framework.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

II. RELATED WORK

There are many definitions of automation and security system offered within the literature.

G. Gu et.al [1] and G. Mingming et.al [2] mentioned that GSM is one in all the foremost wide used cellular technologies within the world. C. Felix et.al [3], C. Peijiang et.al [4] and B. S. Rao [5] explained that with the rise within the variety of GSM subscribers, analysis and development is heavily supported in any work the GSM implementation. Rozita Teymourzadeh et.al [6] targeted on their [5] thoughts and enforced the practicality of GSM protocol for saving the ability like management light-weight, fan and alternative appliance. R. Llamas et.al [7] mentioned GSM primarily based device system with mobile application developed victimization the app artificer for robot mobile phones targeting its giant market that is in a position to be useful for the lots. Then Mahesh N. Jivani et.al [8] used R. Llamas's plan and conjointly has identical practicality as [7] however it includes app artificer for robot mobile. However, i feel here isn't any area for security preventing from thieving or hearth or unwanted scenario that is essentially the most reality in twenty first century, at that time in our analysis, we are about to explore new ideas & thoughts that is that the combination of saving power and well security system of a corporation. For this we tend to use not solely GSM however conjointly Bluetooth, internet server and robot apps to produce a secure organization. Ming Yan et.al[9] arranged and prototyped a substitution reasonable living framework alluded to as home lighting framework exploitation Bluetooth fundamentally based robot Smartphone. At that point B. Murali symbol et.al pursued line Yan's and portrayed Bluetooth principally based remote home computerized framework exploitation FPGA. Bluetooth innovation, that means to trade data remotely amid a fluctuate of short separation by giving a necessary platform to make convenience and controllability. However the actual fact is, it solely works on a restricted vary however in security matter it conjointly fails to make the long vary platform. That's why in our analysis we tend to use conjointly use Bluetooth in conjunction with GSM for long vary platform conjointly. Nathan David et.al explored same because the paper however includes additional sensors and practicality. It additional email notification methodology however in my purpose of read we tend to don't seem to be that a lot of accustomed an email however we tend inform accustomed during a SMS notification therefore in our project and paper we tend to use this SMS notification system supported the requirement .

III. HARDWARE REQUIRED

A. Arduino Controller:

It is a open-source controller PCB board subject to the chip is ATmega 328P microcontroller and made up of Arduino.cc. The board is furnished with group of modernized and basic data (I/O) pins that may be connected to various improvement sheets (shields) and distinctive PCBs. Arduino has Digital pins which is equal to 14 and 6 analog pins, and it can be programmed with its software Arduino IDE (Integrated Development Environment) through USB interface B. It will in general be filled by a USB connect or by an external 9 volt battery, anyway it recognizes voltages some place in the scope of 7 and 20 volts. It is moreover similar to the other arduino's like Arduino nano and Leonardo. The gear reference setup is appropriated under a Creative Commons Attribution Share-Alike 2.5 license and is available on the Arduino site. Configuration and creation records for specific interpretations of the hardware are also available. "Uno" means one in Italian and was picked to check the entry of Arduino Software (IDE) 1.0. The Uno board and structure 1.0 of Arduino Software (IDE) were the reference adjustments of Arduino, directly created to additional cutting-edge releases. The Uno board is the first in a movement of USB Arduino sheets, and the reference model for the Arduino arrange.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

B. PIR(Passive Infrared Sensor)

PIR is basically produced using pyroelectrical sensors to build up an electrical flag because of a change inside the episode warm radiation each living body transmits some low dimension radiations and along these lines the more smoking the body, the a great deal of is transmitted radiation. Modern PIR sensors ordinarily grasp 2 IR-touchy parts with inverse polarization housed amid a tightly fixed metal with a window produced using Infrared pervious material (normally covered semiconductor to monitor the detecting component). When the gadget is inactive, every opening notification a comparative amount of IR, the nearby amount transmitted from the space or dividers or outside.




Figure 1: Working Principle of PIR Sensor

As shown in the figure 1 when a warmth body kind of a living being or a creature crosses it, then it first catches one a large part of the Passive Infrared finders that reason of positive differential change between the 2 parts. When the warm body leaves the detecting space, the invert occurs, whereby the locator creates a negative differential revision. These correction beats region unit what's distinguished. In order to frame the FOV, for example Field Of read of the locator, the identifier is given focal points before of it. The focal point utilized here is shabby and light-weight plastic materials with transmission qualities fit to the required wavelength fluctuate to conceal a great deal of bigger space, discovery focal point is get a separation into numerous segments, each segment of that could be a focal points. Giving a greater differs of IR to the locator it will range over a large number of degree measurement so complete setup improves resistance to changes in foundation temperature, moistness and causes a shorter sinking time of the yield when a body hostage in or out the FOV. Together with electrical wonder identifier, a chip named little Power PIR Motion Detector IC has been utilized.

C. Modem GSM

They have ultra negligible and reliable remote modules. SIM 900A SMT module has a full dual-band GSM / GPRS game plan that can be embedded in client applications. According to the industry-standard interface, the SIM900A is executed for GSM and GPRS 900 a t 1800MHz voice, SMS, data, and fax with little structure factor and low power consumption. With a slight setup of 24mmx24mmx3mm, the SIM900A client can be suitable for all intents and purposes for the traditional enthusiasm of all applications, especially thin and textile. A GSM module is basically a GSM Modem Mod (like the SIM 900) which is related to a PCB with different types of yield obtained from the board - state TTL output (for Arduino, 8051 and specific microcontrollers) and indeed with RS232 output interface). The board has planned a stick to connect with the Mic and the speaker so that the + 5V or different estimates of force and ground affiliation can be excluded. These modes of action change with different modules.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019




Figure 2: GSM Module

Figure 2 shows the general look the GSM modem, it have one antenna port one SIM port where sim can b installed. It have Tx and Rx pins for communicating with Arduino. For activating the GSM modem 12V external power is required.

D. Accelerometer(ADXL 335)

The expansion of speed is a method in which the speed is changed over time and it is a vector sum. Therefore, in addition, speed is a speed and effect. There are two different ways to clarify the introductory expansion rate, one is the change in speed and the other is definitely adjusted. At one time, both are changed at the same time. If we talk about the ADXL 335 accelerometer, then this accelerometer is a device that is used to evaluate the expansion speed of anything. It evaluates the speed of expansion in the three assumptions, for example, as straightforward commitments like X, Y and Z. This is a low mood and less power consuming device. When used for measuring purposes, it is interfering with a controller, for example, microcontrollers or Arduino, etc. It is commonly used to develop working machines, for example, exhaustion, driving weight and depletion, etc. Such running, walking, moving and skipping etc.




Figure 3: ADXL 335

Figure 3 shows how ADXL 335 looks. It have 4 pins one for X axis, 2nd for Y axis, 3rd for Z axis calibration, 2 pins for ground and power supply. ADXL335 requires 3.3 volt. Depending on the use we can use Axis pins. ADXL335 gives raw values which can be further converted into G values.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

E. MQ2(Gas/Smoke Sensor)

MQ2 is most used smoke sensor. It consists of Metal oxide Semiconductor commonly known as Chemiresistor, Its detection is based on the resistance change of the material which is sensing when the material comes in contact with the Gas. Mq2 sensor operating voltage is 5V, and draw power nearly about 800mW. It can be used for detection of multiple things like Liquefied petroleum Gas, Smoke, Propane gas, Methane gas and CO (Carbon Monoxide). In Mq2 there are 4 pins Analog Pin, Digital Pin, VCC and Gnd. The Analog output Voltage of the sensor changes directly proportional to the amount of the Smoke or gas. More the amount of Gas more precise value will be given by the analog pin.



Figure 3: MQ2 Sensor

Figure 3 shows the basic look of MQ2 (Gas/Smoke detector sensor). It have 4 pins Digital pin, Analog pin, Ground, Input Voltage. In this project we have used analog pin for detecting the smoke or leakage of gas. MQ2 operates at 5 volt.

IV. PURPOSED WORK

In Security Framework are basic in the present society, where wrongdoing is developing. The undertaking is gotten ready for perceiving gatecrashers and showing the proprietor by affecting a telephone to make a call. The Passive infrared sensor perceives improvement by recognizing the capability in infrared or breathtaking warmth degree transmitted by the living animals and accelerometer sensor which identifies break through entryways and windows, and makes PIR sensor area progressively solid about the nearness of the intruder. The yield goes high if any of the sensors recognizes or shows detection or change in value. The scope of common Passive Infrared sensor is around six meter or around thirty feet. To give proper output action of PIR sensor, it requires a warm up time of around twenty to sixty seconds. This is required in light of the fact that, the Passive Infrared sensor has a settling time amid which it aligns its sensor as per the earth and balances out the infrared finder. In the midst of this time, there should be next to no movement before the sensor. In case the sensor isn't adequately given adjusting time, the yield of the PIR sensor may not be exact. Exactly when a Passive Infrared sensor perceives any development, the yield of the sensor is high. Accelerometer ADXL 335 is utilized which is put at entryways and windows for security insurance in the event that rupture through entryways or windows and if the movement in entryways and windows or some other opening is recognized will send message to the proprietor of the house and furthermore makes the PIR readings be increasingly careful and exact at the yield. there might be chances that some youngster or pet will be there or break in through window, PIR sensor separates them moreover so this can be overpowered by Accelerometer sensor which basically facilitates the increasing speed in entryways and windows connected by the thing. These readings and information are sent to arduino and by support checks and reasonable code wrap up additionally yield or activity on the off chance that false by, at that point nothing will happen in the event that investigating will be veritable by, at that point converses with the GSM module by strategies for sequential port correspondence to place a telephone call to the pre revamped mobile number and send the picture of the individual on his telephone. A basic thing to be note about PIR sensors is that the yield will be high when it perceives advancement. The yield of the sensor goes low once in a while, regardless

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

of when there is improvement which may trap the microcontroller into contemplating that there is no advancement. This issue must be administered in the programming of Arduino by rejecting the low yield hails that have a shorter range than a predefined time. This is finished by enduring that the improvement before PIR sensor is available always.

V. ADVANTAGES

1. Controlling of device from long distance is possible.
2. Very low cost design
3. It can be easily used in houses.
4. Usability: Any one can use having knowledge of SMS
5. SMS format can be easily understood.
6. International scope

VI. CONCLUSION

Home security system may also be thought of to make bigger its quantifiability and enclosed a whole lot of practicality in 5 to 10 years. However, the foremost capabilities and requirements aren't expected to disagree extensively, whereas security, simplicity and affordability are on the best precedence. One particular decision of a home protection gadget are created at some point of this paper, domestic user will use it as a reference once assemble their very own house safety machine. Though the infrastructure set up for the residence protection system totally stays on the theoretical level, it could be enforced in future once the era of devices is mature on the aspect of the reality that the security of life is decreasing home protection is increasing its tempo for a home consumer to require movements. This project offers users with huge edges of simplicity, being compatible to things wherever the presence close to the machine poses an excellent threat to safety, needing simply basic information of electronic messaging & what additional it has loads of reliableness. One additional advantage of this project is that the management engineer World Health Organization supervises the machine may be engaged in the other additional work, so the corporate will enhance its production. of these options enhance the quality of the project.

VII. FUTURE SCOPE

This project may be any extended to observe over one parameter with a similar simplicity, compatibility. The task idea may even prolonged to use in domestic appliances like gas stoves, wherein the utensil with the material to be cooked can be readied and kept prepared on the exceptional gas stove and can requested to cook by means of the informing administration, for the recommended measure of time with the temperature being kept up at determined points of confinement, before we achieve home. As we find in the left hand side picture there are additionally numerous approaches to execute our program extensively in our everyday life. Thus our project is simply a model of a way to make a home to a GSM based mostly smart home. Into that we tend to additionally show that we tend to created a GSM primarily based good home security system which may sense gas escape, intruders' detector, & device management by an easy SMS. For future enhancements this GSM based smart home security system may be use as wireless remote system exploitation WSN. we tend to additionally add several alternative detector & sensors like escape sensing element, Movement sensing element, Smoke sensing element, lightweight sensing element, lightweight Dependent electrical device Chip, Smoke Detector. If we tend to a say it's a sentence then we are able to say that total home security system is simply succeeding step. We tend to use this idea additionally into the varied industries and by that method the direction of the corporate are machine-driven straightforward.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 5, May 2019

REFERENCES

- [1] G. Gu and G. Peng, "The survey of GSM wireless communication system," in International Conference on Computer and Information Application (ICCIA), Tianjin. pp.121 – 124, 2010.
- [2] G. Mingming, Shaoliangshan, Huixiaowei, and Sunqingwei, "The System of Wireless Smart House Based on GSM and ZigBee," in International International Journal of Computer Applications (0975 – 8887) Volume 165 – No.10, May 2017 38 Conference on Intelligent Computation Technology and Automation (ICICTA), Changsha. PP.1017-1020, 2010.
- [3] C. Felix and I. J. Raglend, "Home automation using GSM," in International Conference on Signal Processing, Communication, Computing and Networking Technologies (ICSCCN), Thuckafay. PP.15-19, 2011.
- [4] C. Peijiang and J. Xuehua, "Design and Implementation of Remote Monitoring System Based on GSM," in Pacific-Asia Workshop on Computational Intelligence and Industrial Application (PACIIA '08), Wuhan. PP.678-681, 2008.
- [5] B. S. Rao, S. D. V. Prasad, and R.M. Mohan, "A prototype for Home Automation using GSM technology," in International Conference on Power, Control and Embedded Systems (ICPCES), Allahabad. PP.1-4, 2010.
- [6] Rozita Teymourzadeh, CEng, Member IEEE/IET, Salah Addin Ahmed, Kok Wai Chan, and Mok Vee Hoong Faculty of Engineering, Technology & Built Environment UCSI University Kuala Lumpur, Malaysia "Smart GSM based Home Automation System", IEEE Conference on Systems, Process & Control (ICSPC2013), 13 - 15 December 2013. PP.1-5, 2013.
- [7] R. Llamas, R Reith, M. Shiere, "Apple Cedes Market Share in Smartphone Operating System Market as Android Surges and Windows Phone Gains, According to IDC", 7th August 2013, IDC Press Release, <http://www.idc.com/getdoc.jsp?containerId=prUS242574> 13. PP.12-87
- [8] Mahesh N. Jivani, "GSM Based Home Automation System Using App-Inventor for Android Mobile Phone", International Journal of Advanced Research in Electrical, Electronics and Instrumentation Engineering (An ISO 3297: 2007 Certified Organization) Vol. 3, Issue 9, September 2014. PP.11-23
- [9] Ming Yan, Hao Shi, "Smart Living Using Bluetooth based Android Smartphone", International Journal of Wireless & Mobile Networks (IJWMN) Vol.5, No. 1. PP.98-189