

A Survey on Emotion Based System for Music Player and Books Reading

Aarti Jawalkar ¹, Sneha Thorave ², Anurag Waghmare³, Rutuja Jadhav⁴, Kirti Panmand⁵
Student, Dept. of Computer Engineering, DR. D.Y. Patil School of Engineering and Technology, Pune,
Maharashtra, India¹

Student, Dept. of Computer Engineering, DR. D.Y. Patil School of Engineering and Technology,
Pune, Maharashtra India²

Student, Dept. of Computer Engineering, DR. D.Y. Patil School of Engineering and Technology,
Pune, Maharashtra, India³

Student, Dept. of Computer Engineering, DR. D.Y. Patil School of Engineering and Technology,
Pune, Maharashtra, India⁴

Assistant Professor, Dept. of Computer Engineering, DR. D.Y. Patil School of Engineering and
Technology, Pune, Maharashtra, India⁵

ABSTRACT: This system represents a method to automatically detect emotional duality and mixed emotional experience using Linux based system. Coordinates, distance and movement of tracked points were used to create features from visual input that captured facial expressions, head, face gestures and face movement. Spectral features, prosodic features were extracted using the camera. Espeak and Pyttax and Face API are used for calculation of features. A combined feature vector was created by feature level fusion and cascade classifier was used for emotion detection. Live participants and actions are to be used for recording simultaneous mixed emotional experience. As per calculated result system will play songs and display books list & video suggestions.

KEYWORDS: Smart Emotion, Face Detection, Emotion Prediction, OpenCV.

I. INTRODUCTION

Emotion recognition has vital applications within the field of drugs, education, marketing, security, and police investigation. Machines will enhance the human-computer interaction by accurately recognizing the human emotions and responding to those emotions. Existing analysis has primarily examined automatic detection of single feeling. However, scientific discipline and behavioral science studies have shown that humans will at the same time expertise and categorical mixed emotions. For example, an individual will feel happy and unhappy at a similar time. During this analysis mixtures of six basic emotions (happiness, sadness, surprise, anger, fear, disgust and neutral state) were used. This system aims are to develop options that capture knowledge from facial expressions to spot multiple emotions. Just in case of single-label categorization drawback every annotated feature-vector instance is simply related to one class label. However, the multiple concurrent emotion recognition is a multi-label classification problem. In a multi-label problem, each feature vector instance is associated with multiple labels such as presence or absence of one of each six basic emotions. The multi-label classification is receiving increased attention and is being applied to a many domains such as text, music, images, and video based systems, security and bio informatics. This system examined recognition of concurrent emotional ambivalence and mixed emotions. Additionally, the study examined two concurrent emotions (emotion duality) to limit the scope of the research based on availability of scenarios.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 11, November 2019

II. RELATED WORK

Currently, there are no dedicated applications to suggest songs based on emotion of user. There are also very few applications that focus on the user preferences and recommendations, and these are not Customizable, like All Music Other applications suggests predefined (not user-specific) song play-lists. An application like moodfuse include features like manual selection of songs, partly shuffle, playlist. Some popular music applications like Saavn, Spotify provide users defined playlists that needs to be created and updated manually. All of these applications focus on general categorization rather than specificity to every user. A dedicated application that focuses more on user preferences, priorities, and the creation of dynamic playlist is required to optimize the user experience. It should contain user specific play-list generated based on the usage and should be efficient in categorization. Many widely used Facial expression categorization techniques like Viola and Jones, etc, can be used for beginning phase to capture and determine the user's emotion, but these techniques have high computational requirement. The alternative is to use a local host web service that process computation in the web. The proposed system uses, Affective fisher face algorithm for face recognition & The Local Binary Pattern Histogram(LBPH) algorithm is a simple result on face recognition problem, which can recognize both front face and side face. for emotion recognition, a system that has already analyzed emotions from over five million faces. This fisherface algorithm helps the application capture, and determine emotion from a picture. Later, this emotion can be used to organization of user's playlist.

III. PROPOSED SYSTEM



FIG1.SYSTEM ARCHITECTURE

User: Use this system.

Server: Connection between User and database

Database: Storage of information related to Facial characteristics, songs and books uploaded.

Our system has mainly three modules, user module, mood detection module and video suggestion module. Various processes involved in these two modules are:

User Module:

User can use system and store songs and books library in the system.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 11, November 2019

Mood detection Module:

As per the facial expression it will recognize mood of user it will show songs list or books library and it will also give video suggestion

Video suggestion Module:

According to the users mood it will give the suggestions of videos.

IV. CONCLUSION

Music is an important means of regulating mood in various everyday situations. Proposed system is readily available to everyone and can be listened to almost anywhere. System is directly dependent upon Facial Expressions of user, so it is very effective.

REFERENCES

- [1] A. S. Patwardhan, Augmenting Supervised Emotion Recognition with Rule-Based decision Model, arXiv, 2016.
- [2] H.Ranganathan, S.Chakraborty and S.Panchanathan. Multimodal Emotion Recognition Using Deep Learning Architectures.WACV, 2016
- [3] I. Cohen, A. Garg and T. S. Huang, *Emotion Recognition from Facial Expressions using Multilevel HMM*, 2015.
- [4] McFee, Brian, Colin Raffel, Dawen Liang, Daniel PW Ellis, Matt McVicar, Eric Battenberg, and Oriol Nieto. "librosa: Audio and music signal analysis in python." In Proceedings of the 14th python in science conference, pp. 18-25. 2015.
- [5] A. S. Patwardhan and G. M. Knapp, "Affect Intensity Estimation Using Multiple Modalities, Florida Artificial Intelligence Research Society Conference, May. 2014.
- [6] A. S. Patwardhan and G. M. Knapp, "Multimodal Affect Analysis for Product Feedback Assessment, IIE Annual Conference Proceedings. Institute of Industrial Engineers-Publisher, 2013.
- [7] SE. Kahou, C. Pal, X. Bouthillier, P. Froumenty, C. Glehre, R. Memisevic, P. Vincent, A. Courville, Y. Bengio, RC. Ferrari and M. Mirza. Combining modality specific deep neural networks for emotion recognition in video. Proceedings of the 15th ACM on International conference on multimodal interaction, 2013.
- [8] F. D. Schönbrodt and J. B. Asendorpf, "The Challenge of Constructing Psychologically Believable Agents," J. Media Psychology, vol. 23, pp. 100-107, Apr. 2011.
- [9] N. C. Krämer, I. A. Iurgel, and G. Bente, "Emotion and motivation in embodied conversational agents," presented at the AISB'05 Conv., Symp. on Agents that Want and Like: Motivational and Emotional Roots of Cognition and Action, Hatfield, UK, 2005.
- [10] J. Cassell, E. Churchill, S. Prevost, and J. Sullivan, Embodied conversational agents. Cambridge, MA: MIT Press, 2000.
- [11] Y. Kim, H. Lee, and E. Mower Provost. Deep learning for robust feature generation in audio-visual emotion recognition. ICASSP, 2013.
- [12] M. Liu, R. Wang, S. Li, S. Shan, Z. Huang, and X. Chen. Combining multiple kernel methods on riemannian manifold for emotion recognition in the wild. ICMI, 2014.