

**International Journal of Innovative Research in Science,
Engineering and Technology**

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019

The Effects of Friction Stir Welding on the Mechanical Properties and Microstructure of 5A06 Aluminum

Naveed Raza Ullah¹, Naveen Kumar²

M.Tech Student, Department of Mechanical Engineering, Yamuna Institute of Engineering & Technology,
Haryana, India¹

Assistant Professor, Department of Mechanical Engineering, Yamuna Institute of Engineering & Technology,
Haryana, India²

ABSTRACT: The display work centers on examining the impact of stick profile and tilt point of the apparatus on the mechanical and small-scale auxiliary characteristics of Intertwined Cu-Zn30 brass joints. UFSW employments water as a cooling medium which reduces temperature and limits the coarsening or dissolution of the accelerates driving to enhanced mechanical properties of the joint. For creating sound and defect-free welds, proper device geometry and welding parameters are required. It is watched that strung stick and concave shoulder with groove foot surrender a defect-free joint in UFSW. Due to tall plastic distortion and shearing of material, strung test profile yields sound joints. Fabric stream and temperature era are governed by device geometry and welding parameters. In UFSW, fabric stream inside the weld is exceptionally complex and ineffectively understood. The temperature dissemination in FSW/UFSW directly impacts the mechanical properties and microstructure (grain estimate, coarsening of accelerates) of the joints. Moo temperature, less temperature angle and tall cooling rate related with the UFSW resulted in fine grains, tall separation thickness and limited precipitate disintegration and coarsening driving to improved mechanical properties as compared to FSW

KEYWORDS: UFSW, Friction stir welding, Microstructure, Mechanical properties

I. INTRODUCTION

The display work centres on examining the impact of stick profile and tilt point of the apparatus on the mechanical and small-scale auxiliary characteristics of Intertwined Cu-Zn30 brass joints. Three distinctive stick profiles viz. Funnel shaped, strung round and hollow and round and hollow were utilized to manufacture the joints at five distinctive tilt points viz. 0°, 1°, 2°, 3° and 4°. Fifteen joints were delivered by diverse combinations of input parameters. The created joints were tried for malleable, hardness and small-scale basic properties in arrange to investigate the weld quality. The comes about of a current ponder clearly appear that instrument tilt point and stick profile essentially influences the weld quality [1]. The comes about of mechanical testing were moreover connected with the small-scale basic changes happen amid the welding prepare. Copper and its combinations, particularly brasses (Cu-Zn al etc. [1-2]. Welding is one of the foremost commonly utilized fabricating forms within the creation and preparing of brass parts [3-4]. The joining of brass utilizing ordinary combination welding methods may be a bit risky, because it requires tall warm input that can in the long run lead to warm mutilation of the joints, higher oxidation rate and surface splits [5].

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019




Fig. 1: FSW Principle - Schematic View

The issues related in joining the brasses with ordinary combination welding can be overcome utilizing FSW as the warm input and crest temperature achieved amid the welding is much lower in FSW. Stop et al. [8] explored the affect of welding, instrument rotational speed on the mechanical characteristics of FSWed CuZn40 joints, and detailed a noteworthy increment within the chunk zone hardness as compared to base amalgam. Encourage, the grain refinement in chunk.

1.2 Friction Stir Welding

Grinding blend welding (FSW) was concocted and licensed in 1991 at TWI in Cambridge (UK) and has been created to a organize where it is connected in arrangement generation. The work pieces of Aluminum Amalgam got to be clamped onto a backing bar and secured against the vertical, longitudinal and sidelong strengths, which is able attempt to lift them and thrust them separated (fixture). Fig.2 illustrates the salient features of the process which operates by generating frictional heat between a rotating tool (of harder material than the work piece being welded) and work piece, to plasticize the abutting weld region.




Fig 2: Schematic Diagram of Friction Stir Welding With a Rotating Tool

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019

1.3 Micro structural zones in FSW

The weld gotten in FSW handle is for the most part fine grained, hot worked with no captured oxides or gas porosity. The primary endeavor on classifying the microstructures of contact mix weld was made by String gill [10-11] for aluminum combinations. The total weld and its encompassing range as gotten by FSW can be classified in four unmistakable locales as:

- A. Unaffected or parent material
- B. Heat affected zone (HAZ)
- C. Thermo-mechanically affected zone (TMAZ)
- D. Weld nugget or Stir zone (WN or SZ)




Fig 3 : Schematic drawing showing micro structural zones
In a friction stir weld

II. EXPERIMENTATION

2.1 Process Parameters

Distinctive welding factors, joint arrangement and device geometry offer significant impact on the fabric development and temperature disseminated over the weld in UFSW, hence influencing the microstructure of the fabric.

2.1.1 Tool Design and Material

For the victory of the FSW/UFSW prepare, FSW instrument plays a noteworthy part. Warm advanced, fabric stream, control prerequisite and consistency of the joint's circles, are appeared in Fig. 3. A notched foot moves the fabric towards the middle of the test, hence advertising an advantage over smooth foot. Winding channels inscrolled surface moreover offer the same wonder helping in stream of fabric from the bear outskirts to the probe. The numerical examination propagation comes about were truly bolstered by the real after-effects of FSW. On account of "cold welding", "warm fragile finishing" caused a diminish within the "yield stress" with no affect on residuary stresses. Whereas on account of "hot welding", "thermal by executing FEA. It was conceivable to predict the longitudinal stresses made within the legitimate way of the FSW method with a great degree of precision with the help of "numerical examination".

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019




Fig. 4: Tool with Different Shoulder Profiles

2.1.2 Welding parameters

The critical welding parameters influencing the quality of welded joint are rotational speed of the apparatus, welding speed of the instrument, instrument tilt point, drive applied by the instrument (pivotal constrain) and dive profundity. These parameter sand properties of the fabric are responsible for the distribution of temperature, rate of cooling and torque applied by the apparatus

2.1.3 Heat generation and Temperature field

For superior understanding the effect of string contributes on warmth age FSW prepare, the variety of warmth age at contact interfacing and in shear layer with increase in string contribute are plotted. It tends to be found that the total warmth age on gadget work piece contact interfacing with hung pins decreases bit by bit when string pitch varies from 1.0 to 3.0 mm, which comes about from the decrease in instrument work piece contact region. The volumetric warmth age in shear layer is affected by some factors. Indeed, in any case string highlight energizes the fabric stream interior the shear layer, the extension of surface warm age also prompts the development in apex temperature, which is able diminish the fabric stream weight.




Fig. 4: Heat generation at the interfaces and in shear layer for different tool pin

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019




Fig.5: Represent. The predicted peak temperature using different thread

Fig. below shows examination of calculated and estimated temperature profiles at the point 15 mm away from the weld center line AS for strung pin with P=1.0 mm. Fig. below shows the anticipated and estimated crest temperature esteems for strung pins with P=1.0 mm at AS and RS, respectively.




Fig. 6: Comparison of measured and predicted temperature

III. METHODOLOGY & OPTIMIZATION TECHNIQUE

3.1 Macro/Micro Structural Evolution

3.1.1 Characteristic zones of FSW/UFSW

FSW microstructure was to begin with characterized by THREADGILL. This work was centered on AAs, and as the conduct of AAs isn't the same as other materials and combinations, this characterization was considered lacking. Appropriately, changed terms were proposed and hence altered and implemented in American Welding Society Standard 17.3M.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019




Fig. 7: Different Characteristic Zones of FSW/UFSW

The hardness profile in non-heat-treatable combinations is generally related to the grain measure in FSW/UFSW. These AAs by and large don't result in softening in the welds. It is additionally watched that hardness tends to extend as the separate from the best surface increases. Usually due to huge warm at the best surface leading to more grain development [10, 12].




Fig. 8 : Tensile properties of joint during FSW and UFSW: (a) 5A06 aluminum

The fabric utilized in this ponder is 5A06 aluminum combination of 5.17 mm thick. The chemical compositions and the mechanical properties of the 5A06 aluminum amalgam at room temperature are recorded in Tables

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019

Table 1 Chemical compositions and mechanical properties for 5A06 Aluminum alloy (wt. %)

Chemical compositions (wt. %)								Mechanical properties		
Mg	Si	Fe	Cu	Mn	Zn	Ti	Al	Tensile strength (MPa)	Yield strength (MPa)	Elongation (%)
6.8	0.04	0.4	0.1	0.5	0.02	0.02	Balance	≥350	≥160	≥15

Fig. 9 : Shows the friction stir welding machine and the welding tool used for the present work.

IV. RESULT AND DISCUSSION

4.1 Results

The morphology of the welded joints Fig. 3 appears the large-scale cross-section of the welded joints. The welding joints are separated into four diverse districts, such as the NZ, the TMAZ, the HAZ and the BM.




Fig.10 : The macro cross-section of the whole weld

4.2 Microstructure and Texture of The Welded Joints

Fig. 10 appears the introduction maps of 5A06 aluminum amalgam by grinding mix welding at different rotate speeds. Fig. 10 appears the grain measure dispersion in all the welds. It is seen from Fig. that the biggest grain estimate is within the arrange of 800 RS TMAZ (22.6µm) > 700 RS TMAZ (20µm) > 700 AS TMAZ (19.8µm) > 800 AS TMAZ (19.3µm) > 700 NZ (16.8µm) > 800NZ (16.3µm) > 400 RS TMAZ (14µm) > 400 AS TMAZ (13.9µm) > 400 NZ (12.8µm). For the smaller grain measure dissemination, grain measure expanded significantly from 400rpm to 700rpm and it decreased slightly with expanding revolution speed from 700rpm to 800 rpm.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019




Fig -11. The orientation maps of 5A06 aluminum alloy by friction stir welding at different rotate speeds




Fig- 12. Grain size distribution in all the welds

V. CONCLUSIONS

1. UFSW employs water as a cooling medium which reduces temperature and limits the coarsening or dissolution of the accelerates driving to enhanced mechanical properties of the joint.
2. For creating sound and defect-free welds, proper device geometry and welding parameters are required. It is watched that strung stick and concave shoulder with groove foot surrender a defect-free joint in UFSW. Due to tall plastic distortion and shearing of material, strung test profile yields sound joints.
3. Rotational speed and welding speed are the dominating components impacting the weld arrangement. At too moo or as well tall rotational speed and welding speed can result in destitute joint properties. As compared to FSW, UFSW requires higher rotational speed and welding speed for creating sound joints.
4. Fabric stream and temperature era are governed by device geometry and welding parameters. In UFSW, fabric stream inside the weld is exceptionally complex and ineffectively understood.

International Journal of Innovative Research in Science, Engineering and Technology

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Visit: www.ijirset.com

Vol. 8, Issue 9, September 2019

5. The temperature dissemination in FSW/UFSW directly impacts the mechanical properties and microstructure (grain estimate, coarsening of accelerates) of the joints.

REFERENCES

- [1] PRAVEEN P, YARLAGADDA P K D V. Meeting challenges in welding of aluminium alloys through pulse gas metal arc welding [J]. Journal of Materials Processing Technology, 2005, 164-165:1106-1112.
- [2] LIU P, LI Y, GENG H, WANG J. Microstructure characteristics in TIG welded joint of Mg/Al dissimilar materials [J]. Materials Letters, 2007, 61(6): 1288-1291.
- [3] THOMAS W M, NICHOLAS E D, NEEDHAM J C, MURCH M, GSMITH P T, DAWES C J. Friction stir butt welding: UK9125978 [P]. 1991-12-06.
- [4] GUERRA M, SCHMIDT C, MCCLURE L C, MURR L E, NUNESA C. Flow patterns during friction stir welding [J]. Materials Characterization, 2003, 49: 95-101.
- [5] RHODES C G, MAHONEY M W, BINGEL W H, SPURLING R A, BAMPTON C C. Effects of friction stir welding on microstructure of 7075 aluminum [J]. Scripta Materialia, 1997, 36(1): 69-75.
- [10] MISHRA R S, MA Z Y. Friction stir welding and processing [J]. Mater Science and Engineering A, 2005, 50: 1-78.
- [11] CHO J H, HAN S H, LEE C G. Cooling effect on microstructure and mechanical properties during friction stir welding of Al-Mg-Si aluminum alloys [J]. Materials Letters, 2016, 180: 157-161.
- [12] SIDDIQUEE A N, PANDEY S, KHAN N Z. Friction stir welding of austenitic stainless steel: A study on microstructure and effect of parameters on tensile strength [J]. Materials Today: Proceedings, 2015, 2(4-5): 1388-1397.