

Treatment of Dairy Waste Water using Orange Peels Powder as a low cost adsorbent

Meghana M¹, Dr D P Nagarajappa², Dr P Shiva Keshava Kumar³

M.Tech Student, Department of Environmental Engineering, UBDTCE, Davanagere-577004, Karnataka, India¹

Professor and Chairman, Department of Civil Engineering, UBDTCE, Davanagere-577004, Karnataka, India²

Professor and Head, Department of Civil Engineering, Proudadevaraya Institute of Technology, Hosapete-583225, Karnataka, India³

ABSTRACT: The dairy production is another significant wellspring of waste generation. It is necessary to give essential treatment before discharging the dairy waste to the surface and also to avoid contamination of ground water. These dairy industry effluents are portrayed with extreme COD, BOD, nutrients and so on. Such effluent is dealt with using Orange peels powder as a low cost adsorbent and analysis is to be conveyed to verify the qualities of water similarly to COD, BOD, TDS, TS and turbidity. Experiments were assessed to check the impact of various dosages of adsorbent, rapid mixing contact time and slow mixing contact time. With the use of low cost adsorbent, the polluting influences from dairy waste water can be evacuated all the more effectively. Maximum removal of COD, BOD, TDS, TS and turbidity was obtained at an ideal dosage of 120 g/L (92.3%, 89.86%, 90.6%, 95.85% and 87.65% respectively) and maximum removal of COD, BOD, TDS, TS and turbidity was obtained at an ideal rapid mixing contact time of 30 min. (85.5%, 83.9%, 83.6%, 88.64% and 81.82% respectively). The maximum removal of COD, BOD, TDS, TS and turbidity was obtained at an ideal slow mixing contact time of 75 min. (89.9%, 88.64 %, 86.3%, 87.41% and 87.83% respectively). The results indicated that the use of Orange peels powder as a low cost adsorbent to remove COD, BOD, TDS, TS and turbidity in the treatment of dairy waste water.

KEYWORDS: Dairy waste water, Orange peels powder, COD, BOD, TDS, TS and Turbidity.

I. INTRODUCTION

Industrial enterprise is spine for improvement of nation. The contamination brought about by modern part is a genuine worry in all through the world. Every modern action, the food sectors have perhaps the most elevated utilization of water and probably the greatest manufacturer of waste material. The dairy production is a case in this regard division. Dairy production is another significant industry in India, along with India positions foremost amongst them, most extreme significant milk delivering country. The dairy production is another significant wellspring of waste generation. The dairy industry include preparing of crude milk into items ,for example, milk, yogurt, cheese etc. and produces lot of wastewater which contains very huge combination of organic substances as, proteins, carbohydrates as well as lipids. Hence, it is expected to give required treatment before release into the environment. The treatment generally classified as aerobic and anaerobic treatment. Huge convergence of pollutants as far as amount and nature of liquid, solids, and gaseous pollutants shows harmful effects on flora and fauna as well as several regions on environment. Untreated industrial waste (lube and oil) causes biologic harms in favour of oceanic life forms, place, creature, as well as similarly, mutagenic and carcinogenic for individual. They release as of various origin to form a film on water surface to facilitate diminish dissolved oxygen level in the water. The goal of this examination is to find out the capacity of adsorbent, which is Orange peels powder as a low cost adsorbent in expelling pollution from wastewater. It includes the portrayal of adsorbent and the recital investigation of the adsorbent.

Adsorption is an exterior occurrence. The process of devotion regarding effluents particulate in distinction to liquid directed towards outside about concerning with adsorbent. The application of adsorption takes place commonly accompanied in the process of batch application as well as column application.

II. OBJECTIVES OF THE STUDY

- To check the feasibility of use of Orange peels powder as a low cost adsorbent for dairy waste water.
- Utilization of low cost as well as minimally accessible adsorbent resources which are nearby available.

- To establish different constraint of processed and unprocessed dairy effluent like, COD, BOD, TDS, TS and turbidity.
- To reclaim the waste water used for different worth for example, farming, cleaning drains, maintenance and cultivation.

III. MATERIAL AND METHODOLOGY

a)Materials used:

Orange peels powder:Latest investigation has shown that orange peel waste is a possibly important source that can be formed into high worth products, for example, such as methane. Orange peels which manage the subsequent parameters in the industrial waste water, for example, pH, COD, TSS (Total suspended Solids), TDS (Total suspended Solids), Chloride, Volatile acidity, Sulphate and total nitrogen, nitrate and nitrite, total phosphorous. Exceptionally extremely coloured industrial waste water is a genuine natural issue as it truly stains waterways as just as blocking daylight for photosynthesizing plant species in the water. Orange peels might be utilized to expel acid dyes from industrial runoff. The orange peels contains the 16.9 % of soluble sugars, 3.75 % of starch, 1.95 % of fats,10.5 % of hemicelluloses along with 6.50 % of proteins”[4].



Fig.1: Orange peels and dried orange peel powder

b)Preparation of orange peels powder:

Orange peels were cut into small pieces, wash down using distil water for expulsion of impurities from their surface and they were dried out under sun light. Then, they are kept in an oven for 4 hours at 100° C to expel extra moisture. Afterwards, orange peels were displaced, composed and crushed out to fine powder. Then powdered orange peels were sieved through sieve of size 300 microns to acquire uniform size for utilization[6].

c) Experimental setup:

For Batch experimentation studies jar-test apparatus has been used.

1. Jar test is the most broadly utilized trial strategies for coagulation-flocculation. The tests were done in sections, viz. coagulation at different time and coagulation at different dosages.
2. Six jars of 1L capacity were utilized for each part of the investigations to coagulate sample of dairy waste water utilizing low cost adsorbents.
3. By accommodating a series of six numbers of jars along with six spindles steel paddles are used for conducting batch experiment.
4. The sample was blended uniformly, before conducting the jar test experiment. At that point, for expressing initial concentration, the sample have to be estimated for pH, COD, BOD, TDS, TS along with turbidity.
5. By varying rotation speed along with use of different amount of adsorbents were included in the beakers for experimentation.




Fig.2: Schematic diagram of Jar test apparatus

d) Collection and analysis of samples:

Investigation of Waste Water Characterization Variation in groupings of certain parameters for the waste water samples from Dairy waste water sources. The water portrayal factors like COD, BOD, BOD, TDS, TS as well as Turbidity. The initial values for COD, BOD, BOD, TDS, TS and turbidity are 790mg/L, 530mg/L, 1803mg/L, 2532mg/L and 1026 NTU respectively. This investigation done with batch experiments which are concerning with rapid mixing at the rotational speed of 150rpm along with slow mixing towards rotational speed of 30 rpm meant for improving flocculation method as well as sedimentation for a period of 60 minutes.

IV. RESULTS AND DISCUSSIONS

a) Impact of Orange Peels Powder:

This might be remarked by Fig.3 for dosage about 120g/L of Orange Peels powder, concentration of COD, BOD, TDS, TS and turbidity variations in dairy waste water diminishes, beyond which they reached a steady state specification. Further, an ideal dose, that is related with expulsion of residuals such as COD,BOD, TDS,TS along with turbidity prevailed for the dairy waste water are exist as 60.83 mg/L, 53.742 mg/L, 169.482 mg/L, 105.078 mg/L and 126.711 NTU respectively. The percentage contraction in accumulation for expulsion regarding COD, BOD, TDS , TS along with turbidity for aOrange Peels powder measurements of 120g/L was 92.3%, 89.86%, 90.6%, 95.85% and 87.65% respectively.




Fig.3: Impact of Orange peels powder dosage

b) Impact of Rapid Mixing Contact Time:

Fig.4 reveals the impact of Rapid mixing contact time for expulsion of COD, BOD, TDS, TS and turbidity variation in dairy waste water with a dosage of 120g/L and also among 30 min. of rapid mixing contact time, accumulation for expulsion regarding COD, BOD, TDS, TS along with turbidity, further that they reaches a steady state condition. For about 30 min. of rapid mixing contact time, percentage contraction in concentration of COD, BOD, TDS, TS and turbidity was85.5%, 83.9%, 83.6%, 88.64% and 81.82% respectively. Further, an ideal Rapid mixing contact time, that is related with removal of residuals such as COD, BOD, TDS , TS along with turbidity acquired for a dairy waste water were 114.55 mg/L, 85.33 mg/L, 295.692mg/L, 287.635mg/L and 186.526 NTU respectively.




Fig.4: Impact of Rapid Mixing Contact Time

c) Impact of Slow Mixing Contact Time:

This might be remarked by Fig.5 about 75 min. of slow mixing contact time, the accumulation of expulsion regarding COD, BOD, TDS , TS along with turbidity diminishes and beyond which they arrived at a steady state condition. Further, an ideal slow mixing contact time that is subsequent with removal of residuals like COD, BOD, TDS, TS along with turbidity prevailed for the dairy waste water were79.79 mg/L, 60.208 mg/L , 247.011 mg/L, 318.778 mg/L

and 124.864 NTU respectively. In this manner, maximum expulsion of COD, BOD, TDS, TS along with turbidity is accomplished with 75 min. of slow mixing contact time was 89.9%, 88.64%, 86.3%, 87.41% and 87.83% respectively.




Fig.5: Impact of Slow Mixing Contact Time

VI. CONCLUSION

The treatment of dairy waste water was analysed by utilizing Orange Peels powder as a low cost adsorbent. Depending upon the performance evaluation of investigation, the subsequent conclusions are summarized as below:

- In the current examination, demonstrations were accompanied to determine the appropriateness of Orange peels powder as a low cost adsorbent for the evacuation of COD, BOD, TDS, TS along with turbidity in treatment of dairy waste water along with varying dose of adsorbents, contrasting Rapid mixing contact time along with slow mixing contact time.
- For adsorption (Orange Peels powder), the results indicated that maximum percentage removal efficiency at an ideal dose about 120 g/L, ideal rapid mixing contact time about 30 min. along with ideal slow mixing contact time about 75 min.
- By analysis we initiated that, the Orange Peels powder has maximum percentage removal efficiency for residuals like COD, BOD, TDS, TS along with turbidity. With the use of low cost adsorbent, the polluting influences from dairy waste water can be evacuated all the more effectively.

REFERENCES

- [1] ChidanandPatil, Ms. Manika Huger, "Treatment of dairy wastewater by natural coagulants", ISSN: 2395-0056, Volume-2, Issue-4, 2016
- [2] Divya K S, Dr. Syed Ariff V Vaishnavi, SadiyaBanu A. S, G. Swetha, Ravi Kiran S, "Experimental study on the Treatment of dairy waste water using low cost Natural Adsorbents", Volume-6, Issue-6, 2019
- [3] Oyebola O. Olabinjo, Agboola S. Ogunlowo, Olabode O. Ajayi, Ayoola P. Olalusi, "Analysis of physical and chemical composition of Sweet orange (Citrus sinensis) peels", ISSN: 2456-1878, Volume-2, Issue-4, Aug-2017
- [4] P. Sasirekha, V. Mutheeswari, S. Sivapackiam, S. Soundharya, J. Ragheljebamariyal, "Treatment of industrial waste water by using Orange peels & Fish Scales", ISSN: 2321-0613, Volume 5, Issue-01, 2017
- [5] Ronke Ruth Ayanunna, Saidat Olanipekun Giwa, Abdulwahab Giwa, "Coagulation-Flocculation Treatment of Industrial waste water using Tamarind seed powder", Volume-9, No-05, pp 771-780, 2016
- [6] Sivakumar D, Shankar D, JanakiSundaram S, "Treating dairy industry effluent using orange peel powder", ISSN: 0974-2115, Volume 9, Issue-3, 2016
- [7] Thuraiya Mahir Al Khusaibi, Joefel Jessica Dumarman, M. Geetha Devi, L. Nageswara Rao and S. Feroz, "Treatment of Dairy Wastewater using Orange and Banana Peels", ISSN: 0975-7384, 2015