



e-ISSN: 2319-8753 | p-ISSN: 2320-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 4, April 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.512

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com



An Experimental Analysis of Integrated Double Slope Double Basin Solar Still Water Heater

Udhayam M¹, Sathish S¹, Sujaai R¹, Sahil Charly C¹, Maheswari K S²

U.G. Student, Department of Mechanical Engineering, Francis Xavier Engineering College, Tirunelveli, Tamilnadu, India¹

Professor, Department of Mechanical Engineering, Francis Xavier Engineering College, Tirunelveli, Tamilnadu, India²

ABSTRACT: In our project, we are using Double Basin Double slope Solar still. So that we are going to fabricate the frame work by means of wood for both lower basin and upper basin is of size 900mm×900mm×300mm and 900mm×600mm×300mm are used. Here the saline water is preheated by passing the saline water into the solar pond and at the other end the hot saline water can be collected. Already be know that wood is good insulator and the heat transfer rate of wood is also too low. Thermal conductivity of wood is 0.04 to 0.12 W/m K. Slope work is carried out by glass sheets in which the upper slope glass having thickness of 5mm and lower slope glass with thickness of 3mm. Inner surface of the lower basin is made up of mild steel sheet metal coated with FRP black paint. Upper basin is fully made up of glass as a stepped basin because of penetration of solar energy to the lower basin. Near the edges of the glass slope, there is a collector placed in all the edges of the slopes in which the pure fresh water is collected and transferred to the solar water heater through tubes. Then the collected fresh water is again passed through the solar water heater which is made up of copper coil to heat the fresh water. This is the fabrication of our solar still.

KEYWORDS: Solar water heater, solar pond, Thermocouple, Stepped glass basin, Solar desalination.

I. INTRODUCTION

People can remain a live for a several days without food, but cannot live for more than a week without water. We have all heard it said that we should drink a minimum of 8 glasses of water each day. However, drinking the minimum will only help maintain a minimum level of health. Our body will use at least 8 glasses of water each day under normal, relatively passive activity to maintain basic bodily functions like digestion, temperature control, joint lubrication, and skin hydration. Each time we exhale, blink our eyes, or make any kind of movement at all, we use up some of the available water in our system. This natural process is copied on a small scale in basin type solar stills. [Bendfeld, J., Broker and Carvallo, P.C.M., 1998].

Today fresh water demand is increasing continuously because of the industrial development, intensified agriculture, improvement in standard of life and increase in the world population. Only 3% of total water is potable but this amount is also evenly not distributed over the earth. Lack of fresh water is a prime factor in inhibiting regional/economical development. Often water sources are brackish/containing harmful bacteria, therefore cannot be used directly for drinking purpose. The oceans constitute an inexhaustible source of water but are unfit for human consumption due to their salt content in the range of 3% to 5%. In addition, there are many coastal locations where seawater is abundant but potable water is not available.

Therefore it is an urgent need for clean and pure drinking water in many countries. In order to solve this problem, some new drinking water sources should be discovered and new water desalination techniques be developed.

In recent years desalination of water has been one of the most important technological work undertaken in many countries. The fossil fuel burning water desalination techniques are in use since long back. These systems range up to 10 ton/day capacity. The main water desalination or purification methods are distillation, reverse osmosis and electro dialysis. Cleaner energies such as natural gas, solar thermal power and photovoltaic technology must be integrated with desalination technology. For bigger systems, reverse osmosis and electro dialysis are more economical, but for smaller ones, simple solar stills could be preferred because of their low costs and less floor area.

II. RELATED WORK

On deserts and islands where underground water is not readily available and cost of water shipping is high, it is worthwhile to produce potable water from saline water using solar energy. Utilization of solar energy for water



desalination is becoming more attractive as the cost of conventional fuels/energy is continuously increasing. Solar desalination is particularly important for locations where solar intensity is high and there is a scarcity of fresh water. Solar desalination is a process where solar energy is utilized to distill the fresh water from saline/brackish water for drinking purposes, in charging of the batteries, research laboratories and medical appliances etc. The combination of solar energy with desalination processes can be classified into two main categories: 100% solar driven desalination plants or partial solar powered desalination plants. Solar plants could be designed to operate in a fully automatic fashion in the sense that when the sun rises, heat collection process is initiated automatically by a sensor measuring the solar radiation.

III. METHODOLOGY

The operating principle of a solar still used for water desalination involves phase change water vapour. It permits the separation of the water constituents into salts deposits and distilled water. In fact, the solar flow transmitted through the glass cover achieves the absorber, which in return emits thermal radiations, this fact heats water. Under the influence of heat, sea water evaporates successively leaving only water's molecules, a dissolved salt deposit and all other residues in seawater. The obtained vapour condenses and the distilled water streams on the interior face of the inclined slope glass put in drains which drives it into a stocking tank. The different heat fluxes intervening in the heat transfers which occur within the still become explicit by many physical phenomena. The various modes of transfer of the exchanged heat between the water and the glass are done by convection, by radiation and by evaporation. The still is a system which exchanges the heat with the outside through the glass by convection and bottom and side insulating walls are done by conduction and radiation. In what follows we determine the heat transfer principle inside and outside the still.

The Absorber: The water layer receives both by conduction and convection a heat flux from the absorber and transmits by conduction a flux to the insulator.

The Water: The Water yields by radiation the flux and by natural convection the flux, by evaporation during the change phase a flux, on the condensation surface (the interior glass of the still).

The Glass: From the inner side, the glass receives the flux by convection, by radiation and by evaporation. Consequently, from the inner side, the glass diffuses to the ambient air the equivalent sum of two flows.

The Insulator: The insulator receives by conduction a flux from the absorber and can yield to the outside and respectively by radiation and convection.


IV. ANALYSIS OF WATER

S.No	Chemical Property	Saline Water	Distilled Water
1	pH	7.49	6.75
2	Alkalinity	430 mg/l	16 mg/l
3	Total Hardness	640 mg/l	6 mg/l
4	E. Conductivity	34800 µmhos/cm	64 µmhos/cm
5	Chlorides	17500 mg/l	10 mg/l

V. EXPERIMENTAL PLAN

Experiments are planned to conduct at the Mechanical Engineering Department block of FXEC, Tirunelveli during the months February and March. Experiments are conducted on the days which are selected in such a way that there should

have clear sky conditions. The cloudy days present in these months are excluded. The experiments are conducted for different water depth at different time intervals of different days of February and March. For these experiments the condition for best performance of solar still is obtained in terms of yield. The selected days for conducting the experiments have similar pattern of global radiation.



VI. EXPERIMENTAL RESULTS

The model presented can be used to study the effect of solar radiation, ambient temperature, wind speed, glass cover temperature, transparent cover properties, etc. on the distillate output. Some of the conclusions are as follows:

- The still output (productivity) is strong function of solar radiation on a horizontal surface. The distillate output increase linearly with solar insolation for a given ambient temperature.
- The increasing of temperature difference between the saline water and the glass leads to a better production.
- Although fabrication of the double basin increased the manufacturing cost a little, high yield of the distillate made it a better one.
- The output was high at the lower water depth of 1 cm for double basin double slope solar stills.
- A maximum of 6.852 l/0.9 m² day was obtained at 1 cm water depth by the simple double basin double slope solar still. But, the double basin double slope solar still coupled with Solar water heater gave 4.165 l/0.9 m² day.
- The increasing of ambient temperature decrease the heat loss from solar still, resulting in higher distillation rate.

VII. FACTORS AFFECTING SOLAR STILL

For using solar energy to distilled brackish and sea water to produce fresh water, there are many parameters affecting the productivity. These can be summarized as:

- Solar radiation

- Ambient air temperature
- Wind velocity
- Depth of the brine in the basin
- Cover material and its shape
- Ground and surrounding losses

VIII. CONCLUSION

- Solar stills are used in cases where rain, piped, or well water is impractical, such as in remote homes or during power outages.
- In subtropical hurricane target areas that can lose power for days, solar distillation can provide an alternative source of clean water.
- Today, seawater and brackish water desalination is a subject of concern of many researchers all over the world.

IX. ADVANTAGES

A typical size solar distiller can produce 6 litres per day during the summer, dropping to 3 litres in the winter season. It should be out in the sun, it takes 10 square feet (0.9 square meters) and it weighs 30kg. The advantages are,

- Free of charge sun energy (during sunlight it eliminates 500 Watt electric consumption per one hour of sunlight)
- There are no moving parts; it is therefore reliable and almost maintenance free (cleaning is required though)
- Water taste is claimed to be better since the device act as a Solar Water Vaporizer and it doesn't boil the water (resembling rain water)
- Neutral pH is claimed (like rainwater), not like the not neutral pH of steamed distilled water
- The recourse to the desalination by distillation using solar energy represents an appreciable element of the water resource and constitutes a realizable, simple, profitable, operational solution technically

X. RECOMMENDATIONS

To increase the productivity we must increase the temperature difference between the water and glass cover. In order to obtain a higher temperature difference, we recommend:

- A preliminary heating of the brine before bringing it into the solar still.
- A cooling of the glass by using a fan working with an electrical energy which is produced by a photovoltaic system.
- A cooling of the outer side of the glass by flowing first the water through the glass, before water it into the solar still.
- And the use of glass having blades at its external side, in order to increase heat losses by convection, leading to cooling the inner side of the glass.

REFERENCES

- [1] KalidasMurugavel, K., et al., Progresses in Improving the Effectiveness of the Single Basin Passive Solar Still, Desalination, 220 (2008), 677-686
- [2] Joe Patrick Gnanaraj S., et al., Enhancing the design to optimize the performance of double basin solar still, Desalination, 411 (2017), 112-123
- [3] 112-123
- [4] Malik, M. A. S., et al., Solar Distillation, Pergamon press, Oxford, UK, 1982
- [5] Singh, H. N., Tiwari, G. N., Monthly Performance of Passive and Active Solar Stills for Different Indian Climatic Conditions, Desalination, 168 (2004), 145-150
- [6] Velmurugan, V., et al., Productivity Enhancement of Stepped Solar Still – Performance Analysis Thermal Science, 12 (2008), 153-163
- [7] Feilizadeh, M., et al., A New Radiation Model for a Single-Slope Solar Still, Desalination, 262 (2010), 166-173
- [8] Madhlopa, A., Johnstone, C. M., Computation of Solar Radiation Distribution in a Solar Still with Internal and External Reflectors, Solar Energy, 85 (2011), 217-233



- [9] Arjunan, T. V., et al., Effect of Sponge Liner on the Internal Heat Transfer Coefficients in a Simple Solar Still, Desalination and Water Treatment, 29 (2011), 271-284
- [10] KalidasaMurugavel, K., et al., Single Basin Double Slope Solar Still with Minimum Basin Depth and Energy Storing Materials, Applied Energy, 87 (2010), 514-523
- [11] Eduardo Rubio, Fernandez, J. L., Porta-Gandara, M. A., Modeling Thermal Asymmetries in Double Slope Solar Stills, Renewable Energy, 29 (2004), 895-906
- [12] KalidasaMurugavel, K., Srithar, K., Performance Study on Basin Type Double Slope Solar Still with Different Wick Materials and Minimum Mass of Water, Renewable Energy, 36 (2011), 612-620
- [13] Hiroshi, T., A Theoretical Analysis of Basin Type Solar Still with Flat Plate External Bottom Reflector, Desalination, 279 (2011), 243-251
- [14] KalidasaMurugavel, K., et al., Experimental Analysis on Variation of Transmittance of Different Thickness Window Glasses at Different Solar Insolation Conditions, 3rd BSME-ASME International Conference on Thermal Engineering, Dhaka, Bangladesh, B. A. 048 (2006), <http://bsmeicte2012.iutoicdhaka.edu/proceedings/3rd-bsme-asme-icte-2006/html/indexret.htm>
- [15] Kabeel, A. E., El-Agouz, S. A., Review of Researches and Developments on Solar stills, Desalination, 276 (2011), 1-12



INNO  **SPACE**
SJIF Scientific Journal Impact Factor

**Impact Factor:
7.512**

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details