



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 8, August 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.569

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

A Case Study on Utilisation of Marble and Granite Slurry to Improve the Properties of Clay Bricks

Anand Lahary¹, Anirudh Bhardwaj², Bhupendra Singh Solanki³, Mukesh Saini⁴

B.Tech. Scholar, Department of Civil Engineering, Arya College of Engineering and Research Centre, Jaipur, India¹⁻³
Assistant Professor, Department of Civil Engineering, Arya College of Engineering and Research Centre, Jaipur, India⁴

ABSTRACT: Marble and Granite sawing powder wastes is one of the main international environmental problems. As a result of environmental and monetary considerations, there's a developing call for for wastes to be reused or recycled. Therefore, this paintings intends to speak about the opportunities of the usage of marble and granite sawing wastes as opportunity uncooked substances withinside the manufacturing of bricks. Samples of marble and granite wastes have been accumulated from organizations which might be close by located . Clay combination and fired business bricks have been accumulated from a brick chamber. A huge unfold want is being felt to make this enterprise environmentally sustainable. It proposes the usage of waste marble and granite slurry in clay bricks. In this look at I located that round 10-15 % alternative of clay with granite slurry and marble slurry offers most compressive electricity. After 15%, the compressive electricity begins offevolved reducing in each granite and sand alternative. Whereas water absorption found for each alternative granite and marble decreases as much as 10% that will increase. Density of brick after alternative of granite constantly decreases and after alternative marble constantly will increase.

KEYWORDS: Marble , Brick , Clay , Graniti , Slurry.

I. INTRODUCTION

Today, one can not believe a production on the exclusion of bricks and such is the significance that bricks have assumed as a constructing cloth. In any country, production money owed for approximately 60 in keeping with cent of the plan outlays everywhere in the world. Out of this, bricks account for greater than 40 percent. Brick production has end up vital withinside the context of imparting refuge that's an vital fundamental human want subsequent to food and clothing. Besides refuge, bricks are getting used withinside the improvement of infrastructure inclusive of production of dams, canals and business homes which might be wished for development withinside the ranges of dwelling of the human beings. In the economic market, brick remains a main wall cladding cloth. Brick making is a conventional unorganized enterprise, normally limited to rural and semi city areas. It is one in every of the most important employment producing industries, using hundreds of thousands of workers. Brick, being one of the oldest constructing substances is considerably used at gift as a first-rate enter in production due to its durability, electricity, reliability, low value and smooth availability. Brick enterprise, which is basically a labour in depth enterprise, offers employment possibility to a tremendous paintings pressure of round numerous hundreds of thousands of human beings in India.

Brick is one of the vital substances for production enterprise. The traditional approach of producing bricks has left this vital cloth aloof in advancement. The infrastructure inclusive of homes for housing and enterprise, and the centers for managing water and sewage would require huge quantities of production substances. Since the huge call for has been positioned on constructing cloth enterprise mainly withinside the final decade because of the growing population, there's a mismatch among call for-deliver control of those substances. Hence to satisfy the constantly growing call for, researchers try to layout and broaden sustainable opportunity answers for the development cloth. The growth withinside the recognition of the usage of environmental pleasant, low value and light-weight production substances in constructing enterprise has added approximately the want to analyze how this could be accomplished through reaping benefits to the surroundings in addition to preserving the cloth necessities affirmed withinside the standards. Brick is one of the maximum accommodating masonry gadgets as a constructing cloth because of its residences. Attempts were made to include waste withinside the manufacturing of bricks, for instance, the usage of paper processing residues, cigarette butts, fly ash, fabric effluent remedy plant (ETP) sludge, polystyrene foam, plastic fiber straw, polystyrene

fabric, cotton waste, dried sludge accumulated from business wastewater remedy plant, rice husk ash, granulated powder combinations have been compressed in a hydraulic press, and the inexperienced our bodies have been dried earlier than firing at 1100°C. Brick making is as historical as human civilization itself. Great architectural wonders and the immortal monuments constructed withinside the vintage beyond have been constructed with bricks except stones and mortar. Ever when you consider that guy found out the housing as fundamental want, he commenced the usage of bricks in numerous paperwork like inexperienced bricks, solar dried bricks and the fired bricks.

II. LITERATURE REVIEW

Ramkumarand studied at the manufacture of bricks from the development wastes of brick particles, quarry dirt and cement. The quarry dirt is used to optimize the not unusualplace blend to obtain the goal electricity through changing the particles with 5%, 10%, 15% and 20 % of quarry dirt. These bricks fulfill the norms and necessities of a everyday brick as in keeping with IS code provisions. Their venture paintings simply tried to reuse the development wastes withinside the production enterprise

Nithiya investigated on production of brick made with one-of-a-kind recyclable substances like coconut fibre, granite waste and egg shell powder. The percent of waste delivered is 0%, three%, 6%, 9%, 12%, and 15% (for all three forms of wastes). These bricks are sufficiently difficult at 4%, 8% and 12% proportions. The percent of granite waste will increase with growth withinside the hardness of the brick. The writer opined that the compression electricity is expanded as much as 6% of granite waste past that it regularly decreases

Chiara Coletti experimented at the brick made through the usage of ceramic sludge from the enterprise and aiming to discover an opportunity green additive to provide “eco-bricks” characterised through appropriate mechanical and aesthetic residences and durability. For those bricks, forms of bricks are produced through a newly designed brick acquired from the herbal clay, with the addition of ceramic sludge in region of the historically used siliceous sand. Based at the consequences, the writer concluded that bricks produced with delivered ceramic sludge can alternative nicely to the conventional bricks, enjoyable aesthetic necessities and preserving enough mechanical residences. The fundamental downside is that a brand new cloth used on this studies has now no longer been replied to freeze thaw cycles, highlighting their capability vulnerability in bloodless climates.

Murugesan this studies well-knownshows that marble sludge powder, a waste product from the industries as admixture for making bricks. In this venture, 2 hundred bricks are solid with partial alternative of marble sludge powder. The end result specializes in evaluation of residences of bricks to reap higher consequences. These bricks are examined at various proportions of marble sludge powder. Marble sludge dirt is surroundings pleasant that reduces the pollutants and forestalls the waste disposal.

Angel Daniel researched at the sawdust (49%) and plastic waste (49%) merchandise may be used as uncooked substances to create timber plastic composite (WPC) with 2% fusa bond for making the brick. The brick is made from in one-of-a-kind shapes (Hexagon, Rectangular, Octagon and Triangular) and of inner geometry holes are designed to growth sound absorption collectively with an development in structural electricity. The brick layout with the shape of triangular holes has the high-quality overall performance and which offers higher sound absorption.

Ahsan Habib his look at changed into carried out directly to decide the impact of the share of the soil and the stabilizers (inclusive of cement and stone dirt) on stabilized earth blocks durability. Adobe brick changed into organized with one-of-a-kind extent fractions of stone dirt various 5%, 10%, 15%, 20% and 25%. The end result has proven that the usage of stone dirt will increase the compressive electricity through 10% to 20 % respectively. The water absorption of the adobe (dredge soil and cement and stone dirt) additionally calculated which may be very comparable and barely modified the share of stone dirt. The writer concludes that the usage of stone dirt of (10 % to 20 %) with 5% of cement primarily based totally adobe complements the mechanical residences and optimization of the stone dirt is needed to get the high-quality overall performance.

Maneeth in his studies an strive has been made to provide bricks through the usage of waste plastic (PET bottles) in variety of 60% to 80% through weight of laterite quarry waste in molten form, which acts as a binder. When this molten plastic changed into now no longer enough for binding capacity, to triumph over this hassle a touch amount of 60/70 grade bitumen is delivered in a variety of 2% to 5% through weight of soil and this bitumen-plastic resin changed into combined with laterite quarry waste to fabricate bricks. Based at the assessments, the compressive

electricity for plastic-soil bricks with 70% plastic content material through weight of soil with the binder (bitumen) content material of 2% through weight of soil offers a compressive electricity of 8.16 N/mm² that's better than laterite stone (3.18 N/mm²) and has a lesser water absorption (0.9536%) than laterite stone (14.58%).

Swaminathan Dhanapandian. In his studies, aimed to signify and compare the opportunities of the usage of the granite and marble sawing wastes, generated through the method industries. Chemical assessments are accomplished for willpower of chemical composition, mineralogical and petrological analysis, particle size, plasticity, FTIR and Mossbauer measurements. As in keeping with the bodily assessments, bulk density, compressive electricity, flexural electricity are located to growth because of the addition of the granite and marble sawing wastes. Technological assessments also are carried out on wastes integrated brick specimens so that it will compare the suitability of addition of wastes withinside the manufacturing of bricks. From the consequences of technological assessments, the writer advised that granite and marble wastes may be integrated as much as 50% wt. into clay substances for the manufacturing of bricks.

III. ACKNOWLEDGEMENT

This is the place to admit that while there appears only author on the cover, this work just as any other, is a product of the interaction with and support during our thesis work, among them, first I express my gratitude to my guides Asst. prof. Vikas Yadav & Asst. prof. Mukesh Saini for their affection throughout guidance, advice and encouragement. Thanks to all my family members for their affection, care and encouragement. Special thanks to my college for giving me the invaluable knowledge. Above all I am thankful to almighty God for everything and all researchers whose research papers in this field have been referred for our study.

REFERENCES

- [1] Er. Ankur Kansal and Er. Sunil Kumar and Er. Vikram
- [2] Dr. Shailesh Chaudhary | Mr. Om Prakash Singh
- [3] S. DHANAPANDIANA* AND M. SHANTHIB
- [4] Kushwah RP Singh (2014). Engineering Utilization of Marble Slurry as Curing Aid. 437-444 Prof. (Dr.) Ishwar Chand Sharma, Prof. (Dr.) PBL Chaurasia (2014). Utilization of "Marble slurry" In Cement Concrete Replacing Fine Aggregate.
- [5] Ali A. Aliabdo, Abd Elmoaty M. Abd Elmoaty (2014). Re-use of waste marble dirt withinside the manufacturing of cement and concrete. *Construction and Building Materials*. 50 (2014) 28–41.
- [6] Ali A. (2014). Re-use of waste marble dirt withinside the manufacturing of cement and concrete. *Construction and Building Materials*. (50): 28-41.
- [7] Patel N., Raval A. and Pitroda J. (2013). Marble Waste: Opportunities for Development of Low Cost Concrete. *Global Research Analysis*.
- [8] Alaa A. Shakir, Ali Ahmed Mohammed (2013). Manufacturing of Bricks withinside the Past, withinside the Present and withinside the Future: A kingdom of the Art Review. *International Journal of Advances in Applied Sciences (IJAAS)* Vol. 2, No. three, September 2013, pp. 145-156 ISSN: 2252-8814.
- [9] Demirel B. (2010). The impact of the usage of waste marble dirt as high-quality sand at the mechanical residences of the concrete. *International Journal of the Physical Sciences*. 5(9): 1372-1380.
- [10] BIS. (1963). *Methods of Test for Aggregates for Concrete*, IS: 2386. New Delhi, India: BIS.
- [11] BIS. (1970). *Specification and Fine Aggregate from Natural Sources for Concrete*: IS 383. New Delhi, India: BIS.
- [12] CBRI. (n.d.). *Utilization of marble Dust in Brick Making*. Roorkee: CBRI.
- [13] Centre, M. M. (n.d.). *Utilization of Marble Dust in Tiles*. Jabalpur, M.P.: Macro Molecular Research Centre, Rani Durgawati University.



**Impact Factor:
7.569**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details