



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Special Issue 2, December 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.569

An Energy Harvested Cognitive Network Combining Co Operative Sensing and Attack Detection

A.Rubithra

Assistant Professor, Department of Computer Science, Parvathy's Arts and Science College, Dindigul,
TamilNadu, India

ABSTRACT: Cognitive Wireless Sensor Network (CWSN) is an incorporating, coordinate cognitive highlights in conventional Wireless Sensor Networks (WSNs) to ease fundamental issues like spectrum occupancy. Security threats are very high in cognitive wireless sensor network, since these sort of networks oversee vital applications and data. Primary User Emulation (PUE) attack is the most deliberate precise attack getting from new cognitive features. The prospective scheme of cooperative spectrum sensing in an energy efficient which can choose a representative sensor hub set in Cognitive Radio Sensor Network (CRSN) under given imperatives. Based on the spectrum recognition data is given by the favored delegate hubs, the evident of DS theory is utilized to decide the action conditions of LU while keeping a similar spectrum detecting precision. From the simulation results, it is found that the proposed plan can promote the detection precision and diminish the energy utilization, as it is effectively lessens the quantity of sensor nodes which perform range detecting and related communication overhead among the hubs.

KEYWORDS: Cognitive Wireless Sensor Network, Spectrum, Primary User Emulation attack

I. INTRODUCTION

Intellectual radio[1] is the key empowering innovation that permits upcoming generation in communication networks, additionally referred to as Dynamic Spectrum Access (DSA) organizations to the suitable spectrum more efficiently in an opportunistic model without meddling with the essential users. It is characterized as a radio[1] which will diminish its transmitter parameters that consists of the communication with the environment during which it works. It contradicts from typical radio devices, where a cognitive radio[1,2] can equip the users with intellectual efficiency and reconfigurability. The cognitive capability alludes to the power to detect and assemble data from the nearby surrounding including data about transmission frequency, bandwidth, power, modulation etc. With this potential, secondary users can analyze the best feasible range.

Reconfigurability[3] indicates the power of quickly adjust the operational boundaries consistent with the detected data to perceive the ideal exhibition. By employing, the range in an entrepreneurial model, cognitive radio[13] empowers the secondary users to detect which segment range are accessible, decide the best available channel organize range access with different users and empty the channel when an essential users get back the range usage right.

II. RELATED WORK

In [4] the authors presented about a Dense Cognitive Vehicular Network (DCVN). To implement a client correlation and double threshold based on cooperative spectrum sensing algorithm to accomplish a trade-off between detecting execution and framework overhead.

In [3] the authors explored a client determination calculation established on dependability and correlation of hybrid users, which yields high cooperative spectrum detecting execution by ideal users. Simulation and analysis results [3] exhibit that portability increments spatial variety and improves the detection execution with in the Primary Protected Region (PPR).

In [2] the authors have proposed a range detecting proposition established on spatial-temporal convenience detection. To validate the hazard and legitimacy of the strategy. This work proposed a more genuine 2-D Cognitive Wireless

Sensor Network(CWSN) topology model [2] in which the essential signal transmitter is shared in a given sensing range randomly at every emphasis.

In [6] the authors proposed a D-S hypothesis cooperative range detecting calculations, which accepts all cognitive clients are authentic and don't consider malicious client existing.

In [7] the authors assert a powerful CSS pattern dependent on D-S theory and adherence degree estimation. It is accomplished in four consecutive steps, which are Basic Probability Assignment, adherence degree calculation, determination and change of BPA and succession by D-S rule, individually.

In [9] the author probes that the matter of spatial-temporal opportunity exposure for range heterogeneous cognitive radio organizations. To detect a given time Secondary Users(SUs) at unique areas may detect diverse range access opportunities.

III. PROPOSED WORK

To detect the activity conditions of Licensed Users(LUs) has tremendous importance for the use of finite radio spectrum. The licensed users can identify meticulously, when it is in activity states. However, the spectrum recognize constantly has some unacceptable detection of a LU state and it will bring about enlarged communication overhead, additionally network energy utilization and hub suddenly passed. To manage with such issues, the proficient energy is helpful in spectrum detecting plan[11] is prospective which can decide an agent sensor hub set in Cognitive Radio Sensor Network(CRSN) under given requirements. An agent hub set which abide of the nodes can give gains to identify the LU state is a subset of the hub network conveyed. The spectrum detects the data, it is given by the preferred representative hub. The proof of DS theory is utilized to determine the activity conditions of LU while keeping a similar range detecting precision if worse.

VI. MODULE DESCRIPTION NETWORK MODEL & ASSUMPTION

It manages a zone where a certain range is shared by primary and CR clients. The spectrum is partitioned into $|p|$ non overlapping channels. There are $|J|$ essential clients nearby and $|I|$ CR clients. While essential clients are assumed to be fixed, CR clients can be portable. The spectrum sharing[14,15] is actualized by the opportunistic access paradigm. Consequently, an essential clients access their allocated channels. Whenever they need without any explicit warnings to CR clients. We expect that the essential clients have a moderately low difference in activity(time of action and idleness in the scope of seconds or minutes). CR clients are just permitted to utilize the channels in the wake of approving these.

Validation alludes to the way towards guaranteeing that no essential transmission is really occurring on the separate channel. This is attained by the range detecting which the CR clients approved channels with a certain probability of detection with a specific periodicity,[16] i.e., Each T sense time the current utilized channels should be approved once more. Mean the spectrum detecting consequence of every CR client I by $V_i = \{v_1, v_2, \dots, v_{p_i}\}$ with $p_i = |V_i| \leq P$ indicating the total number of accessible channels for CR client i.

NEIGHBOR NODE DISCOVERY: At a given time, the secondary user can sense a limited portion of the spectrum and create the accessible channel list In CRAHNS, the two secondary users are supposed to be 1-hop neighbors in the event that they are within the transmission scope of one another. A hub can communicate[17,18] with its 1-hop neighbors when they are tuned to the similar.

For the i^{th} secondary user signified by SU_i , the set of inactive channels detected by SU_i is $V_i = \{v_1, v_2, \dots, v_p\}$, while p is the absolute number of inactive channels identified by SU_i . We expect that the portability of hub is moderate and the channel accessibility at every hub changes at a relatively low rate, such that the network topology doesn't change during the group of development process. Hubs are thought to be GPS equipped to empower geological position mindfulness and time synchronization among hubs. The period of reference point is given by the Fusion Centre.

The Fusion centre generates an arbitrary back off time. If an impact is recognized during this time possibly a primary user abruptly reoccupies the channel or another cluster's beacon comes, the FC won't convey the signal and tune the CR to rehash this cycle.

THE REPRESENTATIVE NODES SELECTION: Prior to performing delegate hubs determination, We propose a hub separating strategy on the areas of sensor hubs. The proposed hub sifting strategy eliminates the hub which are

profoundly dormant and unwavering quality lower than a given limit. Filtering these hubs could reduce the computation loads in later advances and improve the last spectrum detecting precision.




Fig.1. The overview of the proposed cooperative spectrum sensing

Let S indicates the entire hub set in the network, the objective is to choose an appropriate delegate hubs from $S(s \leq S)$, with the goal that the territory of licensed user can make a decision about utilizing the spectrum detecting results from s . There are three basics however vital imperatives as follows, which can limit the upper bound of the number of selected hubs(s) in the subset.

$$s \leq S, Rel_j \geq \lambda, E_n^j \geq E_{\min}$$

Where $e_j R I$ is the node reliability j , $j_n E$ is the node residual energy, λ is the fixed reliability threshold and $\min E$ is the fixed minimum residual energy threshold.

ENERGY COST FUNCTION: In order to give an evaluation of the energy utilization of spectrum detecting. $T E$ is characterized as the total energy utilization[20]. It is made out of $s_j E$ and $t_j E$ that are the energy consumed by the j -th sensor in spectrum sensing and send detecting results to the sink node respectively.

Based on the definition, E_r can be defined as

$$E_T = \sum_{j=1}^n b_j (E_{sj} + E_{tj}) \quad \text{--- (1)}$$

$$\min E_T = \sum_{j=1}^n b_j (E_{sj} + E_{tj})$$

$$s.t. \sum_{j \in s} b_j \leq S$$

$$E_n^j \geq E_{\min}^j$$

$$Rel_j \geq \lambda$$

$$S = \{j | b_j = 1, j \in s\}$$

Likely, We will limit the total energy utilization while meeting the requirements. Hence, the advance target capacity can be determined as

--- (2)

Where $j b$ is a binary variable, i.e. 1 $j b$ indicates the hub j , s is chosen as one of the subset hubs and 0 $j b$. By solving the above Equation, the quantity of agent hubs can be

inferred then the total energy utilization can be incredibly decreased, which can ensure the exact range detection.

V. PERFORMANCE ANALYSIS

The arrangement of execution measurements utilized for contrasting proposed framework.

NETWORK DELAY: This execution metric is utilized to gauge the average end-to-end delay of information packet transmission. The end-to-end delay infers the average time taken between a packet at first sent by the source and finally, the ideal opportunity for effectively getting the message. Estimating this delay considers the lining and engendering deferral of the packets.




Fig.2.Delay analysis

NETWORK THROUGHPUT: The end-to-end network throughput gauges the quantity of packets per second acquired finally. Here, it is considered as an outer proportion of the protocol effectively.

SUCCESS RATE: The complete number of packets delivered at the destinations verses the total number of packets sent from the source.




Fig.3.Packet rate analysis

LATENCY: The average message idleness is characterized as the average measure of time between the initial of dispersing an information and its arrival at a hub keep on accepting the information. Hence, the inactivity estimates the execution time for the individual message.

ENERGY CONSUMPTION: The energy consumption[20] is the amount of utilized energy of all hubs in the organization, Where the pre-owned energy hub is the amount of the energy utilized for interaction as well as transmitting(Pt), receiving(Pr) and idling(Pi). Assuming every transmission dissipates an energy unit, the total energy utilization is identical to the total number of packets sent in the organization.




Fig.4.Energy analysis

NETWORK LIFETIME: It is deliberated as the time until message loss rate is over in a given threshold. The major plenary definition for the lifetime of the organization is “an ideal opportunity to arrange segment”. The network partition arises when there is a cut-set in the network. It will be presented as another measurement, which will utilize the energy variance.

Network lifetime = $E - (U + \sigma)$, where $U = \sum U_i / N$ --- (3)

E is the total initial energy at every hub (full battery charge), U_i is the average utilized energy, N is the complete number of hubs in the network and σ is expressed as

$$\sigma = (U_i - U) / 2N \quad \text{--- (4)}$$

All these metrics are computed utilizing their total average values at time t, the performance value is the average from 0 to t (seconds).

VI. CONCLUSION

In this prospective system, A cooperative range of the proficient energy in detecting scheme depends on the evident of DS hypothesis. It is accomplish in two stages, which are agent sensor hubs choice and decision making depend on proof of DS hypothesis. The proposed agent sensor hubs selection algorithm can productively deal with the hub in historical information to sieve, those idle and less dependable hubs. At that point, the evident of DS theory is received to ascertain the selected sensor hub credibility depend on their present data to choose which sensor hubs ought to be utilized to recognize the condition of an authorized users.

REFERENCES

- [1] Xiaoying Liu, Kechen Zheng and Kaikai Chi, “Cooperative Spectrum Sensing Optimization in Energy Harvesting Cognitive Radio Networks,” IEEE Transaction on Wireless Communications, vol.19, no.11, pp.7663-7676, Aug.2020.
- [2] Zhi zhang, Xianbin and Haixia Xu, “Sensing Nodes Selective Fusion Scheme of Spectrum Sensing in Spectrum-Heterogeneous Cognitive Wireless Sensor Networks,” IEEE sensors Journal, vol.18, no.1, pp.435-436, Jan.2018.
- [3] Meimei Duan, Zhiming Zeng and Caili Guo, “User selection for cooperative spectrum sensing in mobile cognitive radios,” IEEE Conference Publication, Nov.2015.
- [4] S.Zhu, C.Guo, C.Feng and X.Liu, “User correlation and double threshold based cooperative spectrum sensing in dense cognitive vehicular networks”, Proc.Int.Symp.Wireless Commun. System., pp.281-285, 2016.
- [5] Lu, L., Zhou, X., Onunkwo, U. et al. Ten years of research in spectrum sensing and sharing in cognitive radio Wireless Com Network 2012, 28 (2012). <https://doi.org/10.1186/1687-1499-2012-28>.
- [6] Y.Han, Q.Chen and J.Wang, “An Enhanced D-S Theory Cooperative Spectrum Sensing Algorithm against SSDF Attack,” 2012 IEEE 75th Vehicular Technology Conference (VTC Spring), Yokohama, 2012, pp.1-5, doi:10.1109/VETECS.2012.6240040.

- [7] Wang, J., Feng, S., Wu, Q. et al." A robust cooperative spectrum sensing scheme based on Dempster-Shafer theory and trustworthiness degree calculation in cognitive radio networks". EURASIP J. Adv. Signal process. 2014, 35 (2014). <https://doi.org/10.1186/1687-6180-2014-35>
- [8] P.Lee and P.Tsai, "Design and implementation of spatial-temporal spectrum sensing in cooperative cognitive radio sensor network," 2015 International SoC Design Conference(ISOCC), Gyungju,2015,pp.25-26, doi:10.1109/ISOCC.2015.7401647.
- [9] Q.Wu, G.Ding, J.Wang and Y.Yao, "Spatial-Temporal Opportunity Detection for Spectrum-Heterogeneous Cognitive Radio Networks : Two-Dimensional Sensing," IEEE Transactions on Wireless Communications, vol.12,no.2,pp.516-526,February2013,doi:10.1109/TWC.2012.122212.11638.
- [10] T.S.Syed and G.A.Safdar, "History-Assisted Energy-Efficient Spectrum Sensing for Infrastructure-Based Cognitive Radio Networks," IEEE Transactions on Vehicular Technology,vol.66,no.3,pp.2462-2473, March 2017,doi:10.1109/TVT.2016.2585763.
- [11] Qiao, Yu., Jin,Z., Yao,K., & Ma,T. (2018). "An energy- efficient cooperative spectrum sensing scheme based on D-S theory in cognitive radio sensor networks. ACM, Article, 58,6. <https://doi.org/10.1145/3164541.3164597>.
- [12] Min Song, Chunsheng Xin and Yanxiao Zhao, "Dynamic spectrum access: from cognitive radio to network radio," IEEE Wireless Communications, vol.19,no.1,pp.22-29, Feb.2012.
- [13] H.Chen, L.Liu, J.D.Matyjas and M.J.Medley, "Cooperative Routing for Underlay Cognitive Radio Networks Using Mutual-Information Accumulation,"IEEE Trans. On Wireless Commun.,vol.14,no.12,pp.7110-7122, Aug.2015.
- [14] S.Ping, A.Aijaz, O.Holland and A.ghvami, "SACRP: A Spectrum Aggregation-Based Cooperative Routing Protocol for Cognitive Radio Ad-Hoc Networks," IEEE Trans. On Commun., vol.63,no.6,pp.2015-2030, April.2015.
- [15] Xiaolong Ma, Fanzi Zeng and Jisheng Xu, " A novel energy efficient cooperative spectrum sensing scheme for cognitive radio sensor network based on evolutionary game,"IEEE Conference Publication, April.2015.
- [16] M.Li, S.Salinas, P.Li, X.Huang, Y.Fang and S.Glistic, "Optimal Scheduling for Multi-radio Multi-channel Multi-hop Cognitive Cellular Networks," IEEE Trans. on Mobile Computing,vol.14,no.1,pp.139-154,Jan.2015.
- [17] X.Jin, R .Zhang, J.Sun and Y.Zhang, "TIGHT: A Geographic Routing Protocol for Cognitive Radio Mobile AdHoc Networks," IEEE Trans.non Wireless Commun., vol.13,no.8,pp.4670-4681, Aug.2014.
- [18] M.Youssef, M.Ibrahim, M.Abdelatif, L.Chen and A.V.Vasibakos, "Routing Metrics of Cognitive Radio Networks: A Survey," IEEE Commun. Surveys &Tutorials,vol.16,no.1,pp.92-109, Feb2014
- [19] Y.Liu, L.Cai and X.Shen, "Spectrum-Aware Opportunistic Routing in Multi-Hop Cognitive Radio Networks,"IEEE Journal on Selected Areas in Communications,vol.30,no.10,pp.1958-1968, Dec.2012.



**Impact Factor:
7.569**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details