

e-ISSN: 2319-8753 | p-ISSN: 2320-6710

DIA

#### International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

000

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 7, July 2021

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 7.569

9940 572 462

6381 907 438

🚽 ijirset@gmail.com





| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

Volume 10, Issue 7, July 2021

DOI:10.15680/LJIRSET.2021.1007102

### **Deep Beam Analysis by Using FEM Program and ANSYS for ISO-Parametric Elements**

Manoj Agarkar<sup>1</sup>, Prof. Vishal Sapate<sup>2</sup>

P.G. Student, Department of Civil Engineering, G. H. Raisoni University, Amravati, Maharashtra, India<sup>1</sup>

Assistant Professor, Department of Civil Engineering, G. H. Raisoni University, Amravati, Maharashtra, India<sup>2</sup>

**ABSTRACT:** The structural bending members can be broadly divided into two regions. The first region is the Bernoulli regions (B- regions), where the strain distribution is linear There are several analytical tools available for analyzing of a deep beam . Deep beams are the members loaded on one face and supported on the opposite face so that compression struts can develop between the loads and the supports. It is recognized that the distribution of the strain across the section of deep beams is nonlinear and hence, these structural elements belong to the D-Regions. Traditionally, the D-Regions have been designed using empirical formulae or past experience. Recently, the Strut-and-Tie Model (STM) has been recognized as an effective tool for design of both B-and D- Regions but still method has not yet been widely implemented. There are various theories which consider the shear deformation effect, developed by the researchers for the analysis of deep beams. These theories have their own assumptions andlimitations.

There are many software packages available for the analysis of deep beams but we generally use SAP, ANSYS software. In finite element method many isoparametric elements are available such as triangular element, elements of serendipity family. In ANSYS it is modeled using Solid82 for 2D analysis.

In this project, results of deflection, flexural stress and shear stress of cantilever prismatic deep beams obtained using FEM program for isoparametric elements, and ANSYS 2D analysis are compared. A parametric study of deep rectangular beams for point load has been carried out.

**KEYWORDS:** Deep beam, aspect ratio, convergence study, discritisation, flexural stress

#### I. INTRODUCTION

Deep beams are defined as the members loaded on one face and supported on the opposite face so that compression struts can develop between the loads and the supports. In IS-456 (2000) clause 29, It is a fact that in the finite element analysis, as the number of elements increases the result comes closer to the true results. Continuous beams are considered as deep when the ratio L/D is less than 2.5. The effective span is defined as the center to center distance between the supports or 1.15 times the clear span whichever is less.

The use of reinforced concrete deep beam has become more prevalent in recent years. Deep beams often appear in form of transfer girders in high rise building as well as pile caps, foundation walls, water tanks, bins, folded plate roof structures, floor diaphragms, shear walls & brackets or corbels.

Plane section before bending remains plane after bending does not hold good for deep beams. The behavior of deep beam is significantly different from that of beams of more normal proportions, requiring special consideration in analysis, design and detailing of reinforcement. A deep beam is in fact a vertical plate subjected to loading in its own plane. The strain or stress distribution across the depth is no longer a straight line, and the variation is mainly dependent on the aspect ratio of the beam.

#### II. ANALYSIS OF BEEPBEAM

Analysis of deep rectangular beam subjected to point load. Comparative study of deep beams of various aspect ratios using FEM. Comparisons of the results obtained from FEM Program for is oparametric elements, and ANSYS 2D analysis



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

Volume 10, Issue 7, July 2021

DOI:10.15680/IJIRSET.2021.1007102

#### **III. DETAILS OF DEEPBEAM**

A cantilever beam with rectangular cross section (b × h) is subjected to concentrated load P at free end i.e. at x = L at surface z = -h/2 acting in the z direction. The origin of the beam is taken at fixed end i.e. at x = 0. The boundary conditions associated with cantilever beam are as given:




Figure 1: Discretization of a Cantilever Beam for analysis



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

Volume 10, Issue 7, July 2021

DOI:10.15680/IJIRSET.2021.1007102

#### IV. ANALYTICALRESULTS

The common type of isoparametric elements used for 2D elastic analysis are linear, parabolic (quadratic) and cubic elements with 4,8 and 12 nodes respectively. Thus, we have

	Table 1:	Abscissa and weigh	t coefficient	_
	п	ξi	Wi	
	(1)	(2)	(3)	1
	1	0.00000	2.00000	1
	2	±0.57735	1.00000	
	3	±0.77459	0.55555	
	5	0.00000	0.88888	
	4	±0.86113	0.34785	1
	4	±0.33998	0.65214	
		±0.90617	0.23692	1
	5	±0.53846	0.47862	
		0.00000	0.56886	
$\eta = +0.7$ $\eta = 0.0$ $\eta = -0.7$		• 7 η • 4 • 1	<ul> <li>8</li> <li>5 → 5</li> <li>2</li> </ul>	• 9 • 6 • 3
		$\xi = -0.77459$	$\xi = 0.0$ $\xi =$	+0.77459

Figure. 2: Figure 4.4: Location of points in the  $\xi - \eta$  plane for the element




Figure 3: Location of integration points for linear elements



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

DOI:10.15680/IJIRSET.2021.1007102

#### **ANSYS:**

ANSYS software is a powerful and flexible general-purpose finite element analysis and computational fluid dynamics package used for civil engineering. Mechanical engineering, electrical engineering, physis and chemistry simulations. Simulation tools including ANSYS Mechanical APDL, ANSYS CFX and ANSYS FLUENT, can also solve mechanical problems, static/dynamic structural analysis, heat transfer and fluid problem as well as acoustic and electromagnetic problems.




Figure4: PLANE82 Geometry

None, if KEYOPT (3) = 0, 1, or 2 THK - Thickness, if KEYOPT (3) = 3

PLANE82 Input Summary Nodes I, J, K, L, M, N, O, P Degrees ofFreedom UX, UY Real Constants

**Material Properties** 



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007102]

#### EX, EY, EZ, PRXY, PRYZ, PRXZ (or NUXY, NUYZ, NUXZ), ALPX, ALPY, ALPZ (or CTEX, CTEY, CTEZ or THSX, THSY, THSZ), DENS, GXY, DAMP Surface

Loads Pressures -

face 1 (J-I), face 2 (K-J), face 3 (I-K), face 4 (I-L) Body Loads Temperatur es --

T(I), T(J), T(K), T(L), T(M), T(N), T(O), T(P) **Fluences --**FL(I), FL(J), FL(K), FL(L), FL(M), FL(N), FL(O), FL(P)

#### **PLANE82 Output Data**

The solution output associated with the element is in two forms:

- Nodal displacements included in the overall nodal solution
- Additional elementoutput




Figure5 : PLANE82 Stress output.

#### Table 2 : Results of displacement and stresses for various L/D ratios

L/D	METHODS	DEFLECTION (mm)	σx(N/mm²)	τxz (N/mm²)
(1)	(2)	(3)	(4)	(5)
1.0				
	PROGRAM -LINEAR ELEMENT (4NODES)	-0.108	1.388	0.322
	ANSYS	-0.1115	1.3164	0.344
	EBT	-0.06399	0.9598	0.249




| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

#### DOI:10.15680/IJIRSET.2021.1007102

1.25	PROGRAM -LINEAR ELEMENT (4NODES)	-0.1802	1.42	0.3134
	ANSYS	-0.17965	1.519	0.333
	EBT	-0.124997	1.199	0.269


#### Graph showing deflection at the center line of the Beam



Program 4nodes

Figure6 : Deflection curve for L/D=1


#### Graph showing deflection at the center line of the Beam





| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569| || Volume 10, Issue 7, July 2021 || |DOI:10.15680/IJIRSET.2021.1007102|

Variation of Flexural Stress near the Support of the Beam



Program 4 nodes EBT

Variation of Flexural Stress near the Support of the Beam





Figure 8: Flexural Stress curve for L/D=1.25



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569| || Volume 10, Issue 7, July 2021 ||

DOI:10.15680/IJIRSET.2021.1007102


Variation of Shear Stress at the Mid-Span of the Beam



..... Ansys

Figure 9: Shear Stress for curve for L/D=1

Variation of Shear Stress at the Mid-Span of the Beam



.....Program 4 nodes






| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

DOI:10.15680/LJIRSET.2021.1007102

#### ANSYS SCREENSHOT SHOWING FINAL SOLUTION



#### **IV. CONCLUSION**

Deflection values given by EBT are much less than the values given by FEM program and ANSYS in case of rectangular deep beam.From the results given by FEM program, ANSYS it is found that the flexural stress distribution in deep beam is not linear as in case of slender beams, but EBT gives the flexural stress distribution as linear for deep beam.EBTgives the maximum shear stress at the centre line of the beam, but in deep beams the maximum shear stress is below the centre line of the beam.It is observed that the neutral axis moves downward.It is observed that though there is a variation in the results of deflection obtained from FEM Program and ANSYS, the agreement is veryclose.

#### REFERENCES

- 1. Wasulkar P., "Deep Beam Analysis Using Isoparametric Page No. 15 to 70 Elements-A Parametric Study", 2013-14.
- Wai Chi Mun, AhemadRivai, OmarBapokutty"Effects of elements on linear elastic stress analysis: A Finite Element Approach". IJRET: International Journal of Reaserch in Engineering and TechnologyVolume:2 Issue:10-Oct2013
- 3. Sudarshan D. and Patil S.S. (2013) "Analysis and Design of R. C. Deep Beams Using Code Provisions of Different Countries and Their Comparison", International Journal of Engineering and Advanced Technology (IJEAT) ISSN: 2249-8958, Volume-2, Issue-3.
- 4. GodboleP.N.(2013)"IntroductiontoFiniteElementMethod",PageNo.23-184I.K.PublishingHousePvt.
- Ltd.NewDelhiPage 5. NiranjanB.R. and Patil S. S. (2012), "Analysis of Deep Beam By Finite Element Method", IJMER VOL. 2, Issue6.
- 6. Yuwaraj M. GhugalAnd Rajneesh Sharma (2011) "A refined shear deformation theory for flexure of thick beams", Latin AmericanJournalof Solids and Strures Vo1.8183-195.
- Mahdy and O. Sh. Farhan, A. A. A1- Azzawi 1, A. H. (2010) "Finite element analysis of deep beams on nonlinear elastic foundations", Journal of the Serbian Society for Computational Mechanics, Vol. 4, No. 2, pp.13-42
- 8. MuziburRahman, ReazAhmed S. (2008) "Toward The Exact Elasticity Solution Of A Deep Beam With Guided Ends", Proceedings of the 4th BSME-ASME International Conference on Thermal Engineering 27-29 Dhaka, Bangladesh.
- 9. ANSYS 12 Manual (2007), "Element References", Ansysln.,
- Lawrence A, Soltis (1999) StructuralAualys Equations Chapter & MoodHandbook pg 463 U.S. Depositional of Agrieullure, Forest Products Laboratory, Madison, WI.





Impact Factor: 7.569





## INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com