

e-ISSN: 2319-8753 | p-ISSN: 2320-6710

DIA

# International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

000

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 7, July 2021

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 7.569

9940 572 462

6381 907 438

0

🚽 ijirset@gmail.com





| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.1007023|

# **Thermal Analysis of an Automobile Radiator**

Durga Prakash<sup>1</sup>, Maneesh C Srivastava<sup>2</sup>, Vivek Verma<sup>3</sup>

M.Tech [Automobile Engineering], ASET, Amity University, Lucknow Campus, Uttar Pradesh, India<sup>1</sup>

Department of Mechanical Engineering, ASET, Amity University, Lucknow Campus, Uttar Pradesh, India<sup>2,3</sup>

**ABSTRACT:** A radiator is a device which is used to transfer of thermal energy from the one medium to another medium in the automobile. They are mainly used in the constructed function in automobile and electronic devices .The radiator is a source of heat transfer to the environment ,it may be done by the transfer of heat from the engine of the automobile to the environment .As the name suggested the radiator transfer heavy amount of heat to the environment through convection. The automobile radiator's main function is to cool the engine bypassing the coolant through cylinder water jackets. In this paper, Solidworks is used to perform CFD analysis of a radiator at a different flow rate. In this report, the CFD analysis of a radiator is performed with normal water and coolant .Aluminium and brass is used for the construction of the automobile radiator.

KEYWORDS: Modeling; Analysis; Water; Coolant; Solidworks; Fins

#### **I.INTRODUCTION**

As we know that nowadays the speed and the performance of the vehicle is increasing as comparing to the older vehicles and the size decreases and the more modifications are done for the better performance and the better comfort. Due to the rise in the speed of the vehicle the cooling systems are required for cooling the engine the radiators are used for the cooling as it is the most important part of the engine. We know that the heat is produced due to the movement of the piston and the crankshaft and the connecting rod. Some amount of heat it will release with the help of the engine oil and the exhaust gases. The other heat which is left inside the engine is released by the cooling system it helps in maintain temperature and prevents the engine from overheated.



Fig1: - The working condition of the radiator (GOOGLE)

The thermostat is used for measuring the temperature. The working of the thermostat is to release the coolant at a time when the temperature of the engine increases and absorb the heat make it cool and release it to the surrounding and make the engine cool. Nowadays the Aluminum is used for making radiator fins. Inside the radiator, small fins tube the hot water



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

is supplied from the engine through inlet valve and then passes through tubes which led to the decreasing the temperature of the liquid and make the water cool and the supplies it through the outlet valve to the pump and the pump suppliers to the engine. A tabulator is present inside the tubes which are made of aluminum films. The liquid gets cooled faster as it gets more and more in contact with films if the speed of the liquid is slow. As we know that the more the liquid touches the films which led to the transfer of more heat to the environment. For the better transfer of heat, turbulence must be created in the liquid for the touching of more and more liquid to the films which led to the transfer of more heat to the environment. If the transfer of heat from the liquid to the environment is more the more heat will be absorbed from the engine and the performance of the engine will increase.

#### Type of radiator

There are two types of radiator

- 1) Tabular type
- 2) Cellular type core

#### Tabular type

It is the series combination of upper and lower tanks through which water passes. Fins are attached to improve heat transfer around the tubes. Outside of the tubes, the air is passed between the fins that absorbing heat from the water. The water passes through all the tubes the cooling effect of the entire tube is lost if one of the tubes becomes clogged. On a cellular radiator, the clogging of any passage results in a loss but of a small part of the total cooling surface.

#### Cellular type core

Air passes through the tubes and the water flows in the spaces between them in cellular type core. The core contains a large number of air cells that are surrounded by the radiator. It is known as a honeycomb radiator because of its appearance as the cells in front are hexagonal. On a cellular radiator, passage clogging results in a loss but small areas will be affected by it. It consists of many small tubes equipped with a honeycomb-like structure of fins to dissipate heat rapidly and cools hot liquid from the engine.

Parts of radiator

- 1) Upper tank
- 2) Lower tank
- 3) Tubes
- 4) Filler cap
- 5) Fins

#### **Upper Tank:**

Due to absorbing heat from the engine coolant get hot, the liquid expands and creates pressure in the radiator additionally. The pressure causes the coolant to get higher than the pressure cap, to prevent leakage excess coolant needs to be captured somewhere. The excess fluid flows into the pipe and goes into the overflow tank. When the driver parks turn off the engines of the vehicle and the heat dissipates which causes the coolant. The coolant will then contract instead of expanding; resulting in the volume of the coolant. The vacuum effect will take place where the pressure decrease allows the excess coolant in the overflow tank to flow back so it can return to the radiator. Tanks could also be made of brass, plastic, a polyamide).

#### Lower Tank:

Just after it has passed through the heat radiating tubes and fins in the body of the radiator the bottom tank receives the cooling water. The significant temperature takes place. From the block, the thermostat releases water at 180 degrees Fahrenheit. That water can lose as 100 def. F. depending on the ambient air temperature and the efficiency of the radiator by the time it reaches the bottom tank. The water pump holds this cooled water. It will back into the block where it is again heated up.

#### **Tubes:**

On its way to the opposite tank, as the coolant passes through the radiator tubes, it transfers heat to the tubes that transfer the heat to the fins that are attached between the rows. The fins head the heat flow to the ambient air. Radiator tubes are



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

made up of brass. The use of aluminum increased, eventually taking over the vast majority of vehicular radiator applications.

#### Filler cap:

Since the coolant expands the high coolant temperature leads to an increase in pressure in the cooling system. Coolant is press in the tank that will increase the pressure in the tank.

A pressure relief valve in the filler cap opens. It allows air to escape. Partial vacuum forms in the cooling system when the coolant temperature returns to normal. This causes a vacuum in the tank because the Coolant is extracted from the tank.

#### Fins:

Fins are surfaces that are used to increase the rate of heat transfer to or from the environment and they extend from the surface by increasing convection. Fins increase the surface area and can be an economical solution to heat transfer problems.

#### COOLANT

Its primary function is to keep the engine at a constant safe operating temperature but also, with the addition of other chemicals called inhibitors, to control the formation of scale and rust. Inhibitors also prevent cavitation, that is, oxidation from water passing through the cooling system. Anti-freeze / Anti-Boil coolants lower the freezing point of the coolant while raising the boiling point. Corrosion inhibitors have little or no Anti-Freeze / Anti-Boil properties and are used primarily to protect surface materials in the cooling system from corrosion.

#### TYPER OF COOLANT

There are mainly two types of coolant

- 1) Type A
- 2) Type B

Type A has an Anti-Freeze Anti-Boil package included present as Ethylene Glycol or similar, an additive package which raises the boiling point of the water and lowers the freezing point.

Type B does not have an Anti-Freeze Anti-Boil additive package added and are true corrosion inhibitors only with no or little AF/AB properties.

#### **Property of coolant**

There are six property of coolant

- 1. Good heat transfer.
- 2. Protection against deposits.
- 3. High-temperature protection.
- 4. Safe to use with hard waters.
- 5. Won't damage and be neutral with internal components
- 6. Reduced foaming tendency.

#### CALCULATION

In fluid regions SOLIDWORKS Flow Simulation solves the Navies-Stokes equations, which are formulations of mass, momentum, and energy conservation laws:

| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

$$\frac{\partial \rho}{\partial t} + \frac{\partial (\rho u_i)}{\partial x_i} = 0 \tag{1}$$

$$\frac{\partial(\rho u_i)}{\partial t} + \frac{\partial}{\partial x_i}(\rho u_i u_j) + \frac{\partial P}{\partial x_i} = \frac{\partial}{\partial x_i}(\tau_{ij} + \tau_{ij}^R) + S_i$$
(2)

$$\frac{\partial \rho H}{\partial t} + \frac{\partial \rho u_i H}{\partial x_i} = \frac{\partial}{\partial x_i} \left( u_j (\tau_{ij} + \tau_{ij}^R) + q_i \right) + \frac{\partial p}{\partial t} - \tau_{ij}^R \frac{\partial u_i}{\partial x_j} + \rho \varepsilon + S_i u_i + Q_H$$

$$H = h + \frac{u^2}{2}$$
(3)

For calculation of high-speed compressible flows and flows with shock waves the following energy equation is used:

$$\frac{\partial \rho E}{\partial t} + \frac{\partial \rho u_i \left( E + \frac{p}{\rho} \right)}{\partial x_i} = \frac{\partial}{\partial x_i} \left( u_j (\tau_{ij} + \tau_{ij}^R) + q_i \right) - \tau_{ij}^R \frac{\partial u_i}{\partial x_j} + \rho \varepsilon + S_i u_i + Q_H \quad (4)$$

$$E = e + \frac{u^2}{2}$$

These equations are supplemented by fluid state equations defining the nature of the fluid, and by empirical dependencies of fluid density, viscosity, and thermal conductivity on temperature. Inelastic non-Newtonian fluids are considered by introducing a dependency whereby their dynamic viscosity is dependent on flow shear rate and temperature. Special models are used for the description of real gases, volume condensation, and vaporization, cavitations, as well as for porous media.

#### **II.SOLID WORKS**

Flow Simulation can consider both laminar and turbulent flows. Laminar flows occur at low values of the Reynolds number, which is defined as the product of representative scales of velocity and length divided by the kinematic viscosity. When the Reynolds number exceeds a certain critical value the flow transitions smoothly to turbulent. To predict turbulent flows, the Favre-averaged Navies-Stokes equations are used, where time-averaged effects of the flow turbulence on the flow parameters are considered, whereas the large-scale, time-dependent phenomena are taken into account directly. Through this procedure, extra terms known as the Reynolds stresses appear in the equations for which additional information must be provided. To close this system of equations, SOLIDWORKS Flow Simulation employs transport equations for the turbulent kinetic energy and its dissipation rate, using the  $k-\varepsilon$  model.

The modified k- $\varepsilon$  turbulence model with damping functions proposed by Lam and Bremhorst (1981) describes laminar, turbulent, and transitional flows of homogeneous fluids consisting of the following turbulence conservation laws:



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.1007023|

$$\frac{\partial \rho k}{\partial t} + \frac{\partial \rho k u_i}{\partial x_i} = \frac{\partial}{\partial x_i} \left( \left( \mu + \frac{\mu_i}{\sigma_k} \right) \frac{\partial k}{\partial x_i} \right) + \tau_{ij}^R \frac{\partial u_i}{\partial x_j} - \rho \varepsilon + \mu_i P_B,$$
(5)

$$\frac{\partial \rho \varepsilon}{\partial t} + \frac{\partial \rho \varepsilon u_i}{\partial x_i} = \frac{\partial}{\partial x_i} \left( \left( \mu + \frac{\mu_t}{\sigma_{\varepsilon}} \right) \frac{\partial \varepsilon}{\partial x_i} \right) + C_{\varepsilon 1} \frac{\varepsilon}{k} \left( f_1 \tau_{ij}^R \frac{\partial u_i}{\partial x_j} + C_B \mu_t P_B \right) - f_2 C_{\varepsilon 2} \frac{\rho \varepsilon^2}{k}$$
(6)

$$\tau_{ij} = \mu s_{ij}, \ \tau_{ij}^{R} = \mu_{i} s_{ij} - \frac{2}{3}\rho k \delta_{ij} \ , s_{ij} = \frac{\partial u_{i}}{\partial x_{i}} + \frac{\partial u_{j}}{\partial x_{i}} - \frac{2}{3}\delta_{ij} \frac{\partial u_{k}}{\partial x_{k}},$$
(7)

$$P_B = -\frac{g_i}{\sigma_B} \frac{1}{\rho} \frac{\partial \rho}{\partial x_i},\tag{8}$$

Where  $C\mu = 0.09$ ,  $C\varepsilon 1 = 1.44$ ,  $C\varepsilon 2 = 1.92$ ,  $\sigma k = 1$ ,  $\sigma \varepsilon = 1.3$ ,  $\sigma B = 0.9$ , CB = 1 if PB > 0, CB = 0 if PB < 0, the turbulent viscosity is determined from:

$$\mu_t = f_\mu \cdot \frac{C_\mu \rho k^2}{\varepsilon},\tag{9}$$

Lam and Bremhorst's damping function  $f\mu$  is determined from:

3

$$f_{\mu} = \left(1 - e^{-0.025R_{y}}\right)^{2} \cdot \left(1 + \frac{20.5}{R_{t}}\right), \tag{10}$$

Where:

$$R_{y} = \frac{\rho \sqrt{ky}}{\mu}, \tag{11}$$
$$R_{z} = \frac{\rho k^{2}}{\mu}$$

$$\kappa_t = \frac{1}{\mu\varepsilon}, \tag{12}$$

y is the distance from a point to the wall and Lam and Bremhorst's damping functions f1 and f2 are determined from:

$$f_1 = 1 + \left(\frac{0.05}{f_{\mu}}\right)^5, \quad f_2 = 1 - e^{R_t^2}.$$
 (13)

Lam and Bremhost's damping functions  $f\mu$ , f1, f2 decrease turbulent viscosity and turbulence energy and increase the turbulence dissipation rate when the Reynolds number Ry based on the average velocity of fluctuations and distance from the wall becomes too small. When  $f\mu = 1$ , f1 = 1, f2 = 1 the approach reverts back to the original  $k-\varepsilon$  model.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

The heat flux is defined by:

$$q_{i} = \left(\frac{\mu}{\Pr} + \frac{\mu_{i}}{\sigma_{c}}\right) \frac{\partial h}{\partial x_{i}}, \quad i = 1, 2, 3$$
(14)

Here the constant  $\sigma c=0.9$ , Pr the Prandtl Number, and H is the thermal enthalpy.

A particular computational task is finally specified by the definition of its geometry, boundary, and initial conditions. All data for such conditions are defined directly on the native CAD model.



Fig2:-GOVERNING EQUATION

#### **III.RESULTS**

#### FINITE ELEMENT ANALYSIS

#### **CFD FLOW SIMULATION**

Nowadays it is not possible to prepare the model and test it. Designing software is used for preparing models and analyzing the models. Finite element analysis is one of the major parts of the design

#### Computational fluid dynamics (CFD):-

As the name suggested CFD (computational fluid dynamics) is the study of the fluid flow inside the design body software. Surface conditions, boundary conditions, and materials are also being selected for the design. A Solidworks CFD is also used for the flow simulation.

#### Solidworks Flow Simulation Introduction

As the name suggested Solidworks flow simulation is a part of Solidworks. It is used to perform the flow simulation. Flow simulation is present in the add-in options in the Solidworks.

There are two types of analysis

- 1) Internal flow analysis.
- 2) External flow analysis.

Internal flow analysis-

Radiator, valves, pump are all examples of internal analysis studies. Because SolidWorks flow simulation function inside of Solidworks setting up a computational domain, boundary condition, and heat source can be done in a minute External flow analysis –

It is used when we need to understand the fluid behavior around our model based on the environmental condition, winds turbine. In external analysis the computational domain act as our virtual wind turbine.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

#### |DOI:10.15680/IJIRSET.2021.1007023|

#### Dimension used for designing of radiator

The following data is 30% less than the original data

Parts	Size
Radiator length	0.45m
Radiator width	0.43m
Radiator height	0.024 m
Tube width	0.024m
Tube height	0.0015m
Fin width	0.024m
Fin height	0.011m
Fin thickness	0.0002540m
Distance between tubes	0.0015m
Number of tubes	33

# **3D-MODEL OF RADIATOR**



After completing the designing part the flow analysis has to be performed and the result has to be calculated. During performing the analysis part the two medium has to take

- a) Water medium.
- b) WATER AND Coolant as a medium.

As we see that in the  $1^{st}$  case water as a medium has to take. Whereas in the  $2^{nd}$  case water and coolant as a medium (1:4) ratio. After that data has to be collected and comparing both results.

#### 1) USING WATER AS MEDIUM

#### General Settings CFD analysis

In the Solidworks when we performed the CFD analysis some general setting has to be selected. In this software, two types of analysis have to be done internal and external analysis is done. It depends on the model what type of analysis has to be selected. After selecting the analysis type the physical features has to be selected.



# | e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

#### [DOI:10.15680/IJIRSET.2021.1007023]

<ul> <li>Internal</li> <li>External</li> </ul>	Consider closed cavities		Marvi	Analysis type
		1940	<u>_</u>	Fluids
Physical Features	in solids	Value		Solids
Radiation	in cromuta :	[Pert]		
Time-dependent				Wall conditions
Gravity		[ETT]		
Rotation		[ETT]		Instituted as an addition of a
				Initial Conditions
fannes with Q				mual conduons
ference axis: 🔀	-	Denenderovy		rndai conditions

Fig 1.1 – Internal analysis and heat conduction has to be selected

#### Water as fluid

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis the medium has to be selected and flow characteristics have to be selected (Laminar and turbulent).

Fluids	Path	New	Navigator
Gases			An Analysis hope
Liquids			Man Managers Ope
Non-Newt Non-Newt	onian Liquids		Con Fluids
Compressible Liquid	15		
Real Gases			Solida
Steam		_	
			Wall conditions
			Initial conditions
		( Add )	
Project Fluids	Default Fluid	Remove	
Water ( Liquids )			
		Replace	
		_	
Flow Characteristic	Value		
Flow type	Laminar and Turbulent	*	
Cavitation	100		

Fig 1.2- water as fluid and laminar and turbulent flow has to be selected

#### **Computational Domain**

In the Solidworks when we perform the CFD analysis some general setting (material and flow characteristic) has to be selected and the computational domain has to be defined. The computational domain defines the area within which flow simulation has to be performed.



Fig 1.3- computational domain has to be selected along X-axis, Y-axis & Z- axis

#### **BOUNDARY CONDITIONS**

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis, the medium, and the computational domain the boundary condition has to define. Some parameters have to be defined according to the simulation.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.1007023|



Fig1.4 – Inlet mass flow rate 10KG/S and temperature 80°c

#### Material

In the Solidworks when we performed the CFD analysis some general setting has to be selected. One of the most important parts is the material has to be defined. If the material is not defined the simulation will show an error during the simulation process. After selecting the material LID has to be selected for creating a vacuum.



Fig1.5- LID and aluminum 6061

#### Outlet

In the Solidworks, we perform the CFD analysis some general setting has to be selected. After selecting the analysis, the medium, the computational domain, the boundary condition, and the material the static pressure has to be defined. It states the force per unit area by the fluid.



Fig1.6- static pressure has to be 150000Pa and temperature 20.05°c



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569| || Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

# Wall

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the material and the static pressure the outer wall temperature has to be defined. If we did not select the outer wall temperature transfer of heat will not take place.



Fig 1.7:- the entire outer wall has to be selected and thermodynamic parameters should be (25°C)

# **IV.RESULTS AND CONCLUSION**

# 1) Temperature

2) Pressure

As shown in the figure we see that variation of temperature takes place from 29.49°c-80.86°c.



Fig1.8:- Temperature

As shown in the figure we see that variation of pressure take place from -951232.01to 5733935.49 pas (negative pressure is due to relative pressure).



Fig1.9:- Pressure



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]

#### 3) Velocity

As shown in the figure we see that variation of velocity takes place from 0 to 82.560(m/s).



Fig1.10:- Velocity

# 2) USING WATER AND COOLANT AS MEDIUM

When we use water and coolant as a medium all the parameters are the same only medium will be changed. In  $1^{st}$  case, we take water as a medium and in  $2^{nd}$  case water and coolant are used for the simulation (1:4) ratio.

#### General Settings CFD analysis

In the Solidworks when we performed the CFD analysis some general setting has to be selected. In this software, two types of analysis have to be done internal and external analysis is done. It depends on the model what type of analysis has to be selected. After selecting the analysis type the physical features has to be selected.



Fig 2.1 – Internal analysis and heat conduction has to be selected

#### Water as fluid

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis the medium has to be selected and flow characteristics have to be selected.



Fig 2.2- water and coolant as fluid and laminar and turbulent flow have to be selected.

#### **Computational Domain**

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis and the medium the computational domain has to be defining. The computational domain defines the area within which flow simulation has to be performed.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

#### |DOI:10.15680/IJIRSET.2021.1007023|



Fig 2.3- computational domain has to be selected along X-axis, Y-axis & Z- axis

#### **BOUNDARY CONDITIONS**

In the Solidworks when we perform the CFD analysis some general setting has to be selected. After selecting the analysis, the medium, and the computational domain the boundary condition has to define. Some parameters have to be defined according to the simulation.



Fig2.4 - Inlet mass flow rate 10KG/S and thermodynamic parameters 80°c

#### Material

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis, the medium, the computational Domain, and the Boudry condition. One of the most important parts is the material has to be defined. If the material is not defined the simulation will show an error during the simulation process. After selecting the material LID has to be selected for creating a vacuum.



Fig2.5- LID and aluminum 6061

Outlet

In the Solidworks when we performed the CFD analysis some general setting has to be selected. After selecting the analysis, the medium, the computational domain, the boundary condition, and the material the static pressure has to be defined. It states the force per unit area by the fluid.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

#### |DOI:10.15680/IJIRSET.2021.1007023|



Fig2.6- static pressure has to be 150000Pa and temperature 20.05°c

#### Wall

In the Solidworks when we perform the CFD analysis some general setting has to be selected. After selecting the material and the static pressure the outer wall temperature has to be defined.



Fig 2.7:- the entire outer wall has to be selected and thermodynamic parameters should be (25°C)

# RESULTS

After filling all the data accordingly and running the flow simulation. Temperature, pressure, the velocity of a radiator will occur.

#### 1) **Temperature**

As shown in the figure we see that variation of temperature takes place from  $(26.26^{\circ}\text{C}-80.30^{\circ}\text{C})$ .



Fig2.9:- Temperature

#### 2) Pressure

As shown in the figure we see that variation of pressure takes place -100962.71-1442512.26 (Negative pressure is due to relative pressure).



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

[DOI:10.15680/IJIRSET.2021.1007023]



Firg2.10 Pressure

#### 3) Velocity

As shown in the figure we see that variation of velocity takes place (0-20.342) (m/s).



Fig 2.11:- Velocity

INLET	OUTLET
	001221
TEMPERATURE	TEMPERATURE
80	29.49
80	29.19
80	26.26
	INLET TEMPERATURE 80 80

#### FIG 5: - RESULT TABLE

In the above table, we can see that there is a large temperature difference in the simulation when we change the fluid

#### **V.CONCLUSION**

- Brief studies about radiators, working are done in this project.
- Modeling of Radiator is done by using Solidworks 2016 software.
- CFD analysis is performed on the radiator by using solid works Flow simulation module.
- CFD analysis is performed on the radiator by selecting two different fluids i.e. two regular fluid water and coolant.
- Boundary conditions are provided as 80- degree C for inlet temperature of the fluid, which will have cooled by radiator pipe and fins employing convection process on the ambient temperature of 25-degree C.
- Due to convection temperature of fluid flow inside the radiator will decrease; values temperature, velocity, and pressure of fluid after analysis are noted and tabulated.
- From the result table, we can conclude that coolant and water fluids give better convection i.e. give better cooling to the engine compared to water.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

# || Volume 10, Issue 7, July 2021 ||

#### |DOI:10.15680/IJIRSET.2021.1007023|

▶ WATER AND COOLANT give the best result compare to all fluids used for analysis.

#### REFERENCES

- 1. V.L.Bhimani, P.P.Ratho and A.S.Sorathiya, "Experimental study of heat transfer enhancement using water based nanofluids as a new coolant for car radiators". IJETAE Vol.3, Issue 6, June 2013.
- 2. Gaurav Sharma and Lal Kundan," Experimental investigation into thermal conductivity and viscocity of Al2O3 based engine coolant".IJRMET Vol. 3, Issue 6,MayOct 2013.
- 3. .Adnan M.Hussein , R.A.Bakar, K.Kadirgama,G.L.Ming' "Heat transfer augmentation for the car radiator by using nanofluid".MRE, ISBN: 978-1-63248-002 doi.
- 4. Rahul A.Bhogare and B.S.Kotahwale "A review on applications and challenges of nanofluids as coolant in automobile radiator "International journal of scientific and research publications, volume 3,Issue 8, August 2013, ISSN 2250-3153.
- 5. Chavan D.K. and Tasgaonkar G.S. "Study Analysis and Design of Automobile Radiator Proposed with Cad Drawing and Geometrical Model of the Fan" IJMPERD ISSN 2249- 6890, Vol 3, Issue 2, June 2013, 137-146.
- 6. . Deepak Chintakayala and, Rajamanickam C.S. "CFD analysis of fluid flow and heat transfer of an automotive radiator with nano fluid "978-1-4673- 6150- 7/13/\$31.00@2013 IEEE.
- 7. NavidBozorgan, KomalaganKrishnakumar, NarimanBozorgan "Numerical study on applications of CuO nanofluid in Automotive Diesel Engine Radiator "Modern mechanical engineering 2012, 2,130-136.
- 8. Paresh Machhar and FalgunAdroja "Heat transfer enhancement of automobile radiator with TiO2 and water nanofluid "International journal of engineering research and technology, ISSN 2278-0181, vol 2 Issue 5 may-2013.
- 9. https://www.researchgate.net/publication/316200090\_A\_Numerical\_Study\_of\_Heat\_Transfer\_Charcteristics\_of\_a\_Car\_\_Radiator\_Involved\_Nanofluids/link/59a6f209aca272895c169997/download.
- 10. https://www.google.com/search?q=radiator&rlz=1C1CHBD\_enIN888IN888&sxsrf=ALeKk01JB41Iwo\_vqkMYqh\_M FqWVj5srXQ:1622605235217&source=lnms&tbm=isch&sa=X&ved=2ahUKEwjvkJ\_Fg\_jwAhWC\_XMBHYjZDIQ Q\_AUoAXoECAIQAw&biw=1920&bih=976
- 11. https://www.google.com/search?q=radiator&rlz=1C1CHBD\_enIN888IN888&sxsrf=ALeKk01JB41Iwo\_vqkMYqh\_M FqWVj5srXQ:1622605235217&source=lnms&tbm=isch&sa=X&ved=2ahUKEwjvkJ\_Fg\_jwAhWC\_XMBHYjZDIQ Q\_AUoAXoECAIQAw&biw=1920&bih=976.
- 12. https://www.google.com/search?q=radiator&rlz=1C1CHBD\_enIN888IN888&sxsrf=ALeKk01JB41Iwo\_vqkMYqh\_M FqWVj5srXQ:1622605235217&source=lnms&tbm=isch&sa=X&ved=2ahUKEwjvkJ\_Fg\_jwAhWC\_XMBHYjZDIQ Q\_AUoAXoECAIQAw&biw=1920&bih=976.
- 13. https://www.google.com/search?q=radiator&rlz=1C1CHBD\_enIN888IN888&sxsrf=ALeKk01JB41Iwo\_vqkMYqh\_M FqWVj5srXQ:1622605235217&source=lnms&tbm=isch&sa=X&ved=2ahUKEwjvkJ\_Fg\_jwAhWC\_XMBHYjZDIQ Q\_AUoAXoECAIQAw&biw=1920&bih=976.
- 14. https://www.google.com/search?q=radiator&rlz=1C1CHBD\_enIN888IN888&sxsrf=ALeKk01JB41Iwo\_vqkMYqh\_M FqWVj5srXQ:1622605235217&source=lnms&tbm=isch&sa=X&ved=2ahUKEwjvkJ\_Fg\_jwAhWC\_XMBHYjZDIQ Q\_AUoAXoECAIQAw&biw=1920&bih=976
- 15. https://en.wikipedia.org/wiki/Coolant
- 16. https://themechanicalengineering.com/radiator/#:~:text=Radiator%20Working%20Principle%3A&text=In%20the%20r adiator%2C%20the%20coolant,hot%20water%20in%20the%20tubes.
- 17. https://www.123rf.com/photo\_120787522\_car-engine-over-heat-with-no-water-in-radiator-and-cooling-system-overheated-car-machine-broken-down.html
- 18. .https://themechanicalengineering.com/radiator/#:~:text=Radiator%20Working%20Principle%3A&text=In%20the%20 radiator%2C%20the%20coolant,hot%20water%20in%20the%20tubes.





Impact Factor: 7.569





# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com