

Volume 10, Issue 7, July 2021



Impact Factor: 7.569









| e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

DOI:10.15680/IJIRSET.2021.100332

Free Convection Laminar flow of Viscoelastic Fluid Past a Porous Vertical Wall with **Exponentially Decreasing Time Dependent Suction**

Dr. Lakhbir Singh

Associate Professor of Mathematics, Govt. P. G. College, Hisar, India

ABSTRACT: In the present study, the two-dimensional incompressible visco-elastic fluid (Rivlin-Ericksen) flow has been considered by applying the time dependent suction to free convection past a vertical wall. A case of exponentially decreasing suction has been discussed in detail as a particular case. The expressions for velocity distribution, temperature distribution, skin friction and the rate of heat transfer from the wall to the fluid have been obtained.

Nomenclature

k	Permeability parameter
ĸ	r chilicability parameter

Acceleration due to gravity g

N Nusselt number

P Pressure

Heat flux per unit area $\frac{q}{T}$

Temperature in the boundary layer

 T_{w} Temperature at the wall

 T_{∞} Temperature of the free stream

Time

τ Skin friction

и Velocity in the x-direction

 U_{∞} Velocity of the free stream

Velocity in y-direction ν

Velocity in z-direction W

Coordinate system x, y

X, Y, ZComponent of the body force in x, y and z directions respectively

The density ρ

 σ Prandtl number

 θ Dimensionless temperature

 υ The kinematic cross viscosity

β Coefficient of Kinematics visco-elasticity

Formulation of the problem

The equations describing the unsteady free convection flow of a visco-elastic incompressible fluid are given

$$\frac{\partial \overline{u}}{\partial t} + \overline{v} \frac{\partial \overline{u}}{\partial y} = g \beta_1 \left(\overline{T} - \overline{T}_{\infty} \right) + \alpha \frac{\partial^2 \overline{u}}{\partial \overline{v}^2} + \beta \frac{\partial^2}{\partial \overline{v}^2} \left(\frac{\partial \overline{u}}{\partial \overline{t}} + \overline{v} \frac{\partial \overline{u}}{\partial \overline{y}} \right)$$
(1)

$$\frac{\partial \overline{v}}{\partial t} = -\frac{1}{\rho} \frac{\partial \overline{p}}{\partial \overline{u}} + 2(2\beta + v) \frac{\partial \overline{u}}{\partial v} \frac{\partial^2 \overline{u}}{\partial \overline{v}^2}$$
 (2)

by



| e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.100332 |

$$\frac{\partial \overline{v}}{\partial \overline{v}} = 0 \tag{3}$$

$$\frac{\partial \overline{T}}{\partial \overline{t}} + \overline{v} \frac{\partial \overline{T}}{\partial y} = k \frac{\partial^2 \overline{T}}{\partial \overline{y}^2}$$
 (4)

Here the equations (1) and (2) are the equations of motion. The equations (3) and (4) are the equation of continuity and energy respectively.

Let the suction velocity normal to the wall be function of time as

$$\overline{v} = -\overline{v}_0 \left(1 + \varepsilon A e^{-nt} \right), \quad \varepsilon A \le 1 \tag{5}$$

Introducing the following non-dimensional quantities

$$y = \frac{\overline{y}}{L}, \quad t = \frac{\alpha \overline{t}}{L^2}, \quad U = \frac{uL}{\alpha}, \quad V = \frac{\overline{vL}}{\alpha} = \frac{|\overline{v}|}{|\overline{v}_0|}$$

$$p = \frac{\bar{p}L^2}{\rho\alpha^2}, \quad T = \frac{g\beta_1 L^3 \left(\bar{T} - \bar{T}_{\infty}\right)}{\alpha^3} \tag{6}$$

The equations (1) and (4) with the help of (5) and (6) take the following form

$$\frac{\partial U}{\partial t} - \left(1 + \varepsilon A e^{-nt}\right) \frac{\partial U}{\partial y} = T + \frac{\partial^2 U}{\partial y} + S_1 \frac{\partial^2}{\partial y^2} \left\{ \frac{\partial U}{\partial t} - \left(1 + \varepsilon A e^{-nt}\right) \frac{\partial U}{\partial y} \right\}$$
(7)

$$\frac{\partial T}{\partial t} - \left(1 + \varepsilon A e^{-nt}\right) \frac{\partial T}{\partial v} = \frac{1}{\sigma} \frac{\partial^2 T}{\partial v^2}$$
 (8)

respectively, where σ is the Prandtl number and $S_1 = \beta / L^2$.

Solution of the Problem

The relevant boundary conditions of the problem are

$$U(0,t) = 0$$
, $V(0,t) = -F(t)$, $T = \theta(t)$ when $y = 0$

and

$$U(\infty,t) \to 1, \quad \frac{\partial U}{\partial y} \to 0, \quad T \to 0 \text{ , when } y = \infty$$
 (9)

For solving equation (7) and (8) subject to boundary conditions (9), we assume that

$$U(y,t) = U_0(y) + U_1(y)\varepsilon e^{-nt}$$
(10)

and

$$T(y,t) = T_0(y) + T_1(y)\varepsilon e^{-nt}$$
(11)

After putting (10) and (11) in equation (7) and (8), and equating to zero the exponential term, we get

$$S_1 U_0''' - U_0'' - U_0' = T_0 (12)$$

$$\frac{T_0''}{\sigma} = -T_0'$$

$$S_1 U_1''' - (1 - nS_1)(U_1'' - U_1' - nU_1) = T_1 - S_1 A U_0'' + A U_0$$
(14)

$$\frac{T_1''}{\sigma} + T_1' + nT_1 = -AT_0' \tag{15}$$

The boundary conditions (9) reduce to

$$U_0 = U_1 = 0 \qquad \text{when } y = 0$$

$$U_0 \to 1, \ U_1 \to 0$$

$$U_0' \to 0, \ U_1' \to 0$$
when $y = \infty$

$$(16)$$

| e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.100332 |

and

$$T_0 = \theta_0, \quad T_1 = \theta, \quad \text{when } y = 0$$

 $T_0 \to 0, \quad T_1 \to 0, \quad \text{when } y = \infty$ (17)

The solution of equation (13) with their relevant boundary conditions are

$$T_0(y) = \theta_0 e^{-\sigma y} \tag{18}$$

Since S_1 is negative, so substituting $S_1 = -k_0$, then the equation (12) takes the form

$$k_0 U_0''' + U_0'' + U_0' = -\theta_0 e^{-\sigma y} \tag{19}$$

The solution of equation (19) with boundary conditions (16) and $0 \le k_0 \le \frac{1}{4}$ is

$$U_0(y) = 1 + B_1 e^{-H_1 y} + B e^{-\sigma y}$$
(20)

where

$$H_1 = \frac{1}{2} \left[\frac{1 - \sqrt{1 - 4k_0}}{k_0} \right], \qquad B = \frac{\theta_0}{\sigma \left(k_0 \sigma^2 - \sigma + 1 \right)},$$

$$B_1 = -[1+B] \tag{21}$$

Now solution of equation (15) subject to boundary conditions (17) is

$$T_1(y) = (\theta_1 - M)e^{-H_2y} + Me^{-\sigma y}$$
 (22)

where

$$H_2 = \frac{\sigma}{2} - \left\{ 1 + \sqrt{1 - \frac{4n}{\sigma}} \right\}, \quad M = \frac{A\sigma\theta_0}{n}$$
 (23)

with these equations (14) leads to

$$k_0 U_1''' + (1 + nk_0) U_1'' + U_1' + nU_1 = k_1 e^{-H_1 y} + k_2 e^{-H_2 y} + k_3 e^{-\sigma y}$$
(24)

where

$$k_1 = k_0 A H_1^3 B_1 + A H_1 B_1$$
,

$$k_2 = M - \theta_1$$
,

$$k_3 = k_0 A \sigma^3 B + A \sigma B - M . \tag{25}$$

The solution of equation (24) subject to equation (16) is given by

$$U_1(y) = Ne^{-m_1 y} + Pe^{-H_1 y} + Qe^{-H_2 y} + Re^{-\sigma y}$$
(26)

where

$$N = -(P + Q + R), P = \frac{k_1}{k_0 H_1^3 - (1 + nk_0) H_1^2 + H_1 - n}$$

$$Q = -\frac{k_2}{k_0 H_2^3 - (1 + nk_0) H_2^2 + H_2^{-n}},$$

$$R = -\frac{k_3}{k_0 \sigma^3 - (1 + nk_0) \sigma^2 + \sigma - n}.$$
(27)

where $-m_1$ being the root of the following cubic equation

$$k_0 m^3 + (1 + nk_0) m^2 + m + n = 0$$
.

The expression for velocity and temperature distribution under the boundary layer are given by

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



| e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.100332 |

$$U(y,t) = 1 + B_1 e^{-H_1 y} + B e^{-\sigma y} + \varepsilon e^{-nt} \left[N e^{-m_1 y} + P e^{-H_1 y} \right] + Q e^{-H_2 y} + R e^{-\sigma y}$$
(28)

and

$$T(y,t) = \theta_0 e^{-\sigma y} + \varepsilon e^{-nt} \left[(\theta_1 - M) e^{-H_2 y} + M e^{-\sigma y} \right]$$
(29)

Skin Friction and Rate of Heat Transfer

Here we shall have the expressions for skin friction and rate of heat transfer

$$D = \mu \left(\frac{\partial \overline{u}}{\partial \overline{y}}\right) \overline{y} = 0$$

$$= \frac{\mu \alpha}{L^{2}} \left(\frac{\partial U}{\partial y}\right) y = 0$$

$$D = \frac{\mu \alpha}{L^{2}} \left[B_{1}H_{1} + \sigma B + \varepsilon e^{-nt} \left(m_{1}N + PH_{1} + QH_{2} + R\sigma\right)\right]$$

$$q = -\lambda \left(\frac{\partial \overline{T}}{\partial \overline{y}}\right) \overline{y} = 0$$

$$= -\frac{\lambda \alpha^{2}}{g\beta_{1}L^{4}} \left(\frac{\partial T}{\partial y}\right) y = 0$$

$$= \frac{\lambda \alpha^{2}}{g\beta_{1}L^{4}} \left\{\theta_{0}\sigma + \varepsilon e^{-nt} \left[\left(\theta_{1} - M\right)H_{2} + M\sigma\right]\right\}$$
(31)

Conclusion

It is evident from the above expression that the rate of heat transfer decreases from the wall to the fluid and becomes a finite quantity when $t \to \infty$.

References

- 1. M. K. Chowdhury and M. N. Islam: MHD free convection flow of visco-elastic fluid past an infinite vertical porous plate, Heat and Mass Transfer, Vol. 36, P. 439-447 (2000).
- 2. Ahmadi, G., and Manvi, R.: Indian J. Technol. 9(1971) 441.
- 3. Sahoo, D.G., and Sahoo, P.K.: Indian J. Technol., Vol. 24, Sept. 1986.
- 4. Tong-BouChang, A. Mehmood, O. Anwar, M. Narahari, M. N. Islam and F. Ameen: Numerical study of transient free convective mass transfer in a Walters-B viscoelastic flow with wall suction, Communication in Nonlinear Science and Numerical Simulation, Vol. 16, Issue 1, P. 216-225 (2011).
- 5. Sahoo, D.G., and Sahoo, P.K.: The Mathematical Educ., Vol. 24, No. 3, Sept. 1990.
- 6. Gulab Ram and Mishra, R.S.: Indian Pure and Appl. Math., 8 (1977) 637.
- 7. Singh, K.K.: The Mathematical Edu., Vol. X, No. 4, Dec. 1976.
- 8. KrishanLal: Application of fluet suction to free convection laminar flow past a porous vertical wall, Proc. Ind. Soc. Theo. And Appl. Mech., Thirteen Congress, Durgapure (1968), p. 157.
- 9. Kuffousius, N., and Rapits, A.: Rev. Rou. Sci. Tech. Mech. Appl., 26, 1, 11-22, 1981.
- 10. Howarth, L.: Modern Development in Fluid Dynamics, High Speed Flow.
- 11. Rapits, A., Tzivaridis, G., and Kufousius, N.: Letter in Heat and Mass Transform, 81, 417, 1981.
- 12. Rapits, A.A., and Vlahos, J.: Letter Mass Transfer 9 (1982).
- 13. Schlicting, H.: Boundary Layer Theory.
- 14. Siddappa, B.: Oscillatory Motion or a flat plate in a visco-elastic fluid, J.M. Acad. Sci., Vol. 15, p.17 (1970).
- 15. Siddappa, B., and Bujurke, N.M.: Application or fluctuating suction to free convection laminar flow of viscoelastic fluid past a porous vertical, Progress of Maths., Vol. 6, No. 2, p. 41 (1972).
- 16. Siddappa, B., and Gundappa, S. Patel, Math. Edu., XI, No. 4, 1977.
- 17. P. Reddy, P. Sreehari, A.S. Nagarajan, and M. Sivaiah: Hydromagnetic Free Convection Laminar Flow of an Incompressible Viscoelastic Fluid Past a Porous Vertical Wall with Constant Suction, IUP Journal of Computational Mathematics, Vol. 2, Issue 4,P. 56-69 (2009).

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



| e-ISSN: 2319-8753, p-ISSN: 2347-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 10, Issue 7, July 2021 ||

|DOI:10.15680/IJIRSET.2021.100332 |

18. G. M. Seth, S. Sarkar, S. M. Hussain: Effect of Hall current, radiation and rotation on natural convection heat and mass transfer flow past a moving vertical plate, Ain Shams Engineering Journal, Vol. 5, Issue 2, P. 489 – 50, (2014).











Impact Factor: 7.569

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY







📵 9940 572 462 这 6381 907 438 🔀 ijirset@gmail.com

