



e-ISSN: 2319-8753 | p-ISSN: 2320-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 6, June 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.512



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

IoT based Innovation for an Efficient Automotive Security Scheme

Dr. R. Ahila¹, Dr. N. Kalyana Sundaram², Aruna R³, Jalcy J⁴, G. Anusha⁵

Department of Computer Science and Engineering, New Prince Shri Bhavani College of Engineering and Technology,
Chennai, India^{1,3}

Department of Information Technology, New Prince Shri Bhavani College of Engineering and Technology,
Chennai, India^{2,4}

Vikasha Electronics, Chennai, India⁵

ABSTRACT: A competent automotive security system is executed for against burglary and mishap recognition, utilizing an implanted framework comprising of a Global Positioning System (GPS) and a Wi-Fi Module. The framework in case of robbery will send predefined message to the proprietor of vehicle. The client can begin following the place of designated vehicle on Google Earth on a committed vehicle tracker application. Utilizing GPS finder, the objective's present not entirely settled and sent, alongside different boundaries got by vehicle's information port, by means of Internet through Wifi module that is associated with PC or cell phone. Since the primary mechanism of correspondence is web, the term IoT or 'Web of Things' is carried out here. The proprietor will have the decision of slicing the inventory of fuel to the motor to make a quick move capture the criminal. This component will be available on the vehicle tracker application. The other part of the venture is the mishap identification. The cycle is same as in burglary recognition, i.e., when mishap happens; the accelerometer's readings will trigger the framework to begin sending directions of the mishap site to the law implementation specialists and medical clinics, because of which crisis move can be made by them right away.

KEYWORDS: Tracking system, Anti-theft, Internet of Things, Accident detection, Law Enforcement Authorities, Vehicle Tracker app

I. INTRODUCTION

Over the most recent couple of many years, India has advanced at such a gigantic rate that many organizations have unequivocally set up a good foundation for themselves here. These organizations carry an enormous measure of labor force with them. Orchestrating transportation to such an immense mass is an awkward errand including numerous complexities. By and large, this transport is organized through the neighborhood transport merchants on a yearly agreement premise, with progressively happening setbacks, for example, thievery, mishaps and so on representing a greater concern the improvement of satellite correspondence innovation is not difficult to recognize the vehicle areas. Vehicle global positioning frameworks have carried this innovation to the everyday existence of the normal individual. Today GPS utilized in vehicles, ambulances, armadas and police vehicles are normal sights on the streets of created nations. All the current innovation support following the vehicle area and status. The GPS/IoT based framework is one of the main frameworks, which incorporate the two GPS innovation and forthcoming IoT or Internet of Things phrasing. With the assistance of GPS, the vehicle can be followed consistently which related to law requirement specialists or medical clinics can be utilized to follow the vehicle on the off chance that it gets taken or on the other hand assuming the vehicle engages in a genuine setback. The IoT expression is a somewhat new and impending term. As indicated by Wikipedia, The Internet of Things (IoT) is the organization of actual articles or "things" installed with gadgets, programming, sensors, and organization availability, which empowers these items to gather and trade information.




Figure.1 Automobile Internet of Things

The IoT permits objects to be detected and controlled from a distance across existing organization framework, setting out open doors for more straightforward incorporation between the actual world and PC based frameworks, and bringing about superior productivity, precision and financial advantage. Every thing is extraordinarily recognizable through its installed figuring framework however can interoperate inside the current web foundation. The expression "Web of Things" was authored by British business visionary Kevin Ashton in 1999. Ordinarily, IoT is relied upon to offer progressed availability of gadgets, frameworks and administrations that goes past machine to machine correspondence (M2M) and covers an assortment of conventions, areas and applications. The interconnection of these inserted gadgets including shrewd articles is relied upon to introduce mechanization in virtually all fields, while additionally empowering progressed applications like a savvy lattice, and growing to regions like brilliant urban communities.

II. METHODOLOGY




Figure.2 Block Diagram of Security System

Processor - It the core of the framework and fills pretty much every role of the framework. For this framework the ARM v7 (LPC 2138) microcontroller is utilized.

GPS module – The GPS module will get area information (co-ordinates in scope and longitude) of the vehicle from the satellites and will send it to the vehicle tracker application or law requirement or clinic specialists so that definite area of the vehicle which may be taken or met with a mishap be discovered. The ELS GPS 1100 module is utilized in this framework.

Wi-Fi module – The principle assignment of this module is to give association medium to sending area information acquired from GPS module to vehicle tracker application. The ESP 8266 Wi-Fi module will be associated with areas of interest arranged in environmental elements which will empower the framework to send information through Internet to the proprietor.

Accelerometer module – This module estimates changes in g (speed increase) values in three tomahawks viz. X, Y and Z and gives comparing electrical voltage signs to the deviations in the said tomahawks. This module is mindful with mishap location element of the framework. At whatever point the vehicle meets with a mishap, the sharp changes in g esteems happen and the relating computerized qualities (digitization of electrical voltage signals is done by ADC worked in microcontroller) are contrasted and predefined limit esteems, assuming that the qualities surpass those predefined edge esteems, the GPS module is set off and facilitates will be shipped off law requirement and emergency clinic specialists through Internet. For this framework the ADXL 335 accelerometer module is utilized.

External Battery Bank – The battery bank does the trick the power prerequisites for the whole working of the framework. Albeit the framework will initially utilize the power supply from the vehicle's battery pack yet having a helper power supply will help in continuous usefulness of framework in case of vehicle battery pack disappointment or on the off chance that it gets harmed in this manner keeping up with the security of the vehicle consistently.

Power supply – The power supply permits AC sign to DC signal which is needed to run the framework parts (Prototype model as it were). It comprise of step down transformer which lessens the 230V mains supply to simply 12V which is then applied to Bridge rectifier and sifting circuits. At the result of said circuits unadulterated DC (without waves and steady abundancy) is acquired. This DC signal is additionally applied to two voltage controller ICs. One of them is fixed voltage controller IC 7805 which gives a steady 5V and the other IC is LM317 which is variable voltage controller. IC LM317 yield voltage can be changed by utilizing 20 kilo ohm potentiometer. The potentiometer is changed in accordance with acquire 3.3V needed by the microcontroller.

DC motor – Used to address motor of vehicle for beginning model. The stock to the engine comes from the power supply portrayed before.

III. FUNCTIONS

The security system will forever be online 24x7. That is the framework will get constant power from an outer battery bank. This is on the grounds that burglary or mishap can happen whenever and the framework ought to be working ceaselessly with next to no hiccups. Presently consider the situation where the proprietor is beginning his vehicle, on turning the start (with bona fide key), the framework detects that the vehicle's motor has turned over and sends a predefined message to the proprietor that the vehicle has been begun. Additionally the GPS module begins sending directions to the cloud server so they can be involved observing the area of the vehicle in the event that it meets with a mishap. In any case, since the proprietor himself is utilizing the vehicle he/she will disregard the message as this is plainly not an instance of vehicle getting taken. Presently look at that as a criminal in some way gets section into a similar vehicle and some way or another figures out how to begin the vehicle (say by shorting wires to begin start), the equivalent predefined message will be shipped off proprietor of that vehicle. The proprietor will off base understand that his vehicle is currently getting taken. Now the proprietor has two choices:

1. Either promptly press the 'Motor immobilize' highlight present on the 'Vehicle tracker application' introduced on proprietor's advanced mobile phone to pause and capture the hoodlum from pulling off the vehicle on the off chance that he/she wishes to.

2. Or on the other hand begin following the vehicle's position in view of the directions sent by the GPS module (the directions are as of now put away in cloud server and are shipped off application on proprietor's solicitation)

present in the vehicle, start area following on guides and contact the law implementation specialists promptly to catch the hoodlum and recuperate the vehicle.

The same process is applicable in case the vehicle gets involved in an accident. To achieve this, the accelerometer present on system on sensing sharp or heavy movements (if the module gets upside down i.e., when deviations in g values exceed the threshold limits) will trigger the GPS to start sending the coordinates received from satellites (The coordinates are already stored in cloud server) to nearby hospitals and law enforcement authorities so that they can take emergency measures immediately. The utmost important thing is that all the devices (system, smart phone, institutions etc.) must be connected to internet at all the times.

IV. RESULTS AND DISCUSSIONS

The framework was first tried utilizing venture down transformer rather than a battery which was as expected previously (Later on a 12V 1 amp battery was utilized to drive the framework). The progression down transformer down changes over the 230 V, 50 Hz AC supply to 12 V DC which is then applied to rectifier and channel circuits and in the end is utilized to control the singular parts of the framework. A Wi-Fi area of interest (100 Mbps broadband association with switch) was made for the framework to interface with it in order to mimic it as something in IoT idea. The vehicle tracker application was introduced on one of the Smartphone and other telephone was set up which will get GPS facilitates in a SMS at whatever point mishap is distinguished. The four scenarios namely continuous tracking, theft detection, engine immobilize and accident detection was simulated in sequence. There was some delay between the actions taking place for ex:

1. When the system was first started, the app got the status of the system model about theft and accident status after some 15 second delay
2. When eventually the theft got detected (after some seconds), the engine was shut off (after activating the immobilize feature on app) after quite a time (nearly 30 seconds) which isn't that great.
3. When the accident detection scenario was simulated (placing the accelerometer module upside down or tilting it through 90 degrees) the accident status on the app was updated after a delay of nearly 25 seconds which isn't desirable at all.

Off course had the internet speeds be faster, the delay between the said actions could have reduced to some degree. It's clear that the vehicle tracker app does need some optimizations so that it updates as quickly as possible but the inherent internet speed problem is the major factor here. Except the delay problems, the simulation results were promising and there is room for improvements in the project.

V. CONCLUSIONS

Albeit no vehicle can be completely gotten, this undertaking expects to overcome any barrier among adaptability and security. This paper gives a sensible plan to accomplish and further develop security and preventive measures in the occasions of robberies and mishaps. IoT while still in its baby stage can possibly computerize an assortment of capacities partially and guarantee that cycles keep on working without human intercession. This project likewise attempts to enhance existing security frameworks which however give sensible security yet have specific deficiencies. There are regions in which the thought can be developed and further work on the power and abilities of the framework.

REFERENCES

1. M. A. Al-Tae, O. B. Khader, and N. A. Al-Saber, "Remote monitoring of vehicle diagnostics and location using a smart box with Global Positioning System and General Packet Radio Service," in Proc. IEEE/ACS AICCSA, Amman, pp. 385–388, 2007.
2. M. S. Joshi and D. V. Mahajan, "Arm 7 based theft control, accident detection and vehicle positioning system," International Journal of Innovative Technology and Exploring Engineering, vol. 4, no. 2, pp. 29-31, July 2014.
3. M.A.A. Khedher, "Hybrid GPS-GSM localization of automobile tracking system," International Journal of Computer Science and Information Technology, vol. 3, no. 6, pp. 75-85, Dec 2011.
4. J. R. Shaikh and S. M. Kate, "Arm7 based smart car security system, International Journal of Engineering Trends and Technology, vol. 3, no. 2, pp. 210-212, March 2012.
5. J. M. Hu, J. Li, and G. H. Li, "Automobile anti-theft system based on GSM and GPS module," presented at the Fifth International Conference on Intelligent Networks and Intelligent Systems, Tianjin, China, November 1-3, 2012.



**Impact Factor:
7.512**



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details