



e-ISSN: 2319-8753 | p-ISSN: 2320-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 6, June 2021

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

**Impact Factor: 7.512**

9940 572 462

6381 907 438

[ijirset@gmail.com](mailto:ijirset@gmail.com)

[www.ijirset.com](http://www.ijirset.com)



# A Review on Hybrid Energy Storage System for Electric Vehicles

Shravan Jaiswal, Prof. Madhu Upadhyay

PG Student, Department of Electrical and Electronics Engineering, NRI Institute of Information Science & Technology, Bhopal, Madhya Pradesh, India

Department of Electrical and Electronics Engineering, NRI Institute of Information Science & Technology, Bhopal, Madhya Pradesh, India

**ABSTRACT:** Recently, expanded emission standards and a push for less dependence on petroleum derivatives also prompted an expansion in the market for electrified vitality cars. Rapidly open vitality storage frameworks (ESSs) serve as a litmus test for the mainstream consumer penetration of hybrid electric vehicles (HEVs), module HEVs, & electric vehicles (EVs). This is mostly due to exorbitant value of ESS available present-day. Regardless, significant study efforts are being made to decrease the cost of these capacity gadgets, extend their life span, and enhance their vitality thickness. This article intends to include an analysis of the current state of readily available battery & ultracapacitor (Known As UC) technologies as well as a glance forward to promoting advanced battery sciences and cutting-edge ESS. Apart from battery state/parameter calculation and assurance elements, energy management frameworks & various battery changing designs are discussed.

**KEYWORDS:** Electric vehicle, hybrid, energy, storage

## I. INTRODUCTION

At this moment, which start from the usage of non-environmentally friendly power sources caused outpouring of dirtying gases into the climate making the necessity for change in versatility penchants in the present each day life. [1-5]

Photovoltaic modules have gotten an opportunity for feasible force source with respect to nuclear family and business applications. EVs and PHEVs introduce themselves accessible not similarly as advancement for decline of sullyng gases, yet likewise as a technique for improving energy profitability. [6]

ESS would be vulnerable to confined characteristics like preference, need, versatility, lifetime, and so on If you ignore all the drawbacks and focus instead on the positive points, the Systems Unit's system is workability and flexibility makes it a potentially implementable scenario. [7] Regardless, the HESS principle was expansive in thought and nevertheless created an impact on the fundamental tendencies, even as it focused on a far more narrow level of operation. [8] The HESS system should have the flexibility to allow for different components to be included while maintaining controllability, which can then be managed efficiently; and components that are modified should have the ability to utilise either organisation strategy, which means the HESS should have adaptability. [9-10] This paper reviews energy storage system in brief.

## II. ENERGY STORAGE SYSTEM

Plan-in-to-place that provides for planned and more long-term management of the electrical vitality. The diversity of advancements (such as lead-corrosive, lithium-corrosive, and so on) organised in a matrix can help alleviate the downsides and promote generalisation.




Fig. 1: Hybrid storage system (Battery/Supercapacitors) for electric vehicles.




Fig. 2: Weight of hybrid embedded power




Fig. 3: RMS power stress applied to battery cell



the electric vehicle's relative expansion: a used electric vehicle growing be more or less expensive than a similar one that is new. Since running a simulation (Fig. 3.2), it is also obvious that the half-breed EMS3-expandable power supply weighs less than the whole-mercure power supply around the vehicle range of motion. For both actions, there are two periods of time, whether taking or not taking, there are two steps from which the weight of evidence may be advanced. When you have an established weight, the weight expansion rate is one percent per working degree, and when you increase the vehicle weight by one percent as the vehicle is driven. This mechanism explains how the coherent and more rigorous half and one-power principal theory measured under discharge is present charging, whereas the less stringent charge and half-power schemes are each time is used with vitality. Additionally, in the second step, the degree of energy at which the vehicle can expand energetically is contingent on the initial viability of the expansion options. In the most practical way, many of the critical forces and functions were placed on the final scale of the supply network in this last time.

The expanded RMS weight shown in Figure 3 shows the weight to one cell in total of each configuration. By supplying us with this item, this examination, we are able to start the initial battery expansion. as battery voltage is imbalances and among the greatest causes of controller failures, we avoid the battery management system to prevent it from being manipulated when the cells in a controller have differences in voltage Because of the existence of the BMS, it is further predicted that the assistance at the charging and discharging stages would be constant. Due to the relationship between E-RMS requirement and RMS power consumption, half and half power supply in the intensive operation of unrelenting weight, a significant amount of RMS is generated in the time frame of unrelenting weight. Having under estimated the vehicle power requirements, this turned out to be a much more entertaining plan for setting the vehicle on the single HP (type of battery) instead of making an expensive compromise on an unequal arrangement. half and half power supplies EMS1 and EMS2 are given an RMS amplitude equal to working degree, offering low RMS amplitude for engine operating tension. These inferences may be made, since the battery pack itself is said to hold an infinite quantity of electrons.




Fig. 4: Multiphysics model of the hybrid energy storage system.

HEC model (Fig. 4) has been constructed in the context of the expansion of the types of material used for the experiment (Figure 3), to serve as a foundation for the restricted power flow guideline. in different industrial environment ranges of size and scope, diversification preceding commercial scale were investigated for simple and economic e-bikes. As was determined, using this model, the lifespan of the Li-part battery and supercapacitor was seen to be impacted by the amount of charge cycles and/expansions.



### III. CONCLUSION

The concept of Hybrid Energy Storage System stems from realisation that heterogeneous Energy Storage System technologies have complementing properties when it comes to things like power& energy density, service life, reaction time& so on. What this means is that the faster reaction rate that is provided by high power ESS devices is in contrast to the slower response rate that is provided by high energy ESS devices. Because of this, it could be desirable to integrate several kinds of ESS technologies in manner which unify the functional benefits of two heterogeneous current ESS technologies. As a result, this hybridization offers exceptional properties that are not found in a single ESS unit. This innovative technology has been suggested & explored by various researchers in areas of renewable energy & electric mobility. In this context & according to an exhaustive literature investigation, this study intends to evaluate idea of the HESS, hybridization principles & power electronics interface designs, potential topologies, control & energy management methodologies& application fields.

### REFERENCES

- [1] Linda Barelli ID et al., “Dynamic Analysis of a Hybrid Energy Storage System (H-ESS) Coupled to a Photovoltaic (PV) Plant” 10 January 2018; Accepted: 2 February 2018; Published: 8 February 2018
- [2] Mohamed, Naoui & Flah, Aymen & Mouna, Ben. (2019). Wireless Charging System for a Mobile Hybrid Electric Vehicle. 10.1109/ISAECT.2018.8618829.
- [3] Terzi, Ümit & İlhan, Hüseyin & Kaymaz, Habib & Erdal, Hasan & Çalik, Hüseyin. (2020). A Review of Commercial Electric Vehicle Charging Methods. PROMET - Traffic&Transportation. 32. 291-307. 10.7307/ptt.v32i2.3252.
- [4] Al-Otaibi, Mutlaq. (2020). Self-Charging System for Electric Vehicles. Innovative Systems Design and Engineering. 10.7176/ISDE/11-5-04.
- [5] Younghyun Kim, et al., “Computer-Aided Design and Optimization of Hybrid Energy Storage Systems” Electronic Design Automation Vol. 7, No. 4 (2013) 247–338 c 2013
- [3] Ian C. Smith et al., “Benefits of Battery-U Ultracapacitor Hybrid Energy Storage Systems” May 17, 2012,
- [6] Karl BA. et al., “Design and Evaluation of Hybrid Energy Storage Systems for Electric Powertrains” Waterloo, Ontario, Canada, 2010 © Karl BA. Mikkelsen 2010
- [7] S. Pirienkoet al., “Optimization of Hybrid Energy Storage System for Electric Vehicles” Manuscript received: September 15, 2016; accepted: November 24, 2016.
- [8] Tobias Anderssona , et al., “Alternative Energy Storage System for Hybrid Electric Vehicles” IEEE AES magazine, p14- 19, 1992
- [9] M. Gopikrishnan et al, “Battery/ultra-Capacitor Hybrid Energy Storage System for Electric, Hybrid and Plug-in Hybrid Electric Vehicles” Middle-East Journal of Scientific Research 20 (9): 1122-1126, 2014
- [10] Xiaodong Zhang, et al., “A Multi-hybrid Energy System for Hybrid Electric Vehicles” World Electric Vehicle Journal Vol. 4 - ISSN 2032-6653 - © 2010 WEVA



**Impact Factor:  
7.512**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  [ijirset@gmail.com](mailto:ijirset@gmail.com)



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details