



e-ISSN: 2319-8753 | p-ISSN: 2320-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH


IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 5, May 2021

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 7.512

 9940 572 462

 6381 907 438

 ijirset@gmail.com

 www.ijirset.com

Modelling Of Recycled Aggregate Concrete Using Programming Languages

Miss Vartika Sahu¹ N. K. Dhapekar²

Research Scholar, Department of Civil Engineering, Kalinga University, Naya Raipur Chhattisgarh, India¹

Assistant Professor, Department of Civil Engineering, Kalinga University, Naya Raipur Chhattisgarh, India²

ABSTRACT: Concrete is the most important material in the construction industry. The amount of construction and demolition waste has increased significantly of late. This causes many environmental problems. Therefore, disposal of demolition waste is inevitable to solve environmental problems. This paper aims at developing models to predict the recycled aggregate concrete (RAC) compressive strength and Interfacial Transition Zone (ITZ). Writing computer programs is utilized to tackle many plan issues that are hard to settle by regular strategies for designing mechanics. Software has been read the data from previous research paper and analyse the outcomes at different Percentages of micro silica and recycled coarse aggregate. We are going to present an approach to modelling Of Recycled Aggregate Concrete Using Programming Languages. Results show that the t predictive performance compressive strength of recycled aggregate concrete with micro silica. This paper targets to a predictive approach to cost-saving RAC mixture designs.

KEYWORDS: Micro-silica, Demolition, Compressive Strength, Recycled Aggregate Concrete (RAC), Programming Languages.

I. INTRODUCTION

Programming languages are instructions for creating programs. This program language is used across all industries, including the civil engineering dependent sectors, to program and create software that improves the performance of many system. We model the problem of solving a code by calculating the probability of a program similar to how a language model calculated the probability of a natural statement in language. Civil engineering software includes several tools to assist civil engineers through the design and construction process. Concrete is most significant material utilized in the development industry. Concrete is most significant material employed in the construction business. Great amount of natural aggregates were employed in concrete, this causes the character. Currently a day's many structures square measure razed & restored, razing of structures causes drawback with marketing of stuff. Recycled aggregates has small cracks on its surface causes low strength, low workability of concrete. This recoil will be avoided by micro silica. During this paper experimental results were shown for recycled combination incorporating with micro silica.

Concrete could be a heterogeneous material comprising fine aggregate, coarse mixture, potable water and also the binder known as cement. The presence of coarse aggregates contributes additional to the non uniformity. Associate mixture consumes concerning 60% to 75% of the volume of concrete. During the crushing method and because of having loose mortar cover on surface of combination, Recycled combination has small cracks on that. As a results of this, bond between cement and aggregate is weak. This is often answerable for the low concrete strength and low workability. The employment of mineral admixture (i.e. micro silica) might enhance the physical and engineering properties of recycled combination concrete. Small silicon oxide contributes each physically and with chemicals in concrete combine. The size of small silicon oxide particles is smaller than that of cement.

Computers are an integral part of the construction industry. Coding is not an important part of the civil engineering curriculum, but it is an essential skill in modern life. We collect data from Poonam S. Suryawanshi¹, V.G.Patwari² Standard recycled aggregate concrete in incorporate with micro silica Volume: 07 Issue: 02 | Feb 2020 and analyze raw data from other studies, and briefly develop predictions using software that predicts unexpected recycled concrete yield in their research.



II. MATERIAL

Cement

Cement used is standard Portland cement. (OPC). the color of the cement is thanks to iron chemical compound. within the absence of impurities, the colour of cement is grey. standard Portland cement (OPC) – fifty three grade (Birla Sakti Cement) is employed.

Fine Aggregate

Crushed sand is employed that is additionally referred to as as artificial sand which is regionally offered in close space having specific gravity 2.63.

Coarse Aggregate

Natural coarse combination used that square measure regionally obtainable. Aggregates have relative density a pair of .79. 20mm & 10mm size of aggregate were use, in 60% & 40% severally.

Recycled Coarse Aggregate

Aggregate was obtained from faculty field, the beam & cube casted for testing purpose was crushed & 20mm & 10mm combination were separated by sieving. Aggregates having mortar layer over the surface, and having micro cracks on that that the water absorption, density and bonding with cement paste were low. this could provide end in low feasible concrete and low strength of concrete.


Impurities in Recycled Coarse Aggregate

The presentation of reused coarse total can be decreased because of the presence of debasements, which exuded from destruction measure including permeable mortar and concrete glue connected to the parent total. The impact could likewise prompt general decrease in qualities of reused total cement. A portion of the debasements distinguished through visual review from the reused coarse total.


The normal rate debasements present in the reused coarse total added up to about 5% of the absolute mass of the example. In spite of the fact that there is visual proof to show the presence of followed mortar on the parent material, it was essentially difficult to appraise their rate. In any case, the followed mortar doesn't appear to be of huge amount yet its effect on the qualities of reused coarse total cement can't be ignored.

Micro Silica

Miniature silica utilized is ASTM C1240 of cetex brand, having explicit gravity 2.11. At the point when water is added to solidify, hydration happens as appeared underneath:-



The free lime doesn't add to strength, when joined with carbon dioxide; it frames a dissolvable salt, which drains through the solid causing flower, a natural building issue. Concrete is additionally more helpless against compound assault and deterioration, when it is added, the accompanying response happens.



The response diminishes the measure of calcium hydroxide in the concrete.

Typical properties of microsilica

Form	Description
Colour	Grey
Odour	Odorless
Solubility	Insoluble
Specific gravity	2.11
Bulk density	0.416



Water

Water fit for drinking is by and large thought to be good for making concrete. Water ought to be liberated from corrosive, oils, salts, vegetables or other natural pollutions. Delicate water moreover produces more fragile cement. Water has two capacities in concrete blends. Initially, it responds artificially with the concrete to frame a concrete glue wherein the idle totals are held in suspension until the concrete glue has solidified. Besides, it fills in as a vehicle or grease in the combination of fine total and concrete.

III. CONCRETE MIX DESIGN

This table taken from the paper Poonam S. Suryawanshi¹, V.G.Patwari² Standard recycled aggregate concrete in corporate with micro silica Volume: 07 Issue: 02 | Feb 2020 e-ISSN: 2395-0056 p-ISSN: 2395-0072 International Research Journal of Engineering and Technology (IRJET).

Take data from the paper and the software is read that data and predict values of compressive strength and interfacial transition zone.

Table No:1 Concrete Mix Design

RCA (%)	0%	25%	50%	75%
Cement (Kg/m ³)	350.00	350.00	350.00	350.00
Sand (Kg/m ³)	663.83	663.83	663.83	663.83
Gravel (Kg/m ³)	1270.76	953.07	635.68	317.69
RCA. (Kg/m ³)	0.00	317.69	635.68	953.07
Water (Kg/m ³)	154.00	154.00	154.00	154.00
Micro silica (Kg/m ³)				
5%	0	17.5	17.5	17.5
10%	0	35.00	35.00	35.00
15%	0	52.50	52.50	52.50

Table No:2 Result of compressive strength (Mpa) test for concrete mix

RCA (%)	0%MS	5%MS	10%MS	15%MS
0	34.7	34.69	36.34	25.20
25	19.38	23.80	34.50	33.18
50	17.16	-	-	-
75	23.5	-	-	-

From the software the following results are obtained for various percentages and the value of compressive strength and Interfacial Transition Zone (ITZ) are predicted which are mention below in the following table and this values are not experimented by the researchers.

Table No:3 Result of compressive strength (Mpa) and interfacial transition zone (nm) in software

Description	MS 10% RA 15%	MS 10% RA 30%	MS 10% RA 40%	MS 12% RA 30%
Cement (kg/m ³)	350	350	350	350
Sand (kg/m ³)	663.88	663.88	663.88	663.88
Course Aggregate (kg/m ³)	1080.146	889.532	762.456	889.532
Recycled Aggregate (kg/m ³)	190.614	381.228	508.304	381.228
Micro Silica(kg/m ³)	35	35	35	105
Water (kg/m ³)	154	154	154	154
Specific Gravity (CA)	2.79	2.79	2.79	2.79
Specific Gravity (FA)	2.69	2.69	2.69	2.69
Compressive Strength (28 Days)	27.71	28.24	27.33	28.5
Interfacial Transition Zone	15.48	42.84	15.25	15.96

On the table shows that, using of 10% micro silica give good compressive strength, so here take 10% micro silica and recycled aggregate of 15% enhance the strength of compressive strength but 30% & 40% of recycled aggregate and 12% micro silica with 30% recycled aggregate the compressive strength has been decrease. Natural/Virgin aggregates taken 1270.76kg/m³.

IV. RESULT AND DISCUSSION

In this paper to know the properties of concrete having reused totals join with micro silica for discovering compressive strength test and Interfacial Transition Zone (ITZ). Usually researchers used 5% 10% 15% micro silica and 25% 50% 75% of recycled aggregate and find compressive strength but in this paper we find in easy way to calculate compressive strength to using another percentages of recycled aggregates using programming.

Observe that 10% micro silica give good compressive strength, so here take 10% micro silica and recycled aggregate of 15% enhance the strength of compressive strength but 30% & 40% of recycled aggregate and 12% micro silica with 30% recycled aggregate the compressive strength has been decreases.

V. CONCLUSION

Subsequently from the outcomes we can presume that Micro silica improves the strength as referenced before. At 10% micro silica with 0% recycled aggregate total compressive strength will increments by 36.34Mpa. The increment of recycled aggregate from 15-40% with the assistance of programming it is seen that compressive strength is diminishing to 36.34 to 27.33 with the expansion of recycled aggregate. The water ingestion of recycled aggregate total is more as

contrast with the normal aggregate. The joining of micro silica, fundamentally improves properties of recycled v aggregate concrete up to 10% past which it get declines. As the level of micro silica increments usefulness of cement get diminishes.

REFERENCES

- [1] . Poonam S. Suryawanshi;V.G.Patwari;Feb 2020.Standard recycled aggregate concrete in corporate with micro silica, International Research Journal of Engineering and Technology (IRJET),Volume: 07 Issue: 02 e-ISSN: 2395-0056 p-ISSN: 2395-0072.
- [2] Prof.N.K.Dhapekar;Prof.Govardhan Bhatt;Ahsan Rabbani;Pooja Sikdar;2017.Hypothesis testing of road traffic accident data in India,International Journal of Civil engineering and technology,Volume 8,Issue 6,PP.430-435.
- [3] N.K.Dhapekar;SP Misra;2017.Effective utilization of construction and demolition waste concrete-review, Research Journal of engineering sciences,volume 6,Issue7,PP.52-54.
- [4] N.K.Dhapekar;2013.Structural health monitoring of historical monuments by rapid visual VISUAL SCREENING: CASE STUDY OF BHAND DEVAL TEMPLE, ARANG, CHHATISGARH, INDIA;2013. International Journal of Civil,Structural,Environmental and infrastructure engineering research and development(IJCSEIERD),Volume 3,Issue3,PP.131-141.
- [5] Verma Ajay;Chandak Rajeev and Yadav R.K.;2012. Effect of Micro Silica on The Strength of Concrete with Ordinary Portland Cement,IJSR Vol. 1(3), 1-4, Sept.
- [6] Nwzad Abduljabar Abdulla 2014; Effect of Recycled Coarse Aggregate Type on Concrete. ASCE
- [7] N.K. Dhapekar;SP Mishra;2017 Effective utilization of construction and demolition waste recycled concrete-Review, Research Journal of Engineering, Volume 6,Issue 7,PP.52-55.
- [8] Prof.N.K.Dhapekar;Ashelsha Deshmukh;Prof.Ahsan Rabbani;2017. Study of rigid pavements-review, International Journal of Civil Engineering & Technology (IJCET), ,Volume 8,Issue 6,PP.142-152.
- [9] Prof.N.K.Dhapekar; Govardhan Bhatt;Ashlesha Deshmik;,Ahsan Rabbani;2017. Design of rigid pavement-Hypothesis, International Journal of civil engineering and technology,Volume 8;Issue 6,PP.450-456.
- [10] N.K.Dhapekar;2012. Design principles for earthquake resistant and post earthquake study by structural engineering perspectives, international journal of advances in management ,technology and engineering sciences.(IJAMTES),Volume 1,Issue 8, PP.49.
- [11] N.K. Dhapekar; Comparative study of analysis of plane trusses with and without axial deformation with three degree of freedom, International journalof advances in management technology and engineering science,Volume 2,Issues 2,PP.142.
- [12] N.K. Dhapekar; Sandeep Sahu; Experimental Investigation by ETABS software on G+15, International journal of advance research and innovative ideas in education,Volume 6,PP.1800-1808.
- [13] Nwzad Abduljabar Abdulla;2014. Effect of Recycled Coarse Aggregate Type on Concrete.
- [14] . Rattapon Somna;Chai Jaturapitakkul;A.M.ASCE;Wichian Chalee;Pokpong Rattanachu 2012, “Effect of the Water to Binder Ratio and Ground Fly Ash on Properties of Recycled Aggregate Concrete”. ASCE.
- [15] Viviana Letelier;Ester Tarela;Pedro Munozb;Giacomo Moriconi;2016. Combined effects of recycled hydrated cement and recycled aggregates on the mechanical properties of concrete. Science Direct



INNO  **SPACE**
SJIF Scientific Journal Impact Factor

**Impact Factor:
7.512**

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details