

e-ISSN: 2319-8753 | p-ISSN: 2320-6710

EDIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

808

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 5, May 2021

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 7.512

9940 572 462

6381 907 438

 \odot

🖂 ijirset@gmail.com





| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

Constructed Wetland For Domestic Wastewater Treatment : A Review

Prof. Amit Kharwade ¹, Vaibhav .K. Rathod ², Ajay .P. Makde ³, Kajal .A. Badodekar ⁴,

Chetan .M. Raut ⁵, Sumeet .D. Meshram ⁶, Namrata .B. Sakhare ⁷

Professor, Civil Engineering, Nagpur Institute of Technology, Maharashtra, India¹

Student, Civil Engineering, Nagpur Institute of Technology, Maharashtra, India

ABSTRACT : Constructed wetlands have acquired a lot of significance for treating homegrown, modern and farming squanders and are considered as a viable optional or tertiary treatment strategy. The fundamental qualities influence the expulsion effectiveness of Constructed wetland are the vegetation type, pressure driven home time and substrate. The job of materials, plants and creation microorganisms have appeared as a sign of a superior pace of corruption. Constructed Wetlands (CW) are designed wastewater treatment frameworks loaded up with permeable media and planted with developing wetland plants. Water defilement is a significant issue world is confronting today and the kitchen squander is one of the significant variables. It is discovered that phytoremediation is one of the powerful strategies for the expulsion of poisons from water and soil. Phytoremediation comprise of media beds, plants, miniature organic entities which is primarily relies upon physical, compound and natural action to eliminate the toxins. Wastewater treatment by Constructed wetland allowed in a non-industrial nation. It is performed for the evacuation of biochemical oxygen interest, substance oxygen interest, suspended strong, smelling salts and nitrogen from pre-treated homegrown wastewater, the treatment of wetland convey under two pressure driven stacking for example

 3 cm d^{-1} and 6 cm d^{-1} , the treatment of wastewater by developed wetland diminish COD by 41

- 73% for bay natural stacking and 1602kg ha⁻¹ d ⁻¹ furthermore, the BOD lessen by 41 - 58% in natural stacking. Phragnites Australis, Canna, Typha, Reed, lotifolia are the plants used effectively in Constructed Wetland.

KEYWORDS: Constructed Wet land, Phyto-remediation, cana-indica, occasional variety, Artificial wetland

I. INTRODUCTION

Current cultures have built enormous concentrated waste water treatment offices that treat huge volumes of water utilizing both substance and natural cycles. this interaction comprises of minimal effort medicines and built by locally accessible material. as contrast with traditional waste water medicines the expense of such medicines are less. Developed wetland was one of the waste water treatment frameworks that had been underlying numerous spots on the planet to deal with squander water from settlement, mechanical, rural and numerous other water contamination source s. execution of a developed wetland was impacted by the plan, substrate, plant and maintenance time. The Constructed wetland strategy utilized for the essential, optional and tertiary treatment of homegrown wastewater and mechanical wastewater, by utilizing CW technique we can treat modern waste contain high



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

II. LITERATURE REVIEW

2.1 Comparison Of Treatment Performance Between Constructed Wetlands With Different Plants G.Baskar1, V.T.Deeptha, R.Annadurai(Volume 3, Issue 1, January 2014)

The utilized Constructed wetland has end up being a dependable arrangement in created country, in this paper study site is situated in SRM University grounds Kattan kulathur. In reactor the foundations layer of rock, sand, and plant types of Phragmites and Typha Latifolia was utilized and HRT is 2468 days. the gulf chamber size $0.41 \times 0.21 \times 0.27$ m. in outlet chamber $0.12 \times 0.41 \times 0.27$ m. in this investigation pre-treated wastewater of sewage plant was dissected, boundary check for examination was contrasts both in quality and amount.

2.2 Full-Scale Experiment on Domestic Wastewater Treatment by Combining Artificial Aeration Vertical- and Horizontal-Flow Constructed Wetlands System Jizheng Pan & Houhu Zhang & Wenchao Li & Fan Ke.(2012) 223:5673–5683

In this examination join home grown wastewater treatment framework built between Daqing he stream and Hai he waterway around there, china and channel material utilized for bed was accessible locally around there. Fake air circulation VFCW with profundity 1.70 m having stream rate approx 1.60 m day m and maintenance time is 11.3 h, HCW having profundity 1.65 m and having stream rate 0.78 m day having maintenance time 18.7 h. The boundary incorporate for investigation are smelling salts, COD, BOD, SS and it is dissected by standard strategy.

2.3 Performance Studies on Wastewater Treatment Efficiency of an Artificial Wetland S. Ramakrishna Rao1,*, S. Bala Prasad, P. S. Raja Sekhar, S.A. Rahiman (VOL.2 NO.3, DECEMBER 2013 ISSN: 2165-8315)

In this paper Constructed wetland measure is utilized to treat kolleru lake water at Andhrapradesh, this water was dirtied by in move through little stream of untreated sewage water from close by town and human action. To treat this water monetarily they utilized fake developed wetland strategy, this water is treated in three unique seasons.

The counterfeit wetland lab model has been developed utilizing Perspex sheet, plan measurement is 1.5 m length, 0.3 m width and 0.6 m profundity. the model was loaded up with soil, vegetation brought from Kollaru lake, steady stream rate is approx. 1 liter/hour. the gulf and outlet wastewater test gathered from counterfeit wetland during Winter, Summer and Monsoon and examined in research center for checking boundary, for example, pH, EC, TDS, TSS, DO, BOD, COD, PO, NO3 depicted in standard strategy.

Chromium fixation and profound shading content, that cause the cut off natural issue. the significant motivation behind this innovation to treat balanced out pH wastewater in the long way. the Constructed wetland strategy showing the great control on natural materials contains supplement and microbe, treated wastewater by CW used to inundate yield, ground and development work.

2.4 Constructed Wetland for Wastewater Treatment and Rescue; A Case Study for Developing Country. AtifMustafa (Vol. 4, No. 1, February 2013)

In this paper the developed wetland strategy treatment is arranged in Karachi. The Max. temperature is

36^oC and least Min. 20^oC, water gathered from Staff Colony and Civil Colony. It contain home grown sewage and low stream from labs. The plan of developed wetland comprise of channel bed having delta



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

and outlet pipe with plant types of Phragmite Karka. test water is gathered in plastic jug and boundary, for example, BOD, COD, DO, Nitrogen and Ammonia were broke down.

2.5 Constructed Wetland with Vertical Flow: Sustainable Approach to Treat Dairy Effluent by Phytoremedeation Patel Pratik A., DharaiyaNishith A.(Volume 3, Issue 1, January 2014)

Constructed wetland is designing wastewater framework by new plant wastewater, it is a mix of fluid or water conveyed squander from home, institutional and modern . the point of the examination was to dissected the dairy squander by Phyto-remediapion strategy utilizing TyphaAngustata and Phragmit Esaustralis. In present examination subsurface stream framework are utilized to treat dairy effluents in group measure utilizing two types of hydrophytes and expulsion different poisons from dairy squander. developed wetland was built by division of life sciences, HNG University.

In this framework T. Angustata and P. Australis with vegetation from lake in Baspa Village of Patan. the model was

comprised of plastic had measurement $0.82m \ge 0.54m \ge 0.73m$. volume of bed is $0.32m^3$, surface space of bed is 0.44m. Porosity of sub layers is 100. test was required day by day following 24 hour and examination done according to APHA standard strategy.

III. WHAT IS CONSTRUCTED WET LAND (CTW)

In the field of wastewater treatment, energy-intensive and highly mechanized technologies are giving way to naturebased technologies that utilize solar energy and living organisms.

Constructed treatment wetland (CTW) technology has played an important role in bringing about the change. Wetland technology can provide cheap and effective wastewater treatment in both temperate and tropical climates, and are suitable for adoption in both industrialized as well as developing nations. Currently, CTWs are being utilized for removal of a range of pollutants and a broad variety of wastewaters worldwide. The objective of this article is to provide a comprehensive review of the CTW technology and to present the pollutant removal performance experiences gathered through the application of this technology around the world.

IV. WORKING AND PRINCIPALS

As energy and construction costs have increased, new methods of wastewater treatment with potentially lower energy and capital costs have become increasingly attractive. Relatively simple wastewater technologies can be designed to provide low cost sanitation and environmental protection while providing additional benefits from the reuse of water. Effluents from conventional treatment kilties not only contain some unstable organic matter but also nutrients, which represent potential energy. It is therefore illogical to utilize external energy sources to dissipate energy stored within the wastewater. A natural treatment system makes use of aquatic animals and plants to improve the water quality and reclaim nutrients. In addition, persistent toxic environmental contaminants such as pesticides, aromatic hydrocarbons and metal scan be removed from wastewater through biological treatment process. Natural wastewater treatment systems include algal mass culture, macro-phyte treatment systems (including constructed wetlands) and aquaculture. Natural systems maybe utilized to treat agricultural, domestic and industrial wastewater. Climate, soil conditions, space, waste characteristics and other factors relate to its applicability.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| www.ijirset.com | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

V. TYPE OF PLANT USED IN CONSTRUCTED WETLAND

Wetland plants which have a few properties identified with the treatment cycle could assume an essential part in CW, and are considered to be the fundamental segment of the plan of CW treatments. Be that as it may, a couple of plant animal types have been broadly utilized in Constructed wetlands. Choosing plants utilized in CW ought to hence be the focal point of the flow research on economical plans of CW. For the choice of plants, resilience of waterlogged anoxic and hyper eutrophic conditions and limit of contamination assimilation are prescribed other than adaption to contemptable environments.

1) Typhas

The typhas are aquatic or semi aquatic, rhizomatous, herbaceous perennial plants. Typhas are often the among the first wetland plants to colonize area of newly expose wet mud. It absorb the impurities from the water, its Major role to absorb Nutrients from the wastewater.



Fig.1 Typhas Plant

2) Eichhornia crassipes

It is also known as common water hyacinth, is an aquatic plant native to the amazon basin, A nd is often to highly problematic invasive species outside its native range. The three commonl y used control methods against water hyacinth infestations are physical, chemical and biologi cal controls. The roots of Eichhornia crassipes naturally absorb pollutants, including lead, mer cury, and strontium-90, as well as some organic compounds believed to be carcinogenic, in co ncentrations 10,000 times that in the surrounding water. Water hyacinths can be cultivated for waste water treatment. To reduce the impurities from the water.



Fig.2 Eichhornia Crassipes



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

VI. MATERIALS SELECTION IN CONSTRUCTED WETLANDS

The materials are the critical design parameter in CW and SSF CW specifically, on the grounds that it can give a reasonable developing medium to plant and further more permit successful movement of wastewater through it. Besides, substrate sorption may assume the main part in engrossing different toxins like phosphorus. Choice of reasonable materials to use in CW for domestic waste water, and for modern wastewater treatment is a significant issue.

For the choice of wetland material particularly for practical phosphorus expulsion from wastewater, and the oftentimes utilized substrates basically incorporate normal material, artificial media and industrial by products, like rock, sand, mud, calcite, marble, ver miculite, slag, fly ash, bentonite, dolomite, limestone, shell, zeolite, wollastonite, initiated carbon, light weight aggregate. Results from these examinations likewise recommend that substrates like sand, gravels, and rock are the helpless possibility for longterm phosphorus stockpiling, yet on the other hand, artificial and industrial byproducts with high Hydraulic conductivity and phosphorus sorption capacity could be alternative substrates in CW.

Type of Material commonly used in CW world wide :

Natural material- sand, gravel, clay, calcite, marble, vermiculate, bentonite, dolomite, lime stone, shell, shale, peat, wollastonite, maerl, zeolite.

Industrial By- Products- slag, fly ash, coal, alumsludge, hollow brick crumbs, moleanos limestone, wollastonite tailings.

Artificial products - Activated carbon, Light weight aggregates

VII. FEEDING TO THE PLANTS

The feeding mode of influent has been demonstrated to be another significant plan boundary. The distinction of feeding mode , (for example, constant, batch and irregular) may influence the oxidation– decrease conditions and oxygen transfer and diffusion in wetland frameworks and, thus, adjust the treatment efficiency. Different investigations were directed to assess the impact of influent feeding mode on the expulsion efficiency of CW treatments. By and large, batch feeding mode can get the better execution than consistent activity by advancing more oxidized conditions. explored the influence of cluster versus ceaseless flow on the expulsion efficiencies in tropical SSF CWs. They demonstrated that the wetlands with clump flow mode showed significantly higher ammonium evacuation efficiencies (95.2%) contrasted and the consistently taken care of frameworks (80.4%). How-ever, there still exists vulnerability about whether group activity Results showed that the intermittent feeding mode enhanced the ammonium removal effectively in CW without any significant effect for FWS flow in CW

| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163



Fig. 3. Summary of present improvements and the elements of CW

VIII. CONCLUSION & FUTURE SCOPE

This study based review described that the features for CW construction and procedure such as plant selection, material selection, loading rate, and feeding mode are crucial to achieve the maintainable treatment performance. Seeing the successful and maintainable application of full-scale CW, future studies should focus on the experimental treatment of domestic waste water treatment by using CW reactor and the suggested study parameters are pH, Biological Oxygen Demand (BOD), Nitrate, Conductivity and Turbidity.

REFERENCES

[1] Performance studies on wastewater treatment efficiency of an artificial wetland s. ramakrishna rao1,*, s. bala prasad, p. s. raja sekhar, s.a. rahiman (vol.2 no.3, december 2013 issn: 2165-8315)

[2] Constructed Wetland with Vertical Flow: A Sustainable Approach to Treat Dairy Effluent by Phytoremedeation Patel Pratik A., Dharaiya Nishith A.(Volume 3, Issue 1, January 2014)

[3] Comparison Of Treatment Performance Between Constructed Wetlands With Different Plants G.Baskar1, V.T.Deeptha, R.Annadurai (Volume 3, Issue 1, January 2014)

[4] Full-Scale Experiment on Domestic Wastewater Treatment by Combining Artificial Aeration Vertical- and Horizontal-Flow Constructed Wetlands System Jizheng Pan & Houhu Zhang & Wenchao Li & Fan Ke.(2012) 223:5673–5683

[5] Constructed Wetland for Wastewater Treatment and Rescue; A Case Study for Developing Country. Atif Mustafa (Vol. 4, No. 1, February 2013)

[6] Reed. S.C.. Middle brooks. E.J.. Crities. P.W. Natural systems for waste Management and treatment. McGraw Hill. New York. NY. 1988.



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.512|

||Volume 10, Issue 5, May 2021||

DOI:10.15680/IJIRSET.2021.1005163

[7] Reed. S.C. Nationwide Inventory: Constructed Wetlands for Wastewater Treatment. Biocycle 1991;

32(1): 44-49. [8] UN-Habitat, Constructed wetlands manual, Nepal, Kathmandu, 2008.

[9] A. Upadhyay, Aquatic Plants for the wastewater Treatment: Daya Publishing House, Delhi, India, 2004.

[10] Keffala C., Gharbi.A., 2005. Nutrient and bacterial removal in constructed wetlands treating domestic wastewater. Desalination 185. 383-389.

[11] Shuh-Ren Jing, Yin-Feng Lin, Der-Yun Lee, Tze-Wen Wang, 2001. Nutrient removal from polluted river water using constructed wetlands. BioResource Technology 76. 131-135.

[12] APHA-AWWA-WPCF. (2001). Standard methods for the examination of water and wastewater (20th ed.). Washington, DC: American Public Health Association.

[13] Bezbaruah, A. N., & Zhang, T. C. (2003). Performance of a constructed wetland with a sulfur/limestone denitrification section for wastewater nitrogen removal. Environmental Science and Technology, 37, 1690–1697.

[14] Z. Song, Z. Zheng, J. Li, X. Sun, X. Han, W. Wang, M. Xu, "Seasonal and annual performance of a full-scale constructed wetland system for sewage treatment in China," Ecological Engineering, vol. 26, no. 3, pp. 272-282, March 2006.

[15] U.S. Guidelines for Water Reuse, Environmental Protection Agency, Report No. EPA/625/R -04/108, Cincinnati, OH, USA, 2004.



Impact Factor: 7.512





INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com