



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJIRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 10, Issue 5, May 2021

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 7.512



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

# Thin-Film Displays based on Light-Emitting Polymer Technology

**Pradeep V**

Lecturer in Electronics Engineering, Government Polytechnic College, Nedumangad,  
Thiruvananthapuram, India

**ABSTRACT:** Light-Emitting Polymers (LEPs), also known as polymer light-emitting diodes (PLEDs), have emerged as a promising class of materials for next-generation thin-film display technologies. Their unique advantages, including solution processability, flexibility, lightweight nature, and tunable emission characteristics, make them highly attractive for a wide range of applications, from foldable smartphones to large-area signage and wearable electronics.<sup>1</sup> This paper provides a comprehensive overview of the fundamental principles behind LEP operation, recent advancements in materials science and device architecture, and the challenges and future prospects for their widespread adoption in thin-film displays. Key areas of discussion include synthesis and characterization of emissive polymers, charge injection and transport mechanisms, device fabrication techniques, and strategies for improving efficiency, lifetime, and color purity.

## I. INTRODUCTION

The display industry is constantly seeking innovative materials and technologies to enhance performance, reduce cost, and enable new form factors.<sup>2</sup> Traditional display technologies, such as liquid crystal displays (LCDs) and inorganic light-emitting diodes (LEDs), have achieved significant success, but often face limitations in terms of flexibility, transparency, and manufacturing complexity for large-area applications. Organic light-emitting diodes (OLEDs), particularly those based on small molecules, have revolutionized the display market with their self-emissive nature, high contrast ratios, fast response times, and thin profiles.<sup>3</sup> However, the vacuum deposition techniques typically employed for small-molecule OLEDs can be costly and challenging for large-scale production and flexible substrates.

Light-Emitting Polymers (LEPs), also known as polymer light-emitting diodes (PLEDs), are a class of organic materials that exhibit electroluminescence. Discovered in 1990, LEPs emit light when an electric current is passed through a thin film of the polymer. This phenomenon arises from the recombination of electrons and holes within the conjugated polymer structure, leading to the emission of photons.

Light-Emitting Polymers (LEPs), offer an exciting alternative to small-molecule OLEDs. LEPs combine the desirable optoelectronic properties of organic semiconductors with the advantages of polymer processing, such as solution casting, ink-jet printing, and roll-to-roll manufacturing.<sup>4</sup> This enables the fabrication of large-area, flexible, and potentially lower-cost displays. This paper will delve into the science and technology of LEPs, highlighting their potential to drive the next wave of innovation in thin-film display applications.

LEPs have emerged as a promising technology for thin-film displays due to their unique properties, offering an alternative to traditional display technologies like Liquid Crystal Displays (LCDs) and Cathode Ray Tubes (CRTs).

## II. FUNDAMENTALS OF LIGHT-EMITTING POLYMERS

LEPs (Light Emitting Polymers) are conjugated polymers that exhibit electroluminescence when subjected to an electric field. The typical architecture of an LEP-based display involves a multilayer structure comprising an anode, a hole transport layer, an emissive layer, an electron transport layer, and a cathode. The emissive layer is often composed of a polymer blend that facilitates efficient charge injection and light emission.

## 2.1 Basic Structure

An LEP device is generally composed of several thin organic layers, including a semiconducting polymer film, placed between two electrodes. Crucially, at least one of these electrodes is transparent. In a typical LEP display, the semiconducting polymer film is positioned between an anode, which is usually transparent (e.g., Indium Tin Oxide - ITO) and a cathode, often made from a low work function metal. This entire assembly is then deposited onto a substrate, which can be either rigid (like glass) or flexible (like plastic).

A typical LEP device architecture includes:

- Substrate: Can be rigid (glass) or flexible (plastic films like PEN, PI).
- Anode: Transparent and high work function (e.g., Indium Tin Oxide - ITO).
- Hole Transport Layer (HTL): Facilitates hole injection and transport, blocks electrons (e.g., PEDOT:PSS).
- Emissive Layer (EML): The active polymer layer where exciton formation and light emission occur.<sup>7</sup>
- Electron Transport Layer (ETL): Facilitates electron injection and transport, blocks holes (optional, but often used to improve efficiency).
- Cathode: Low work function for efficient electron injection (e.g., Ca/Al, Ba/Al).<sup>8</sup>

## 2.2. Fabrication Techniques

LEP based displays can be fabricated using various solution-based methods, offering significant advantages. Techniques such as spin coating, inkjet printing, and roll-to-roll processing enable the deposition of thin polymer films onto diverse substrates, including flexible ones. This versatility facilitates the production of lightweight and conformable display panels, opening doors for innovative product designs. Despite various hurdles, solution-based processing holds immense potential for cost-effective and scalable manufacturing of next-generation displays.

Advanced Fabrication Techniques are:

- Inkjet Printing: Enables patterning of individual pixels with different colors from solution, leading to efficient material utilization and large-area manufacturing.
- Slot-Die Coating and Blade Coating: Suitable for uniform deposition of large-area films, particularly for transport layers and emissive layers.
- Roll-to-Roll Processing: The ultimate goal for low-cost, high-throughput manufacturing of flexible LEP displays, allowing continuous production on flexible substrates.
- Laser Patterning: Used for defining pixel structures and removing unwanted material.

## 2.3. Working Principle

The core principle of operation involves the injection of electrons from the cathode and holes from the anode into the emissive polymer layer.<sup>6</sup> These charge carriers migrate under an applied electric field and recombine within the emissive layer to form excitons (bound electron-hole pairs). The radiative decay of these excitons results in the emission of light.

The working principle involves:

- Charge Injection: When a voltage is applied across the electrodes, electrons are injected from the cathode into the polymer's lowest unoccupied molecular orbital (LUMO), and holes are injected from the anode into the polymer's highest occupied molecular orbital (HOMO).
- Charge Transport: These injected charge carriers (electrons and holes) migrate through the polymer film towards each other.
- Exciton Formation: When an electron and a hole meet, they form a bound excited state called an exciton.
- Light Emission (Electroluminescence): As these excitons decay from their excited state back to the ground state, they release energy in the form of photons, resulting in visible light emission. The color of the emitted light is determined by the bandgap of the specific polymer used.

### III. CURRENT RESEARCH AND FUTURE TRENDS

Ongoing research and development in LEP (Light-Emitting Polymer) technology are actively addressing current limitations and hold significant promise for the future of thin-film displays.

Key areas of focus include:

#### 1. Material Innovation:

- Improved Light Emitting Polymers: Development of new, more stable, and highly efficient light-emitting polymers, with a particular emphasis on improving blue emission. Research into thermally activated delayed fluorescence (TADF) and exciplex-based emitters is ongoing to enhance efficiency.
- New Emissive Polymer Architectures: Designing novel polymer backbones and side chains to improve efficiency, stability, and color purity across the visible spectrum.
- Advanced Charge Transport Materials: Development of high-mobility, solution-processable, and stable charge transport layers.
- Efficient Blue Emitters: Continued focus on overcoming the efficiency and lifetime limitations specific to blue LEPs.

#### 2. Device Architecture and Manufacturing:

- Novel Device Architectures: Exploring new device structures to improve charge injection, transport, and light extraction efficiency.
- High-Resolution and Large-Area Displays: Continued efforts to scale up manufacturing processes for larger displays with higher pixel density, often in conjunction with advanced TFT (Thin-Film Transistor) backplanes (e.g., LTPS or IGZO).

#### 3. Protection and Durability:

- Advanced Encapsulation Technologies: Innovations in thin-film permeation barriers and the development of ultra-thin, highly effective barrier layers to protect the active layers from environmental degradation, especially crucial for flexible displays.

#### 4. Emerging Applications and Integration:

- Flexible and Wearable Electronics: Leveraging the inherent flexibility of LEPs to drive research into rollable, foldable, and transparent displays for next-generation consumer electronics, medical devices, and smart surfaces.
- Integrated Sensing Capabilities: Exploring the integration of sensors directly into LEP display panels for interactive functionalities.

#### 5. Advanced Methodologies:

- AI and Machine Learning Integration: Utilizing computational methods to accelerate the discovery and optimization of new LEP materials, and exploring AI's role in optimizing material design, predicting degradation, and enhancing display performance through intelligent control algorithms.

#### 6. Sustainability:

- Focusing on recyclable materials and energy-efficient manufacturing processes to reduce the environmental footprint of LEP displays.

### IV. EMERGING APPLICATIONS

- Flexible and Foldable Displays: LEPs are uniquely suited for truly flexible and foldable devices, enabling new form factors for smartphones, tablets, and laptops.<sup>15</sup>
- Wearable Electronics: Lightweight, flexible, and low-power LEPs are ideal for smartwatches, fitness trackers, and other wearable devices.<sup>16</sup>
- Transparent Displays: By engineering transparent electrodes and active materials, LEPs can be used to create transparent displays for augmented reality applications, smart windows, and automotive displays.
- Large-Area and Rollable Displays: The solution processability of LEPs makes them attractive for manufacturing very large displays for digital signage, electronic billboards, and rollable TVs.



- Lighting Applications: Beyond displays, LEs hold potential for solid-state lighting, offering tunable color temperature and flexible light sources.<sup>17</sup>
- Bio-integrated Devices: The biocompatibility of some polymers opens avenues for bio-integrated displays and sensors.

## V. CONCLUSION

Light-Emitting Polymers (LEPs), also known as PLEDs, represent a transformative and maturing approach to thin-film display technologies. Since their discovery, LEPs have evolved from laboratory curiosities into viable candidates for next-generation displays, offering significant advantages in flexibility, scalability, and cost-effectiveness due to their inherent solution processability, flexibility, and lightweight nature.

While challenges related to efficiency, lifetime, and manufacturing scalability persist, continuous innovation in materials science, device architecture, and fabrication techniques is rapidly addressing these limitations. Ongoing research and development efforts are consistently pushing the boundaries of what is possible with LEP-based displays.

As research progresses, LEP displays are poised to play a crucial role in shaping the future of visual technology. Their potential applications are diverse and expanding, ranging from consumer electronics and wearable devices to automotive interiors and smart infrastructure. Ultimately, LEPs are expected to enable highly versatile, energy-efficient, and aesthetically appealing visual experiences, contributing to a more immersive and interactive world.

## REFERENCES

1. Rees, I. D., Robinson, K. L., Holmes, A. B., Towns, C. R., & O'Dell, R. (2011). Recent Developments in Light-Emitting Polymers. *MRS Bulletin*, 27(6), 451-455.
2. Keum, C., Murawski, C., Archer, E., Kwon, S., Mischok, A., & Gather, M. C. (2020). A substrateless, flexible, and water-resistant organic light-emitting diode. *arXiv preprint arXiv:2007.02465*.
3. Bradley, D. D. C., Brown, A. R., Burroughes, J. H., Marks, R. N., Mackay, K., Friend, R. H., Burns, P. L., & Holmes, A. B. (2010). Light-emitting diodes based on conjugated polymers. *Nature*, 347(6293), 539-541.
4. Forrest, S. R. (2004). The road to high efficiency organic light-emitting devices. *Nature*, 428(6986), 911-918.
5. Hameed, A., Hameed, M. S., & Hameed, S. A. (2010). POLYMER LIGHT EMITTING DIODES - A REVIEW ON MATERIALS AND TECHNIQUES. *Research Journal of Applied Sciences, Engineering and Technology*, 2(1), 1-11.
6. Adachi, C. (2014). Third-generation organic electroluminescence materials. *Nature Photonics*, 8(7), 498-504.
7. Raccuglia, P., Elbert, K. C., Adler, P. D., Falk, C., Wenny, M. D., Mollo, A., Luscombe, C. K. (2016). Automated synthesis of organic semiconductors with machine learning. *Nature*, 533(7604), 42-46.
8. Highly Efficient Emitters (TADF, Exciplex): 6. Adachi, C. (2014). Third-generation organic electroluminescence materials. *Nature Photonics*, 8(7), 498-504.
9. Sun, C. J., Zhang, C. H., & Yang, B. (2013). General method to solution-process multilayer polymer light-emitting diodes. *Applied Physics Letters*, 103(1), 013302.
10. Aydin, M. A. (2019). Sustainable Materials and Process Techniques for Engineering Solution-Based Organic Light-Emitting Devices. *TUprints*.



**Impact Factor:  
7.512**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details