



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 8, August 2022

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 8.118

9940 572 462

6381 907 438

[ijirset@gmail.com](mailto:ijirset@gmail.com)

[www.ijirset.com](http://www.ijirset.com)



# Wearable Pulse Oximeter and Temperature-Prevention from Covid-19

J.Abinaya<sup>1</sup>, L. Brindha<sup>2</sup>, M. Dheepthi<sup>3</sup>, M. Divya Priya<sup>4</sup>, N.Suthanthira Vanitha<sup>5</sup>, S.Saravanan<sup>6</sup>

UG Scholars, Department of Electrical and Electronics Engineering, Muthayammal Engineering College,

Tamilnadu, India <sup>1,2,3,4</sup>,

Professor, Department of Electrical and Electronics Engineering, Muthayammal Engineering College,


Tamilnadu, India <sup>5,6</sup>

**ABSTRACT:** The Ideal design is completely designed for tracking people's health due to COVID 19 epidemic. Corona viruses (CoV) are a large family of contagions that beget ails ranging from the common deep freeze to more severe conditions. A Novel Corona virus (CoV) is a new strain that has not been preliminarily linked in humans. That position of testing can be done indeed briskly. Labor-free and with a lot further perfection like smart watches and testing bias. In this design, an operation is created, and an array of detectors (Palpitation Oximeter and Temperature) are used in these wearable devices to determine the liability that a person is affected by COVID 19, as well as the information we can gain. Microcontroller has a programming function that also communicates with different supplemental and collects data for getting an affair. Bluetooth will capture periodic data and shoot it to the Gateway device at regular intervals. However, the Gateway/ Wristband will induce an alarm, If there's an abnormality in the health. In addition, Social Distancing can also be measured using Bluetooth and the Entered Signal Strength Indicator value. As a result, this system monitors people's vital signs while maintaining social distance. The simulation result is attained the colorful temperature value like inner temperature, skin temperature, heat temperature.

**KEYWORDS:** ESP 32, Pulse Oximeter, Temperature Sensor, OLED Display.

## I. INTRODUCTION

The COVID 19 epidemic has brought into sharp focus the necessity to harness and influence our digital structure for remote case monitoring. As current viral tests and vaccines are slow to crop, we see a desire for further robust complaint discovery and monitoring of individual and population health, which may be moreover by wearable detectors. While the mileage of those technologies has been accustomed to relate physiological criteria to diurnal living and mortal performance, the restatement of comparable technology to word prognosticating the prevalence of COVID 19 remains a necessity. Identifiable data, as an example remote monitoring of Cohorts (Family, Businesses, and Installations) related to individualities diagnosed with COVID 19, can give precious data similar to the acceleration of transmission and symptoms onset. The COVID 19 first honored in December 2019 in Wuhan, China is because of the rearmost respiratory complaint epidemic presently languishing global health. Temperature dimension is extremely important to COVID 19 discovery and has formerly been extensively employed by multitudinous countries as an on-the-spottest to work out if trippers or citizens could also be infected with COVID 19.



**Figure 1. Block Diagram of Pulse Oximeter and Temperature Band**

This proposed operation is to produce an array of detectors Palpitation Oximeter and Temperature. These detectors are being used as a wearable to find the chance of a person who's affected by COVID 19 and this information can be notified by the buzzer. Palpitation Oximeter All Probes LED which shines two types of red light through the apkins. If the oxygen position is abnormal it'll warn with the beep sound and stored in the pall. Periodically the data is captured by Bluetooth Low Energy Device and transferred to the gateway device in regular intervals. In case of any abnormality occurs in health, and also the gateway bar wristband will induce an alert. In addition, with the support of Bluetooth Low Energy and Entered SignalStrength Indicator value, Social Distancing between the people can be measured.

### II.EXISTING METHOD

It's a non-invasive test that measures the oxygen achromatism position of blood. It can describe small changes in oxygen situations. The purpose of a Palpitation Oximeter is to check the oxygen status of the blood. Medical professionals use Pulse Oximeter for covering the health conditions of the cases could corroborate the blood oxygen position, situations during the symptoms of COVID 19, To determine whether someone needs supplemental oxygen remedy. Temperature detector is a simple instrument that measures the degree of roguishness or coolness and converts it into a readable unit. A Thermometer is the best form of Temperature Cadence that is used to measure the degree of roguishness and coolness. The working of the temperature cadence depends upon the voltage across the diode. The temperature change is directly commensurable to the diodes resistances. The cooler the temperature, lower will be the resistance and vice versa. The resistance across the diode is measured and converted into readable units of temperature (Fahrenheit, Celsius, Centigrade, etc ...) and, displayed in numeric form over read out units.

### III.PROPOSED METHOD

Pulse Oximeter is a bitty, feather light, Band like contrivance that assists us with knowing blood oxygen situations, circulatory strain, and palpitation in virtually no time. Exhaustively, there are three kinds of Oximeters, A Movable fingertip Palpitation Oximeter, Handheld Pulse Oximeter and Wrist Oximeter. ESP32 is a progression of a minimum expenditure, low- power frame on a chip microcontroller with coordinated Wi-Fi and double mode Bluetooth. ESP-IDF is the authority programming enhancement system for the chip. Arduino and different prosecutions for the enhancement will be innovated on ESP-IDF.



**Figure.2: Pulse Oximeter Board**



**ESP 32**

ESP 32 is a progression of minimum expenditure low- power frame on a chip microcontroller with coordinated with Wi-Fi and double mode Bluetooth. ESP-IDF is the authority programming enhancement system for the chip. Arduino and different prosecutions for the enhancement will be innovated on ESP-IDF.



**Figure.3: ESP 32**


**THE WIFI**

ESP32 carries out TCP/ IP, full 802.11 b/ g/ n/ e/ I WLAN MAC convention, and Wi-Fi Direct detail. This implies ESP 32 can address the maturity of the Wi-Fi Routers out there when employed in station mode. ESP32 also upholds the Wi-Fi Direct. Wi-Fi-Direct is a great choice for participating associations without the need for a hallway. The Wi-Fi-Direct is simpler to the arrangement and the information move pets are far superior to Bluetooth. This would potentially be suitable to be employed to arrange ESP32 grounded systems from a telephone/ tablet that upholds Wi-Fi directly.

**BLUETOOTH LOW ENERGY**

ESP32 doesn't simply uphold the most recent BLE Bluetooth4.2, it also upholds exemplary Bluetooth. It unnaturally implies it can address old and new Bluetooth telephones/ tables. The ESP32 Bluetooth Radio and Baseband upholds the accompanying highlights

**SIMPLIFIED CIRCUIT DIAGRAM**



**Figure.4: Circuit Diagram**

**DESCRIPTION:**

The charging circuit can be accustomed to charging the battery by 5V power supply, then, at that point, the battery will be charged. Through the battery power supply to the microcontroller (ESP 32). There are two sensors utilized here, one is Pulse Oximeter and another is Temperature sensor. Beat Oximeter impart through I<sup>2</sup> Communication. Four pins are associated with Pulse Oximeter. Sequential Clock(SCL) and Serial Data(SDA) are associated with microcontrollers. One more two pins are associated with 5V and Ground. The temperature Sensor module is LM 35. The temperature sensor will be in Analog signal(When the potentiometer perusing is different than the worth will be changing)which is



associated in Analog to Digital Signal Channel 1. The Buzzer will work in a 5V power supply that is associated with General Purpose Input and Output Pin (Gpio) with the end goal of On and Off. Also, the Light Emitting Diode (LED) is utilized for sign reasons. For Example: When an individual wears a band while somebody draws nearer it will make them aware of keeping a social separation. The distance will be estimated through working out the Received Signal Strength Indicator (RSSI) esteem.

#### IV.SIMULATION AND RESULTS

In this Project, Arduino Integrated Development Environment (IDE), contains a text editor for writing code, a message area, a text console, a toolbar with buttons for common functions and a series of menus. Because programming a microcontroller is somewhat different from programming a computer, there are number of device- specific libraries.

#### BEACON SCANNER

Beacon is a small device approx. 3cm x 5cm x 2cm that constantly sends out radio signals to nearby smart phones and tablets, containing a small amount of data. The signal strength and time between each signal can be configured to give a desired coverage. Mobile apps can listen for the signals being broadcast and, when they hear a relevant signal, can trigger an action on your phone. Note that beacons only operate/talk in one direction (i.e. they can broadcast data but cannot read things off your phone). Beacons work using Bluetooth Low Energy (BLE) which is a version of the more common Bluetooth protocol, designed to use very little power and send less data – typically 1- 20% of standard Bluetooth power and at 15-50% of the speed. They are often powered by batteries and as such the performance/battery life needs careful balancing to suit the application as the battery life can be anywhere from 1 month to 2-3 years (there are beacons using USB/mains power or solar panels so last much longer, and some beacons are coming out which are built into lights or light sockets). The beacons themselves are typically stuck to walls/ceilings or hidden in other objects since you can detect a beacon up to 70m away with no obstructions (depending on the power level).

#### V.HARDWARE IMPLEMENTATION

It is a device that can be operated automatically. It's a non-invasive test that measures the oxygen saturation position of blood. It can describe small changes in oxygen situations.




Figure 5: Hardware Prototype

Medical professionals use Pulse Oximeter for covering the health conditions of the cases could corroborate the blood oxygen position. Due to this type of special arrangement the device can be operated without any interruption. Malfunctioning of the device can be rectified immediately by saving the data. The hardware prototype shows the entire working process of a wearable band.

#### VI.CONCLUSION

In this task, we planned and carried out Wearable Pulse Oximeter and Temperature Band: Prevention from COVID-19.

These examinations show that to find the manifestations of COVID-19 impacted Person. A crisis framework for self-observing of patients with COVID-19 was created in the current review. The proposed framework permitted us to rapidly answer early anomalies in these patients. It will send a signal when the oxygen level and pulse are more prominent than or lesser than to the typical level rate it will send an alarm with signal sound and by interfacing, with IoT it will likewise send the caution to the cloud. In this specific situation, we planned to foster a Band to dissect the manifestations of COVID-19 impacted individuals, which might be valuable to isolated individuals to keep away from the spread of this sickness.

#### REFERENCES

1. Li Q, Guan X, Wu P, Wang X, Zhou L, Tong Y, et al. Early transmission dynamics in Wuhan, China, of novel coronavirus-infected pneumonia. *N Engl J Med.* (2020) 382:1199–207. doi:10.1056/NEJMoa2001316
2. PNAS. Activation of the SARS Coronavirus Spike Protein via Sequential Proteolytic Cleavage at Two Distinct Sites. *PNAS.* (2020).
3. Yan R, Zhang Y, Li Y, Xia L, Guo Y, and Zhou Q. Structural basis for the recognition of SARS-CoV-2 by full-length human ACE2. *Science.* (2020) 367:1444–8. doi:10.1126/science.abb2762
4. Fauci AS, Lane HC, and Redfield RR. Covid 19—navigating the uncharted. *N Engl J Med.* (2020) 382:1268–9. doi:10.1056/NEJMe2002387
5. Paules CI, Marston HD, and Fauci AS. Coronavirus infections—more than just the common cold. *JAMA.* (2020) 323:707–8. doi:10.1001/jama.2020.0757
6. Berkeley Lovelace WF Jr. WHO Officials Say it's Unclear Whether Recovered Corona virus Patients are Immune to Second Infection. *CNBC.* (2020).
7. P.Selvappriya, V.Shalini, M.Uma Maheswari, R.Punitha, S.Saravanan, "Cultivation of Cash Crops under Automated Greenhouse using Internet of Things", *International Journal of Innovative Research in Science, Engineering and Technology*, Vol.10, Issue.10, Pp.13897-13905, 2021
8. A.C.KVigneshkumar, N.Tamilselvan, S.Vishva, C.S.Satheesh, G.Dineshkumar, S.Saravanan, "Wireless Power Transmission Using Class C Power Amplifier from Solar Input", *International Journal of Innovative Research in Science, Engineering and Technology*, Vol.10, Issue.10, Pp.13906-13912, 2021
9. J.Vinoth, T.Muthukumar, M.Murugandam and S.Saravanan, "Efficiency Improvement of Partially Shaded PV System, *International Journal of Innovative Research in Science, Engineering and Technology*, Vol.4, Special issue 6, pp.1502-1510, 2015
10. M.B.Malayandi, Dr.S.Saravanan, Dr. M.Muruganandam, "A Single Phase Bridgeless Boost Converter for Power Factor Correction on Three State Switching Cells", *International Journal of Innovative Research in Science, Engineering and Technology*, Vol. 4, Special Issue 6, pp. 1560-1566, May 2015.
11. A.Sasipriya, T.Malathi, and S.Saravanan, "Analysis of Peak to Average Power Ratio Reduction Techniques in SFBC OFDM System" *IOSR Journal of Electronics and Communication Engineering (IOSR-JECE)*, Vol. 7, No.5, 2013.
12. P.Ranjitha, V.Dhinesh, M.Muruganandam, S.Saravanan, "Implementation of Soft Switching with Cascaded Transformers to drive the PMDC Motor", *International Journal of Innovative Research in Science, Engineering and Technology*, Vol. 4, Special Issue 6, pp. 1411-1418, May 2015.
13. C.Sowmiya, N.Mohanandhini, S.Saravanan and M.Ranjitha, "Inverter Power Control Based On DC-Link Voltage Regulation for IPMSM Drives using ANN" *International Research Journal of Engineering and Technology (IRJET)*, Vol.5, Issue 11, pp.1442-1448, 2018.
14. N.Yuvaraj, B.Deepan, M.Muruganandam, S.Saravanan, "STATCOM Based of Adaptive Control Technique to Enhance Voltage Stability on Power Grid", *International Journal of Innovative Research in Science, Engineering and Technology*, Vol. 4, Special Issue 6, pp. 1454-1461, May 2015.
15. P.Manikandan, S.Karthick, S.Saravanan and T.Divya, "Role of Solar Powered Automatic Traffic Light Controller for Energy Conservation" *International Research Journal of Engineering and Technology (IRJET)*, Vol.5, Issue 12, pp.989-992, 2018.
16. R.Satheesh Kumar, D. Kanimozhi, S. Saravanan, "An Efficient Control Scheme for Wind Farm Using Back to Back Converter," *International Journal of Engineering Research & Technology (IJERT)*, Vol. 2, No.9, pp.3282-3289, 2013.
17. K.Prakashraj, G.Vijayakumar, S.Saravanan and S.Saranraj, "IoT Based Energy Monitoring and Management System for Smart Home Using Renewable Energy Resources," *International Research Journal of Engineering and Technology*, Vol.7, Issue 2, pp.1790-1797, 2020



**INNO SPACE**  
SJIF Scientific Journal Impact Factor  
**Impact Factor: 8.118**



**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details