

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

EDIA

#### International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 2, February 2022

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

### Impact Factor: 7.569

9940 572 462

6381 907 438

 $\bigcirc$ 





International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 11, Issue 2, February 2022 || | DOI:10.15680/IJIRSET.2022.1102094 |

## Non Darcian Approach to Flow of an Electrically Conducting Stratified Incompressible Viscous Fluid through Highly Porous Medium between Two Semi-Infinite Parallel Plates

#### Dr.Shiva Shanker K.

Associate Professor, Dept of Mathematics, Kakatiya Institute of Technology & Science, Warangal, Telangana, India

**ABSTRACT**: The flow of an electrically conducting stratified incompressible viscous fluid is examined between two semi-infinite parallel plates. The space between the parallel plates is filled with highly porous medium. The flow of an electrically conducting incompressible viscous produces induced electric current and the induced current produces induce magnetic field. The expressions for velocity of the fluid, flow rate of the fluid, induced magnetic field and current density are obtained in elegant forms

KEYWORDS: electrically conducting incompressible viscous fluid, porous medium, permeability parameter

#### I. INTRODUCTION

The study of flow through porous medium assumed importance because of the interesting applications in the diverse fields of science, Engineering and Technology. The practical applications are in the percolation of water through soil, extraction and filtration of oils from wells, the drainage of water, irrigation and sanitary engineering and also in the inter disciplinary fields such as biomedical engineering etc. The classical Darcy's law Musakat [1] states that the pressure gradient pushes the fluid against the body forces exerted by the medium which can be expressed as

$$\vec{V} = -\left(\frac{k}{\mu}\right)\nabla P$$

The law gives good results in the situations when the flow is uni-directional or the flow is at low speed. In general, the specific discharge in the medium need not be always low. As the specific discharge increases, the convective forces get developed and the internal stress generates in the fluid due to its viscous nature and produces distortions in the velocity field. In the case of highly porous medium such as fiber glass, papus of dandelion the flow occurs even in the absence of the pressure gradient.

Modifications for the classical Darcy's law were considered by the Beavers and Joseph [2], Saffman [3] and others. A generalized Darcy's law proposed by Brinkmann [4] is given by

$$O = -\nabla P - \left(\frac{\mu}{K}\right) \overrightarrow{v} + \mu \nabla^2 \overrightarrow{v}$$

Where  $\mu$  and K are coefficients of viscosity of the fluid and permeability of the porous medium.

#### II. RELATED WORK

The applications of flows through porous medium bears wide spread interest in Geophysics, biology and medicine. In many of these areas the flow consists of more than one phase, such type of flows find applications in the inter disciplinary fields such as bio-medical engineering etc., the flow of blood is one such application. The blood may be represented as Newtonian fluid and the flow of the blood is in two layered. Lightfoot [5], Shukla *et al.* [6] and Chaturani [7]. Bird *et al.* [8] found an exact solution for the laminar flow of two immiscible fluids between two

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

|| Volume 11, Issue 2, February 2022 ||

| DOI:10.15680/IJIRSET.2022.1102094 |

parallel plates. Earlier Narasimhacharyulu et *al.* [9] studied Two phase flow of an Incompressible Viscous fluid between two semi-infinite parallel plates under transverse magnetic field.

In this present paper flow of an electrically conducting stratified incompressible viscous fluid is examined between two semi-infinite parallel plates. The space between the parallel plates is filled with highly porous medium.. The expressions for velocity of the fluid, flow rate of the fluid, induced magnetic field and current density are obtained in elegant forms.

#### **III.MATHEMATICAL FORMULATION OF THE PROBLEM**

The flow of an electrically conducting stratified incompressible viscous fluid is considered between two semi infinite parallel plates given by  $y = \pm h$ . The space between the plates is filled with highly porous region. The coordinate system is taken such that x-axis lies parallel to the length of the plates and y-axis perpendicular to the length of the plates. The fluid flows under a constant pressure gradient.  $G = -\frac{\partial p}{\partial x}$ .

The velocity of the fluid  $\vec{V} = (u, 0, 0)$  satisfies the equation of continuity, the physical quantity depends only on y. The equation of motion is given by

$$\frac{d^2 u}{dy^2} - \frac{u}{k} = -\frac{G}{v} e^{\beta y} \qquad -h < y < h \qquad (2.1)$$

Induced magnetic field is given by the equation

$$\frac{1}{\mu}\frac{d^2h_x}{dy^2} + H_0\frac{du}{dy} = 0$$
 ...... (2.2)

Where  $G = -\frac{\partial p}{\partial x}$  is a constant pressure gradient in the x direction, v is coefficient of viscosity of the fluid, k is

permeability of the porous medium  $h_x$  is induced magnetic field,  $H_0$  magnetic field strength component,  $\beta$  stratification parameter

Using the following Non dimensional quantities.

$$u^* = \frac{uh}{v}, y^* = \frac{y}{h}, G^* = \frac{Gh^3}{v} \qquad \dots \qquad (2.3)$$

After removing \*, the non-dimensional form of equation of motion is

$$\frac{d^2 u}{dy^2} - \frac{h^2}{k} u = -\frac{G}{v} e^{\beta y} \quad -1 < y < 1 \qquad \dots \quad (2.4)$$

The boundary conditions are given by

$$u = 0 \quad \text{at} \quad y = \pm 1 \}$$
  

$$h_x = 0 \quad \text{at} \quad y = \pm 1 \}$$
...(2.5)

#### **IV.SOLUTION OF THE PROBLEM**

Solving the equation (2.4) and (2.2) employing boundary conditions (2.5) fluid velocity and flow rate are given by

$$u = \frac{G}{\nu\beta^{2}} \left( y \sinh \beta + \cosh \beta - e^{\beta y} \right)$$
(2.6)  
Flow rate is  
$$Q = \int_{-1}^{1} u dy$$
$$Q = \frac{2G}{\nu\beta^{2}} \left( \cosh \beta - \frac{\sinh \beta}{\beta} \right)$$
(2.7)

Induced magnetic field

$$h_{x} = \frac{\mu G H_{0} \sinh \beta}{\nu \beta^{2}} \left( \frac{e^{\beta y}}{\sinh \beta} + 1 - \frac{y}{\beta} - y^{2} - \coth \beta \right)$$
(2.8)

International Journal of Innovative Research in Science, Engineering and Technology (IJIRSET)



| e-ISSN: 2319-8753, p-ISSN: 2320-6710| <u>www.ijirset.com</u> | Impact Factor: 7.569|

Volume 11, Issue 2, February 2022

DOI:10.15680/IJIRSET.2022.1102094

Current density

$$J = -\frac{dh_x}{dy} = \frac{\mu GH_0}{\nu \beta^2} \left( 2y \sinh \beta + \frac{\sinh \beta}{\beta} - e^{\beta y} \right)$$
(2.9)

#### V. CONCLUSION

The flow of an electrically conducting stratified incompressible viscous fluid is considered between two semi infinite parallel plates The space between the plates is filled with highly porous medium. The coordinate system is taken such that x-axis lies parallel to the length of the plates and y-axis perpendicular to the length of the plates. The fluid flows under a constant pressure gradient. From the obtained analytical solutions, it is observed that as the viscosity of the fluid is increasing the velocity of the fluid, flow rate and induced magnetic field are decreasing. Further it is also observed that as viscosity of the fluid is increasing, the current density is also decreasing. It has been observed that both stratification parameter and viscosity of the fluid have significant role on the velocity profile

#### REFERENCES

- 1. .Musakat, M. 1937. Flow of homogeneous fluid through porous medium, Mc Graw Hill Inc., New York, 1937.
- Beavers S.G. and Joseph D.D. 1967. Boundary conditions at natural permeable wall, Int.J.of Fluid Mechanics, 30: 197-207.
- 3. Saffman P.G. 1971. On the boundary conditions at the surface of porous medium. Studies of Applied Maths, **50:** 93-101.
- 4. Brinkman H.C. 1947. The calculation of viscous force exerted by a flowing fluid on a dense swerf of particles. Jl. of Applied Science Research **27**, **A1**: 27-34
- 5. Lightfoot, E.N. 1974. Transport phenomena in living system, John-Wiley and Sons, New York, 1974.
- 6. Shukla, J.B., Parihar, R.S. and Gupta, S.P., 1980. Effects of peripheral layer viscosity on blood flow through the artery with mild stenosis, Bulletin of Mathematical Biology, **42**: 797-805.
- 7. Chaturani, P. and PonnalagarSamay R. 1985. A study of non-Newtonian aspects of blood flow through stenosed arteries and it's applications in arterial diseases. J. Biology, **22**: 521.
- 8. ,Bird, R.B., Stewart, W.E. and Lightfoot, E.N. 1960. Transport phenomena. John wiley and sons, Inc, New York.
- 9. Narasimhacharyulu, V. and Shiva shanker K. Two phase flow of an Incompressible Viscous fluid between two semi-infinite parallel plates under transverse magnetic field. International Journal of computational and Applied Mathematics. Vol(8), 1 (2013), PP 25-35.
- 10. Shivashanker .K. Non darcian approach to flow of an electrically conducting incompressible viscous fluid through highly porous medium between two semi-infinite parallel plates Vol (11), 2 (2022)





Impact Factor: 7.569





## INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com