



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 7, July 2022

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.118



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

The Effect of Wind Load on Tall Buildings with Varying Structural Height

Surya Prakash V¹, Sagar SR²

P.G. Student, Department of Civil Engineering, SJB Institute of Technology, Kengeri, Bangalore, India¹

Assistant Professor, Department of Civil Engineering, SJB Institute of Technology, Kengeri, Bangalore, India²

ABSTRACT: For prolonged span, tall, slim structure dynamic analysis of structure is essential. Wind gust causes fluctuating forces on the structure which persuade massive dynamic motions, consisting of oscillations. An attempt has been made to showcase the effect of wind load on tall constructions in one of a terrain categories. This project accentuates on difference of an excessive upward shove form (G+10), (G+20), (G+30) which is design irregular. Modelling and assessment of the above R.C.C framed form is done in the ETABS 2015 Software. The parameters are borrowed from IS 875-1987 (Part 3). The shape is analysed for maximum storey displacement, maximum storey drift, maximum storey stiffness. The static wind analysis is carried out for analysing the structure.

KEYWORDS: *High-rise structures, Displacement, Stiffness, Storey drift, ETABS software.*

I. INTRODUCTION

For every building project, the wind classification of a building site is critical. It ensures that a structure is designed and built to a level appropriate to withstand the wind forces it will be subjected to safely. Assessing and determining the wind classification for a site ensures that the project is designed and built to the installation standard and ensures it is not structurally compromised in instances of high wind. Wind region, terrain category, shielding, and topography are four key areas that determine a site's wind classification. Here, wind in terrain categories is considered and explained.

The wind blows at a given height, with lower velocity in rougher terrains and higher velocities in smoother terrains. In any landscape, wind tempo will increase alongside the pinnacle up to the gradient pinnacle, and the gradient height values are tremendous for rougher terrains. The greater the ground's roughness, the slower the wind. Wind velocity will extend with the power of the structural height. At any pinnacle in each terrain, the magnitude of wind pace relies on the averaging time shorter than the averaging time, and the recommended wind speed is extended. The model of wind tempo with pinnacle is also structured upon the floor roughness and is subsequently incredible for every terrain category.

The Paper is organised as follows. Section II describes the literature survey summary, and connected component analysis. The methodology is described in Section III. Section IV presents the results and the observation with illustrating graphs. Finally, Section V presents the conclusion.

II. RELATED WORK

A potential wind load must be considered in the building to design a multi-storied structure. The nature of the wind flow must be considered and specified at the design time. The complications occur due to the unpredictable nature of the wind flow and the wind flow interaction with the structure. The wind speed is zero at the ground level and maximum at the critical height, which is one of the essential factors of consideration.

Therefore, one should be careful in terms of building specifications. Specifications consist of the structure's height, breadth, length, and the number of stories along with wind zone, terrain, and location topography. All the specifications mentioned are the variables for the analysis of the study.

Once all the specifications are precise, software like E.T.A.B.S. is used for the 3D model and planning of the structure, which helps in visualising the design with the considered parameters for the analysis of the structure.

From various works of literature, various parameters were considered for this study. The aspect ratio of 1:400 was considered with different wind velocities and heights of the structures as per the literature Seifu. A. Bekele Karl, Vonder Putten et al., (2005), [15] and Mashalkar, et al., (2015), [7].

For dynamic properties like storey stiffness, storey shear, displacement, axial forces, bending moment, and shear forces, Dean Kumar B. and Swami B.L.P, (2010), [5], Mashalkar, et al., (2015), [7], Prof. Wakchare, et al., (2015), [12], Shaikh Muffassir et al., (2016), [14], Adarsh S.B, Sridhar R et al., (2017), [3], HuseyinGokcekus, et al., (2020), [8], and Shraddha. J. Patil et al., (2015), [16], were referred.

To summarize all the literature mentioned above, in this study, reinforced concrete framed structure and shear wall structures with parameters such as storeys, aspect ratio, terrain categories for Square, C-shaped, L-shaped, I-shaped and T-shaped structures with openings by equivalent static and dynamic analysis.

III. METHODOLOGY


This project accentuates on the difference of an excessive upward shove form (G+10), (G+20), and (G+30), which is design irregular. The above R.C.C framed form will be modelled and assessed in the E.T.A.B.S.2015 Software. The constants are taken from IS 875-1987 (Part 3). Here, to analyse the conduct of G +10, G+20, and G+30 storey buildings, floor-to-floor height is considered as 3m, and the residences are well-defined for the structure. The ground floor to floor height is considered as 3.5m. The wind quarter is regarded as 1 and the soil shape is medium. The shape modelling is carried out for wind load as per IS 875-1987(part 3).

The analysis is carried out to discover the wind response on the structures created using E.T.A.B.S. software. The assessment is carried out to decide the maximum storey displacement, storey drift and storey stiffness. After analysis, results are displayed through graphical representation for different geometrical shapes and storey heights.

IV. EXPERIMENTAL RESULTS


- Figures The displacement is observed to be lowest in Square shape and the displacement in T shape is found to be more when compared to other forms. C and shaped-shaped values are closely placed and therefore cannot be distinguished in the graph.

Fig. 1. Maximum storey displacement for G+10, G+20, and G+30 storey structures, respectively




- ii. The drift is minimum for a square shape. T-shape has maximum drift in both directions. C, L, and I shape show the similar drifts. The angle with which the wind strikes affect the structure.


Fig. 2. Maximum storey drift for G+10, G+20, and G+30 storey structures, respectively



- ii. From the stiffness graphs plotted with respect to the storey, it is seen that the stiffness is more in square-shaped structure and shaped-shaped structure shows the least stiffness. This is due to the geometrical arrangements of the structure.

Fig. 3 Maximum storey stiffness for G+10, G+20, and G+30 storey structures, respectively





(c)

V. CONCLUSION

The wind pressure and velocity of the wind mainly depend on the structure's geometric shape with respect to terrain categories. Based on the observations and the results, one should consider the effect of wind on tall structures while designing the structure. The following conclusions can be deduced based on the results presented and the discussions.

- The square shape is the best geometrical shape for stability since it has lesser storey displacement, storey drift and higher stiffness with respect to different storey heights.
- The displacement is least in square shape structures and higher in L, I, C and T-shaped structures.
- From the results, it is observed that increases in storey displacement results in a decrease in storey stiffness.

REFERENCES

- [1] IS875-1987(PART 3) Code of practice for design wind loads for building and structures. Published by Bureau of Indian Standards.
- [2] SP 64: Explanatory Handbook on Indian Standard Code of Practice for design loads.
- [3] Adarsh S B, Sridhar R "Study on Wind Analysis of Multi-Storied Building with Regular and Irregular Plan" (IJAREM) ISSN: 2456-2033 PP. 28-34 (2017).
- [4] A.K. Roy "Wind Pressure Coefficients on Pyramidal Roof of Square Plan Low Rise Double Storey Building" Computational Engineering and Physical Modeling, 2588-6959 (2019)
- [5] B. Dean Kumar and B.L.P Swamy "Wind effect on tall building frames-influence of dynamic parameters" Indian Journal of Science and Technology, Vol.3 No.5 (May 2010) ISSN:6846.
- [6] B. Shobha, Dr. H. Sudarshan Rao, Dr. Vaishali G. Gorpade "Effect of wind load on low, medium, high-rise buildings in different terrain category" IJTIMES-2018.
- [7] B. S. Mashalkar, G. R. Patil, A.S. Jadhav. "Effect of Plan Shapes on the Response of Buildings Subjected to Wind Vibrations" (IOSR-JMCE) e-ISSN: 2278-1684, p-ISSN: 2320-334X PP 80-89, (2015)
- [8] Hüseyin Gökçeku, s. Raafat Al Zoubi "The Possibility of Generenecccldvjvkeicflngnvcbbucknctnhvcfdifjcfu
- [9] ating Electricity Using Small-Scale Wind Turbines and Solar Photovoltaic Systems for Households in Northern Cyprus: A Comparative Study" (22 April 2019)
- [10] Mohammad Asim Ahmed, Moid Amir, Savita Komar, Vajaiinath Halhalli "Effect of Wind Load on tall buildings in different terrain category" IJRET: eISSN 2319-1163 pISSN 2321-8 Volume: 04 Issue: 06 (June-2015)
- [11] Madhurima Dutta, "wind analysis and design of a multi storied Structural frame considering using staad pro", ISSN: 2394-2827 Volume-4, Issue-5, (Oct 2017)
- [12] Pallab Kheyari and sujit Kumar Dalui "Estimation of wind load on a tall building under interference effects: A case study" Jordan Journal of Civil Engineering, Volume 9, No1, 2015.
- [13] Prof. M. R. Wakchaure, Sayali Gawali "Effects of Shape on Wind Forces of High-Rise Buildings Using Gust Factor Approach" (IJSETR), Volume 4, Issue 8, (August 2015)
- [14] Ravindra Jori, Omkar Kamble, Eklavya Sarnaik, "Gust Analysis of Tall Building by IS 875(Part3)-1987 and by ETabs software", IJETSR ISSN 2394 – 3386 Volume 5, Issue 3 (March 2018).
- [15] Shaikh muffassir, L.G. Kalurkar "Study of wind analysis of multi storey composite structure for plan irregularity" International Journal of advanced technology in engineering and science, Vol-4, Issue No.9, (September 2016).
- [16] Seifu A. Bekele, Karl VonderPutten, "The effect of tall building base openings on wind loads and local flow structures", CTBUH 2005 7th World congress, New York (2005).



- [17] Shraddha J. Patil, Mahesh Z. Mali, Dr.R.S. Talikoti, “Effect of wind load on high rise structure” (IJETR) ISSN: 2321-0869 (O) 2454-4698 (P), Volume-3, Issue-7, (July 2015)
- [18] Khalid Nayaz Khan, Syed Ahamed Raza, Dr. N.S. Kumar, “Effect of Wind Pressure on R.C Tall Buildings using Gust Factor Method”, (IJERT) ISSN: 2278-0181 Vol. 3 Issue 7, (July 14).



INNO  SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.118



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details