



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 7, July 2022

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.118



9940 572 462



6381 907 438



ijirset@gmail.com



www.ijirset.com

Analysis of Seismic Loading by Using Response Spectrum Method and Analysis of Wind Loading On G+11 Building

Sachin K Mandawkar¹, Prof. Sushant M. Gajbhiye²

Research Scholar, Department of Civil Engineering, Guru Nanak Institute of Technology Nagpur,
Maharashtra, India¹

Assistant Professor, Department of Civil Engineering, Guru Nanak Institute of Technology Nagpur,
Maharashtra, India²

ABSTRACT: Primary planning requires underlying investigation and quake or seismic examination and wind Analysis of any design before development. Quake or seismic investigation is the computation of the reaction of a design exposed to tremor excitation. Different seismic information are important to do the seismic investigation of the designs Computer programming's are likewise being utilized for the computation of powers, bowing second, stress, strain & deformation or diversion for a complex underlying framework. The rule objective of this undertaking is "Concentrate on Analysis Results of Multistoried Residential Building (G+11) by STAADPRO ". STAADPRO is one of the main programming's for the plan of designs. In this task broke down the G+11 working Through reaction range examination to foster the monetary plan. This study presents an investigation of wind burdens to conclude the plan heaps of a G+11 building. The meaning of this assessment is to gauge the plan loads for a construction which is exposed to twist loads in a specific locale. It is verifiable truth that the breeze burdens might be assessed specifically zone with a predefined zone factor. Then the breeze heap of that zone can likewise be assessed in light of the essential breeze speed and different variables of that specific district. Notwithstanding, the breeze speed is stochastic and time subordinate. In the current review a multi-celebrated building is examined for wind loads utilizing IS 875 code. In this Analysis, G+11 celebrated building is thought of and applied different burdens like breeze load, static burden and results are examined and contrasted between and wind load or without wind load.

KEYWORDS: Multi-story Building, Stadd-Pro, IS 875, Wind Load.

I. INTRODUCTION

To plan a design to oppose wind and tremor stacks, the powers on the construction should be indicated. The specific powers that will happen during the existence of the construction can't be expected. Most National Building Codes recognize a few variables as per the limit states of each building considered in the examination to accommodate life wellbeing. A reasonable gauge for these elements is significant; but the expense of development and thusly the monetary suitability of the task is fundamental. The codes presents improved on strategies for the plan which rely upon various elements for wind and quake that administer the plan and impact the outcomes. The plan of tall structures that are situated in destinations where both outrageous breezes and storms, or hurricanes, happen is a subject of extraordinary importance. Wind is the power which acts even to the world's surface with a more prominent force. Wind force is certainly not a steady one it will change from one spot to another and time to time. On the off chance that the spot is an uneven region at an open country, the force of wind is more. Yet, on the off chance that it is a plane ground and loaded with deterrents like structures and trees, the power will be lesser at lower levels however it will increment with expansion in the level of the structure. The breeze force can likewise be shifted in view of the climatic circumstances. In light of the past investigations of the breeze fiascoes in Andhra Pradesh, Visakhapatnam is where the Hudhud. A hurricane, that causes a broad harm and death toll in eastern India and Nepal. That is the explanation, the breeze investigation and plan of the G+11 High-ascent multi story building is finished at Vizag, where the maximum harm happened because of wind powers.

II. LITERATURE REVIEW

S. R. Kangle (2020), directed a concentrate on "Reaction Spectrum Analysis for Regular Multistory Structure in Seismic Zone III" The standard goal of this undertaking is "The Near Study on Analysis Results of Multistoried Commercial Building (G+15) by STAADPRO and ETABS". STAADPRO is one of the main programming's for the plan of designs. In this undertaking we had broke down the G+15 working through reaction range examination to foster the monetary plan. ETABS is additionally driving plan programming in present days utilized by numerous underlying architects. Here They have likewise broke down a similar construction involving ETABS programming for the design. IS: 1893 (Part I) for seismic plan is used to play out the unique examination. The outcomes were seen that the multistoried structures are firm for quake excitation as modular cooperation factor is viewed as in excess of 75%.

B DhanaBabu and K Sasidhar, (2020), directed concentrate on " Wind Analysis and Design of Highrise Residential Building by Using STAAD.Pro" Wind load is the one of the heaps, is to be considered concerning the level of the structure. As the power of wind will increment with expansion in the level of building. For tall structures and underlying model relies upon the breeze load as its dynamic in nature. Highrise structures are convoluted to examine and it requires bunches of investment for unwieldy estimations utilizing ordinary manual strategies. The target of this study is to break down the impact of various breeze speeds and the impact of wind on various level of the multistoried structure. In this Analysis, G+11 celebrated building is thought of and applied different burdens like breeze load, static burden and results are contemplated. In this venture, investigation of primary way of behaving of the structure is examined under wind load cases by utilizing STAAD.Pro.

Daljeet Pal Singh (2019), dealt with " Seismic Analysis of G+12 Residential Building in Lucknow (Zone 3) Region and Study of RC Jacketing Technique for Retrofitting " This examination will give a short show about tremor safe plan and the strategy about seismic investigation and retrofitting of existing designs. It likewise gives specific parts of PC programming displaying against seismic loads and shows the need of seismic updating in a G+12 outline working of Shalimar One World Residential Building in Lucknow.

C.V.Siva Rama Prasad, Sumith.K, Shivani.R, Tejaswini.R (2019), directed concentrate on "Quake and Wind Analysis of Multi story building utilizing Staad.Pro" On request of developing populace development of tall structure is being made necessary for staying away from land shortage in future. As these tall structures are hard to, to be examined physically so many mechanized business programming's are accessible for dissecting a design. STAAD.Pro is one of the expert decisions for investigating a construction carefully. It utilizes limit state technique in R.C.C for planning thinking about all the standard code books and gives the plan. A general construction of 7 stories is considered for examination and configuration considering seismic burdens in concurring with Indian codal arrangements IS-456:2000, SP-16, IS-1893:2002.

III. METHODOLOGY

1. Open Stadd-Pro Wizards and set out the name of the structure. Then select the unit which is used while the analysis of the structure. Then after Plane of the structure choose and then following display box is opened.






Figure 1 Initializing display of the Stadd-pro

2. Then go to geometry and click on Run Structure Wizards. One of the dialogue box is opened in which the frame model is to be formed with the set out the dimension of the structure i.e. feet to meter. Then click on model type and select frame model and then select bay frame. Then after put out the data i.e. number of story, height width and length of the story etc.



a)



b)

Figure 2 a) Frame model type to be input b) data enter to the software for the building structure

3. The building structure has some of the properties i.e. column size, beam size, slab thickness etc.

Building Story:- G+11

Building Height:- 36m

Story Height:- 3m

Column Size:- 0.45m x 0.45m

Beam Size:- 0.35m x 0.35m

Slab Thickness:- 0.125m

Zone Factor:- V

Soil Type:- Medium Type Soil

Support:- Fixed

Material:- Concrete

Damping Ratio:- 5%

IV. RESULTS AND DISCUSSION

Nodal Displacement

There are about 514 nodes are formed for G+11 story building without wind load and with wind load structure. After the analysis of this 2 structure the nodal displacement data is formed. The maximum nodal displacement due to the application of Live load, dead load and wind load are calculated by the software and the comparative data is taken out by the software that is shown below.

Table No. 4.1 Comparative nodal displacement of the structure

Nodal Displacement in mm			
	Max X	Max Y	Max Z
Building Without wind load	638.427	33.273	638.427
Building with Wind load	638.427	74.983	3180




Figure 4.2 Nodal Displacement of the structure

In the above figure it is shown that the displacement in x direction for the both the cases is same i.e. 0.638m while in Y direction after the application of the wind load to the structure, it may get increased 33.273mm to the 74.983mm which has a difference of about 40mm. in Z direction the displacement with wind load may get goes on increases extreme to the limit of the structure.

4.4 Beam Displacement

Beam is the basic part of the structure. The tension and the compression of the structure to the structure is occurred in the beam section. The beam sizes in the structure are 0.35m x 0.35m. the loading condition are applied to the structure as 3.0625KN. which is calculated by the formula i.e. area of the beam x Unit weight of the concrete. There are about 68 beams are provided to the structure which is equally spaced and placed on the column of the structure. The maximum beam displacement of the structure is calculated and the comparative analysis between the tree structure is made that is shown below.

Table no. 4.2 Comparative beam displacement of the structure

Beam Displacement			
	Max X	Max Y	Max Z
Building Without wind load	638.493	34.699	638.427
Building with Wind load	638.493	75.021	3180




Figure 4.3 Beam Displacement of the structure

In the above figure it is clear that as the node displaced, the beam portion is also displaced due to which only little difference occur in between node and beam displacement. The displacement occur in that beam is quite similar to that of nodal displacement only difference occur in the Y direction.

V. CONCLUSION

1. The axial force is formed due to the wind load gives maximum value as compare to the without wind load model.
2. The nodal displacement value is maximum for the wind load applied to the model as compare to the without wind load model.
3. The beam displacement is also interconnected to the nodal displacement in which the maximum value is occurring in with wind load of the structure.

4. The shear force value is also maximum for the 2nd model because the extra wind load is applied to the structure due to which the maximum force is developed and the displacement is occurring.
5. With the help of shear force diagram, the bending moment diagram is also formed. As shear force is maximum in that structure with wind load then the bending moment is also maximum.
6. The maximum displacement is occurring in the structure with the wind load because extra wind load is applied to the structure and due to which the displacement occur.
7. The dynamics is also found to be maximum in wind load structure and the plate load force is also maximum in wind load structure.

REFERENCES

1. A. Kale (2015), Conducted study on " Seismic& Wind Analysis of Multistory Building: A Review " International Journal of Science and Research (IJSR) ISSN (Online): 2319-7064 Index Copernicus Value.
2. A.A.Jadhav ,Dr.S.Kulkarni (2016) " Comparison of effect of earthquake and wind loads on performance of RC Framed Shear wall building with its different orientation" IJARIE-ISSN(O)-2395-4396 Vol-2 Issue-6.
3. A.Eugene Victor & S. Yokesh (2018), "A Comparative Analysis on Absolute and SRSS Methods of Response Spectrum using STAAD-PRO" International Journal of Engineering Research & Technology (IJERT) ISSN: 2278-0181 IJERTV7IS120095 Vol. 7 Issue 12.
4. AnupamRajmani, Prof. PriyabrataGuha (2015) "Analysis of wind and earthquake load for different shapes of high rise building" International journal of Civil Engineering and Technology(IJCIET), Vol.6, Issue 2 , Feb 2015, p 38-45.
5. Azlan Adnan, SuhanaSuradi,(2008) "Comparison on the effect of earthquake and wind loads on the performance of reinforced concrete buildings" World Conference on Earthquake Engineering Beijing, China.
6. B DhanaBabu& K Sasidhar, (2020), " Wind Analysis and Design of Highrise Residential Building by Using STAAD.Pro" International Journal for Modern Trends in Science and Technology ISSN: 2455-3778 :: Volume: 06, Issue No: 04.
7. B. Shankar (2018)"Seismic &Wind Evaluation Of G+10 Residential Building " International Journal of Civil Engineering and Technology (IJCIET) Volume 9, Issue.
8. C.V.Siva Rama Prasad, Sumith.K, Shivani.R, Tejaswini.R (2019) "Earthquake and Wind Analysis of Multi storey building using Staad.Pro" JETIR March ,Volume 6, Issue 3.



INNO  SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.118



ISSN  INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 9940 572 462  6381 907 438  ijirset@gmail.com



www.ijirset.com

Scan to save the contact details