



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 5, May 2022

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.118

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

Comparative Study of Quarry Dust Pavement Block and PET Bottle Pavement Block

Prof. Jacky Harish Gurnani¹, Vaibhav Rajkumar Kohale², Yash Sanjay Dorlikar³, Divyani Arvind Tripathi⁴, Shivani Wasudeo Chachere⁵, Mayuri Wamanrao Ukey⁶

Assistant Professor, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India¹

UG Student, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India²

UG Student, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India³

UG Student, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India⁴

UG Student, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India⁵

UG Student, Department of Civil Engineering, Nagpur Institute of Technology, Nagpur, Maharashtra, India⁶

ABSTRACT: The Plastic Pavers is ready by utilizing waste plastics. Plastic waste which is extending bit by bit transforms into an imperfection and in this manner dirties the environment, especially in Metropolitan areas. A ton of plastic is being brought into the parcel regions are discarded or consumed which prompts the contamination of the environment and air. Consequently, these waste plastics are to be effectively utilized. The point of this paper is to figure out the correlation of quarry dust asphalt square and pet jugs asphalt blocks. In this paper, the strength and their motivations to be romanticized by figuring out some writing paper and needful need for assembling of quarry residue and pet jugs asphalt blocks. This paper supportive to glorify the fundamental of asphalt blocks producing with various materials and their solidarity by utilizing this material is to be examined in this paper.

KEYWORDS: Quarry Dust, Pet bottles, plastics.

I. INTRODUCTION

Waste plastics

A material which contains more polymers which have more sub-atomic weight Solid are in completed state or same state while assembling or handling into wrapped up articles is known as Plastic. Squander the executives with regard to plastic should possible by reuse. In the event that they are not reused then they will turn out to be large poisons to the climate as they don't break down effectively and furthermore not permit the water to permeate to the dirt and they are likewise toxic. India creates 5.7 million metric huge loads of plastic waste every year. Based on actual properties, plastic can be delegated thermoplastic (remolded) and thermosetting material what shares 80% and 20% separately in absolute plastic waste age. Polyethylene Terephthalate (PETE or PET), High-Density Polyethylene (HDPE), Polyvinyl Chloride (PVC), Low thickness polyvinyl chloride, (LDPE) Polypropylene (PP), Polystyrene or Styrofoam (PS) are a few instances of thermoplastic which can be reused and which are utilized for making plastic paver blocks. Plastic utilized for making plastic paver block is gathered from different sources.

Polyethylene Plastic

HDPE is a sort of polyethylene that is acquire by the flammable gas ethane. Whenever ethane is warmed to 1500 degrees Fahrenheit, the atoms fall to pieces. One of the new particles framed is ethylene. Ethylene is a gas that turns into a pitch during the course of polymerization. A polymer is a chain of particles which structures as a result of compound responses including impetuses and tension. Whenever ethylene atoms are polymerized, they produce polyethylene. Polyethylene and other plastic can be altered to improve specific wanted qualities, like adaptability, strength or impenetrability to a specific substance. Polyethylene can be make into various sorts of plastics: Low-thickness polyethylene, or LDPE, and polyethylene terephthalate, otherwise called PET or PETE.

Defining of Plastic- Looking to the worldwide issue of ecological contamination by post-purchaser plastic waste, research endeavors have been centered around consuming this loss for a huge scope in a productive and harmless to the ecosystem way. Plastic contains in strong as well as in completed state.



Need of reusing the Plastic- Recycling plastic is vital as a result of this material is utilized in the assembling of different items, Recycling is significant to leave this planet for our people in the future. While we having waste plastic then we can use as reuse, reuse and lessen. Be aware of how you treat, regard for the things you purchase, and consistently look at yourself to check whether you want it or then again assuming that it arrives in a bundle with less waste.

II. LITERATURE REVIEW

Tapkire et al (2020) Investigated Recycled plastic utilized in the substantial paver block measure of plastic waste more and the issue for their removal, so squander used in the development business, plastic waste like plastic containers, beds, convey sacks; polypropylene (PP) and polyethylene Terephthalate (PET) were as elective substitutions of a piece of the customary totals of cement. 20% Recycled plastic are utilized instead of totals in concrete, which doesn't influence the properties of cement.

VikramPakrashi et al (2016) Examined Eco-tile is a reasonable asset for development purposes with various potential applications. The blocks are moderately effortlessly made with controlled weight and pressing. Eco tiles have moderately great compressive strength, with values matching that of essential substantial 3D squares. The heaviness of Eco-block was seen to hold an almost relationship with load at disappointment and with explicit strength. Eco-tiles have a somewhat decent explicit strength. They are lightweight however solid for the weight they bear.

Samuel Kofi Tulashie, et al., (2020) broke down the change of plastic squanders into asphalt blocks in Ghana. The physical and synthetic properties of the pit sand, ocean sand, plastic squanders, and asphalt block were considered. The plastic-pit sand asphalt block (PPPB) had stringy surface with more modest pore volume and grain size than the plastic-ocean sand asphalt block (PSAB). At 20% plastic organization, the water absorptivity of plastic-pit sand asphalt square and plastic-ocean sand asphalt expanded at 3.98% and 4.60%, individually. The most extreme compressive qualities of PPPB and PSPB were 40 N/mm² and 28 N/mm². The most extreme elasticity of PPPB (8.2 N/mm²) surpassed the PSPB (6.1 N/mm²). Moreover, expanding the plastic organization further developed the normal infiltration opposition of both asphalt blocks. The outcomes showed that changing over plastic squanders into asphalt blocks is plausible. How much plastic diminished the water absorptivity of the squares however expanded the compressive strength. The greatest water absorptivity of PSPB was 15.5% higher than the PPPB. This was recorded at 20% plastic organization. From the FTIR, Quartz and Kaolin minerals were the fundamental parts of the sand tests, though those of the plastic squanders were polyethylene and polypropylene. The compressive and elasticity of the two squares remained almost steady at 80% and 90% plastic creation. The generally speaking compressive strength, rigidity, and penetrative opposition property of PPPB outperformed the PSPB, which make PPPB a better useful material than PSPB. The outcomes recommend that it is achievable to consolidate pit sand with thermoplastic squanders to frame asphalt blocks, which could be reasonable for building and development of streets in Ghana. This would likewise diminish clog of the ocean and other stream bodies with plastics.

Melina Gomez, et al., (2020) concentrated on the plastic part of waste electrical and electronic hardware (WEEE) contains a lot of brominated fire retardants and weighty metals, which guess a gamble of medical problems to people and the climate. To change this loss into a helpful and to be non-perilous material, they have fostered a clever adjustment system. A center shell reused plastic total (RPA) comprising of crushed WEEE (center) and a combination of concrete and a few added substances like an exceptionally fine total, dirt or actuated charcoal (shell) was acquired. They demonstrated that the center shell system, in which concrete actuated charcoal shell was utilized, produces an adjustment of the unsafe mixtures. Pressure strength tests showed that reused plastic totals could be utilized as swap for sand in concrete mortar. This impact could be tackled with the utilization of initiated charcoal as a settling added substance. Essential to notice to date there could be no other report about the BFRs filtering in concrete network. Additionally, a necessary applied review for the utilization and revalue of this kind of risky waste for common development materials were introduced. The outcomes acquired with initiated charcoal as a balancing out added substance opens a colossal field of study for future explores on various sources and measurements of this and different added substances in the production of the manufactured total. It is deduced that the proposed material will have great properties as warm encasing material because of its high polymer content.

Alejandra VidalesBarriguete, et al., (2020) zeroed in on dissecting the water-safe properties of gypsum compounds with plastic link squander included request to decide the appropriateness of their utilization as a choice to battle dampness issues in structures. The test tests made were presented to the fine water assimilation, water fume porousness, wet chamber, water-oven cycle and absolute water retention tests, and their porosimetry were likewise inspected utilizing the mercury porosimetry test. The outcomes recorded that the critical decline in water assimilation and maintenance limit. Consequently, the material noticed is a decent option in contrast to the gypsums which is to be applied in the space of structures generally presented to the water and it adds to lessen natural effects. With the

utilization of plastic link squander as totals in gypsum lattices, compounds with a water ingestion limit essentially lower than gypsum without plastic link squander were accomplished, while holding, as per the air porousness test, the ability to control relative dampness in the indoor rooms of structures normal for gypsum, as well as keeping their mechanical properties over the base qualities demonstrated in the guidelines. Gypsum with PW can thusly be viewed as a decent mortar to apply in areas of structures with more noteworthy openness to water, for example, storm cellar floors or ground floors on tirades, dividers with breaks and, surprisingly, outside dividers safeguarded by folded rooftops, yards, and so on This would address a decline in the utilization of these normal assets by between 25% to 30%, notwithstanding the decrease in how much existing plastic waste, would add to limiting natural effect through building materials.

III. METHODOLOGY

Batching

The measurement of materials for making block is termed as batching. Use of weight system in batching facilitates accuracy, flexibility and simplicity. The collected waste bottles are cleaned with water and dried to remove the water present inside the plastic and then crushed in crusher machine in a size of 3-4mm and then weighted. The other material like cement, quarry dust, coarse aggregate and the plastic bottles were weighed in various proportion among which the plastic were taken for burning process.

Burning of Plastic



BURNING OF PLASTIC

After batching the crushed plastic bottles were taken for burning in which the crushed plastic are put into the container and allowed to melt at 75°C to 255°C. The first step of burning process includes the arrangement of container and furnace. The setup was arrange to hold the container and it is ignited. The container is placed over the setup and it is heated to remove the moisture present in it.

Precaution to be taken-

- Take a proper ventilated place to burn the plastic.
- Wear a proper mask to protect yourself from toxic gases.
- Wear a well quality hand gloves.

Mixing of Material

Mixing of materials is essential for the production of uniform and strengthens block. The mixing should ensure that the mass becomes homogeneous , uniform in colour and consistency. Generally there are two types of mixing which is hand mixing and mechanical mixing. In this project, we adopted hand mixing. Now, the crushed plastic bottles are added into the container one by one , until the entire plastic content required for making block of one mix proportion is added into it and this plastic is thoroughly mix by using trowel before its hardens.



MIXING OF QUARRY DUST PAVEMENT BLOCK



MIXING OF PET BOTTLE PAVEMENT BLOCK

Mixing of materials is essential for the production of uniform and strengthened block. The mixing should ensure that the mass becomes homogeneous, uniform in colour and consistency. Generally there are two types of mixing which is hand mixing and mechanical mixing. In this project, we adopted hand mixing. Now, the crushed plastic bottles are added into the container one by one, until the entire plastic content required for making block of one mix proportion is added into it and this plastic is thoroughly mixed by using trowel before its hardens.

Moulding



MOULDING

The mixture is then poured into the block mould and for proper compacted by using tamping rod or steel rod. The tamping is done 24 times in at a time filling the mould. The surface is finished by using trowel. Before placing the mixture into the mould, the sides of mould are oiled to easy removal of blocks. Mould removes after 24 hours. The mould is used for preparing block in uniform shape. The size of mould is 19x9x9cm. the mould were assembled and placed on the base plate. The faces must be thinly coated with mould oil to easily De-mould after casting.

Curing

In this process during which chemical reaction or physical action takes place controlling the moisture content from concrete. Curing ensures hydration of cement, which in turn enhance its strength and durability.



IV. RESULT AND DISCUSSION

Calculation and result

This chapter discusses the results of the experimentation carried out in order to compare the graphs along with a brief summary on the quarry dust pavement block and PET bottle pavement block that has been used for the experimentation purpose. Further, a brief discussion is done on the obtained results.

Compressive strength test

Compressive strength of bricks is the capacity of brick to resist or withstand under compression when tested on Compressive testing machine [CTM]. The Compressive strength of a material is determined by the ability of the material to resist failure in the form of cracks and fissure.


Compressive Strength = Max load at which Specimen starts breaking (N) /Contact area (mm²)

Compressive strength test of 3 days curing


Observation table 1

Sr. no.	Specimen	Area	Maximum Load (N)	Apparent Compressive Strength (N/mm ²)	Corrected Compressive Strength (N/mm ²)
1	M20	15776.48	72	4.58	5.13
2	M20	15922.44	83	5.21	5.84
3	M20	15888.04	90	5.66	6.33
4	Plastic block	16734.96	156	9.31	10.43
5	Plastic block	15910.69	154	9.70	10.86
6	Plastic block	15738.03	154	9.78	10.95

Graph of pet bottle pavement block




Graph of quarry dust pavement block





Comparison of compressive strength of 3 days curing




Compressive strength test of 7 days curing

Observation table 2


Sr. no.	Specimen	Area	Maximum Load (N)	Apparent Compressive Strength (N/mm ²)	Corrected Compressive Strength (N/mm ²)
1	M20	15798.02	102	6.46	7.24
2	M20	15812.34	107	6.77	7.58
3	M20	15896.67	112	7.05	7.89
4	Plastic block	15803.06	160	10.12	11.33
5	Plastic block	15890.57	162	10.19	11.41
6	Plastic block	16543.69	169	10.22	11.45

Graph of pet bottle pavement block






Graph of quarry dust pavement block



Comparison of compressive strength of 7 days curing



Water absorption test

The cubes after casting were immersed in water for 28 days curing. They were then weighted and this weight was noted as the wet weight of the paver block. These specimens were then oven dried at the temperature 110°C until the mass became constant and again weighed. This weight was noted as the dry weight of the paver block. % Water Absorption = $[(WW - DW) / DW] \times 100$ Where, WW = Wet Weight of paver block, DW = Dry Weight of paver block.

Water Absorption of Concrete			
Type of Concrete	Wet Weight of cubes in Grams	Dry Weight of cubes in Grams	% water Absorption
M20	3036	2942	3.2
M20	3112	3021	3.01
M20	2993	2910	2.85
Plastic Blocks	2967	2893	2.56
Plastic Blocks	2814	2765	1.77
Plastic Blocks	2774	2722	1.91

V. CONCLUSION

1. We in this study quarry dust pavement block and plastic pavement block obtained higher average compressive strength.
2. Though the various pavement block may be used for footpath, light traffic, walkway.
3. The plastic pavement block made from waste plastic and quarry dust may be cheaper and represent an alternative way of turning waste material into useful product for more sustained construction.
4. Plastic waste use as transitional material could be turned into a resource for cost effective, yet a durable and sustainable material for construction.



5. Other advantage include minimizing plastic waste in the environment, the landfills and water bodies contributing to cleaner cities and towns and creation of more jobs.
6. By addition of plastic it improves the strength up to 40% and reduce the water absorption.

REFERENCES

- [1] P.O. Awoyera, A. Adesina. (2020). 'Plastic wastes to construction products: Status, limitations and future perspective' - *Case Studies in Construction Materials*, 12e00330.
- [2] Samuel Kofi Tulashie, Enoch Kofi Boadu, Francis Kotoka, David Mensah. (2020). 'Plastic wastes to pavement blocks: A significant alternative way to reducing plastic wastes generation and accumulation in Ghana' - *Construction and Building Materials*, 241118044
- [3] Melina Gómez a, Lucas Ernesto Peisino, Jerónimo Kreiker, Rosana Gaggino a, Ariel Leonardo Cappelletti, Sandra E. Martín, Paula M. Uberman, María Positieri, Bárbara Belén Raggiotti. (2020). 'Stabilization of hazardous compounds from WEEE plastic: Development of a novel core-shell recycled plastic aggregate for use in building materials' - *Construction and Building Materials*, 230 116977
- [4] Alejandra Vidales-Barriguete, Evangelina Atanes-Sánchez, Mercedes del Río-Merino, Carolina Piña-Ramírez. (2020). 'Analysis of the improved water-resistant properties of plaster compounds with the addition of plastic waste' - *Construction and Building Materials*, 230116956
- [5] Zhiqiang Yang, Zhiqin Qiang, Min Guo, Guilan Yi, Yonglin Shi, Fangqin Cheng, Mei Zhang. (2020). 'Pilot and industrial scale tests of high-performance permeable bricks producing from ceramic waste' - *Journal of Cleaner Production*, 254120167
- [6] Isaac I. Akinwumi, Ayebaemi H. Domo-Spiff, Adeniyi Salami. (2019). 'Marine plastic pollution and affordable housing challenge: Shredded waste plastic stabilized soil for producing compressed earth bricks' - *Case Studies in Construction Materials*, 11e00241
- [7] M.K. Mondal, B.P. Bose, P. Bansal. (2019). 'Recycling waste thermoplastic for energy efficient construction materials: An experimental investigation' - *Journal of Environmental Management*, 240119–125
- [8] P. Pooja, Manendra Vaitla, Gudapati Sravan, Mt. Purusotham Reddy, Bhagyawati.M. (2019). 'Study on Behavior of Concrete with Partial Replacement of Fine Aggregate with Waste Plastics' - *Materials Today: Proceedings*, 8182–187



INNO SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.118



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details