



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJIRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 11, Issue 5, May 2022

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 8.118

# Home Automation Using the Internet of Things

**Saravanan B<sup>1</sup>, Kavinkumar M<sup>2</sup>, Hari Prasath K<sup>3</sup>, Dhaaneshwar<sup>4</sup>, Hari Krishna S<sup>5</sup>**

UG Scholar, Department of Computer Science and Engineering, Sri Eshwar College of Engineering, Kinathukadavu, Tamilnadu, India<sup>1, 2, 3</sup>

Assistant Professor, Department of Computer Science and Engineering, Sri Eshwar College of Engineering, Kinathukadavu, Tamilnadu, India<sup>4</sup>

Principal & Professor, Sri Eshwar College of Engineering, Kinathukadavu, Tamilnadu, India.<sup>4</sup>

**ABSTRACT:** IoT to regulate home appliances, so automating trendy homes through the net. this technique uses 3 masses to demonstrate house lighting and a disciple. Our easy interface permits a user to simply manage these home appliances through the net. For this technique, we have a tendency to use an associate degree AVR family microcontroller. This microcontroller is interfaced with WLAN electronic equipment to urge user commands over the net. Also, we've got an associate degree show LCD digital display alphanumeric display} to display system standing. Relays square measure won't switch masses. the whole system is battery-powered by a twelve V electrical device. when receiving user commands over the net, the microcontroller processes these directions to work these masses consequently associate degree displays the system standing on an LCD. So, this technique permits economical home automation over the net.

**KEYWORDS:** Wireless Sensor Network, Microcontroller, MySQL server, Relay, LCD

## I. INTRODUCTION

Homes of the twenty-first century can become additional and additional self-controlled and automatic thanks to the comfort it provides, particularly once used in an exceedingly non-public home. A home automation system may be a implies that permits users to regulate electrical appliances of varied sorts. several existing, well-established home automation systems square measure supported wired communication. This doesn't cause a tangle till the system is planned well prior to and put in throughout the physical construction of the building. except for already existing buildings, the implementation value goes terribly high. In distinction, Wireless systems may be of nice facilitate for automation systems. With the advancement of wireless technologies like Wi-Fi and cloud networks in the recent past, wireless systems square measure used daily and all over.

## II. METHOD

### EXISTING SYSTEM

Home automation systems face four main challenges, these are high price of possession, inflexibility, poor tractableness, and problem in achieving security.

### PROPOSED SYSTEM

The projected system may be a distributed home automation system, consisting of a server, and sensors. The server controls and monitors the varied sensors, and might be simply organized to handle additional hardware interface modules (sensors). The Intel uranologist development board, with an integral Wi-Fi card port into which the cardboard is inserted, acts because of the webserver. Automation System will be accessed from the online browser of any native computer within the same computer network mistreatment server IP, or remotely from any computer or mobile hand-held device connected to the net with an applicable application through server real IP (internetIP). Wi-Fi technology is chosen to be the network infrastructure that connects the server and also the sensors. Wi-Fi is chosen to enhance system security (by employing a secure Wi-Fi connection) and to extend system quality and quantifiability.



### **III.SYSTEM DESIGN**

#### **MICROCONTROLLER**

The Microcontroller used here is AN Arduino UNO. The UNO could be a Microcontroller board supported by ATMEGA 328P. The ATMEGA 328P has 32kB of nonvolatile storage for storing code. The board has fourteen digital input and output pins, half a dozen analog inputs, sixteen megacycles per second quartz, USB, AN ICSP circuit, and a push. The UNO may be programmed with the Arduino package

#### **SENSORS**

A device could be a device, module, machine, or system whose purpose is to notice events or changes depending upon the transducer in its setting and send the knowledge to alternative physical science, oftentimes a microcontroller. A device is often used with alternative physical science.

#### **THE ARCHITECTURE OF OUR PROPOSED IoT**

The planned IoT design system consists of Network and Transport Layer, circuit Layer, Application and Presentation Layer, and Physical Layer. IoT entrance router, device manager, and plenty of contact protocols are a part of the info link layer. All the dominant devices are enclosed within the physical layer section. For dominant several devices, an online portal is intended as an online page at the application and presentation layer. The devices may be controlled by creating a BLINK app on an itinerant. the online portal and mobile app do similar works. And the microcontroller will respond accordingly to ensure protection. All this noticeable information /current status happening has to be conveyed to the user.

### **IV.IMPLEMENTATION**

To examine the architecture of our proposed technique, a prototype has been developed that is checked in our laboratory. The implementation part is mainly divided into two parts. One is the hardware part and another is the software part.

#### **HARDWARE IMPLEMENTATION**

The major components of hardware parts are an Arduino UNO, Camera, PIR sensor, LM35 sensor, Humidity sensor, and Relay Bank. Many sensors are interfaced with Arduino UNO through Arduino software programming language and the output is seen in Web and Android App.

#### **SOFTWARE IMPLEMENTATION**

Configure the Arduino UNO. Then, we write a code using Arduino software. programming language to remotely control lights, fans, television, refrigerator, and other home appliance. We use the third-party server as Adafruit for this proto-type but for business purposes we use our server. We connect the code between Arduino UNO and the third-party live server. The Arduino UNO is interfaced with many sensors such as LM35 sensors, Flame sensors, Humidity sensors, and PIR sensors. These sensors are continuously updated data to the server after 3-sec lefts. This can easily change by the user. We develop an Android app using Android Studio to control and monitor home appliances. First, the android app connected the server and sends data to the server from the user's mobile phone via the internet when the user presses the visual button in this android app. Arduino UNO reads the data from the server and executes this instruction. Also, the Android app gets updated JSON data from the live server and is displayed on the mobile screen.

#### **CONTROL VIA MOBILE APP**

Smartphones are often accessed on the house automation system through scientific discipline addresses. [Www.io.adafruit.com](http://Www.io.adafruit.com) could be a hosted server of the smartphone and therefore the remote user sends and receives information through this server. Through a smartphone and scientific discipline address, the user will check the standing and instruct the devices. we've developed an online portal that will additionally manage and monitor the devices. To enter the system AN authentication user-id and watchword are needed that protected the unauthorized user and guarantee security. we tend once we after we with success completed our authentication then we are able to visible the standing of the sunshine, fan, TV, and white goods in each of the rooms wherever they're turned ON/OFF. we tend to be able to see all the devices and we will choose any devices that we wish to regulate.



## **V. CONCLUSION**

Home automation mistreatment of the web of Things has been through an experiment proved to figure satisfactorily by connecting easy appliances thereto and therefore the appliances were with success controlled remotely through the web. The designed system not solely monitors the detector knowledge, like temperature, gas, light, and motion sensors however conjointly actuate a method in keeping with the necessity, for instance, change on the sunshine once it gets dark. It conjointly stores the detector parameters within the cloud in an exceedingly timely manner. this may facilitate the user to research the condition of varied parameters within the home anytime anyplace.

## **VI. FUTURE WORK**

Using this method as the framework, the system will be swollen embrace to incorporate varied different choices that might include home security features like capturing the image of someone on the road the house and storing it onto the cloud. this can scale back the information storage than mistreatment of the CCTV camera which can record all the time and stores it. The system will be swollen for energy observance or weather stations. this type of system with individual changes will be enforced within the hospitals for disabled folks or in industries wherever human invasion is not possible or dangerous, and it may also be enforced for the environmental observance.

## **REFERENCES**

- [1] A. Alheraish, —Design and Implementation of Home Automation System, IEEE Trans. Consum. Electron., vol. 50, no. 4, pp. 1087–1092, 2004.
- [2] H. Jiang, Z. Han, P. Success, S. Robidoux, and Y. Sun, —Voice-activated environmental control system for persons with disabilities, Bioeng. Proc. Northeast Conf., pp. 167–168, 2000.
- [3] A. R. Al-Ali and M. Al-Rousan, —Java-based home automation system, IEEE Trans. Consum. Electron., vol. 50, no. 2, pp. 498–504, 2004.
- [4] S. I. Azid and S. Kumar, —Analysis and performance of a low-cost SMS-based home security system Int. J. Smart Home, vol. 5, no. 3, pp. 15–24, 2011.
- [5] H. ElKamchouchi and A. ElShafee, —Design and prototype implementation of SMS-based home automation system, Int. Conf. Electron. Devices, Syst. Appl., pp. 162–167, 2012.
- [6] J. Pan, R. Jain, S. Paul, T. Vu, A. Saifullah, and M. Sha, —An Internet of Things Framework for Smart Energy in Buildings: Designs, Prototype, and Experiments, IEEE Internet Things J., vol. 2, no. 6, pp. 527–537, 2015.
- [7] D. Li, Z. Aung, J. Williams, and A. Sanchez, —P3: Privacy preservation protocol for automatic appliance control application in smart grid, IEEE Internet Things J., vol. 1, no. 5, pp. 414–429, 2014.
- [8] A. Rajandekar and B. Sikdar, —A survey of MAC layer issues and protocols for machine-to-machine communications, IEEE Internet Things J., vol. 2, no. 2, pp. 175–186, 2015.





**INNO SPACE**  
SJIF Scientific Journal Impact Factor  
**Impact Factor: 8.118**



**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
**INDIA**



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details