



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 8, August 2023

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

Study and Behaviour of Partial Replacement of Cement by Using Silica Fume

SIRANJEEVI A¹, Mr.M. SELVABHARATHI²

Department of Structural Engineering, JAYAM College of Engineering and Technology, Dharmapuri,
Tamilnadu, India

ABSTRACT: Our work was once aimed at learn about and conduct of partial substitute of cement by using the usage of silica fume. In this challenge we in part change the cement by means of the use of silica fume to make bigger the power of concrete. We use the silica fume 30% of weight of cement. Maintenance, restore and rehabilitation of current cement concrete constructions additionally contain a lot of troubles inflicting tremendous expenditure.

The venture for any such material, which can be used as an choice or as a supplementary for cement need to lead to international sustainable and lowest feasible environmental have an effect on Silica fume are some of pozzolanic substances which can be used in concrete as partial substitute of cement.

Here, in this lookup represents the series of statistics from more than a few preceding research accomplished on the compressive strength, flexural strength, tensile power checking out of concrete incorporating silica fume through most advantageous substitute of cement. Portland cement is now days in part changed by using silica fume, a spinoff from silicon alloy factories. The fundamental goal of this literature survey used to be to decide the water permeability and compressive power of concrete containing silica fume, fly ash and excessive slag cement to reap the nice concrete combination having lowest permeability. Nano technological know-how is most fascinating place of science and technology. It is revolution in development industry.

This lookup assessment represents the series of information from a number preceding research finished on the compressive strength, flexural strength, and tensile power checking out of concrete incorporating silica fume by means of greatest alternative of cement. Portland cement is now days in part changed by using silica fume, a spinoff from silicon alloy factories. From a number research Silica fume is a non-metallic and nonhazardous Material having very giant floor region which is appropriate for concrete mix.

KEYWORDS: Silica Fume, Torsional Load, Geopolymer Concrete Longitudinal Reinforcement

I. INTRODUCTION

Leaving the waste substances to the surroundings without delay can motive environmental problem. Hence the reuse of waste fabric from Industries has been emphasized. Waste can be used to produce new merchandise or can be used as admixtures so that herbal assets are used greater effectively and the surroundings is included from waste. These industrial wastes are dumped in the close by land and the herbal fertility of the soil is spoiled. Silica fume is also regarded as micro silica or condensed silica fume, is used as an synthetic pozzolanic admixture.

It is a cloth ensuing from discount of quartz with coal in an electric powered arc furnace in the manufacture of silicon or ferrosilicon alloy. Chemical composition of silica fume Contains extra than ninety percentage silicon dioxide Other elements are carbon, Sulphur and oxides of aluminum, iron, calcium, magnesium, sodium and potassium. The bodily composition of silica fume Diameter is about 0.1 micron to 0.2 microns, Surface location about 30,000 m²/kg and Density varies from one hundred fifty to seven hundred kg/m³. Concrete is a combination of cement, sand, coarse mixture and water.

Its success lies in its versatility as can be designed to face up to cruelest environments whilst taking on the most inspirational forms. Any building undertaking requires numerous substances such as concrete, steel, brick, stone, clay, mud, glass, wooden and many more. However, the cement concrete stays the important building fabric used in building industry. Silica fume is broadly recognised as micro silica or condensed silica fume, is used as an synthetic pozzolanic

admixture. It is a product ensuing from discount of quartz with coal in an electric powered arc furnace in the manufacture of silicon or ferrosilicon alloy.

II. RELATED STUDY

Yogendran (1987) made an try to regulate the homes of concrete with appreciate to its power and different residences by means of the use of silica fume and chemical admixtures. They concluded that most suitable alternative of cement through silica fume for excessive electricity is observed to be 15% for a water cementations ratio of 0.34 at all age.

F. Curcio, B.A. De Angelis, and S. Pagaliolico (1998) in their investigation, super-plasticized mortars containing Silica fume (MK) as 15% alternative of cement and with a water/binder ratio of third have been characterised with 4 commercially handy MK samples have been studied and in contrast to silica fume. Three out of 4 Silica fume samples confirmed enchancement in compressive electricity at early ages, when in contrast to SF, however at ninety days and later the distinction is reduced. The mechanisms by using which silica fume and metal fibers, decrease the harm have been investigated. The outcomes point out that, metal fiber correctly restrained the invitation and propagation of cracks all through the failure.

The presence of metal fibers in excessive energy concrete was once wonderful in restoring the shape below fatigue and affect by using delaying the harm process. Silica fume correctly extended the shape of the inter-face, eradicated the weak spot of the interfacial zone, decreased the range and measurement of cracks, and stronger the capacity of metal fibers to withstand cracking and restrain damage. As a result, the incorporation of metal fibers and silica fume can collectively extend significantly one overall performance of HSC subjected to have an effect on and fatigues. The filler impact of silica fume can limit the quantity and measurement of the unique cracks in the interfacial region and in the bulk of concrete and more suitable the interfacial effect. Steel fibers on the whole strengthen, toughen and withstand cracking in HSC.

M. Frias, M.I. Sanchezderojas, J. Cabrera (2000) in their experimental work, the have an effect on of the pozzolanic undertaking of the Silica fume(MK) on the hydration warmth has been studied in evaluation to the behaviors of different ordinary pozzolanic substances such as flyash and silica fume. The effects printed that MK mortars produce a mild heating expand when in contrast to a a hundred percent Portland cement mortar, due to the excessive pozzolanic recreation of MK. With admire to the hydration heat, MK-blended mortar confirmed nearer behaviors to silica fume than to fly ash.

MoisesFrais, Joseph Cabrera the creator suggests the effects of an investigation focusing on the impact of Silica fume (MK) on the micro-structure of MK-blended pastes. Pastes containing 0%, 10%, 15%, 20% and 25% of MK have been organized at a consistent water/binder ratio of 0.55 and cured at 200°C for hydration intervals from 1 to 360 days. They investigated complete capillary and gel porosity evolution with the curing length and additionally estimated the diploma of hydration in the normal Portland cement and Silica fume blended pastes.

The values of the diploma of hydration are calculated from the quantity of Ca (OH)₂ existing in the paste and from the statistics of differential thermal evaluation (DTA) thermo gravimeter (TG). A true affiliation between porosity and diploma of hydration has been established.

Mr.Sabale Vishal Dhondiram, Miss. Manali Deepak.,ShindeSuraj Dadasahe.b, Miss. BhagwatMayuri (2013) cement substitute up to 10% with silica fume leads to amplify in compressive strength, splitting tensile power and flexural strength, for each M60grade. Beyond 10% there is a minimize in compressive strength, tensile energy and flexural energy for 28 days curing period. There is a reduce in workability as the alternative degree increases, and consequently water Consumption will be extra for greater replacements.


The most substitute stage of silica fume is 10% for M60grade of concrete. Use of silica fume offers good sized end result on residences of concrete as in contrast to regular concrete.

V. M. Malhotra (2014) superb plasticized concretes exhibit good sized will increase in droop barring any considerable segregation. Super plasticized, high-strength concretes can be positioned in closely bolstered and inaccessible areas. The loss of hunch with time is one of the serious obstacles of these new water reducers. However via really appropriate resolution of the dosage price and via adding brilliant plasticizers to concrete at a jobsite this hassle can be minimized or eliminated.



At the producers advocated splendid plasticizer dosages, the 28-day compressive strengths are equal to or larger than the corresponding strengths of the reference mix, whether or not or now not compacted with the aid of vibration. This suggests that high- electricity amazing plasticized concretes can be positioned in types besides mechanical compaction. Data on the elastic houses of awesome plasticized concretes are restrained and inconclusive.

III. SYSTEM METHODOLOGIES



IV. MATERIALS

i. Cement

Ordinary Portland Cement of Ultratech company of fifty three grade confirming to IS: 12269-1987(9) was once used in the existing study. A cement is a binder, a substance used for development that sets, hardens, and adheres to different substances to bind them together. Cement is seldom used on its own, however instead to bind sand and gravel (aggregate) together. It finds utility in foundations and slabs-on-ground, walls, beams, columns, floors, roofs, bridges, pavements, and different infrastructure.

It constitutes solely about 20 per cent of the complete quantity of concrete mix; it is the lively element of binding medium and is the solely scientifically managed ingredient of concrete. Portland cement referred as (Ordinary Portland Cement) is the most vital kind of cement and is a first-class powder produced through grinding Portland cement clinker. The OPC is labeled into three grades, particularly 33 Grade, forty three Grade, fifty three Grade relying upon the power of 28 days.



ii. Coarse Aggregate

Coarse Aggregate Crushed combination conforming to IS: 383-1987 used to be used. Those particles that are predominantly retained on the 4.75 mm (No. 4) sieve and will skip via 3-inch screen, are known as coarse aggregate. The coarser the aggregate, the greater competitively priced the mix. Larger portions provide much less floor region of the particles than an equal quantity of small pieces.



iii. Fine Aggregate

- The Wainganga sand was once used as best aggregate. Fine aggregates furnish dimensional steadiness to the mixture.
- The elastic modulus and abrasion resistance of the concrete can be influenced with exceptional aggregate.
- Fine aggregates first-rate additionally have an impact on the combination proportions and hardening properties.
- The houses of exceptional aggregates additionally have a tremendous affect on the shrinkage of the concrete.



iv. Water

Water conforming to as per IS: 456- 2000 used to be used for mixing as nicely as curing of concrete specimens. Water is needed, however after the want is met, it starts to harm the concrete. There are two sorts of water in concrete: water of necessity (also recognized as water of hydration) and water of convenience. The principal elements of concrete are pleasant combination (sand), coarse mixture (gravel or stone), cement and water.



V. COMPRESSIVE STRENGTH RESULTS AND COMPARITIVECHARTS


COMPRESSIVE STRENGTH FOR NORMAL CONCRETE IN GRADE M50

Water cement ratio : 0.32

Concrete ratio : 1:0.86:1.88


COMPRESSIVE STRENGTH FOR 7 DAYS

S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM ²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm ²
1	150x150x150	22500	860	38.22
2	150x150x150	22500	880	39.11
3	150x150x150	22500	870	38.67



COMPRESSIVE STRENGTH AT 28 DAYS

S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM ²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm ²
1	150x150x150	22500	1190	52.88
2	150x150x150	22500	1200	53.88
3	150x150x150	22500	1210	53.78



COMPRESSIVE STRENGTH FOR CONCRETE REPLACING 20% OF SILICA FUME IN GRADE OF M50 AT 7 DAYS

S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm²
1	150x150x150	22500	850	37.78
2	150x150x150	22500	8700	38.67
3	150x150x150	22500	860	38.22





Chart of concrete (80% cement+20% silica fume at 7 days)

20% OF SILICA FUME IN GRADE OF M50 AT 28 DAYS



S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM ²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm ²
1	150x150x150	22500	1210	53.77
2	150x150x150	22500	1230	54.67
3	150x150x150	22500	1220	54.22



COMPRESSIVE STRENGTH FOR CONCRETE REPLACING 30% OF SILICA FUME IN GRADE OF M50 AT 7 DAYS

S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM ²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm ²
1	150x150x150	22500	840	37.33
2	150x150x150	22500	850	37.78
3	150x150x150	22500	830	36.89




Chart of concrete (70% cement+30% silica fume at 28 days)



COMPRESSIVE STRENGTH FOR CONCRETE REPLACING 30% OF SILICA FUME IN GRADE OF M50 AT 28DAYS

S.NO	SIZE OF CUBE IN MM	AREA OF LOADING FACE IN MM ²	LOAD AT FLEXURE IN(KN)	COMPRESSIVE STRENGTH AT 7 DAYS IN N/mm ²
1	150x150x150	22500	1180	52.44
2	150x150x150	22500	1190	52.89
3	150x150x150	22500	1170	52




Chart of concrete (70% cement+30% silica fume at 28 days)

COMPRESSIVE STRENGTH GRADE M50 28 DAYS

S.NO	USED MATERIALS	COMPRESSIVE STRENGTH
1	M50 at 100% cement only used	53.33N/mm ²
2	M50 at 80% cement & 20% silica fume used	54.22N/mm ²
3	M50 at 80% cement & 20% silica fume used	54.22N/mm ²

VI. RESULTS

SPECIFIC GRAVITY TESTING MACHINE



COMPRESSIVE STRENGTH MACHINE



CONCRETE CUBE MOULD (150MM X 15MM X 150MM)



WE USED SILICA FUME



VII. CONCLUSION

We entire our assignment effectively of STUDY AND BEHAVIOUR OF PARTIAL REPLACEMENT OF CEMENT BY USING SILICA FUME.

It effects whilst addition of S.F as proven in below Based on the laboratory take a look at results, it is located that the concrete is increasing with addition of pozzolans in identical proportions such as 20% and 30% by weight of cement. The compressive power bought for proportions after 28 days are.

M50 at one hundred percent cement solely used = 53.33N/mm²

M50 at 80% cement & 20% silica fume used = 54.22N/mm²

M50 at 80% cement & 20% silica fume used = 54.22N/mm²

This addition offers the concrete true stoop and compaction factor. It is suggested that further evaluation will be carried out the different share of pozzolans brought with concrete compressive energy can be achieved.

The most electricity of concrete in evaluation barring is very less. But the rate of acquire of power of fly ash concrete is very low inside 28 days however there after for the 60 and ninety days cured samples the rods is excessive and the exceeds that of conventional concrete. Concrete containing silica fume can have very excessive power and can be very durable.

REFERENCES

- [1] D.L.Y. Kong, J.G. Sanjayan, Damage behavior of geopolymer composites exposed to elevated temperature, *Cement Concrete Composites*, 2008, pp. 986-991.
- [2] J. Davidovits, Properties of geopolymer cements, *International Journal of Alkaline Cements and Concretes*, 1994, pp. 131-149.
- [3] D. Khale, R. Chaudhary, Mechanism of geopolymerization and factors influencing its development: a review, *Journal of Material Science*, 2007, pp. 729-746.
- [4] N.A. Lloyd, B.V. Rangan, Geopolymer concrete: a review of development and opportunities, In the Proceedings of 35th conference on our world in concrete and structures, Singapore Concrete Institute, Singapore, 2010, pp 25-27.
- [5] G. Li, X. Zhao, Properties of concrete incorporating fly ash and ground granulated blast furnace slag, *Cement Concrete Research*, 2003, pp. 293-299.
- [6] R. Siddique, D. Kaur
Properties of concrete containing ground granulated blast furnace slag (GGBFS) at elevated temperatures
Journal of Advanced Research (2012), pp. 45-51
View PDF View article View in Scopus
- [7] P. Purushothaman, Reinforced concrete structural elements, behavior, analysis and design. New Delhi, Tata McGraw Hill Publishing Company Limited, 1984, pp. 169.
- [8] B.C. Punmia, Jain Ashok Kumar, Jain Arun Kumar, Limit state design of reinforced concrete. New Delhi, Laxmi Publications (P) Ltd, 2007, pp. 194.
- [9] H.J. Cowan HJ, Tests of the torsional strength and deformation of rectangular reinforced concrete beams, *Concrete Construction Engineering*, 1951, pp. 51-9.
- [10] T.T.C. Hsu, Torsion of structural concrete-interaction surface for combined torsion, shear and bending in beams without stirrups. American Concrete Institute, 1968, pp. 51-60.



INNO SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.423



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

9940 572 462 6381 907 438 ijirset@gmail.com



www.ijirset.com

Scan to save the contact details