



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

IJIRSET

International Journal of Innovative Research in
SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 1, January 2023

ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA

Impact Factor: 8.118

9940 572 462

6381 907 438

ijirset@gmail.com

www.ijirset.com

Depression Intensity Estimation via Social Media: *A Deep Learning Approach*

Mr. Prajwal Dudhe¹, Mr. Anurag Jaiswal², Mr. Rohan Ghodke³, Mr. Prajoth Kamble⁴, Prof. Asharani Chadchankar⁵

B. E. Student, Department of Computer Engineering, NBN Sinhgad School of Engineering, Ambegaon Bk, Pune, India¹

B. E. Student, Department of Computer Engineering, NBN Sinhgad School of Engineering, Ambegaon Bk, Pune, India²

B. E. Student, Department of Computer Engineering, NBN Sinhgad School of Engineering, Ambegaon Bk, Pune, India³

B. E. Student, Department of Computer Engineering, NBN Sinhgad School of Engineering, Ambegaon Bk, Pune, India⁴

Professor, Department of Computer Engineering, NBN Sinhgad School of Engineering, Ambegaon Bk, Pune, India⁵

ABSTRACT: One of the most prevalent and disabling mental conditions that seriously influence society is stress and depression. The use of social networking to improve the detection of stress and depression may require automatic health monitoring systems. Sentiment analysis refers to the use of content mining and natural language processing techniques with the goal of identifying feelings or opinions. Full of emotion Computing is the study and development of systems and equipment that can recognize, understand, process, and imitate human effects. Deep learning and sentiment analysis approaches could provide effective algorithms and frameworks for a target evaluation and observation of mental issues, particularly depression and stress. This research discusses the use of sentiment analysis and deep learning approaches for the detection and monitoring of stress and depression. Additionally, a fundamental foundation for a multimodal framework that integrates estimating investigation and extensive methods for processing feelings is given. This framework will be used to assess for stress and sadness. The paper specifically traces the fundamental problems and compares them to the framework's structure.

KEYWORDS: Stress and depression; e-health; sentiment analysis, social media, deep learning.

I. INTRODUCTION

The richest source of human-generated text input is likely social media. Internet users' opinions, comments, and criticisms reveal their attitudes and feelings about subjects. This paper introduces a knowledge-based system that monitors users' emotional health in order to identify users who may be experiencing psychological problems, including sadness and stress. In most cases, these psychiatric disorders' symptoms are passively observed. The author contends that in this case, extracting online social behaviour provides a chance to actively recognize psychological disease at an early stage. Because the psychological aspects covered in the typical diagnostic criteria questionnaire cannot be seen by the registers of online social activities, diagnosing the disease might be challenging.

One of the most prevalent and incapacitating mental disorders, depression and stress also has a significant social influence. Currently, strategies for stress and depression identification and diagnosis rely on self-reporting along with the knowledgeable judgement of healthcare professionals. To enhance the performance of healthcare professionals and reduce healthcare expenses, it may be essential to provide efficient health monitoring systems and diagnostic tools. Sentiment and deep learning technologies may be able to aid with these goals by offering efficient tools and systems

for impartial evaluation. These programs and tools could assist the decisions made by psychologists and psychiatrists rather than trying to replace them.

Our new and cutting-edge method for identifying psychological disorders does not rely on respondents' self-reports of those psychological characteristics on surveys. Instead, suggest a machine learning technique for the detection of psychological disorders in social networks that makes use of the features gathered from the data of social networks to precisely identify potential disorders. In addition to analysing features of the two categories of psychiatric diseases, we analyse characteristics 2 and apply machine learning to huge data sets.

II. MOTIVATION

This study talked about how difficult it is to identify early-stage depression from user tweeting behaviour. We proposed a deep learning approach for evaluating the severity of depression using social media data. This study was motivated by the need to use social media to evaluate depression severity in real time so that appropriate therapy may be provided based on the degree of the depression. We developed a self-supervised relabeling method for a benchmark depression dataset, created a comprehensive set of discriminative depression-related user factors, and proposed an LSTM network to identify different levels of depressed Twitter users. The effectiveness of our method, which outperformed the other options for intensity estimate, was demonstrated by extensive studies on a standard dataset.

III. LITERATURE SURVEY

- A. Hao, G. Pang et al, proposed based providing appropriate social support to prevention of depression for highly anxious sufferers. In this study, AI and DI follow the Gaussian distribution, according to the researchers. As a result, when clustering AD points, a GMM has been used. As a result, a number of useful clusters have been discovered, each with its own semantics and observations. Correlation analysis was used to evaluate the relationship between anxiety, depression, and SS. Based on the examination of real data sets, our findings imply that high-level SS can minimize the risk of depression in extremely stressed undergraduates.
- B. Pappa, V. Ntella et al, proposed based "Prevalence of depression, anxiety, and insomnia among healthcare workers during the COVID-19 pandemic: A systematic review and meta-analysis. In this paper, our systematic review and meta-analysis provide a timely and complete synthesis of the available information, showing healthcare professionals' high rates of depression, anxiety, and insomnia. The findings can be used to quantify staff support needs and to inform tiered and personalized treatments that improve resilience and reduce susceptibility in pandemic situations.
- C. Anwaret al, proposed based Inferring location types with geo-social-temporal pattern mining. In this Study, Our systematic review and meta-analysis provide a timely and complete synthesis of the available information, showing healthcare professionals' high rates of depression, anxiety, and insomnia. The findings can be used to quantify staff support needs and to inform tiered and personalized treatments that improve resilience and reduce susceptibility in pandemic situations.
- D. Shen et al, proposed based "Depression detection via harvesting social media: A multimodal dictionary learning solution. The goal of this study is to use social media to diagnose depression in real time. This study uses a multimodal depressive dictionary learning method to detect depressed people in Twitter, using benchmark depression and non-depression datasets as well as well-defined discriminative depression-oriented feature groups. On a large-scale depression-candidate dataset, the researchers looked at the contribution of feature modalities and identified depressed users to uncover some underlying online behaviour differences between depressed and non-depressed users on social media.
- E. Shen et al, proposed based on Cross-domain depression detection via harvesting social media. The addressed the issue of using multi-source datasets to improve depression identification using social media in this work. A cross-domain Deep Neural Network model with Feature Adaptive Transformation & Combination approach (DNN-FATC)

to transmit meaningful information across diverse domains is presented in Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence.

IV. EXISTING SYSTEM

They previously gave a credible signal of the potential for the COVID-19 pandemic to impair the mental health of HCWs in earlier research. Furthermore, because all of the studies in our meta-analysis were cross-sectional, the long-term effects of the COVID-19 pandemic on HCW mental health require further investigation. Flatency is a broad measure that can be used to solve any problem in which a system must quickly analyse a sequence of elements connected with an object and make a prediction about the object's class. They exclusively look at Flatency in the context of early depression identification on social media. To compare each model to the baseline, Wilcoxon's Signed Rank significance test was employed as before (vanilla BS). These compared the performance of three affective strategies: affective word embeddings as input, affective loss functions, and affectively diverse decoding, and showed how they might be combined. MDL, which covers both clinical depression criteria and online social media activities. Their multimodal depressive dictionary learning model approaches the problem as a binary classification problem, determining whether or not a user is depressed. For depression intensity measurement, MDL is combined with our labelling technique.

V. CONCLUSION

The goal of this study is to use social media to diagnose depression in real time. Mental health has been a major worry throughout the ongoing COVID-19 pandemic and frequent lockdowns. Using social media data, we suggested a deep learning method for estimating the severity of depression. This project intends to estimate the severity of depression in real time using social media in order to aid in correct therapy based on the severity of the depression. In a self-supervised way, we built a relabelling technique for a benchmark depression dataset, designed a rich collection of discriminative depression-related variables for users, and proposed an LSTM network to detect depressed users of various levels on Twitter. Extensive studies on a standard dataset proved the performance of our method, which outperformed the other alternatives for intensity estimate. Our binary classification approach outperforms the existing binary classification method by more than 2% of the time. This research points in various promising directions for the future. For recognizing the spread of depression among social communities, it would be interesting to investigate the social network structure and user locations. The researcher will lead the development of automatic preliminary assessment methods based on social data in future study.

REFERENCES

1. F. Hao, G. Pang, Y. Wu, Z. Pi, L. Xia, and G. Min, "Providing appropriate social support to prevention of depression for highly anxious sufferers," *IEEE Trans. Comput. Social Syst.*, vol. 6, no. 5, pp. 879–887, Oct. 2019.
2. Sugumar, R. (2022). Estimation of Social Distance for COVID19 Prevention using K-Nearest Neighbor Algorithm through deep learning. *IEEE 2 (2):1-6*.
3. Dong Wang, Lihua Dai (2022). Vibration signal diagnosis and conditional health monitoring of motor used in biomedical applications using Internet of Things environment. *Journal of Engineering 5 (6):1-9*.
4. S. Pappa, V. Ntella, T. Giannakas, V. G. Giannakoulis, E. Papoutsis, and P. Katsaounou, "Prevalence of depression, anxiety, and insomnia among healthcare workers during the COVID-19 pandemic: A systematic review and meta-analysis," *Brain, Behav., Immunity*, vol. 88, pp. 901–907, Aug. 2020.
5. Vemula VR. Adaptive Threat Detection in DevOps: Leveraging Machine Learning for Real-Time Security Monitoring. *International Machine learning journal and Computer Engineering*. 2022 Nov 17;5(5):1-7.
6. T. Anwar, K. Liao, A. Goyal, T. Sellis, A. S. M. Kayes, and H. Shen, "Inferring location types with geo-social-temporal pattern mining," *IEEE Access*, vol. 8, pp. 154789–154799, 2020
7. R. Sugumar, A. Rengarajan and C. Jayakumar, Design a Weight Based Sorting Distortion Algorithm for Privacy Preserving Data Mining, *Middle-East Journal of Scientific Research 23 (3): 405-412*, 2015.
8. G. Shen et al., "Depression detection via harvesting social media: A multimodal dictionary learning solution," in *Proc. 27th Int. Joint Conf. Artif. Intell.*, Aug. 2017, pp. 3838–3844.



9. T. Shen et al., “Cross-domain depression detection via harvesting social media,” in Proc. 27th Int. Joint Conf. Artif. Intell., Jul. 2018, pp. 1611–1617.
10. F. Sadeque, D. Xu, and S. Bethard, “Measuring the latency of depression detection in social media,” in Proc. 11th ACM Int. Conf. Web Search Data Mining, Feb. 2018, pp. 495–503.
11. Praveen Sivathapandi, Prabhu Krishnaswamy (2022). Advanced AI Algorithms for Automating Data Preprocessing in Healthcare: Optimizing Data Quality and Reducing Processing Time. Journal of Science and Technology (Jst) 3 (4):126-167.
12. K. Thandapani and S. Rajendran, “Krill Based Optimal High Utility Item Selector (OHUIS) for Privacy Preserving Hiding Maximum Utility Item Sets”, International Journal of Intelligent Engineering & Systems, Vol. 10, No. 6, 2017, doi: 10.22266/ijies2017.1231.17.
13. M. Trotzek, S. Koitka, and C. M. Friedrich, “Utilizing neural networks and linguistic metadata for early detection of depression indications in text sequences,” IEEE Trans. Knowl. Data Eng., vol. 32, no. 3, pp. 588–601, Mar. 2020.
14. Srinivasarao Thumala, "Building Highly Resilient Architectures in the Cloud," Nanotechnology Perceptions 16(2), 2020. [Online]. Available: Shekhar Mishra <https://iaeme.com/Home/journal/IJCET> 1676 editor@iaeme.com https://www.researchgate.net/publication/387871975_Building_Highly_Resilient_Architectures_in_the_Cloud [
15. T. Cai, J. Li, A. S. Mian, R. Li, T. Sellis, and J. X. Yu, “Targetaware holistic influence maximization in spatial social networks,” IEEE Trans. Knowl. Data Eng., early access, Jun. 17, 2020, doi: 10.1109/TKDE.2020.3003047.
16. T. Anwar, K. Liao, A. Goyal, T. Sellis, A. S. M. Kayes, and H. Shen, “Inferring location types with geo-social-temporal pattern mining,” IEEE Access, vol. 8, pp. 154789–154799, 2020.
17. Soundappan, S.J., Sugumar, R.: Optimal knowledge extraction technique based on hybridisation of improved artificial bee colony algorithm and cuckoo search algorithm. Int. J. Bus. Intell. Data Min. 11, 338 (2016)
18. Sandeep Belidhe, Sandeep Kumar Dasa & Santosh Jaini, “Optimizing Object Detection in Dynamic Environments With Low-Visibility Conditions”, International Journal of Advanced Trends in Engineering and Technology, Volume 6, Issue 2, Page Number 64-67, 2021.
19. R. I. Shader, “COVID-19 and depression,” Clin. Therapeutics, vol. 42, no. 6, pp. 962–963, 2020



INNO SPACE
SJIF Scientific Journal Impact Factor
Impact Factor: 8.118



ISSN INTERNATIONAL
STANDARD
SERIAL
NUMBER
INDIA



INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

 **9940 572 462**  **6381 907 438**  **ijirset@gmail.com**



www.ijirset.com

Scan to save the contact details