



e-ISSN: 2319-8753 | p-ISSN: 2347-6710

# IJRSET

International Journal of Innovative Research in  
**SCIENCE | ENGINEERING | TECHNOLOGY**

# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 12, Issue 9, September 2023

**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

[ijirset@gmail.com](mailto:ijirset@gmail.com)

[www.ijirset.com](http://www.ijirset.com)

# Optimization Error of Massive MIMO System using Channel Equalization Technique

Ekta Khobragade

Assistant Professor, Department of Electronics and Communication Engineering, Madhyanchal Professional University, Bhopal, India

**ABSTRACT:** The emerging Fifth Generation (5G) communication supports not only voice communications but also high speed data and multimedia services. Nowadays, multicarrier systems are quickly developing in wireless communication because of high data rate requirements. Orthogonal Frequency Division Multiplexing (OFDM) is a digital modulation method implemented in many wired or wireless communications. The main drawback of multicarrier transmission is signal degradation due to propagation loss that limits its applications. The target of future wireless technology is to provide the effective utilization of higher bandwidth at higher quality of service with efficient transmission technique. Channel estimation in linear system is carried out with conventional Least Square (LS) and Minimum Mean Square Error (MMSE) estimation algorithms. The performance of MIMO-OFDM system is evaluated on the basis of BER and mean square error. The channel estimation plays an important role in MIMO-OFDM system to increase the capacity of the system by improving the system performance in terms of BER.

**KEYWORDS:** Orthogonal Frequency Division Multiplexing (OFDM), Multiple Input Multiple Output (MIMO), Bit Error Rate (BER), Channel Estimation

## I. INTRODUCTION

For voice transmission, the original (1G) was a straightforward FDMA (frequency division multiple access) framework. In order to enhance client limit, voice quality, and range proficiency, the 2G cell frameworks employ advanced adjustment plans based on time division different access (TDMA) with source and error amendment coding procedures. These frameworks had the option to impeccably offer essential types of assistance data transfer capacity administrations like communication, Web access and mixed media whenever and from anyplace through a solitary gadget. Wideband services like remote Internet access (with a maximum speed of 384 Kbps) and video transmissions (with a maximum information rate of 2 Mbps) are available.

The media transmission inquire about network started working for the fourth generation (4G) of remote correspondence as the 3G innovation and its predecessor, 3.5G, clogged in a few years. The goal is to have information rates between 100 and 500 Mbps with high quality and security. Co-channel interference occurs when users of different cells use the same resource, while adjacent cell interference occurs when users of the same cell create interference. Spreading, frequency diversity, and space diversity were used as countermeasures to combat these impairments. As a result, the international telecommunications union (ITU) has standardized the MIMO MC CDMA system for 4G and beyond.

Doppler spread and excessive multi-path propagation degrade the current wireless communication system's performance. The proportion of time dispersion caused by multipath delay spread decreases as the symbol duration increases in lower rate parallel SCs. Despite OFDM's resistance. In contrast to conventional schemes like TDMA/FDMA, this can also handle the asynchronous nature of multimedia traffic in order to cater to a larger number of users with enhanced services. Due to the hostile frequency selective channel and the spreading processing gain, CDMA systems can coherently combine the components of multiple paths by employing Rake receivers. This makes them resistant to interference from multiple users conventional CDMA does not appear to be an option when data rates reach 100 megabits per second. Further to upgrade the exhibition, the MIMO gathering mechanical assemblies at the two pieces of the deals association recognizes of the transmitter and relay in the network to reduce ISI, accommodate a larger number of users, and enhance performance in order to resolve.



II. METHODOLOGY

Exploration of untapped frequency spectrum, such as mmWave, has begun as a result of the massive rise in popularity of smartphones and mobile data applications that require bandwidth and data rates of the order of Gb/s. In addition to catering to achieving high QoS and QoE and providing seamless connectivity, ongoing research is advancing our understanding of biological safety at high frequencies. It is necessary to update government policies regarding safety standards and regulations and to guarantee the exposed public's safety and dependability. This article is blessed to give a knowledge into wellbeing impacts relating to mmWave frequencies, tending to viewpoints like warm warming in the body tissues with temperature increase, explicit ingestion rate (SAR), power thickness. EM (Electromagnetic) radiation reduction for the mobile communication system has been proposed as a solution in the form of a proposed mode known as "Thermal Radiation" (TR), which endorses its safe use, promotes Green WCN, increases energy efficiency, and reduces complexity for upcoming generations. Based on simulation results, the proposal also confirms that human tissue produces lower power density, SAR, and temperature elevations when compared to other models. It has the potential to improve the security and dependability of future 6G networks and beyond. Since their inception in the 1970s, the wireless and mobile communication systems have experienced remarkable growth over the past ten years [6].

Due to the effects of electromagnetic radiation on humans, plants, animals, and the ecosystem as a whole, the number of base stations that are being built is increasing rapidly [3]. There have been developing worries and examinations with respect to the unfriendly effect that the radiation openness has caused on the organic wellbeing of the creatures. In addition to increasing the location of base stations, research is underway to explore the mmWave frequency band and other unused spectrum bands.

In, the International Commission on Non-Ionizing Radiation Protection (ICNIRP) outlined the permissible exposure limits and safety standards for EM radiation up to 300 GHz. In, the National Radiological Protection Board (NRPB) of the United Kingdom has also provided guidelines for the same in a number of reports, citing effects like injury, illness, and thermal heating of human tissues.





Fig. 1: Block Diagram of OFDM with Channel Estimation






Fig. 2: Block Diagram of MIMO System with PN Sequence

These worries have additionally been featured in the new occasions during ITU. More than half of the emissions are caused by mobile networks alone, followed by telecom devices. This figure is supposed to rise considerably more soon. The frequency of operation and transmission power of the EM radiation emission sources are present. There are numerous negative effects from this. Because they receive the most exposure, the brain, skin, and eyes are the most affected areas in humans. Damage to the cornea results from radiation absorption by the eyes. Radiation absorption by the epidermis, the skin's surface layer, and the dermis, the skin's deeper layer, also has an impact on the skin. Tissues become heated as a result of the rising temperature, and it has also been confirmed that the power density exposure to the human body is also high at high frequencies like mmWave. After the mode has been identified, the UE, gNB, and AMF do not receive any UL or DL NAS messages or information when they encounter the flight mode. Figure 2 provides a description of the proposed state transition for the user equipment from the Idle state to the Connected state.

### 1.1 CHANNEL EQUALIZATION TECHNIQUES

When contemplating a wireless broadcast, the channel incorporates not only ISI, but also anything called fading, arising from disruptive conflict between different routes. In this regard, the user movements which create a frequency offset because of the doppler effect causes phase and power fluctuations over time. These channel differences must be modified by equalizers. Time diversity or frequency diversity are important in achieving high-quality; lower SNR. Researchers quickly discovered yet another way to improve quality: to leverage spatial variability. Why not have more than one antenna instead of communicating from one antenna or, likewise, why not use a more than 1 antenna to receive information if a single transmitting antenna is used? As a consequence, the so-called MISO and SIMO systems have been developed. New equalization strategies have been suggested which lead to substantial decreases of the recipient output BER. Finally, with the above situations being generalized, we may consider multiple transmitting and receiving antennas leading to MIMO structures.

The equalization is the process of removing the effect of noise due to ISI in the channel. There are two types of equalization, linear and non-linear. The main advantages of using MIMO-OFDM technology are increased diversity and range gain which increases the coverage area and enhances the service quality of the communication system. The main aim of the work is to find a solution for the distortion in the communication channel and increase the capacity of the system to obtain better BER performance by using an efficient Wiener Hammerstein equalization technique. The MIMO technology can be used effectively to meet these requirements by taking advantage of multipath propagation without interference. This method diminishes the path loss by developing the multipath tolerance of OFDM with the WH equalization technique, that gives an improved result in terms of efficiency and BER.

## III. SIMULATION RESULT

Practically ICE is not possible therefore the proposed system is tested with the actual channel estimation using pilot signal. Hence the MPCE based MMSE increases the  $E_b/N_0$  requirement from 9.8 dB to 10 dB. Equalization and channel estimations are carried out in the receiver when the channel is affected by multipath fading effect. To improve the channel quality ITBF is incorporated in the transmitter side that allows the transmitter to concentrate the transmitted power onto a desired spatial direction; thus augmenting the received SNR at the intended receiver and drastically reducing the interference of non desired ones.




Fig. 3: Execution of 2 x 2 x 2 receiving wire setup for 16 QAM

Thus the ITBF technique reduces the  $E_b/N_0$  requirement from 10 dB to 7.2 dB. The channel quality between the transmitter and receiver is improved by NR which in turn reduces the  $E_b/N_0$  to 4.2 dB for NR with single antenna and 2.8 dB for NR with two antennas. After incorporating all the techniques the overall performance due to the reduction of ISI, increase in SNR and improvement in link reliability.

The simulation results are depicted in Figures 4 and 5, and the system's performance is also evaluated using 16 QAM modulation, which show the BER performance of MIMO MC CDMA for 64 SCs using 2 x 2 x 2 antennas and 2 x 1 x 2 antennas, respectively. As ITBF improves gain in the desired direction, rejects interference, and relay increases link reliability, the BER of ITBF with NR decreases.




Fig. 4: Execution of 2 x 1 x 2 receiving wire setup for 16 QAM




Fig. 5: Execution of 2 x 2 x 2 receiving wire setup for 16 QAM

This zone will be working in low recurrence and not extremely high frequencies so that the destructive influence is restricted as likewise keeping in view the necessity of information pace of such kind of group. Materials with a high penetration loss or material loss will be used in any construction in this area. This is being done to make the zone much safer to use. Concrete wall, concrete slab, and dry wall can be used as building materials in these areas due to their high path loss. It is possible to construct recreational parks, schools for children under the age of 10, and other activities that do not require the labor associated with high data demand in this area. The most vulnerable members of society can be made to operate in much safer and greener areas in this manner.




Fig. 6: Execution of 4 x 1 x 4 receiving wire setup for 16 QAM

#### IV. CONCLUSION

MIMO MC CDMA with Equalization under ICE is practically impossible, so MIMO MC CDMA with MPCE can still be used to optimize the proposed system's performance. To make the framework more practical, MPCE is integrated and the framework execution is tried for various receiving wire design, various SCs and adjustment. MIMO MC CDMA with equalization by MPCE has a performance of 16.66 percent, which is 1.67 percent lower than the system with equalization under ICE for QPSK (128/4 x 4), which is in line with the estimation here. However, for various modulations, the performance is enhanced by increasing antenna diversity and frequency diversity.

When the channel is impacted by multipath fading, the receiver incorporates MPCE-based MMSE equalization to boost system performance. To decrease the impact of multipath blurring in the channel and to further develop the connection execution, the transmitter is outfitted with ITBF in which a variety of receiving wires is coordinated to the ideal client, to further develop the gathering quality. The BER performance improves when an ITBF-based MPCE-based MMSE equalization is used in a MIMO MC CDMA system. The results of a second simulation with different antenna configurations and SCs indicate that the proposed system performs 28% better than MIMO MC CDMA with equalization.

The proposed system also includes cooperative communication through an AF relay node to boost system performance. NR with one antenna (2x1x2,4x1x4) and NR with two antennas (2x2x2,4x2x4) are used in the simulation for MIMO MC CDMA with ITBF and MPCE-based MMSE equalization. Based on the findings, it can be deduced that the proposed NR with a single antenna performs better than MIMO MC CDMA with MPCE-based MMSE equalization and ITBF by 41.66%. Therefore, the loss and noise are the result of NR's reliable link and spatial diversity.

#### REFERENCES

- [1] Mustafa S. Aljumaily and Husheng Li, "Hybrid Beamforming for Multiuser MIMO mm Wave Systems Using Artificial Neural Networks", International Conference on Advanced Computer Applications, IEEE 2021.
- [2] Osama I., Mohamed R., Mohamed E. and Sami E., "Deep Learning Based Hybrid Precoding Technique for Millimeter-Wave Massive MIMO Systems", IEEE International Conference on Electronic Engineering, IEEE 2021.
- [3] Amirashkan F., Alireza S., Ulf G., Alex A. and Frans M. J., "Dropnet: An Improved Dropping Algorithm Based on Neural Networks for Line-of-Sight Massive MIMO", Special Section on Beyond 5G Communications, IEEE Access 2021.
- [4] Zhitong Xing, Kaiming Liu, Aditya S. Rajasekaran, Halim Yanikomeroglu and Yuanan Liu, "A Hybrid Companding and Clipping Scheme for PAPR Reduction in OFDM Systems", IEEE Access 2021.
- [5] Farzana Kulsoom, Anna Vizziello, Hassan Nazeer Chaudhry and Pietro Savazzi, "Joint Sparse Channel Recovery With Quantized Feedback for Multi-User Massive MIMO Systems", IEEE Access 2020.
- [6] Ismayil S. C., Tamilselvan S. and Sneha V. V., "Frequency Domain Learning Scheme for Massive MIMO Using Deep Neural Network", International Conference on Intelligent Computing and Control Systems (ICICCS), IEEE 2020.
- [7] Giordani M., Polese M., Mezzavilla M., Rangan S., Zorzi M., "Toward 6G Networks: Use Cases and Technologies", IEEE Communication Magic, 58:55–61, 2020.
- [8] Siyad C. I. and Tamilselvan S., "Deep Learning Enabled Physical Layer Security to Combat Eavesdropping in Massive MIMO Networks", Lecture Notes on Data Engineering and Communications Technologies IEEE pp. 643-650, 2020.
- [9] Malik P.K., Wadhwa D. S. and Khinda J. S., "A Survey of Device to Device and Cooperative Communication for the Future Cellular Networks", International Journal Wireless Information Networks, IEEE 2020.
- [10] H. Chen, J. Hua, J. Wen, K. Zhou, J. Li, D. Wang, and X. You, "Uplink interference analysis of F-OFDM systems under non-ideal synchronization," IEEE Trans. Veh. Technol., vol. 69, no. 12, pp. 15500–15517, Dec. 2020.
- [11] Ganesan Thiagarajan and Sanjeev Gurugopinath, "A Novel Hybrid Beamformer Design for Massive MIMO Systems in 5G", 3rd 5G World Forum (5GWF), IEEE PP. NO. 436-441, 2020.
- [12] Fanbo Wei, Ting Zhou, Tianheng Xu and Honglin Hu, "BER Analysis for Uplink NOMA in Asymmetric Channels", Communications Letters, IEEE 2020.
- [13] N. Ye X. Li H. Yu L. Zhao W. Liu and X. Hou "DeepNOMA: A unified framework for NOMA using deep



- multi-task learning" IEEE Trans. Wireless Commun. vol. 19 no. 4 pp. 2208-2225 Apr. 2020.
- [14] J. Ding D. Qu and J. Choi "Analysis of non-orthogonal sequences for grant-free RA with massive MIMO" IEEE Trans. Commun. vol. 68 no. 1 pp. 150-160 Jan. 2020.
- [15] X. Shao X. Chen and R. Jia "A dimension reduction-based joint activity detection and channel estimation algorithm for massive access" IEEE Trans. Signal Process. vol. 68 pp. 420-435 2020.





**INNO SPACE**  
SJIF Scientific Journal Impact Factor  
**Impact Factor: 8.423**



**ISSN** INTERNATIONAL  
STANDARD  
SERIAL  
NUMBER  
INDIA



# INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

**9940 572 462** **6381 907 438** **ijirset@gmail.com**



[www.ijirset.com](http://www.ijirset.com)

Scan to save the contact details