

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

DIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 2, February 2024

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

 \bigcirc





e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302029 |

Analysis And Design Of Commercial Building by using Etab

BASAVARAJ HIREMATH PG Student, Dept. of Civil Engineering, Bheema Institute of Technology & Science (BITS), ADONI, Karnool Dist.(A.P). INDIA

Dr.P.LAKSHMAIAHCHOWDARY, Professor, Dept. of Civil Engineering, Bheema Institute of Technology & Science (BITS), ADONI, Karnool Dist.(A.P). INDIA

ABSTRACT: This Project deals an overview of the key aspect in the design of Commercial Building structures by using ETAB. the main aim of this review is to introducing the different types of structural elements in commercial building structure that are design and supports, of column, Beams, Footing, Slabs. they may also be used to support different types of RCC elements are used in commercial building structures that have similarities to structural steel building.

The design requirements of RCC structures the Analysis, codes and industry practice, design criteria, design loads and other designed conditions.

KEYWORDS: Design Modeling: Rcc structure; Analysis; Axial Force: Shear Force : Beam Reaction

I. INTRODUCTION

The goal of structural design is to create a building that is safe, functional, and long-lasting while also being aesthetically pleasing and economically sound. Structural engineering is a science that encompasses not only creative thinking and conceptualization (the art of design), but also practical considerations (such as familiarity with applicable design codes and bylaws), as well as a wealth of experience, institutional knowledge, and professional judgment. The first step in design is designing the structure, with the main goal of making sure it can fulfill the building's functional needs. It is common practice for architects to focus on aesthetics and practical needs, while structural designers ensure the building is safe, serviceable, durable, and economical for its intended use throughout its lifetime. In some cases, a structural engineer will need to play dual roles in these roles.

1.2 Stages in Structural Designs: Process of structural design involves following stages.

I. Structural Planning , II. Estimation of Loads , III. Analysis of Structure, IV.Member Design

V. Drawing, detailing and preparation of Schedule

1.3 Structural Planning: etermining structure's shape, material, structural system, component arrangement, analytical technique, and design philosophy are all part of this process.A R.C.C. building frame primarily consists of the following components: Slabs to cover large area

I. Beams to support slabs and walls , II. Column to support beams , III.Footing to distribute concentrated column loads over a large area Of the supporting soil

Obtaining a building's architectural design is first step in structural planning frame. Determining following is involved in this. (a) Column position (b) beam location (c) panning of slabs (d) Layout and planning of stairs (e)Type of footing **a)Positioning of columns:** A few of principles that aid in determining the locations of the columns are as follows. As its primary purpose is to support beams often installed under walls, columns are best positioned at or near building corners & wall intersections. However, if the columns are located in walls that adjoin property line, an exemption may apply. To accommodate column footing inside property, it might be necessary to move column inside along transverse wall, since footing demands specific space beyond column.

Orientation of Column: Standard for constructing columns is a rectangular shape, with a width that is equal to or greater than the supported beam's width, to provide efficient weight transmission. Additionally, in order to prevent deviations, the breadth of the column should not surpass the wall's thickness.

In order to achieve the required load bearing capacity within the width restrictions, the other sides of the columns must

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

be bigger.

b) Positioning of Beams: When deciding where to put beams, keep in mind the following guidelines:

It is common practice to place beams behind walls or under a concentrated heavy load to divert weight away from slabs. Quickest approach to foundation must carry most weight when planning arrangement of component parts.
 Maximum span of slabs will determine spacing of beams, since their primary purpose is to support slabs. When compared to other components, slab's volume-to-load ratio is very high, meaning that it takes the maximum amount of concrete to support a given load. For that reason, you should not make the slab any thicker than necessary. A minimum of 100 mm and a maximum of 200 mm is considered practical for use in residential, commercial, and public structures. Loading and limiting thickness dictate maximum and minimum slab spans, which in turn determine spacing of beams, as shown above.

C) Spanning of Slabs: The placement of the walls and beams that support the structure determine this. If supports are perpendicular to slab or run in only one direction, we say that the slab is one-way supported. A two-way supported slab is one that has two sets of supports that are perpendicular to one other. A number of factors, including slab's support method, aspect ratio & boundary circumstances, determine two actions of slab. As a result, the designer has complete discretion over boundary conditions. So, it's up to the designer to determine whether the slab should be one-way or two-way. The following considerations could go into making this call:.

- Slabs with an aspect ratio of Ly/Lx > 2 are intended as one-way slabs, whilst slabs with an aspect ratio of Ly/Lx less than 2 function as two-way slabs.
- Since main steel in a two-way slab runs length of both spans, transferring weight to all four supports, it is often more cost-effective than a one-way slab, which only uses main steel along the short span and transmits the load to the two opposing supports. No load-transferring capabilities exist in the long span's steel; it only serves as distribution steel.
- Slab can be made to function as a one-way slab across the short span if it has supports on all sides but a Ly/Lx value less than 2. This is achieved by adding main steel along short span and distribution steel along long span. Increasing the amount of steel in one direction makes the slab stiffer in that direction.

d) Layout of Stairs

Readily accessible staircase room's dimensions & placement of beams and columns around staircase's perimeter are primary determinants of the steps' kind and arrangement. In order to help you decide on a staircase arrangement, we have included some helpful recommendations.

In general, stair slabs are heavier than floor slabs for two reasons: (i) the dead load is higher on stairs than on floors because of inclined length of slab acting over the horizontal span, & (ii) added weight of the steps makes slab even heavier. Hence, flights should not have a lengthier duration if at all feasible. Beams or walls should ideally support stair flights. Avoid voiding landing slab supports as much as feasible. Particularly when the landing slabs' span is more than double the stair's width, since this places extra strain on the landing slabs' supporting structure where they meet.

e) **Choice of Footing Type:**

Column's weight & soil's bearing capability determine kind of footing. Unless the soil has very poor bearing capacity, isolated column footings are usually the way to go for the framed structure under consideration. For deeper pile foundations, this kind of soil or black cotton soil may be suitable. A raft foundation is another option to consider in cases when the spacing of the columns is very near and the soil's carrying capability is poor.

Marking of Frame Components: Marking or designating R.C. frame components is usually important before beginning structural design in order to enable identification, listing, and scheduling. The many forms that the SP-34 Code of practice suggests for identifying, listing, and scheduling substances.

1.5 Common Building Components are: (1) Super Structure: (2) Sub structure

Everything above ground that contributes to building's functionality is known as superstructure. It comprises Plinth

2.Wall and columns 3.Beams 4.Arches 5.Roofs and slabs 6.Lintel and rches 7. Chejjas 8.Parapet 9.Steps and

stair.Loads on superstructure: Here are some of loads that are being studied for structure:

a)Dead load & super imposed dead load (IS875 part-I

b)Live load (IS875 Part-II, Since wind load is not taken into account for buildings up to G+3 storeys, it is necessary to include it with dead load and live load when designing a structure.

1. Substructure: Substructure transports weight of superstructure to subsoil; it is placed below ground level and

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302029 |

comprises, **Foundation:** This is what the foundation needs: The foundation has to be sturdy enough to avoid uneven and excessive settling.

- 2. Properly, the code has cautioned against building on such loose soils that may subside after an earthquake, leading to significant differential settlement.
- 3. Foundation's design must take the carrying capability of the soil into account.
- 4. Utilize raft or pile foundation if the soil contains black cotton, loose fine sand, or costly clay.

II. LITERATURE REVIEW

VARALAKSHMI V ET.AL [2014]^[1]EXAMINED A G+5 RESIDENTIAL BUILDING AND PLANNED ITS FOUNDATION, SLAB, BEAM, AND COLUMNS. FOR THIS PROJECT, WE USED THE GUIDELINES LAID FORTH BY IS 875(PART I & II)-1987 TO DETERMINE THE LIVE AND DEAD LOADS, AND WE EMPLOYED HYSD BARS, NAMELY FE 415, IN ACCORDANCE WITH IS 1986-1985. ACCORDING TO THEIR FINDINGS, THE STRUCTURAL ANALYSIS, DESIGN, AND REINFORCEMENT DETAILING OF THE BUILDING FRAME ARE CRUCIAL FACTORS IN DETERMINING THE SAFETY OF REINFORCED CONCRETE BUILDINGS. THESE FACTORS CONTRIBUTE TO THE STABLITY AND DUCTILE PERFORMANCE OF THE BUILDING'S ELEMENTS.

CHANDRASEKHAR ET.AL [2015]^[2]PERFORMED ETABS ANALYSIS AND DESIGN FOR THE MULTI-STORY STRUCTURE. THE RESEARCH USED ETABS TO ANALYZE THE LATERAL LOADING EFFECTS OF WIND AND EARTHQUAKE ON A G+5 STORY STRUCTURE. THEY HAVE ALSO TAKEN INTO ACCOUNT THE POTENTIAL FOR FIRE SPREAD AND THE SIGNIFICANCE OF USING FIREPROOF MATERIALS THAT MEET OR EXCEED ALL PERFORMANCE AND RELIABILITY REQUIREMENTS. IN ORDER TO CUT DOWN ON DESIGN TIME, THEY RECOMMENDED ETABS, A PROGRAM THAT IS BOTH CREATIVE AND EASY TO USE FOR HIGH-RISE PROJECTS.

BALAJI.U AND SELVARASAN M.E ET.AL [2016]^[3] designed and analyzed multi-story buildings using ETABS for both static and dynamic loading scenarios. This study used ETABS to analyze the seismic stresses on a G+13 story residential structure. Performing static and dynamic studies, they presupposed that the material properties would be linear. We conducted the non-linear analysis taking severe seismic zones into account, and we evaluated the behavior taking type II soil conditions into account. We plotted and evaluated several outcomes, including displacements and base shear.

GEETHU ET.AL [2016]^[4]COMPARED THE CAPABILITIES OF STAAD.PRO AND ETABS IN THE CONTEXT OF MULTI-STORY BUILDING ANALYSIS AND DESIGN. THEY SUPPLIED PLANS FOR BOTH COMMERCIAL AND RESIDENTIAL STRUCTURES. WE USED AUTO CAD TO DEVELOP THE PLANS, AND THEY WERE ALL IN LINE WITH THE NATIONAL BUILDING CODE. AFTER LOOKING AT THE FINDINGS FROM BOTH PROGRAMS, THEY CAME TO THE CONCLUSION THAT THE BENDING MOMENT AND AXIAL FORCE VALUES SHOWN BY ETABS ARE GREATER.

AMAN,ET.AL[2016]^[5]KALABURAGI, KARNATAKA, INDIA: STAAD PROAIET ANALYSIS AND DESIGN OF A MULTI-STOREY BUILDING STRUCTURAL ENGINEERS ARE FEARLESS WHEN IT COMES TO DESIGNING STRUCTURES THAT CAN WITHSTAND A WIDE RANGE OF LOADING CONDITIONS, AND THEIR PRIMARY GOAL IS TO ENSURE THE SAFETY OF COMPUTER TECHNOLOGY. IT WAS FORMERLY BELIEVED THAT ALL LOADS ACTING ON A STRUCTURE WERE STATIC, BUT IN REALITY, ALL LOADS ON A STRUCTURE ARE DYNAMIC, WITH THE EXCEPTION OF THE SELF-WEIGHT, ALSO KNOWN AS A DEAD LOAD. THE DISCIPLINE OF CIVIL ENGINEERING NOW HAS ACCESS TO A PLETHORA OF APPLICATION SOFTWARE. ALL OF THESE PROGRAMS SERVE AS THE FOUNDATION FOR MORE COMPLEX ONES. IN THIS RESEARCH, WE LOOK AT THE EFFICACY OF CERTAIN CIVIL ENGINEERING APPLICATION SOFTWARE USING FINITE ELEMENT ANALYSIS, WHICH TAKES INTO ACCOUNT THE IMPACT OF DYNAMIC LOADS LIKE WIND AND EARTHQUAKE EFFECTS. WE HAVE CHOSEN AN ONGOING PROJECT FOR THIS REASON. THE UNITY BUILDERS IN GULBARGA CITY ARE RESPONSIBLE FOR THIS INITIATIVE. "BHARAT PRIDE" IS THE PROJECT'S NAME.

C.V.S.LAVANYA ET.AL[2017]^[6] ISN THIS MODERN ERA, A GREAT DEAL OF COMPLEX AND IRREGULAR STRUCTURES HAVE BEEN DESIGNED TO WITHSTAND THE EARTH'S QUICK AND WIND. TO DESIGN THESE STRUCTURES, ENGINEERS HAVE TURNED TO SOFTWARE LIKE ETABS, STAAD PRO, AND TEKLA. ON THIS PARTICULAR PROJECT, WE FOLLOWED THE COMPANY'S RECOMMENDATION AND UTILIZED ETABS TO DETERMINE THE BEAM'S SHEAR FORCE, THE COLUMN'S AREA REINFORCEMENT, THE FOUNDATION'S REACTION, THE SITE'S SAFE BEARING CAPACITY OF SOIL, AND THE HEIGHT OF THE FOUNDATION. ADDITIONALLY, WE DESIGNED THE RETAINING WALL USING THIS SOFTWARE.

III. OBJECTIVIES

CONSTRUCT MULTI-STORY COMMERCIAL BUILDING UTILIZING ETABS FOR ANALYSIS AND DESIGN.

*Creating structural plan *Modeling *Loading *Analysis *To design structural components like beam, slab, column

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302029

and footing.

To draw and give reinforcement details of structural components by using Auto Cad, Design by using IS456-2000

IV. DESIGN PROCEDURES

1.1 **STRUCTURAL PLANNING :** Using execution plan in figure 4.1 as a guide, a structural frame plan is created, outlining placements of columns and beams in a way that distributes building's weight equally. All of the columns are bound together in both the X and Y axes by the beams' placement. Figure 4.2 illustrates the structural plan, which also displays the c/c spacing between the columns. This is useful for building ETABS structural models.

4.2 BUILDING DETAILS : Floor to floor height 3 mts, Number of floor = G+3, Base to ground floor height = 1.5 mts Size of building = $(76'9''x89')=445m^2$, Over all height of





of soil considered = 180 Kn/sq mts , Type of building = 180 kn/sq mts ,

Type of building = COMMERCIAL BUILDING, Minimum clear width of stair =1.3mts

4.3 MODELLING

Modeling using ETABS

| | | 0 |
|-------------|--|---|
| | | 0 |
| | | |
| Netric Si | | 0 |
| inden | 14 | |
| 15 800 2007 | | 0 |
| 15 456 2000 | | 0 |
| | Wenc 51 Indan 15 800 2007 15 455 2000 | Namic 51 v Indan v 15 800 2007 v 15 456 2008 v |





Open the ETABS Program
 Click the File menu > New model command



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| <u>www.ijirset.com</u> | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal | || Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

3) Picking NO will bring up the following form of the Building Plan Grid System and Story Data Definition. Determine the distance between the grid lines and the line itself. Use the Edit narrative Data command to set the narrative height data.



- 4) Click on grid only. A new window of ETABS will be displayed.
- 5) Edit grid data and storey data as per the structural framing plan.
- 6) Click the Define menu > Material Properties



Add New Material or Modify/Show Material used to define material properties





7) ETABS Segment beams and columns are defined by using Set the attribute of the section and then frame it. Sizes of beams and click Providing concrete cover as per reinforcement instruction

Size the columns and then click The directive to provide concrete cover and employ two choices for reinforcement Verification or design of reinforcement

| Aman Amar Amar Amar Amar Amar Amar Amar Amar | Popor Motion Region Motion Region Motion Region Motion Region R | Daing Tear O FROM Darge Column © FROM Darge Column © FROM Darge Column © FROM Darge Column © FROM Darge Column Tear to unput the Residence Tear to unput t | New York Constraints of the cons | Barry Star Data Star Image: Star Star Star Star Star Star Star Star |
|--|--|--|--|--|
| 1040 | Modfy Show Rebar . | OK Canod | × | Continuent Rai San an Alina 10 v at 10 |
| | | | Shoe Sacket Popelas. Canod | and Assessed and Assessed |

8) Define wall/slab/deck

To define a slab as membrane element using Define > slab section.

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302029



9) Generate the model Draw beam using Create Line Command and draw column using Create Column command



| * | Select Object Reshape Object | 18 3 | □•●•⊡ ₩ ₩ ₩ •••□ |
|-------|--|------|---|
| | Draw Joint Objects Draw Beam/Column/Brace Objects | | |
| | Draw Floor/Wall Objects | | Draw Floor/Wall (Plan, Elev, 3D) |
| × | Draw Links | | Draw Rectangular Floor/Wall (Plan, Elev) |
| NYY R | Draw Grids Draw Dimension Lines Draw Reference Points Draw Reference Planes Draw Section Cut | | Quick Draw Floor/Wall (Plan, Elev) Draw Walls (Plan) Quick Draw Walls (Plan) Draw Wall Openings (Plan, Elev, 3D) |
| 2 | Draw Developed Elevation Definition | | |
| 田職 | Draw Wall Stacks (Plan, Elev, 3D) Auto Draw Cladding | | 8 |
| °0 | Snap Options | | Ŕ |

Above creating option used to generate the model as shown in below figure.

10) Assign support condition

×

Ť٢.

7

\$1

<u>m l</u>

للنس

×Ţ

D.

Drop-down box in the lower right-hand corner of the ETABS window, Select only bottom single storey level to assign fixed support using assign > Joint/Point>Restrain (Support)







- (a) Grade of steel = Fe 415, Grade of concrete = M25, Density of concrete = 2500 kg/m3, Assumed sections = B 230x550, Column = C1 - 230x450 Rectangular, C2 - 230x500 mm Rectangular Beam = B230x500Slab = TW150 -150 mm thick (two way) =OW150 -150 mm thick (one-way)
- (b) Supports : Fixed supports are provided at all the column bases.

L SET

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

4.4.1 LOADING : Define various loads (Dead load, Live load, SDL)

| oads | Tune | Self Weight | Auto | Click To: Add New Load | | |
|---------------------|----------------------------|-------------|------|---------------------------|---------------------------------|------|
| SDL | SUPER DEAD | | | Modify Load | | |
| DEAD LIVE SDL | DEAD LIVE SUPER DEAD | 1 0 0 | | Modify Lateral Load | Shell Load Assignment - Uniform | |
| | | | | Delete Load | Load Pattern Name | Live |
| | | | | | Load 5 Direction Gravity | |

Dead Load: The default value for the self-weight multiplier for calculating dead load is 1. There will be a live load case by default. Super dead load, please.

First, click the assign button once you've chosen the person to whom you want to allocate the load.



4.4.2) Define Load combination, Define>load combinations>add new/ modify combo/add auto load combination



Only static verticalloads are considered , **Types of loads :** Dead l;oads (DL) as per IS 875 part-I, Live Load (LL) = 2kn/m^2 as per IS 875 part – II ,For staircase = 3kn/m^2 , For balcony & passage = 3kn/m^2 , Super dead Load (SDL) Floor Finish = 1.5kn/m^2 (Assumed) , 230 thick wall load = (3.2-0.45)x20x0.23,=12.65kn/m 150 thick wall Load = 1.2x20x0.15=3.6kn/m, Density of masonry wall considere as 20kn/m^3

Load Combination:-

| Load Combinations | Remarks |
|-------------------|--|
| 1.5(DL+SDL) | DL = Dead Load of The Structure LL = Live Load on the structure SDL= Super Dead Load |
| 1.5 (DL+SDL+LL) | |

4.5 Analysis: (a) Check model for errors in line

よう IJIRSET

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302029 |

elements, points, area elements with tolerance factor 0.001mAnalyze>check model command., Static analysis of structureAnalyze>Run analysis command

| G | Check Model | E Longe Tolerance for Checks | Ana | lyze Display Design Detailing Options Too | la I | Owine Databas Outras Tests M | |
|---|---|--|-----|---|------|--|--|
| 1 形 111 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | Set Active Degrees of Freedom | Lange, Haurgere to Chanka I per de la construction de la construcción | | Check Mandel. Cettani Cettania Cettania Cettania Cettania Set Active Degrees of Freedom Set koad Geas To Rom Advanced Suffrance Automotic Rectangular Methis Settings for Floors Automatic Rectangular Methis Settings for Walls Analysis Media for Nanina Settings | | Drage Detailing Options Teston 14 Testo Darage Consolid Frame Design Consolid Frame Design Compacts Extern Design Compacts Extern Design Decomplete Frame Design Decompacts Parent Design Decompacts Start Vold Design Istart Connections Design Direct Design Istart Connections Design Direct Design | Ver (1) (1) (1) (1) (1) (1) (1) (1) (1) (1) |
| • | Analysis Model for Nonlinear Hinges Run Analysis F5 | Other Decks Deck Masteria for All Norms Deck Londing for All Some Deck Londing for All Some | • | Run Analysis PS Model Alive Modify Undeformed Geometry | | Set Lateral Explorement Targets. Set Targe Period Targets. | Facet Design Section to Last Analysis Verify Analysis in Design Section . Verify All Mandaen Passad. |
| ۲ | Model Alive | Fee EST Tore on External Frances and Haven Justice to Fee Problems | 1 | Last Analysis Run Log | | | Exect All Overweter Delete Decign Results |
| 2. | Modify Undeformed Geometry | E2 Joint Story Assignment | - | Lock Model | | | |
| | Last Analysis Run Log | Salasi (Devalor A | | | | | |











COLUMN NUMBERING

BEAM NUMBERING

SLAB NUMBERING

AXIAL FORCE DIAGRAM BENDING MOMENT DIAGRAM

4.5 OUTPUT FILES: 4.6.1 LOAD COMBINATIONS

| | LOAD | COMBINATI | IONS | - |
|-------|---------------|-----------|--------------|-----------------|
| COMBO | COMBO TYPE | CASE | CASE TYPE | SCALE FACTOR |
| DCON1 | ADD | DEAD | Static | 1.5 |
| | | SDL | Static | 1.5 |
| DCON2 | ADD | DEAD | Static | 1.5 |
| | | SDL | Static | 1.5 |
| | | LIVE | Static | 1.5 |

4.6.2 SUPPORT REACTIONS

| | TABLE: Design Reactions | | | | | |
|------|-------------------------|---------|----------|---------|---------|--------|
| tory | FX | FY | FZ | МХ | МҮ | MZ |
| Base | 28.8924 | 17.6921 | 576.0964 | -8.3047 | 14.5157 | 0.0248 |
| Base | 42.8883 | 15.4359 | 1262.556 | -7.9723 | 20.9315 | 0.0977 |
| Base | 39.0223 | 7.5789 | 918.8117 | -4.3269 | 19.2315 | 0.0741 |
| Base | 74.8778 | 3.7859 | 2020.861 | -2.3416 | 32.6461 | 0.0264 |



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

| Base | 40.5278 | 39.5118 | 1227.413 | -17.3292 | 19.762 | 0.0338 |
|------|----------|----------|----------|----------|----------|--------|
| Base | 54.2371 | 13.8804 | 2133.996 | -7.2336 | 23.0885 | 0.0647 |
| Base | 59.1041 | -12.4232 | 1371.736 | 5.6654 | 23.4065 | 0.0497 |
| Base | -39.5153 | -18.0574 | 1482.15 | 8.1368 | -16.09 | 0.0433 |
| Base | 57.098 | -6.068 | 1096.012 | 2.5778 | 21.2833 | 0.0414 |
| Base | -47.1812 | 35.4897 | 1554.227 | -17.7477 | -20.3986 | 0.0588 |
| Base | 108.8482 | 0.6469 | 1140.765 | -0.6554 | 40.7284 | 0.0844 |
| Base | 21.0547 | -9.1711 | 446.9689 | 4.0939 | 4.571 | 0.0689 |
| Base | 40.662 | -66.6995 | 1526.159 | 31.5131 | 12.6387 | 0.0498 |
| Base | -79.2969 | -23.8677 | 799.9187 | 10.4845 | -34.4804 | 0.0679 |
| Base | -52.8963 | 19.0371 | 1623.918 | -9.9744 | -23.3803 | 0.082 |
| Base | -46.2754 | -24.6011 | 807.9243 | 10.8333 | -20.5113 | 0.0316 |
| Base | 61.3548 | -29.5187 | 1707.81 | 13.4909 | 23.4227 | 0.0436 |

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 A Monthly Peer Reviewed & Referred Journal |



|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

| | TABLE: Beam Forces | | | | | | | |
|--------|--------------------|----------|----------|---------|---------|---------|----------|--|
| Story | Beam | Р | V2 | V3 | Т | M2 | M3 | |
| Story4 | B1 | -7.287 | -32.0947 | 0.0034 | 1.9432 | -0.0411 | -25.8877 | |
| Story4 | B2 | -2.9995 | -61.8831 | -0.0063 | -2.963 | 0.0381 | -64.6215 | |
| Story4 | B5 | -3.7325 | 44.9421 | 0.002 | -0.3694 | -0.0058 | -41.6339 | |
| Story4 | B6 | -0.087 | 5.0559 | -0.0154 | 0.2508 | -0.0072 | 13.9491 | |
| Story4 | B7 | -4.0447 | -43.9546 | 0.0013 | -0.8117 | 0.0096 | -19.985 | |
| Story4 | B8 | -1.8761 | -0.9026 | -0.0041 | 0.7658 | -0.0017 | 10.8444 | |
| Story4 | B9 | 0.8329 | 37.3787 | -0.0219 | 0.0543 | 0.0515 | -24.7827 | |
| Story4 | B10 | -2.8526 | 65.272 | 0.0031 | -1.6017 | -0.0217 | -57.4988 | |
| Story4 | B11 | 0.639 | -51.998 | -0.0023 | 0.1653 | 0.0296 | -48.2955 | |
| Story4 | B12 | 0.3964 | -36.5034 | 0.0356 | 0.9091 | 0.0114 | -26.4903 | |
| Story4 | B13 | -0.2413 | 2.331 | -0.0317 | -1.091 | 0.0401 | 11.6317 | |
| Story4 | B14 | -11.0152 | -62.6414 | 0.0038 | -0.3718 | -0.0213 | -63.4728 | |
| Story4 | B15 | 0.2656 | -4.2456 | -0.0037 | -0.1248 | 0.0719 | 13.0301 | |
| Story4 | B16 | -2.0118 | -2.443 | 0.0125 | 0.6276 | -0.093 | 24.3416 | |
| Story4 | B17 | -9.3819 | -44.5056 | 0.0194 | -0.3117 | -0.0102 | -43.4519 | |
| Story4 | B18 | -1.6299 | -5.9503 | -0.0089 | 0.1463 | 0.0605 | 27.9616 | |
| Story4 | B19 | -1.2337 | -35.9775 | 0.0085 | -0.21 | -0.0508 | -22.391 | |
| Story4 | B20 | -4.8452 | -1.5664 | 0.0031 | -0.3459 | -0.0118 | 66.9251 | |
| Story4 | B21 | -9.5017 | 74.7339 | 0.0029 | 1.9929 | -0.0238 | -58.906 | |
| Story4 | B22 | -4.4831 | 67.7393 | -0.0078 | 0.6289 | 0.0272 | -58.1816 | |
| Story4 | B23 | -9.1436 | 44.063 | -0.003 | -1.3716 | 0.0116 | -35.9058 | |
| Story4 | B24 | -12.0667 | 20.043 | -0.013 | 9.4203 | -0.0203 | -13.7871 | |
| Story4 | B25 | -5.5312 | 60.4286 | 0.0068 | 3.0324 | -0.0022 | -29.343 | |
| Story4 | B26 | -2.8253 | -36.0688 | -0.0128 | -2.4692 | -0.047 | -42.1495 | |
| Story4 | B27 | -6.375 | -56.2106 | -0.0048 | -1.3712 | -0.0412 | -37.959 | |
| Story4 | B28 | -4.9715 | 9.7693 | -0.0012 | 0.2931 | 0.0257 | 38.5549 | |
| Story4 | B29 | -2.8321 | 1.948 | 0.0041 | -0.0548 | -0.0125 | 43.5091 | |



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

| Story4 | B30 | -2.8997 | 2.0343 | 0.0086 | -0.3228 | 0.0014 | 39.5359 |
|--------|-----|----------|----------|---------|---------|---------|----------|
| Story4 | B30 | -2.8997 | 57.5196 | 0.0086 | -0.3228 | -0.0181 | -39.3326 |
| Story4 | B31 | 0.1352 | -33.2695 | -0.0008 | 0.9831 | 0.0279 | -24.8646 |
| Story4 | B33 | -0.5854 | -0.808 | -0.0137 | 0.1984 | -0.0317 | 16.8829 |
| Story4 | B34 | -1.0575 | 32.942 | -0.0055 | 1.8198 | 0.0187 | -19.2831 |
| Story4 | B35 | -13.7599 | 28.6946 | 0.0307 | 0.7052 | -0.0589 | -23.725 |
| Story4 | B36 | -7.1142 | 26.7617 | 0.0057 | -0.1123 | 0.0002 | -30.1991 |
| Story4 | B37 | -17.7725 | 65.6828 | 0.0136 | -1.008 | -0.0772 | -58.7833 |
| Story4 | B38 | -0.0522 | 36.8839 | 0.0012 | -0.6081 | -0.0194 | -26.4029 |
| Story4 | B39 | 0.3379 | 5.7957 | 0 | -0.0642 | 0 | 25.16 |
| Story4 | B42 | -12.502 | -73.5639 | -0.0037 | -0.8789 | 0.0214 | -71.3121 |
| Story4 | B43 | -8.6027 | -78.5781 | 0.0384 | 6.9933 | 0.0223 | -71.1026 |
| Story4 | B44 | -9.7246 | -70.926 | 0.064 | 0.5815 | 0.0253 | -69.0467 |
| Story4 | B45 | -1.3154 | 14.6701 | 0.0217 | 2.3546 | 0.0004 | -6.1993 |
| Story4 | B47 | -7.3624 | -65.8067 | -0.0037 | -0.0306 | 0.037 | -41.9399 |
| Story4 | B48 | -12.6731 | -86.6298 | -0.029 | -6.7622 | -0.0035 | -87.1408 |
| Story4 | B49 | -1.7217 | -21.3779 | -0.0192 | -3.9698 | -0.0335 | -15.6968 |
| Story4 | B50 | -0.0344 | 19.2165 | -0.0019 | -4.7274 | 0.0019 | -10.6913 |
| Story4 | B56 | -4.5154 | 71.5806 | -0.0057 | -0.6359 | 0.0457 | -68.6378 |
| Story4 | B57 | -3.7858 | -50.4662 | 0.0012 | 0.0373 | -0.021 | -53.0071 |
| Story3 | B1 | 0.3335 | -66.3713 | 0.0006 | 5.4928 | -0.0008 | -48.203 |
| Story3 | B2 | -0.6808 | -164.771 | 0.0035 | -9.0082 | 0.0014 | -159.029 |
| Story3 | B3 | -0.1522 | 124.8163 | -4E-05 | -1.7329 | 0.0044 | -122.749 |
| Story3 | B4 | -0.1237 | 124.5955 | -0.0017 | -1.7329 | 0.0038 | -116.439 |
| Story3 | B5 | 0.2317 | 104.9906 | 0.0021 | -0.581 | 0.0016 | -79.6971 |
| Story3 | B6 | 0.2317 | 78.4845 | -0.0006 | 1.3605 | -0.0106 | -35.8269 |
| Story3 | B7 | -0.5784 | 104.0993 | -0.0011 | -1.3377 | 0.0098 | -77.3345 |
| Story3 | B8 | -0.3991 | -55.1822 | 0.0018 | 1.8234 | 0.0106 | -20.9201 |
| Story3 | B9 | -0.6729 | 72.6676 | -0.0022 | 0.2273 | -0.0031 | -43.1445 |

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302029



5. <u>DESIGN OF SLAB</u>

6. DESIGN OF BEAMS

Consider B6 at First floor plan beam for design since it is subjected to maximum Bending Moment and Shear Force. b = 230mm ,D= 550mm, $f_{ck} = 25 \text{ N/mm}^2$ ' $f_y = 415 \text{ N/mm}^2$ ' $M_u = 255.0868 \text{ KN m}$, Check for depth:Since $M_u > M_{ulim}$ (Doubly Reinforced beam) For $f_y = 415 \text{ N/mm}^2$ From IS456-2000 $M_{ulim} = 0.148 f_{ck} bd^2 M_{ulim} = 212.75 \text{ kNm}$ Fsc= ϵ sc * Es = {(0.0035((0.48x500)-50)/(0.48x500)}x(2x10^5)



Fig 6.1 BEAM REINFORCEMENT DETAILS

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302029 |

 $= 554.16 \text{ N/mm}^{2} > 0.87 \text{ fy}=361\text{N/mm}^{2} \quad \text{Asc}= \{(Mu-Mulim)/(fsc(d-d'))\} \qquad \qquad \text{Asc}=169.77\text{mm}^{2}, \\ \text{Ast}=Asc=169.77\text{mm}^{2} \qquad \text{Provide } \#2-20\text{mm dia }, \\ \text{Ast}=\{0.36 \text{ x fck x b x Xulim}/(0.87 \text{ x fy})\}, \quad \text{Ast}=1375.98\text{mm}2 \qquad \text{Provide } \#6-20\text{mm dia } \\ \text{Shear reinforcement :} V_{u}=254.62\text{KN}$

$$\begin{split} \tau_v &= \frac{Vu}{bd} = \frac{254.62 \times 10^3}{230 \times 500} = 2.21 \text{N/mm}^2 \text{, Pt provided} = \frac{100 \text{Ast}}{bd} = \\ \frac{100 \times 1545.75}{230 \times 500} = 1.3\% \text{, From IS 456, Table No: 19 ,} \\ \tau_c &= 0.29 \\ \text{N/mm}^2 \text{,} \\ V_{us} &= V_u \text{-} \\ \tau_c \text{xbd} \text{,} = 211.97 \times 1000 \text{-} \\ 0.29 \times 230 \times 500, \\ = 221.27 \text{ KN } \text{, From IS 456, 40.4(a), S}_v = \frac{0.87 \text{ fy Asv d}}{Vus} \text{,} \\ = \frac{0.87 \times 415 \times 2 \times \pi / 4 \times 8 \times 8 \times 500}{221.27 \times 10^3} \text{, } \\ = 82 \text{mm c/c , Provide 2L-8mm dia} \\ \text{stirrups @ 80 \text{mmc/c }, \\ \end{array}$$

Design of mid-span section as T-Beam: Effective width of flange = bf = $l_0/6$ +bw+6Df , = $\frac{5880}{6}$ + 230 +6x200 =2396.67mm ,M_u = 255.0868 KN-m ,Assuming the neutral axis lies within the flange, M_u= 0.36f_{ck}xbfxX_u (d-0.42X_u) 255.0868x10⁶ = 0.36x25x2396.67xXu (500-0.42X_u), X_u=24.14mm, Hence assumption is correct, Area of steel = M_u= 0.87f_yA_{st}d (1- $\frac{Astxfy}{bfxdxfck}$) , 255.0868 x10⁶ = 0.87x415xA_{st}x500 (1- $\frac{Astx415}{2396.67x500x25}$), A_{st}= 1441.8mm²,

Provide 5 bars of 20mm diameter.

7. DESIGN OF COLUMN :

One definition of a column is an element whose primary function is to bear the axial compression loads applied by a beam. Axial force and a few seconds act on every column. The column is a uniaxial column in design. The SP 16 Code practice influenced the column's design.We may infer the column's resistance to the maximum axial load and moment axial from the Etabs output numbers.

| Member Number | Axial Load KN (Max) | Moment KNm |
|---------------|------------------------|------------|
| C6 | 2133.996 | 23.0885 |

Location Base Floor to Ground Floor:

 $P_u = 2133.996$ kN , $M_u = 23.0885$ kNm , $f_{ck} = 25$ N/mm²

 $f_y = 415$ N/mm², L = 1.5m, From IS 456-2000 Page No.94

 $L_{eff.}$ = 0.65 1 = 0.65x1.5 = 0.975m , Assuming 1% reinforcement, then cross sectional area of column A_g is calculated by using SP16 Page No.110 chart 25.

 A_g = 100000mm² , B = 230mm , D = 100000/230 = 434.78mm Say 450mm , Check for minimum eccentricity along depth.E_{min} = (le/500)+(D/30) , = 97.5/500+45/30

= 1.695 cm, E_{min}/D = 1.695/60 = 0.028<0.0365 Hence Safe



IJIRSET©2024









The ortical section for one way shear is taken at a distance equal to the effective depth from the column face.

Shear Force at critical section along X direction SFu X = 505.61 kN

Shear Force at critical section along Z direction SFu Z = 388.54 kN



|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

DESIGN OF DOG -LEGGED STAIR CASE

|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302029 |

INPUT DATA



Assuming $12mm \phi$ bars with clear cover of 50mm, d' = 50 $+\frac{12}{2} = 56$ mm , Ratio d'/D = 56/500 = 0.112, P_u/f_{ck}bD 2133.996x10^3 25x230x500 = 0.74, $M_u/f_{ck}bD^2 = \frac{23.088 \times 10^6}{25 \times 230 \times 500^2}$ = 0.016, Using above ratios $\frac{d'}{D} = \frac{56}{500} = 0.112$, From SP 16 Page No. 117 Chart 32 $P_t/f_{ck} = 0.10$, $P_t = 0.10x25 = 2.5\%$, Area of steel $A_{st} =$ $(2.5/100) \times 230 \times 450 = 2587.5 \text{mm}^2$, Provide 8 bars of 20mm **b** $A_{st} = 2587.5 \text{mm}^2$, **Design of lateral ties:**According to IS 456-2000 Page No.49, Diameter of lateral ties = 0.25x20 =5mm, adopt 8mm¢ Spacing of lateral ties: lesser of the following

1. Least lateral dimension = 230mm , 16 times diameter of bar =16x20=320mm ,230mm ,Let us provide 8mm ϕ lateral ties @ a pitch of 200mm c/c.

9. DESIGN OF STAIR CASE

The primary function of a staircase is to facilitate the movement of pedestrians inside a building. Depending on the specifics of each scenario, staircases may take on a wide variety of geometric shapes. In most cases, there are two primary considerations when designing a staircase: its form and its structural arrangement.

- 1. Kind of structure that surrounds the staircase, such as a brick structure or a reinforced concrete and brick structure.
- Availability of space.Planned structure has a bifurcated staircase with two stories. Both flights begin at different levels; the first ascends from the plinth to the lintel, while the second descends from the lintel to the ceiling.



| The Vertical distance between the floors | = | 1.6 m |
|---|-------------|-----------------------|
| live load | = | 3 kn/m2 |
| Rise | = | 150 mm |
| Iread | = | 300 mm |
| width of each flight | = | 1.07 m |
| No or Risers required | = | 11 |
| No of treads required | - | 10 |
| width of landing | = | 1.07 m |
| Grade of Concrete | = | 20 N/mm2 |
| Grade of Steel | = | 500 N/mm2 |
| The bearing of the landing slab in beam | = | 230 mm |
| Assume the depth of slab | = | 200 mm |
| Dia of bar | = | 12 mm |
| Calculation | = | |
| Space occupied by treads | = | 300 cm |
| Effective span | = | 4.2 m |
| effective depth | = | 179 mm |
| Weight of Slab | _ | 6.5 kp/m2 |
| Weight of Slab | - | 0.5 KH/HZ |
| Dead Weight of horizontal Area | = | 7.27 Kn/m |
| w1=W * Sqrt(R ² +T ²)/T | | |
| Dead weight of step | = | 1.88 kn/m2 |
| Total load | = | 13.64 kn/m |
| Factored load | = | 20.46 kn/m |
| Bending moment | = | 45.12 kn-m |
| Shear force | = | 42.97 kn |
| xumax/d Ru= 36*fck*xumax/d*(1-0.416*xumax/d) | = | 0.42 |
| Ru=.36*fck*xumax/d*(1-0.416*xumax/d) | = | 2.50 |
| d req= | = | 134.46 mm |
| | DEPTH IS OK | |
| Steel Reinforcement Ast | = | 637 mm ² |
| | | 444 |
| Area or 12mm bar | = | 114 mm |
| Spacing of bars | = | 179.0 mm |
| No. of 12mm bars | = | 6.0 |
| Distribution Reinforcement | = | 300.0 mm ² |
| Area of Distribution bar 8mm | = | 50.3 mm ² |
| Spacing of 8mm bars | = | 168.0 mm |

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302029 |

V. CONCLUSION

- 1. All horizontal members exhibit a short-term deflection of less than 20 mm.
- 2. BUILDING STRUCTURAL COMPONENTS ARE SHEAR AND FLEXURE SAFE.
- 3. Both the column and the beam must not exceed dimensions of $230 \text{ mm} \times 550 \text{ mm}$.
- 4. WE CAN ONLY PROVIDE SLABS WITH A MAXIMUM THICKNESS OF 150MM.
- 5. ANALYSES OF ETABS DO NOT SHOW A SIGNIFICANTLY DIFFERENT PATTERN.
- 6. IT IS POSSIBLE TO CREATE THIS STRUCTURE USING THE SPECIFIED DIMENSIONS OF THE COMPONENTS.
- 7. PROVIDED QUANTITY OF STEEL FOR THE BUILDING IS ECONOMICAL.
- $8. \ \ Cutting \ Down \ on \ Analysis \ and \ design \ time \ is \ possible \ with \ the \ help \ of \ ETABS \ software.$

VI. FUTURE SCOPE OF STUDY

- Designing members individually or in groups might make the design more inexpensive while preserving the same software analysis outcomes.
- > It is possible to achieve precise load distribution by meshing the slab element.

REFERENCES

[1] Varalakshmi V,G shivakumar and R S Sarma (2014) "Designed and d G+5 residential building by ETABS", International Conference on Advance in Engineering and Technology.

[2] Chandrashekar and Rajashekar (2015), "Analysis and Design of Multi Storied Building by Using ETABS Software", International journals of scientific and research vol.4: issue.7: ISSN no. 2277-8179.

[3] Balaji and Selvarasan (2016), "Design and Analysis of multi-storeyed building under static and dynamic loading conditions using ETABS", International Journal of Technical Research and Applications e-ISSN: 2320-8163, www.ijtra.com Volume 4, Issue 4, PP. 1-5

[4] Geethu S N, Depthi M, Abdul Nasir N A and Izzudeen K M(2016) "Comparative study on design and analysis of multi storied building by STAAD.Pro and ETABS softwares".

[5] Aman, Manjunath Nalwadgi, Vishal, Gajendra Analysis And Design Of Multi-Storey Building By Using STAAD Prointernational Research Journal of Engineering and Technology (IRJET) e-ISSN: 2395 -0056 Volume: 03 Issue: 06 | June-2016

[6].C.V.S. Lavanya, Emily.P.Pailey, Md. Mansha Sabreen and U.P.B.C. Sekhar, Analysis and Design of G+4 Residential Building Using ETABS. InternationalJournal of Civil Engineering and Technology, 8(4), 2017, pp. 1845-1850.

[7] P. Jayachandran and S. Rajasekaran, Structural Design of Multi-story Residential Building for in Salem, India, mini project report, PSG College of Technology, Coimbatore, Tamil Nadu, India-2006.

[8] IS: 1893-2002, Part 1, "Criteria for Earthquake Resistant Design of Structures -General

Provisions and Buildings", Bureau of Indian Standards, New Delhi, India.

[9] IS: 875 (Part 1), "Indian Standard Code of Practice for design loads for building and structures, Dead Loads" Bureau of Indian Standards, New Delhi.

[10] IS: 875 (Part 2), "Indian Standard Code of Practice for design loads for building and structures, Live Loads" Bureau of Indian Standards, New Delhi.

[11] IS: 875 (Part 3), "Indian Standard Code of Practice for design loads (Other than

earthquake) for building and structures, Wind Loads" Bureau of Indian Standards, NewDelhi.

[12] IS 456:2000, "Indian Standard plain and reinforced concrete-Code of Practice", Bureau of Indian Standards, New Delhi, 2000.

[13]Indian standards code of practice for design SP-16 and detailing SP-34.









INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com