

e-ISSN: 2319-8753 | p-ISSN: 2347-6710

DIA

International Journal of Innovative Research in SCIENCE | ENGINEERING | TECHNOLOGY

INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY

Volume 13, Issue 2, February 2024

INTERNATIONAL STANDARD SERIAL NUMBER INDIA

Impact Factor: 8.423

9940 572 462

6381 907 438

 \bigcirc







|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302077 |

Seismic and Wind Analysis of Diagrid Steel Structure on High Rise Building

Shaikh Suhaib ^{*1}, Shaikh A.N ^{*2}

M. Tech (Structure Engineering), Department of Civil Engineering, M.S Bidwe Engineering College, Latur, India^{*1}

Professor, Department of Civil Engineering, M.S Bidwe Engineering College, Latur, India*2

ABSTRACT: Diagrid steel structures, a revolutionary technology that has changed the face of modern architecture. Diagrid steel structure is a type of structural system that utilizes diagonal members to create a grid-like pattern. Unlike traditional steel structures, which typically use vertical and horizontal beams, diagrid structures distribute loads more efficiently and provide greater strength and stability. One of the key benefits of diagrid steel structures is their ability to resist lateral forces such as wind and earthquakes. The diagonals act like a truss system, providing additional strength and stiffness to the building. In addition, the use of diagonals allows for greater flexibility in building design, as the structure can be shaped to fit the desired form. Overall, diagrid steel structures offer a combination of strength, because of the way they are designed, diagrid steel structures can support much heavier loads than traditional steel structures. This makes them ideal for use in high-rise buildings and other large structures. Diagrid steel structures also have a unique aesthetic appeal. Because of their intricate design, they can create stunning visual effects that are not possible with traditional steel structures. The use of diagonal members also allows for more open and flexible floor plans, as well as improved aesthetics. Diagrid structures are often used in high-rise buildings, bridges, and stadiums, where their unique properties can be leveraged to great effect. Compared to traditional steel structures, diagrid structures require less material to achieve the same level of strength and stability, resulting in cost savings and a reduced environmental impact. In this study, the seismic performance of typical diagrid structures was investigated. The response spectrum, base shear, storey drift (wind and seismic analysis) of steel diagrid structure was analysed with the help of Staad Pro V8i. Staad Pro V8i stands for structural analysis and design, and the software is widely used to develop & analyze various structure designs like steel structures, skyscrapers, tunnels, bridges, dams, culverts, or petrochemical plants. Indian standard codes is used for the calculations i.e. is: 800, is 1893, and is 875.

KEYWORDS: Diagrid Steel Structures, Modern Architecture, High-Rise Buildings.

I. INTRODUCTION

In recent decades, the evolution of architectural and engineering innovations has propelled the construction industry toward novel and visually striking solutions to meet the demands of urbanization and population growth. One such transformative development is the adoption of diagrid steel structures, a revolutionary approach that redefines the aesthetics and efficiency of tall building design. The term "diagrid" is derived from the combination of "diagonal" and "grid," encapsulating the defining characteristic of this structural system. Unlike traditional building frameworks, diagrid structures employ a network of diagonal steel members that form an intricate lattice pattern on the exterior of the building. This unique design not only contributes to the iconic appearance of the structure but also serves as a fundamental component in optimizing both its structural stability and architectural flexibility. The increasing global trend towards taller buildings, driven by the scarcity of urban space, has underscored the need for structural systems that can efficiently bear the load of height while offering visually compelling designs. Diagrid steel structures have emerged as a preferred solution due to their inherent advantages, including a high strength-to-weight ratio, ease of assembly, and the ability to efficiently resist both gravity and lateral loads. This project aims to explore the intricacies of diagrid steel structures, shedding light on their architectural significance, structural efficiency, and the technological advancements that have propelled their widespread adoption. Through a comprehensive examination of iconic examples, engineering principles, and advancements in construction technologies, this exploration seeks to provide a deeper understanding of the role and impact of diagrid structures in shaping the skyline of modern cities.

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302077 |

II. METHODOLOGY

- To study the analysis of diagrid steel structure and typical steel structure with different parameters.
- To go through the different literature reviews related to diagrid steel structure and typical steel structure.
- It is the study on lateral forces applied on the tall structures.

MODELING AND ANALYSIS

The 10 storey structure of dimension 30m x 30m plan dimensions, consisting with six bays in horizontal direction and six bays in lateral direction is taken and analyzed it by response spectrum analysis. The storey height is 3 meters and the horizontal spacing between bays is 5 meters and lateral spacing of bays is 5 meters. The height of the building is 30m.

Load Parameters:-

- 1. SEISMIC LOAD :-
- Zone : 2
- Response Reduction Factor : 5
- Importance Factor : 1
- Soil type : Medium Soil
- Structure type : Steel Frame Building
- Damping ratio : 5 Percent
- Selfweight : 1
- Member weight : Uniform load 3kN/m
- EQ X : Seismic Load X-Direction Factor 1
- EQ Z : Seismic Load Z-Direction Factor 1
- 2. WIND LOAD :-
- Wind Type : 1
- ASCE 7 2010
- Building Classification Category : 2
- Basic Wind Speed : 7 kmph
- Exposure Category : Exposure B
- Structure Type : Building Structures
- Building Natural Frequency : 2 Hz
- Enclosure Classification : Partially Enclosed
- Building Damping Ratio : 1 Percent
- Building Wall To Generate Wind Load On : Windward
- Exposures : 1
- WX : Wind Load X(Windward Face) Factor- '1' & '-1'
- WZ : Wind Load Z(Windward Face) Factor- '1' & '-1'
- 3. DEAD LOAD :-
- Selfweight :- 1
- 4. LIVE LOAD :-
- Floor load :- Y-Range '3-30'
- Pressure- '-9.812 kN/m2'

Calculation of Lateral Forces (Base Shear)

 $V_B = A_h W$ (7.2.1, IS 1893 PART 1 2016) Page no.21 where

 A_h = design horizontal acceleration coefficient value, using approximate fundamental natural period T_a along the considered direction of shaking.

W = seismic weight of the building

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |

Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302077 |

Ah= $\frac{z}{2}X\frac{I}{R}X\frac{Sa}{g}$ (6.4.2, IS 1893 PART-1:2016) Page no. 9 where Z = seismic zone factor I = importance factor R = response reduction factor $\frac{Sa}{g}$ = design acceleration coefficient for different soil types

$$Z = 0.10$$
.....(table 3, IS 1893 Part-1:2016) Page no. 10

 $I = 1$
.....(table 8, IS 1893 Part-1:2016) Page no. 19

 $R = 5$
.....(table 9, IS 1893 Part-1:2016) Page no. 20

 $\frac{Sa}{g} = \frac{1.36}{T}$
(for medium stiffness soil)

 $T_a = 0.085h^{0.75}$
(for steel MRF building)

 $h = 30m$
(height of building)

 $T_a = 0.085 \times 30^{0.75}$ =1.08958 sec

$$\frac{Sa}{g} = \frac{1.36}{T} = \frac{1.36}{1.08958} = 1.248$$

 $Ah = \frac{z}{2} X \frac{I}{R} X \frac{Sa}{g}$ $= \frac{0.1}{2} X \frac{1}{5} X 1.248$ = 0.0125

 $V_B = A_h W$ = 0.125 X 47202.79 = 589.18 KN



Figure 1: Dimensions of a structure along x & z axis

e-ISSN: 2319-8753, p-ISSN: 2347-6710 www.ijirset.com | Impact Factor: 8.423 | A Monthly Peer Reviewed & Referred Journal |



|| Volume 13, Issue 2, February 2024 ||

| DOI:10.15680/IJIRSET.2024.1302077 |



Figure 2: Height of a structure



Figure 3: Shear Force with external diagrid steel structure.



Figure 5: Shear Force for Typical steel structure



Figure 4: Shear Force without external diagrid steel Structure.



Figure 6: Bending Moment with external column diagrid steel structure

|e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

DOI:10.15680/IJIRSET.2024.1302077 |



Figure 7: Bending Moment without external diagrid steel structure

Figure 8: Bending Moment without external diagrid steel structure

III. RESULTS AND DISCUSSION

It is the study of comparison between Typical steel structure, Diagrid steel structure without external columns & Diagrid Steel Structure with external columns. As we have analyzed Base shear and storey drift as shown below in the table and in graph.

SN.	Model Type	Base	Seismic
		Shear	Zone
1	Typical steel structure	581.74	2
2	Diagrid steel structure without external columns	585.53	2
3	Diagrid steel structure with external columns	589.18	2
4	Conventional steel structure with shear wall on both axis	666.44	2
5	Diagrid steel structure without external columns with shear	670.23	2
	wall on both axis		
6	Diagrid steel structure without external columns with shear	673.88	2
	wall on both axis		

e-ISSN: 2319-8753, p-ISSN: 2347-6710| www.ijirset.com | Impact Factor: 8.423| A Monthly Peer Reviewed & Referred Journal |



Volume 13, Issue 2, February 2024

| DOI:10.15680/IJIRSET.2024.1302077 |



Figure 7: Graph of storey drift

IV. CONCLUSION

In this report, the study of diagrid steel structure with or without external columns & typical steel structures. The analysis of a steel structure having sizes $30m \times 30m$ is carried out. Lateral forces and self weight have applied on the structure. The base shear and storey drift is analyzed. Shear wall is also applied to structures. The results is as shown in the table given above.

REFERENCES

- 1. Jani Khushbu, "Analysis and Design of Diagrid Structural System for High Rise Steel Buildings", M. Tech. Dissertation, Nirma University, Ahmedabad, 2012.
- 2. 223 Gyusoo Kim and Seulgi Lee, "2014 Payment Research", Bank of Korea, Vol. 2015, No. 1, Jan. 2015.
- 3. Moon K.S., "Material-Saving Design Strategies for Tall Building Structures", CTBUH 8th World Congress, Dubai, March 2008.
- 4. IS: 875(Part-3)-1987. Code of practice for design loads (other than earthquake) for buildings and structures, wind loads. Bureau of Indian Standard, New Delhi.
- 5. IS: 1893(Part-I)-2002. Criteria for Earthquake Resistant Design of Structures. Bureau of Indian Standard, New Delhi.
- 6. IS: 800-2007. General Construction in Steel Code of Practice. Bureau of Indian Standard, New Delhi.









INTERNATIONAL JOURNAL OF INNOVATIVE RESEARCH

IN SCIENCE | ENGINEERING | TECHNOLOGY





www.ijirset.com